SAFETY DATA SHEET

AUTOCOLOR

Date of issue/Date of revision

: 1 November 2023

Version : 1.02

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: AQUABASE PLUS CLEAR ADJUSTER
Product code	: P990-8999/E1
Product description	1 () () () () () () () () () (
Product type	: Liquid.
Other means of identification	: Not available.
1.2 Relevant identified uses	s of the substance or mixture and uses advised against
Product use	: Industrial applications.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Industries (UK) Ltd. Needham Road, Stowmarket, Suffolk, IP14 2AD, UK Tel: +44 (0) 1449 773 338 PPG Industries Italia S.r.l., Via Comasina, 121, 20161 Milano, Italy Tel: +39 02 6404.1

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

- Company emergency telephone number : +44 (0) 1449 773 338 (0900-1600)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to UK CLP/GHS Not classified.

The product is not classified as hazardous according to UK CLP Regulation SI 2019/720 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	-	Dispose of contents and container in accordance with all local, regional, national and international regulations.
		P501
Supplemental label elements	1	Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction. Safety data sheet available on request.

Code : P990-8999/E1 AQUABASE PLUS CLEAR ADJUSTER	Date of issue/Date of revision	: 1 November 2023
SECTION 2: Hazards identification	1	

Annex XVII - Restrictions on the manufacture,	:	Not applicable.
placing on the market and use of certain dangerous substances, mixtures and articles		
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

Mixture

3.2 Mixtures ŝ, **Product/ingredient name Identifiers** % Classification Туре 2-butoxyethanol REACH #: ≥5.0 - <10 Acute Tox. 4, H302 [1] [2] 01-2119475108-36 Acute Tox. 3, H331 EC: 203-905-0 Skin Irrit. 2, H315 CAS: 111-76-2 Eye Irrit. 2, H319 Index: 603-014-00-0 2,4,7,9-tetramethyldec-5-yne-<1.0 Eye Dam. 1, H318 REACH #: [1] 4,7-diol Skin Sens. 1B, H317 01-2119954390-39 EC: 204-809-1 Aquatic Chronic 3, CAS: 126-86-3 H412 See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of firs	t aid measures
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

English	(GB)
g	(22)

Code : P990-8999/E1	Date of issue/Date of revision : 1 November 2023		
AQUABASE PLUS CLEAR A			
SECTION 4: First aid			
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Kee person warm and at rest. Do NOT induce vomiting.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.		
4.2 Most important symptom	s and effects, both acute and delayed		
Potential acute health effects			
Eye contact	: No known significant effects or critical hazards.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		
Over-exposure signs/sympt	oms		
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	No specific data.		
Ingestion	: No specific data.		
4.3 Indication of any immedia	ate medical attention and special treatment needed		
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large		
	quantities have been ingested or inhaled.		
Specific treatments	: No specific treatment.		
SECTION 5: Firefight	ing measures		
5.1 Extinguishing media			
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.		
Unsuitable extinguishing media	: None known.		
5.2 Special hazards arising fi	rom the substance or mixture		
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.		
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides		
5.3 Advice for firefighters			
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident in there is a fire. No action shall be taken involving any personal risk or without suitable training.		
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. 		
SECTION 6: Acciden	tal release measures		

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Code : P990-899 AQUABASE PLUS CLEA		Date of issue/Date of revision	: 1 November 2023
SECTION 6: Accid	dental release	measures	
6.2 Environmental precautions	•	sal of spilt material and runoff and contact v Inform the relevant authorities if the produc	

pollution (sewers, waterways, soil or air).

motorial for containment and cleaning

6.3 Methods and material	for containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
	Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Storage temperature: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Code : P990-8999/E1

Date of issue/Date of revision

: 1 November 2023

AQUABASE PLUS CLEAR ADJUSTER

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.
	STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m ³ 15 minutes. TWA: 123 mg/m ³ 8 hours.

Biological exposure indices

Product/ingredient name	Exposure indices
2-butoxyethanol	2-BUTOXY ETHANOL

Recommended monitoring : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2-butoxyethanol	DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	26.7 mg/kg bw/day	General population	
	DNEL	Long term Inhalation	59 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	98 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	147 mg/m ³	General population	Local
	DNEL	Short term Inhalation	246 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	426 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	1091 mg/m ³	Workers	Systemic
2,4,7,9-tetramethyldec-5-yne- 4,7-diol	DNEL	Long term Oral	0.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.43 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	0.5 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	0.75 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.75 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	1.29 mg/m ³	General population	Systemic
	DNEL	Short term Dermal	1.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.76 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	5.28 mg/m ³	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
₽-butoxyethanol	Fresh water	8.8 mg/l	Assessment Factors
	Marine water	0.88 mg/l	Assessment Factors
	Fresh water sediment	34.6 mg/kg	Equilibrium Partitioning
	Marine water sediment	3.46 mg/kg	Equilibrium Partitioning
	Soil	3.13 mg/kg	Equilibrium Partitioning
	Sewage Treatment Plant	463 mg/l	Assessment Factors
2,4,7,9-tetramethyldec-5-yne-4,7-diol	Fresh water	0.04 mg/l	Assessment Factors
	Marine water	0.004 mg/l	Assessment Factors
	Sewage Treatment Plant	7 mg/l	Assessment Factors
	Fresh water sediment	0.32 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	0.032 mg/kg dwt	Equilibrium Partitioning
	Soil	0.028 mg/kg dwt	Equilibrium Partitioning

8.2 Exposure controls

Engl	ish ((GB)	
g.		UUU	

Code : P990-8999/E1	Date of issue/Date of revision	: 1 November 2023
AQUABASE PLUS CLEAR ADJUSTER		

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measu	Ires
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Safety glasses with side shields.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Gloves	: For prolonged or repeated handling, use the following type of gloves:
	Recommended: butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Wear a respirator conforming to EN140. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Mask type: full-face mask half-face mask Filter type: organic vapour filter (Type A) particulate filter P3 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>					
Physical state	: Liqui	d.			
Colour	: Colo	urless.			
Odour	: Faint	t odour.			
Odour threshold	: Not a	available.			
Melting point/freezing point				mperature: 0°C (32°F) This is bas ighted average: -7.83°C (17.9°F)	
Initial boiling point and boiling range	: >37.	78°C (>100°F)			
Flammability (solid, gas)	: liquio	ł			
Upper/lower flammability or explosive limits	: Not a	applicable.			
Flash point	: Clos	ed cup: 100°C	(212°F) [Product of	loes not sustain combustion.]	
Auto-ignition temperature	:				
Ingredient name		°C	°F	Method	
₽-butoxyethanol		230	446	DIN 51794	

English (GB)

Code	: P990-8999/E1	Date of issue/Date of revision	: 1 November 2023
AQUABASE	PLUS CLEAR ADJUSTER		

SECTION 9: Physical and chemical properties

Decomposition temperatur	e:					
рН	: Not	available.				
Viscosity	: Kin	ematic (40°	°C): >21 mm²/s			
Solubility(ies)	:					
Media	R	esult				
cold water	P	artially solu	ble			
Miscible with water	: Yes					
Partition coefficient: n-octa water	anol/ : Not	applicable				
Vapour pressure	:					
	V	apour Pres	ssure at 20°C	V	apour pres	sure at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
Relative density Vapour density	: 1.0 ⁻		\sim	1) (2 butoweth		
	: Highest known value: 4.1 (Air = 1) (2-butoxyethanol).					
	- NI.4					
Explosive properties		available.				
Explosive properties Oxidising properties <u>Particle characteristics</u>			not present an oxid	lizing hazard.		

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	When exposed to high temperatures may produce hazardous decomposition prod Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	Depending on conditions, decomposition products may include the following materials: carbon oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LC50 Inhalation Vapour	Rat	3 mg/l	4 hours
-	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
2,4,7,9-tetramethyldec-	LC50 Inhalation Dusts and	Rat	>20 mg/l	1 hours
5-yne-4,7-diol	mists		-	
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	4.6 g/kg	-

Code	: P990-8999/E1	Date of issue/Date of revision	: 1 November 2023

AQUABASE PLUS CLEAR ADJUSTER

SECTION 11: Toxicological information

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
QUABASE PLUS CLEAR ADJUSTER	1200	N/A	380666.5	34.2	N/A
2-butoxyethanol		N/A	N/A	3	N/A
2,4,7,9-tetramethyldec-5-yne-4,7-diol		N/A	N/A	N/A	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observatio
2-butoxyethanol	Eyes - Irritant	Rabbit	-	24 hours	21 days
	Skin - Moderate irritant	Rabbit	-	4 hours	28 days
2,4,7,9-tetramethyldec-5-yne- 4,7-diol	Eyes - Severe irritant	Rabbit	-	0.1 Mililiters	-
-, <i>i</i> - dioi	Skin - Mild irritant	Rabbit	-	0.5 Grams	-
Conclusion/Summary	: Not available.				
Skin	: There are no data available or	n the mixture its	elf.		
Eyes	: There are no data available or	n the mixture its	elf.		
Respiratory	: There are no data available or	n the mixture its	elf.		
<u>Sensitisation</u>					
Conclusion/Summary					
Skin	: There are no data available or	n the mixture its	elf.		
Respiratory	: There are no data available or	n the mixture its	elf.		
<u>Mutagenicity</u>					
Conclusion/Summary	: There are no data available or	n the mixture its	elf.		
<u>Carcinogenicity</u>					
Conclusion/Summary	: There are no data available or	n the mixture its	elf.		
Reproductive toxicity					
Conclusion/Summary	: There are no data available or	n the mixture its	elf.		
<u>Teratogenicity</u>					
Conclusion/Summary	:				
	There are no data available or	n the mixture its	elf.		
Specific target organ toxicit	<u>y (single exposure)</u>				
Not available.					
Specific target organ toxicit	<u>y (repeated exposure)</u>				
Not available.					
Aspiration hazard					
Not available.					
formation on likely routes	: Not available.				
f exposure					
otential acute health effects					
Eye contact	: No known significant effects o	r critical hazard	s.		
nhalation	: No known significant effects o	r critical hazard	S.		
Skin contact	: No known significant effects o	r critical hazard	s.		
	: No known significant effects or critical hazards.				

Symptoms related to the physical, chemical and toxicological characteristics

Conforms to Regulation (EC) N	o. 1907/2006 (REACH), Annex II, as amended by UK REAC	H Regulation SI 2019/758
Code : P990-8999/E1 AQUABASE PLUS CLEAR ADJUSTER		Date of issue/Date of revision	: 1 November 2023
SECTION 11: Toxico	logical informa	tion	
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: No specific data.		
Ingestion	: No specific data.		
Delayed and immediate effect	ts as well as chronic	effects from short and long-term e	xposure
<u>Short term exposure</u>			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Long term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Potential chronic health eff	<u>ects</u>		
Not available.			
Conclusion/Summary	: Not available.		
General	: No known significa	ant effects or critical hazards.	
Carcinogenicity	: No known significa	ant effects or critical hazards.	
Mutagenicity	: No known significa	ant effects or critical hazards.	
Reproductive toxicity	: No known significa	ant effects or critical hazards.	

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
₽-butoxyethanol	Acute LC50 1474 mg/l Chronic NOEC >100 mg/l	Fish Fish	96 hours 21 days
Conclusion/Summary	: Not available.		

12.2 Persistence and degradability

Conclusion/Summary	: Not available.		
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-butoxyethanol	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-butoxyethanol	0.81	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Code	: P990-8999/E1	Date of issue/Date of revision	: 1 November 2023
AQUABASE	PLUS CLEAR ADJUSTER		

SECTION 12: Ecological information

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product			
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.		
Hazardous waste	: Yes.		
Waste catalogue			
Waste code	Waste designation		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances		
Packaging			
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.		
Type of packaging	Waste catalogue		
Container	15 01 02 plastic packaging		
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.		

SECTION 14: Transport information

	-			
	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	9003	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	SUBSTANCES WITH A FLASH-POINT ABOVE 60 °C AND NOT MORE THAN 100 °C (2-butoxyethanol) (2-butoxyethanol)	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.
ADR/RID :	None identified.	•		

English (GB)

ADN

: The product is only regulated as a dangerous good when transported in tank vessels.

Code AQUABAS	: P990-8999/E1 E PLUS CLEAR AD		November 2023
SECTIO	N 14: Transpo	information	
IMDG	: None ident	d.	
IATA	: None ident	d.	
14.6 Specia user	al precautions for	Transport within user's premises: always transport in closed coupright and secure. Ensure that persons transporting the product the event of an accident or spillage.	
14.7 Transport in bulk: Not available.according to IMOinstruments		Not available.	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Seveso Directive

This product is not controlled under the Seveso Directive.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and
	Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019
	No. 720 and amendments
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = GB CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Not classified.

Full text of abbreviated H statements

	990-8999/E1 S CLEAR ADJUSTER	Date of issue/Date of revision	: 1 November 2023
SECTION 16	: Other information		
H302	Harmful if swallowed.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		
H331	Toxic if inhaled.		
H412	armful to aquatic life with long lasting effects.		
Full text of class	ifications		
Acute Tox. 3	ACUTE TOXICITY - Cate	gory 3	
Acute Tox. 4			
Aquatic Chronic 3			
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1		
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2		
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2		
Skin Sens. 1B	• •		

<u>History</u>

Date of issue/ Date of revision	: 1 November 2023
Date of previous issue	: 11 November 2022
Prepared by	: EHS
Version	: 1.02

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.