

P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	: P-H-430 2,5L 2,5L Steel jerricans
Product code	: 0000000050680077
1.2 Relevant identified uses of t	he substance or mixture and uses advised against
Use of the	: Spraying
Substance/Mixture	hardener
1.3 Details of the supplier of the	e safety data sheet
<u>Company:</u>	<u>Contact address:</u>
BASF Coatings GmbH	BASF plc
Postfach 6123	4th and 5th Floors, 2 Stockport Exchange
48136 Münster	Railway Road, Stockport, SK1 3GG
Deutschland	United Kingdom

Telephone: +44 161 475 3000 E-mail address: product-safety-uk-and-ireland@basf.com



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - single exposure, Category 3, Central	H336: May cause drowsiness or dizziness.



to aquatic life with long lasting

P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

nervous system

Long-term (chronic) aquatic hazard,	H412: Harmful
Category 3	effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:		
Signal Word	:	Warning	
Hazard Statements	:	H226 H317 H332 H335	Flammable liquid and vapor. May cause an allergic skin reaction. Harmful if inhaled. May cause respiratory irritation.
		H336	May cause drowsiness or dizziness.



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

H412	Harmful to aquatic life with long lasting
	effects.

Precautionary	Preventio	on:
Statements	· P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P261	Avoid breathing mist or vapors.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
	Respons P303 + P	e: 361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
	P370 + P	378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Hazardous ingredients which must be listed on the label: Hexamethylen-1,6-diisocyanat Homopolymer

2-heptanone

2-butoxyethyl acetate

1,6-hexamethylene diisocyanate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : organic solvent

Components

Chemical name	CAS-No.	Classification	Concentratio
---------------	---------	----------------	--------------



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

	EC-No.		n (% w/w)
	Index-No.		
	Registration		
	number		
Hexamethylen-1,6-diisocyanat	28182-81-2	Acute Tox. 4;	>= 50 - < 75
Homopolymer	500-060-2	H332	
	01-2119485796-17	Skin Sens. 1;	
		H317	
		STOT SE 3; H335	
		(Respiratory	
		system)	
2-heptanone	110-43-0	Flam. Liq. 3; H226	>= 20 - < 25
	203-767-1	Acute Tox. 4;	
	606-024-00-3	H302	
	UK-20-	Acute Tox. 4;	
	0537843089-5-	H332	
	0000	STOT SE 3; H336	



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

		(Central nervous system)	
1-methoxy-2-propylacetate	108-65-6	Flam. Liq. 3; H226	>= 7 - < 10
	203-603-9	STOT SE 3; H336	
	607-195-00-7	(Central nervous	
	UK-20-	system)	
	9702550300-0-		
	0000		
	UK-20-		
	0537843089-5-		
	0000		
	UK-20-		
	9642318150-0-		
	0000		
2-butoxyethyl acetate	112-07-2	Acute Tox. 4;	>= 7 - < 10
	203-933-3	H302	
	607-038-00-2	Acute Tox. 4;	
	UK-20-	H332	
	UK-2U-		



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

	0537843089-5- 0000	Acute Tox. 4; H312	
	UK-20- 9642318150-0- 0000		
Hydrocarbons, C9, aromatics	64742-95-6	Flam. Liq. 3; H226	>= 3 - < 5
	265-199-0	STOT SE 3; H336	
	UK-20- 0537843089-5-	(Central nervous system)	
	0000	STOT SE 3; H335	
		(Respiratory system)	
		Asp. Tox. 1; H304	
		Aquatic	
		Chronic 2; H411	
1,6-hexamethylene diisocyanate	822-06-0	Acute Tox. 4;	< 0.1
	212-485-8	H302	
		Acute Tox. 1;	



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

615-011-00-1	H330
UK-20-	Skin Irrit. 2; H315
0537843089-5- 0000	Eye Irrit. 2; H319
UK-20-	Resp. Sens. 1;
9642318150-0-	H334
0000	Skin Sens. 1;
	H317
	STOT SE 3; H335
	(Respiratory
	system)
	specific
	concentration
	limit
	Resp. Sens. 1;
	H334
	>= 0.5 %



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

	Skin Sens. 1; H317	
	>= 0.5 %	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice	 First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Move out of dangerous area. Never give anything by mouth to an unconscious person.
If inhaled	: If symptoms persist, call a physician.



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

.
ficial
ter es.
nse eyelids,
r



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.		
Risks	: May cause an allergic skin reaction.		
	Harmful if inhaled.		
	May cause respiratory irritation.		
	May cause drowsiness or dizziness.		
3 Indication of any immediate medical attention and special treatment needed			

4.3

: No known specific antidote. Treat symptomatically.



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing	:	Water spray jet
media		Dry powder
		Alcohol-resistant foam
		Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet
5.2 Special hazards arising from t Specific hazards during fire		substance or mixture Fire will produce dense black smoke containing
fighting		hazardous combustion products (see section 10).
5.3 Advice for firefighters Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Further information	:	In the event of fire, cool tanks with water spray.
		Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
		Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protect	tive	equipment and emergency procedures
Personal precautions :	:	Avoid breathing vapours.
		Keep away from sources of ignition.
		Advice on product handling can be found in sections 7
		and 8 of this safety data sheet.
		For non-emergency personnel:
		For emergency responders:



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Use personal protective equipment.

Ensure adequate ventilation, especially in confined areas.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain and collect spillage with non-combustible
		absorbent materials, e.g. sand, earth, vermiculite,
		diatomaceous earth. Place in a suitable container. The
		contaminated area should be cleaned up immediately
		with a suitable decontaminant. One possible
		(flammable) decontaminant comprises (by volume):
		ethanol or isopropyl alcohol (50 parts); water (45 parts);



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

concentrated ammonia solution (5 parts). A nonflammable alternative is: sodium carbonate (5 parts); water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13).

Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust



P-H-430 2,5L 2,5L Steel jerricans

VersionRevision Date:SDS Number:Date of last issue: 07.01.20253.028.03.202500000000050680
077Date of first issue: 10.10.2023

ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Advice on protection against fire and explosion	:	Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.
--	---	---

Hygiene measures: Remove contaminated clothing immediately and dispose
of safely. Wash hands before breaks and at the end of
workday. Keep away from food, drink and animal
feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on	:	Avoid direct sunlight. Close containers carefully once
storage conditions		opened and store them upright in order to prevent any
		leakage. No smoking. No admission for unauthorised
		personnel. Always keep in containers of same material
		as the original one. Observe label precautions. Keep in a



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

dry, cool and well-ventilated place.

Advice on common storage :	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Packaging material :	:	Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)
7.3 Specific end use(s) Specific use(s) :	:	Please refer to the technical leaflet for further information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type	Control parameters	Basis
		(Form of		



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

		exposure)			
Hexamethylen- 1,6-diisocyanat Homopolymer	28182-81-2	TWA	0.02 mg/m3 (NCO)	GB EH40	
	Further infor	mation: Capable o	mation: Capable of causing occupational asthr		
		STEL	0.07 mg/m3	GB EH40	
			(NCO)		
	Further information: Capable of causing occupational asthma.				
2-heptanone	110-43-0	STEL	100 ppm	GB EH40	
			475 mg/m3		
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		TWA	50 ppm 237 mg/m3	GB EH40	
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal				



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

	absorption will lead to systemic toxicity.					
		TWA	50 ppm	2000/39/EC		
			238 mg/m3			
	Further information: Identifies the possibility of significant uptake					
	through the	skin, Indicative				
		STEL	100 ppm	2000/39/EC		
			475 mg/m3			
	Further infor	mation: Identifies	the possibility of significar	nt uptake		
	through the	skin, Indicative				
1-methoxy-2-	108-65-6	TWA	50 ppm	GB EH40		
propylacetate			274 mg/m3			
	Further infor	mation: Can be ab	sorbed through the skin. 1	he assigned		
	substances are those for which there are concerns that dermal					
	absorption will lead to systemic toxicity.					
		STEL	100 ppm	GB EH40		
			548 mg/m3			



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		STEL	100 ppm	2000/39/EC	
			550 mg/m3		
			the possibility of signification	nt uptake	
	through the	skin, Indicative			
	TWA 50 ppm 2000/39/E				
			275 mg/m3		
	Further information: Identifies the possibility of significant uptake				
	through the	skin, Indicative			
2-butoxyethyl	112-07-2	TWA	20 ppm	GB EH40	
acetate	133 mg/m3				
	Further information: Can be absorbed through the skin. The assigned				
	substances are those for which there are concerns that dermal				
	absorption v	absorption will lead to systemic toxicity.			
		STEL	50 ppm	GB EH40	



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

			332 mg/m3	
	substances a	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	50 ppm 333 mg/m3	2000/39/EC
		mation: Identifies skin, Indicative	the possibility of significar	it uptake
		TWA	20 ppm 133 mg/m3	2000/39/EC
		mation: Identifies skin, Indicative	the possibility of significar	nt uptake
1,6- hexamethylene diisocyanate	822-06-0	TWA	0.02 mg/m3 (NCO)	GB EH40
	Further infor	mation: Capable o	f causing occupational ast	hma.
		STEL	0.07 mg/m3	GB EH40



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

		(NCO)	
Further infor	mation: Capable o	f causing occupational ast	hma.

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Hexamethylen-1,6- diisocyanat Homopolymer	28182-81-2	isocyanate- derived diamine (Isocyanates): 1 μmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT
1,6-hexamethylene diisocyanate	822-06-0	isocyanate- derived diamine (Isocyanates): 1 μmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

8.2 Exposure controls		
Engineering measures Ensure adequate ventilation.		
Personal protective equipm	ent	
Eye/face protection	:	Safety glasses with side-shields conforming to EN166
		Required when there is a risk of eye contact.
Hand protection		
Remarks	:	Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

		Preventive skin protection Suitable materials for short- term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)
Skin and body protection	:	chemical-resistant disposable coveralls
		Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.
Respiratory protection	:	Suitable respiratory equipment:
		full face mask with AB2P3 class combination filter
		When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
		In case of mist, spray or aerosol exposure wear suitable



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

		personal respiratory protection and protective suit.
Protective measures	:	Do not breathe vapour/spray.
		Eye wash fountains and safety showers must be easily accessible.
		If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.
		Avoid contact with the skin, eyes and clothing.
		Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Color	: colorless
Odor	: ketone-like
рН	: substance/mixture is non-polar/aprotic
Melting point/ range	: not determined



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Boiling point/boiling range	:	not determined
Flash point	:	45 °C Method: ISO 3679
Lower explosion limit / Lower flammability limit	:	> 35 g/m3
Vapor pressure	:	not determined (20 °C)
		not determined (50 °C)
Relative vapor density	:	Heavier than air.
Density	:	1.014 g/cm3 (20 °C)
Solubility(ies) Water solubility Partition coefficient: n- octanol/water Autoignition temperature	:	not determined not applicable for mixtures > 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, kinematic	:	7.3 mm2/s (23 °C)



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

		not determined (40 °C)
Flow time	:	> 30 s at 23 °C Cross section: 3 mm
		Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
9.2 Other information		
Flammability (liquids)	:	Flammable liquid and vapour.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

10.3 Possibility of hazardous reactions				
Hazardous reactions	:	Vapours may form ignitable mixture with air.		
10.4 Conditions to avoid				
Conditions to avoid	:	Avoid direct sunlight.		
		Heat, flames and sparks.		
10.5 Incompatible materials				
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.		

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Harmful if inhaled.



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Product:		
Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg
		Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 13.86 mg/l Exposure time: 4 h
		Test atmosphere: vapor
		Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg
		Method: Calculation method
<u>Components:</u> 2-heptanone:		
Acute oral toxicity	:	LD50 (Rat): 1,600 mg/kg



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Acute inhalation toxicity	:	LC50 (Rat): 16.7 mg/l Exposure time: 4 h		
		Test atmosphere: vapor		
2-butoxyethyl acetate:				
Acute oral toxicity	:	LD50 (Rat): 1,880 mg/kg		
Acute dermal toxicity		LD50 (Rabbit): 1,500 mg/kg		
Acute definition toxicity	•			
I				
Skin corrosion/irritation				
Not classified due to lack of data.				
Serious eye damage/eye irritation Not classified due to lack of data.				
		n		
Respiratory or skin sensiti	2a110			
Skin sensitization	antic			
May cause an allergic skin reaction.				
Respiratory sensitization				
Not classified due to lack of data.				
Germ cell mutagenicity				
Not classified due to lack of o	bata.			



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Carcinogenicity Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Based on available data, the classification criteria are not met.

Product:

No aspiration toxicity classification

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Hexamethylen-1,6-diisocyanat Homopolymer:



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Partition coefficient: n- octanol/water	:	log Pow: 9.81 (25 °C)
2-heptanone: Partition coefficient: n- octanol/water	:	log Pow: 2.26 (30 °C) pH: 7 Method: Regulation (EC) No. 440/2008, Annex, A.8 GLP: yes
1-methoxy-2-propylacetate: Partition coefficient: n- octanol/water	:	log Pow: 1.2 (20 °C) pH: 6.8 Method: OECD Test Guideline 117 GLP: yes
2-butoxyethyl acetate: Partition coefficient: n-	:	log Pow: 1.51 (25 °C)



Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

	octanol/water	рН: 7
		Method: OECD Test Guideline 107
		GLP: no
	Hydrocarbons, C9, aromatics:	
		log Pow: 3.17
	octanol/water	GLP: no
12.4	Mobility in soil	
	No data available	
12.5	Results of PBT and vPvB asses	ssment
	Product:	
	Assessment :	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

12.6 Other adverse effects		
Product:		
Endocrine disrupting	:	This substance/mixture does not contain components
potential		considered to have endocrine disrupting properties for
		environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods		
Product	:	Do not discharge into drains/surface waters/groundwater.
		Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC
		Packaging that is not properly emptied must be disposed of as the unused product.



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

SECTION 14: Transport information

14.1 UN number

ADN	: UN 1866
ADR	: UN 1866
RID	: UN 1866
IMDG	: UN 1866
ΙΑΤΑ	: UN 1866

14.2 UN proper shipping name

ADN	: RESIN SOLUTION
ADR	: RESIN SOLUTION
RID	: RESIN SOLUTION
IMDG	: RESIN SOLUTION
ΙΑΤΑ	: RESIN SOLUTION



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

14.3 Transport hazard class(es)

			Class	Subsidiary risks
	ADN	:	3	
	ADR	:	3	
	RID	:	3	
	IMDG	:	3	
	ΙΑΤΑ	:	3	
14.4	Packing group			
	ADN			
	Packing group	:	III	
	Classification Code	:	F1	
	Hazard Identification Number	:	30	
	Labels	:	3	



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

ADR

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
Tunnel restriction code	:	(D/E)
RID		
Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
IMDG		
Packing group	:	III



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
IATA (Cargo)		
Packing instruction (cargo aircraft)	:	366
Packing instruction (LQ)	:	Y344
Packing group	:	III
Labala		
Labels	:	Flammable Liquids
Labels IATA (Passenger)	:	Flammable Liquids
		355
IATA (Passenger) Packing instruction	:	
IATA (Passenger) Packing instruction (passenger aircraft)	:	355
IATA (Passenger) Packing instruction (passenger aircraft) Packing instruction (LQ)	:	355 Y344 III

14.5 Environmental hazards



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

ADN

Environmentally hazardous	:	no
ADR		
Environmentally hazardous	:	no
RID		
Environmentally hazardous	:	no
IMDG		
Marine pollutant	:	no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)		Conditions of restriction for the following entries should be considered:
		Number on list 3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Control of Major Accident Ha Regulations 2015 (COMAH)	izards P5c	FLAMMABLE LIQUIDS
	34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)
		(1/00) south the $(1/00)$

Volatile organic compounds

: Volatile organic compounds (VOC) content: 438 g/l



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 43.97 %

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:	
Subcategory as indicated in Annex IIB:	dropped
Limit value for maximum VOC content as specified in Annex IIB:	dropped

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

SECTION 16: Other information

Full text of H-Statements		
H226	:	Flammable liquid and vapor.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing
		difficulties if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H411	:	Toxic to aquatic life with long lasting effects.
Full text of other abbreviation	ns	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Resp. Sens.	:	Respiratory sensitization
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitization
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

		list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration,



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information Other information	: For multi-pack systems all components. Restricted to professior	observe material safety data sheets of nal users.
Classification of the mixtur	re:	Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Acute Tox. 4	H332	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



P-H-430 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
3.0	28.03.2025	00000000050680 077	Date of first issue: 10.10.2023

GB / EN