



Art.-No.: 6.1140.1850 6.1140.4850  
6.1140.2450  
6.1140.3050  
6.1140.3650

# 1140

## Trillennium Masking Tape

### Characteristics

A quality, smooth crepe pressure-sensitive masking tape with good quick stick and holding properties. This product is designed for paint masking requiring clean and easy removal from a variety of surfaces. Can be exposed to oven temperatures up to 121 °C (250 °F) for 30 minutes. Waterproof and IR resistant. Excellent for masking rubber trim and plastic parts.

### Application

Automotive, truck, bus and marine paint masking. Recommend warm removal, although can be removed cold.

### Technical Data

Backing	Coarse crepe paper
Colour	Dark blue
Adhesive	Rubber / Resin
Adhesion to steel (oz/in of width)	26 (7.1 N/25mm)
Quick stick to kraft (oz/in of width)	5 (1.4 N/25mm)
Quick Stick to steel (oz/in of width)	12 (3.3 N/25mm)
Tensile strength (lbs/in of width)	23 (100 N/25mm)
Elongation (% at break)	8
Thickness (mils)	6.7 (0.17mm)

### Storage and Transportation

Store in a clean, dry place. Temperature of 21 °C and 40% to 50% relative humidity are recommended. 12 months shelf life, when stored under suggested storage conditions.