



Art.-No.:6.1172.0333  
 6.1172.0633  
 6.1172.0933  
 6.1172.1233

1172

## Fine Line Tape Blue

### Characteristics

4CR 1172 High Temperature Fine Line Tape uses a thermally stabilized PVC backing with a Rubber based pressure sensitive adhesive. This fine line tape will perform in temperatures up to 138°C for at least 45 minutes and leave a sharp, clean separation line. 4CR 1172 adheres to a wide variety of surfaces, is solvent resistant and has a high conformability. It follows contours and remains in place as long as necessary and leaves no residue upon removal. This is a splinter and fibre free tape leaving no contaminants in paintline.

### Tech Tip

Masking tape for multi colour and design jobs. Medium flexibility.

### Application

Preferred where tape must conform and follow contours without wrinkling or tearing. 4CR 1172 is used when flake resistance and removal without adhesive transfer is important.

### Technical Data

Carrier	PVC
Colour	DK Blue Gloss
Adhesive	Rubber Based Pressure Sensitive Adhesive
Thickness	0.163mm PSTC-33
Width	3mm, 6mm, 9mm and 12mm (+/- 1mm)
Length	33m (+/- 0.1m)
Tensile Strength	0.215 kg/mm ASTM D-3759
Elongation strength	600 %
Adhesion to steel	33.6 g/mm ASTM D-3330
Heat resistance	138°C Maximum for 45 minutes