

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product identifier** : WB 887  
**Product name** : Permahyd® Mixing Colour 285 FINE BLUE PEARL  
**Product type** : Liquid.  
**Other means of identification** : 4025331471639  
**Date of issue/ Date of revision** : 27 April 2024  
**Version** : 1.1  
**Date of previous issue** : 3 March 2024

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** : Coating component.  
**Uses advised against** : Not for sale to or use by consumers.

### 1.3 Details of the supplier of the safety data sheet

Axalta Coating Systems Germany GmbH & Co. KG  
Christbusch 25  
DE 42285 Wuppertal  
+49 (0)202 529-0  
**e-mail address of person responsible for this SDS** : sds-competence@axalta.com

### 1.4 Emergency telephone number

#### Supplier

**Telephone number** : +(44)-870-8200418  
**Hours of operation** :

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture  
**Classification according to UK CLP/GHS**  
Eye Irrit. 2, H319

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

## SECTION 2: Hazards identification

Hazard pictograms :



Signal word :

Warning

Hazard statements :

H319 - Causes serious eye irritation.

**Precautionary statements**

**Prevention** :

P280 - Wear eye or face protection.

**Response** :

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical advice or attention.

**Storage** :

Not applicable.

**Disposal** :

Not applicable.

**Supplemental label elements** :

EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

Not applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** :

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** :

None known.

## SECTION 3: Composition/information on ingredients

3.2 Mixtures :

Mixture

| Product/ingredient name | Identifiers   | %  | Classification  | Type    |
|-------------------------|---|----|---|---------|
| 2-butoxyethanol         | REACH #:<br>01-2119475108-36<br>EC: 203-905-0<br>CAS: 111-76-2<br>Index: 603-014-00-0 | ≤5 | Acute Tox. 4, H302<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319   | [1] [2] |
| butan-1-ol              | REACH #:<br>01-2119484630-38<br>EC: 200-751-6<br>CAS: 71-36-3<br>Index: 603-004-00-6  | <3 | Flam. Liq. 3, H226<br>Acute Tox. 4, H302<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>STOT SE 3, H336   | [1] [2] |
| 2-dimethylaminoethanol  | REACH #:<br>01-2119492298-24<br>EC: 203-542-8<br>CAS: 108-01-0<br>Index: 603-047-00-0 | <1 | Flam. Liq. 3, H226<br>Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Acute Tox. 3, H331<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br><br><b>See Section 16 for the full text of the H statements declared above.</b> | [1] [2] |

### SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

Due to the organic solvents content of the mixture:

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

Due to the organic solvents content of the mixture:

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Permahyd® Mixing Colour 285 FINE BLUE PEARL

**SECTION 7: Handling and storage**

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

**Information on fire and explosion protection**

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in accordance with local regulations.

**Notes on joint storage**

Keep away from: oxidising agents, strong alkalis, strong acids.

**Additional information on storage conditions**

Observe label precautions. Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

**7.3 Specific end use(s)**

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limits**

| Product/ingredient name | Exposure limit values   |
|-------------------------|---|
| 2-butoxyethanol         | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b><br>STEL: 50 ppm 15 minutes.<br>TWA: 25 ppm 8 hours.<br>STEL: 246 mg/m <sup>3</sup> 15 minutes.<br>TWA: 123 mg/m <sup>3</sup> 8 hours. |
| butan-1-ol              | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b><br>STEL: 154 mg/m <sup>3</sup> 15 minutes.<br>STEL: 50 ppm 15 minutes.  |
| 2-dimethylaminoethanol  | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b><br>STEL: 22 mg/m <sup>3</sup> 15 minutes.<br>STEL: 6 ppm 15 minutes.<br>TWA: 2 ppm 8 hours.<br>TWA: 7.4 mg/m <sup>3</sup> 8 hours.                           |

**Biological exposure indices**

| Product/ingredient name | Exposure indices  |
|-------------------------|---|
| 2-butoxyethanol         | <b>EH40/2005 BMGVs (United Kingdom (UK), 8/2018)</b><br>BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine].<br>Sampling time: post shift. |

**Recommended monitoring procedures** : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

**SECTION 8: Exposure controls/personal protection**

| Product/ingredient name | Type       | Exposure              | Value                     | Population          | Effects            |
|-------------------------|------------|-----------------------|---------------------------|---------------------|--------------------|
| 2-butoxyethanol         | DNEL       | Long term Inhalation  | 20 ppm                    | Workers             | Systemic           |
|                         | DNEL       | Long term Oral        | 6.3 mg/kg bw/day          | General population  | Systemic           |
|                         | DNEL       | Short term Oral       | 26.7 mg/kg bw/day         | General population  | Systemic           |
|                         | DNEL       | Long term Inhalation  | 59 mg/m <sup>3</sup>      | General population  | Systemic           |
|                         | DNEL       | Long term Inhalation  | 98 mg/m <sup>3</sup>      | Workers             | Systemic           |
|                         | DNEL       | Short term Inhalation | 147 mg/m <sup>3</sup>     | General population  | Local              |
|                         | DNEL       | Short term Inhalation | 246 mg/m <sup>3</sup>     | Workers             | Local              |
|                         | DNEL       | Short term Inhalation | 426 mg/m <sup>3</sup>     | General population  | Systemic           |
|                         | DNEL       | Short term Inhalation | 1091 mg/m <sup>3</sup>    | Workers             | Systemic           |
|                         | butan-1-ol | DNEL                  | Long term Oral            | 1.5625 mg/kg bw/day | General population |
| DNEL                    |            | Long term Dermal      | 3.125 mg/kg bw/day        | General population  | Systemic           |
| DNEL                    |            | Long term Inhalation  | 55.357 mg/m <sup>3</sup>  | General population  | Systemic           |
| DNEL                    |            | Long term Inhalation  | 155 mg/m <sup>3</sup>     | General population  | Local              |
| DNEL                    |            | Long term Inhalation  | 310 mg/m <sup>3</sup>     | Workers             | Local              |
| 2-dimethylaminoethanol  | DNEL       | Short term Dermal     | 100 µg/cm <sup>2</sup>    | Workers             | Local              |
|                         | DNEL       | Long term Oral        | 0.148 mg/kg bw/day        | General population  | Systemic           |
|                         | DNEL       | Long term Dermal      | 0.25 mg/kg bw/day         | Workers             | Systemic           |
|                         | DNEL       | Long term Inhalation  | 0.43755 mg/m <sup>3</sup> | General population  | Systemic           |
|                         | DNEL       | Short term Dermal     | 1.2 mg/kg bw/day          | Workers             | Systemic           |
|                         | DNEL       | Long term Inhalation  | 1.76 mg/m <sup>3</sup>    | Workers             | Local              |
|                         | DNEL       | Long term Inhalation  | 1.76 mg/m <sup>3</sup>    | Workers             | Systemic           |
|                         | DNEL       | Short term Inhalation | 5.28 mg/m <sup>3</sup>    | Workers             | Systemic           |
|                         | DNEL       | Short term Inhalation | 13.53 mg/m <sup>3</sup>   | Workers             | Local              |

**PNECs**

| Product/ingredient name | Compartment Detail     | Value            | Method Detail |
|-------------------------|------------------------|------------------|---------------|
| 2-butoxyethanol         | Sewage Treatment Plant | 463 mg/l         | -             |
|                         | Soil                   | 2.33 mg/kg       | -             |
|                         | Marine water sediment  | 3.46 mg/kg       | -             |
|                         | Marine water           | 0.88 mg/l        | -             |
|                         | Fresh water            | 8.8 mg/l         | -             |
| butan-1-ol              | Fresh water sediment   | 34.6 mg/kg       | -             |
|                         | Fresh water            | 0.082 mg/l       | -             |
|                         | Marine water           | 0.0082 mg/l      | -             |
|                         | Fresh water sediment   | 0.324 mg/kg dwt  | -             |
|                         | Marine water sediment  | 0.0324 mg/kg dwt | -             |
|                         | Soil                   | 0.017 mg/kg dwt  | -             |
|                         | Sewage Treatment Plant | 2476 mg/l        | -             |

## SECTION 8: Exposure controls/personal protection

|                        |                        |            |   |
|------------------------|------------------------|------------|---|
| 2-dimethylaminoethanol | Fresh water            | 0.066 mg/l | - |
|                        | Marine water           | 0.007 mg/l | - |
|                        | Soil                   | 0.01 mg/kg | - |
|                        | Sewage Treatment Plant | 10 mg/l    | - |
|                        |                        |            |   |

### 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.

#### Skin protection

##### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : Duration / breakthrough time: <1 hour,  
Glove material: NBR, nitrile rubber, material thickness as splash protection: at least 0.2 mm, (EN374)  
Glove material: NBR, nitrile rubber Material thickness for short-term contact: at least 0.5 mm, (EN374)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

Expert judgment

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

**Environmental exposure controls** : Do not allow to enter drains or watercourses.

**SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**9.1 Information on basic physical and chemical properties****Appearance**

|   |                                       |
|---|---------------------------------------|
| <b>Physical state</b>                               | : Liquid.                             |
| <b>Colour</b>                                       | : Blue.                               |
| <b>Odour</b>  | : Not available.                      |
| <b>Odour threshold</b>                              | : Not available.                      |
| <b>Melting point/freezing point</b>                 | : Technically not possible to measure |
| <b>Initial boiling point and boiling range</b>      | : 100 to 100.1°C (212 to 212.2°F)     |
| <b>Flammability (solid, gas)</b>                    | : Not available.                      |
| <b>Upper/lower flammability or explosive limits</b> | : Not available.                      |
|   | Not available.                        |

|                                  |   |
|----------------------------------|---|
| <b>Flash point</b>               | : Closed cup: 54°C (129.2°F) [Product does not sustain combustion.] |
| <b>Auto-ignition temperature</b> | : 230°C (446°F)   |
| <b>Decomposition temperature</b> | : Not applicable.   |
| <b>pH</b>                        | : 7.2 to 8  |
| <b>Viscosity</b>                 | : Dynamic: >129 mPa·s<br>Kinematic: >118 mm <sup>2</sup> /s         |

**Solubility(ies)**

:

| Media      | Result  |
|------------|---------|
| cold water | Soluble |

|  |                            |
|--|----------------------------|
| <b>Solubility in water</b>                     | : Not available.           |
| <b>Miscible with water</b>                     | : Yes.                     |
| <b>Partition coefficient: n-octanol/ water</b> | : Not applicable.          |
| <b>Vapour pressure</b>                         | : 1.6 kPa (12.2 mm Hg)     |
| <b>Relative density</b>                        | : Not available.           |
| <b>Density</b>                                 | : 1.096 g/cm <sup>3</sup>  |
| <b>Vapour density</b>                          | : Not available.           |
| <b>Explosive properties</b>                    | : Not available.           |
| <b>Oxidising properties</b>                    | : Not available.           |
| <b>Weight volatiles</b>                        | : 74.7 % (w/w)             |
| <b>VOC content</b>                             | : 8.3 % (w/w) (2010/75/EU) |

**9.2 Other information****9.2.1 Information with regard to physical hazard classes**

Further information Not available.

**9.2.2 Other safety characteristics**

**Miscible with water** : Yes.

Further information Not available.

**room temperature (=20°C)**



**SECTION 10: Stability and reactivity**

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.  
Not applicable

**SECTION 11: Toxicological information****11.1 Information on toxicological effects**

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Acute toxicity**

| Product/ingredient name | Result                 | Species | Dose                    | Exposure |
|-------------------------|------------------------|---------|-------------------------|----------|
| 2-butoxyethanol         | LD50 Dermal            | Rat     | 2010 mg/kg              | -        |
|                         | LD50 Oral              | Rat     | 917 mg/kg               | -        |
| butan-1-ol              | LC50 Inhalation Vapour | Rat     | 24000 mg/m <sup>3</sup> | 4 hours  |
|                         | LD50 Dermal            | Rabbit  | 3400 mg/kg              | -        |
|                         | LD50 Oral              | Rat     | 790 mg/kg               | -        |
| 2-dimethylaminoethanol  | LC50 Inhalation Gas.   | Rat     | 1641 ppm                | 4 hours  |
|                         | LD50 Oral              | Rat     | 2 g/kg                  | -        |

**Acute toxicity estimates**

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|-------------------------|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| mixture                 | 13522.0      | N/A            | 517665.6                 | 247.6                       | N/A                                 |
| 2-butoxyethanol         | 1200         | 2010           | N/A                      | 11                          | N/A                                 |
| butan-1-ol              | 790          | 3400           | N/A                      | 24                          | N/A                                 |
| 2-dimethylaminoethanol  | 2000         | 1100           | 1641                     | N/A                         | N/A                                 |

**Irritation/Corrosion**

## SECTION 11: Toxicological information

| Product/ingredient name | Result                            | Species | Score | Exposure        | Observation |
|-------------------------|-----------------------------------|---------|-------|-----------------|-------------|
| 2-butoxyethanol         | Eyes - Moderate irritant          | Rabbit  | -     | 24 hours 100 mg | -           |
| butan-1-ol              | Skin - Mild irritant              | Rabbit  | -     | 500 mg          | -           |
|                         | Eyes - Cornea opacity             | Rabbit  | 2.11  | -               | 7 days      |
|                         | Eyes - Severe irritant            | Rabbit  | -     | 0.005 MI        | -           |
|                         | Eyes - Severe irritant            | Rabbit  | -     | 24 hours 2 mg   | -           |
| 2-dimethylaminoethanol  | Skin - Moderate irritant          | Rabbit  | -     | 24 hours 20 mg  | -           |
|                         | Eyes - Oedema of the conjunctivae | Rabbit  | 3     | -               | -           |
|                         | Eyes - Severe irritant            | Rabbit  | -     | 5 uL            | -           |
|                         | Skin - Mild irritant              | Rabbit  | -     | 445 mg          | -           |

### Sensitisation

### Mutagenicity

### Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

### Reproductive toxicity

### Teratogenicity

### Specific target organ toxicity (single exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| butan-1-ol              | Category 3 | -                 | Respiratory tract irritation |
| 2-dimethylaminoethanol  | Category 3 | -                 | Narcotic effects             |
|                         | Category 3 |                   | Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**SECTION 11: Toxicological information****Short term exposure****Potential immediate effects** : Not available.**Potential delayed effects** : Not available.**Long term exposure****Potential immediate effects** : Not available.**Potential delayed effects** : Not available.**Potential chronic health effects**

Not available.

**Conclusion/Summary** : Not available.**General** : No known significant effects or critical hazards.**Carcinogenicity** : No known significant effects or critical hazards.**Mutagenicity** : No known significant effects or critical hazards.**Reproductive toxicity** : No known significant effects or critical hazards.**Other information** : Not available.**SECTION 12: Ecological information****12.1 Toxicity**

| Product/ingredient name | Result                              | Species   | Exposure |
|-------------------------|-------------------------------------|---|----------|
| 2-butoxyethanol         | Acute EC50 >1000 mg/l Fresh water   | Daphnia - Water flea - <i>Daphnia magna</i>                       | 48 hours |
|                         | Acute LC50 800000 µg/l Marine water | Crustaceans - Common shrimp, sand shrimp - <i>Crangon crangon</i> | 48 hours |
|                         | Acute LC50 1250 ppm Marine water    | Fish - Inland silverside - <i>Menidia beryllina</i>               | 96 hours |
| butan-1-ol              | Acute EC50 1983 mg/l Fresh water    | Daphnia - Water flea - <i>Daphnia magna</i>                       | 48 hours |
|                         | Acute LC50 1730000 µg/l Fresh water | Fish - Fathead minnow - <i>Pimephales promelas</i>                | 96 hours |
| 2-dimethylaminoethanol  | Acute EC50 98.37 mg/l               | Daphnia   | 48 hours |
|                         | Acute LC50 146.63 mg/l Fresh water  | Fish  | 96 hours |

**Conclusion/Summary** : Not available.**12.2 Persistence and degradability**

| Product/ingredient name | Test   | Result                     | Dose | Inoculum |
|-------------------------|--|----------------------------|------|----------|
| 2-dimethylaminoethanol  | OECD 302C<br>Inherent<br>Biodegradability:<br>Modified MITI<br>Test (II) | 60.5 % - Readily - 28 days | -    | -        |

**Conclusion/Summary** : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| 2-dimethylaminoethanol  | -                 | -          | Readily          |

**12.3 Bioaccumulative potential**

| Product/ingredient name | LogP <sub>ow</sub> | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| 2-butoxyethanol         | 0.81               | -   | Low       |
| butan-1-ol              | 1                  | -   | Low       |
| 2-dimethylaminoethanol  | -0.55              | -   | Low       |

## SECTION 12: Ecological information

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

#### Waste catalogue

| Waste code | Waste designation   |
|------------|---|
| 08 01 19*  | aqueous suspensions containing paint or varnish containing organic solvents or other hazardous substances |

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | Waste catalogue  |
|-------------------|--|
|                   | 15 01 10* packaging containing residues of or contaminated by hazardous substances |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|  | ADR/RID        | ADN            | IMDG           | IATA           |
|--|----------------|----------------|----------------|----------------|
| <b>14.1 UN number</b>                  | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| <b>14.2 UN proper shipping name</b>    | -              | -              | -              | -              |
| <b>14.3 Transport hazard class(es)</b> | -              | -              | -              | -              |
| <b>14.4 Packing group</b>              | -              | -              | -              | -              |

Permahyd® Mixing Colour 285 FINE BLUE PEARL

## SECTION 14: Transport information

|                                   |     |     |     |     |
|-----------------------------------|-----|-----|-----|-----|
| <b>14.5 Environmental hazards</b> | No. | No. | No. | No. |
|-----------------------------------|-----|-----|-----|-----|

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

### UK (GB)/REACH

#### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** Not applicable.

### Seveso Directive

This product is not controlled under the Seveso Directive.

### National regulations

| Product/ingredient name | List name | Name on list | Classification | Notes |
|-------------------------|-----------|--------------|----------------|-------|
|                         |           |              |                |       |

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

🔍 Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
 GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = GB CLP-specific Hazard statement  
 N/A = Not available

Permahyd® Mixing Colour 285 FINE BLUE PEARL

## SECTION 16: Other information

PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 SGG = Segregation Group  
 vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification

| Classification     | Justification      |
|--------------------|--------------------|
| Eye Irrit. 2, H319 | Calculation method |

### Full text of abbreviated H statements

|      |  |
|------|--|
| H226 | Flammable liquid and vapour.             |
| H302 | Harmful if swallowed.                    |
| H312 | Harmful in contact with skin.            |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation.                  |
| H318 | Causes serious eye damage.               |
| H319 | Causes serious eye irritation.           |
| H331 | Toxic if inhaled.                        |
| H332 | Harmful if inhaled.                      |
| H335 | May cause respiratory irritation.        |
| H336 | May cause drowsiness or dizziness.       |

### Full text of classifications

|               |   |
|---------------|---|
| Acute Tox. 3  | ACUTE TOXICITY - Category 3                                   |
| Acute Tox. 4  | ACUTE TOXICITY - Category 4                                   |
| Eye Dam. 1    | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                |
| Eye Irrit. 2  | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                |
| Flam. Liq. 3  | FLAMMABLE LIQUIDS - Category 3                                |
| Skin Corr. 1B | SKIN CORROSION/IRRITATION - Category 1B                       |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2                        |
| STOT SE 3     | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |

Date of issue/ Date of revision : 4/27/2024

Version : 1.1

Date of previous issue : 3/3/2024

### Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.

Permahyd® Mixing Colour 285 FINE BLUE PEARL

## SECTION 16: Other information