

ECO Fiberglass Putty - Blue - 1.8kg MFE1.8

v.01-04.2012

Features :

This fiberglass putty is easy to work with and sand with P120-P150 grit. It can be used directly under the filler layer. This product is designed for use on steel, aluminum, and fiberglass-reinforced plastic. Ideal for hand or machine sanding. This product is also easy to work with on even surfaces, even in thick layers. It adheres very well to the surface and can be used on damaged surfaces.

Application :

The surface to be treated must be clean, degreased, matte, and dry. Mix the product thoroughly with 2-3% of the selected hardener. Once ready to use, apply within 5 minutes at a temperature of 20°C. If the temperature is too high, the pot life may be reduced and drying time may be accelerated.

Note : Be careful not to use too much hardener as this may cause discoloration of the top coat. It is not recommended to use the sealant at a temperature below 15°C.

Technical data :

VOC content : 2004/42/II(b)(250) <250

Fiberglass putty MFE1.8

Color : blue

Shelf life : 12 months Density: 1,75 g/cm³



Cleaning



Hardener	addition	Fiberglass putty 100 g
		BPO hardener 2-3 g



Filling 3 - 5 min.



Drying time 16 - 30 min.



Hand sanding / dry P120 - P320



Machine sanding 120 - P320



Store in cold place