

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Page 1/12

Printing date 08.09.2025

V- 4.0 (replaces version 3.0)

Revision: 29.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: CARROSS DURCISSEUR ULTIMATE MAT

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use: professional use.

Uses advised against: do-it-yourself use

Application of the substance / the mixture Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

CARROSS SAS

16 rue de Serrières

69540, Irigny, France

Tel +33 (0)1 60 27 20 19

contact@carross.eu

Further information obtainable from: contact@carross.eu

1.4 Emergency telephone number:

+33 (0)1 60 27 20 19 (8:30-18:00 du lundi au jeudi, 9:30-17 le vendredi)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 H226

Flammable liquid and vapour.



GHS07

Skin Sens. 1 H317

May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Warning

Hazard-determining components of labelling:

hexamethylene diisocyanate homopolymer

n-butyl acetate

tosyl isocyanate

Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

(Contd. on page 2)

Trade name: CARROSS DURCISSEUR ULTIMATE MAT

(Contd. of page 1)

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Determination of endocrine-disrupting properties

The product does not contain a substance included in the list established pursuant to Article 59(1) of Regulation (EC) No 1907/2006 as having endocrine disrupting properties or a substance that would be identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in a quantity $\geq 0.1\%$.

* **SECTION 3: Composition/information on ingredients**

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	50-100%
CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119485796-17	hexamethylene diisocyanate homopolymer ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	25-50%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10-<20%
CAS: 4083-64-1 EINECS: 223-810-8 Reg.nr.: 01-2119980050-47	tosyl isocyanate ⚠ Resp. Sens. 1, H334; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335, EUH014, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C $\geq 5\%$ STOT SE 3; H335: C $\geq 5\%$ Skin Irrit. 2; H315: C $\geq 5\%$	0.1-<1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out of danger area and lay down.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)

Trade name: CARROSS DURCISSEUR ULTIMATE MAT

(Contd. of page 2)

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

Hydrogen cyanide (HCN)

Vapours of isocyanates.

Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents.

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Do not allow to enter sewers/ surface or ground water.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

Information about storage in one common storage facility:

Store away from foodstuffs.

(Contd. on page 4)

Trade name: CARROSS DURCISSEUR ULTIMATE MAT

(Contd. of page 3)

Store away from oxidising agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

7.3 Specific end use(s) No further relevant information available.

* **SECTION 8: Exposure controls/personal protection**

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:	
123-86-4 n-butyl acetate	
WEL (Great Britain)	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
IOELV (EU)	Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm
108-65-6 2-methoxy-1-methylethyl acetate	
WEL (Great Britain)	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
IOELV (EU)	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin
4083-64-1 tosyl isocyanate	
WEL (Great Britain)	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO

Regulatory information

WEL (Great Britain): EH40/2020

IOELV (EU): (EU) 2019/1831

DNELs		
123-86-4 n-butyl acetate		
Dermal	DNEL	7 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	960 mg/m ³ (acute - systemic effects, workers) 960 mg/m ³ (acute - local effects, workers) 480 mg/m ³ (long-term - systemic effects, workers) 480 mg/m ³ (long-term - local effects, workers)
28182-81-2 hexamethylene diisocyanate homopolymer		
Inhalative	DNEL	1 mg/m ³ (acute - local effects, workers) 0.5 mg/m ³ (long-term - local effects, workers)
108-65-6 2-methoxy-1-methylethyl acetate		
Dermal	DNEL	153.5 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	275 mg/m ³ (long-term - systemic effects, workers)
4083-64-1 tosyl isocyanate		
Dermal	DNEL	0.92 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	3.24 mg/m ³ (long-term - systemic effects, workers)
PNECs		
123-86-4 n-butyl acetate		
PNEC	0.18 mg/l (freshwater environment) 0.018 mg/l (marine environment)	

(Contd. on page 5)

Trade name: CARROSS DURCISSEUR ULTIMATE MAT

(Contd. of page 4)

	0.36 mg/l (intermittent releases) 35.6 mg/l (sewage treatment plants) PNEC 0.981 mg/kg (freshwater sediment environment)
28182-81-2 hexamethylene diisocyanate homopolymer	
PNEC	0.127 mg/l (freshwater environment) 0.0127 mg/l (marine environment) 1.27 mg/l (intermittent releases) 38.3 mg/l (sewage treatment plants)
PNEC	266,700 mg/kg (freshwater sediment environment) 26,670 mg/kg (marine sediment environment) 53,182 mg/kg (soil)
108-65-6 2-methoxy-1-methylethyl acetate	
PNEC	0.635 mg/l (freshwater environment) 0.0635 mg/l (marine environment) 6.35 mg/l (intermittent releases) 100 mg/l (sewage treatment plants)
PNEC	3.29 mg/kg (freshwater sediment environment) 0.329 mg/kg (marine sediment environment)
4083-64-1 tosyl isocyanate	
PNEC	0.03 mg/l (freshwater environment) 0.003 mg/l (marine environment) 0.3 mg/l (intermittent releases) 0.4 mg/l (sewage treatment plants)
PNEC	0.0172 mg/kg (marine environment) 0.172 mg/kg (freshwater sediment environment) 0.0168 mg/kg (soil)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep ignition sources away - Do not smoke.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

A2/P2 filter (EN 14387)

Hand protection



Protective gloves

Check the permeability prior to each renewed use of the glove.

(Contd. on page 6)

Trade name: CARROSS DURCISSEUR ULTIMATE MAT

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

When choosing protective gloves, the breakthrough time, rate of penetration and degradation (EN 374) should be taken into account.

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

PVA gloves

Recommended material thickness: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Permeation level and breakthrough time: level 6 ≥ 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles (EN 166 / EN 170)

Body protection: Protective work clothing (EN 14325)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Liquid

Colour:

Colourless/light yellow

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

124 °C

Flammability

Flammable.

Lower and upper explosion limit

Lower:

1.2 Vol %

Upper:

15 Vol %

Flash point:

>23 °C

Decomposition temperature:

Not determined.

pH

Not applicable.

Viscosity:

Kinematic viscosity

Not determined.

Dynamic:

Not determined.

Solubility

water:

Reacts with water.

Partition coefficient n-octanol/water (log value)

Not determined.

Vapour pressure at 20 °C:

10.7 hPa

Density and/or relative density

Density at 20 °C:

0.96-0.97 g/cm³

Vapour density

Not determined.

9.2 Other information

Appearance:

Form:

Fluid

(Contd. on page 7)

Trade name: CARROSS DURCISSEUR ULTIMATE MAT

(Contd. of page 6)

Important information on protection of health and environment, and on safety.	
Ignition temperature:	Not determined.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No decomposition if used according to specifications.

10.2 Chemical stability No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Reacts with water.

Reacts with alkali, amines and strong acids.

Reacts with oxidising agents.

Fumes can combine with air to form an explosive mixture.

10.4 Conditions to avoid Protect from heat and direct sunlight.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Formation of toxic gases is possible during heating or in case of fire.

*

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
123-86-4 n-butyl acetate		
Oral	LD50	10,760 mg/kg (rat)
Dermal	LD50	>14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	23.4 mg/l (rat)
28182-81-2 hexamethylene diisocyanate homopolymer		
Oral	LD50	>2,500 mg/kg (rat)

(Contd. on page 8)

Trade name: CARROSS DURCISSEUR ULTIMATE MAT

(Contd. of page 7)

Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	ATE	1.5 mg/l (dust/ mist)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/6 h	4,345 mg/l (rat)
4083-64-1 tosyl isocyanate		
Oral	LD50	2,330 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties
None of the ingredients is listed.

* **SECTION 12: Ecological information**

12.1 Toxicity

Aquatic toxicity:	
123-86-4 n-butyl acetate	
LC50/96 h	18 mg/l (fish)
TT/16 h	115 mg/l (microorganisms)
EC50/48 h	44 mg/l (daphnia)
EC50/72 h	675 mg/l (algae)
108-65-6 2-methoxy-1-methylethyl acetate	
LC50/96 h	>100 mg/l (fish)
EC50/48 h	>500 mg/l (Daphnia magna)
EC20/30 min	>1,000 mg/l (microorganisms)
EC50/72 h	>1,000 mg/l (algae)
EC50	>100 mg/l (algae)
	>100 mg/l (fish)
	>100 mg/l (Daphnia magna)
4083-64-1 tosyl isocyanate	
EC50/48 h	>100 mg/l (Daphnia magna)
EC50/72 h	30 mg/l (algae)
LC50/48 h	>45 mg/l (fish)
12.2 Persistence and degradability	
123-86-4 n-butyl acetate	
Biodegradation	83 % (readily biodegradable) (OECD 301 D, 28 d, aerobic)

(Contd. on page 9)

Trade name: CARROSS DURCISSEUR ULTIMATE MAT

(Contd. of page 8)

28182-81-2 hexamethylene diisocyanate homopolymer	
Biodegradation	1 % (not readily biodegradable) (OECD 301 C, 28 d, aerobic)
108-65-6 2-methoxy-1-methylethyl acetate	
Biodegradation	100 % (readily biodegradable) (OECD 302 B, 8 d, aerobic)
4083-64-1 tosyl isocyanate	
Biodegradation	86 % (readily biodegradable) (OECD 301 D, 28 d, aerobic)
12.3 Bioaccumulative potential	
123-86-4 n-butyl acetate	
BCF	15.3 (-)
log Pow	2.3
28182-81-2 hexamethylene diisocyanate homopolymer	
BCF	3.2 (-)
log Kow	9.81 (Kow)
108-65-6 2-methoxy-1-methylethyl acetate	
log Pow	0.56
12.4 Mobility in soil	
123-86-4 n-butyl acetate	
log Koc	1.27
108-65-6 2-methoxy-1-methylethyl acetate	
Koc	1.7

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	1263 PAINT RELATED MATERIAL
IMDG, IATA	PAINT RELATED MATERIAL

(Contd. on page 10)

Trade name: CARROSS DURCISSEUR ULTIMATE MAT

(Contd. of page 9)

14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
	
Class	3
Label	3
14.4 Packing group	
ADR, IMDG, IATA	
II	
14.5 Environmental hazards:	
Not applicable.	
Marine pollutant (IMDG):	
No	
14.6 Special precautions for user	
Warning: Flammable liquids.	
Hazard identification number (Kemler code): 33	
EMS Number:	
F-E, S-E	
Stowage Category	
B	
14.7 Maritime transport in bulk according to IMO instruments	
Not applicable.	
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	1L
UN "Model Regulation":	
UN 1263 PAINT RELATED MATERIAL, 3, II	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act

Regulated explosives precursors
None of the ingredients is listed.
Regulated poisons
None of the ingredients is listed.
Reportable explosives precursors
None of the ingredients is listed.
Reportable poisons
None of the ingredients is listed.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 11)

Trade name: CARROSS DURCISSEUR ULTIMATE MAT

(Contd. of page 10)

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The above information is based on currently available data characterising the product. They do not constitute a guarantee or quality specification. It should be regarded as a guideline for safe use, storage, transport, disposal in case of release into the environment. It is the responsibility of the user to create conditions for the safe use of the product and the user accepts responsibility for any consequences resulting from improper use of this product.

Relevant phrases

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

EUH014 Reacts violently with water.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids

Bridging principles

Skin sensitisation

Specific target organ toxicity (single exposure)

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Version number of previous version: 3.0

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)

Trade name: CARROSS DURCISSEUR ULTIMATE MAT

(Contd. of page 11)

ELINCS: European List of Notified Chemical Substances

CAS: chemical number assigned to the chemical in the Chemical Abstracts Service list

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration

LC50: median lethal concentration

LD50: lethal dose 50%

PBT: persistent, bioaccumulative and toxic

vPvB: very persistent and very bioaccumulative

Flam. Liq. 3: Flammable liquid substance. Hazard category 3

Acute Tox. 4: Acute toxicity. Hazard category 4

Skin Irrit. 2: Skin corrosion/irritation. Hazard category 2

Eye Irrit. 2: Serious eye damage/eye irritation. Hazard category 2

Resp. Sens. 1: Respiratory sensitisation. Hazard category 1

Skin Sens. 1: Skin sensitisation. Hazard category 1

STOT SE 3: Toxic effects on target organs - single exposure. Hazard category 3

Sources European Chemicals Agency, <http://echa.europa.eu/>

*** Data compared to the previous version altered.**