# **SAFETY DATA SHEET**



MM 962 WaterBase 900+ Series Mica Green

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : MM 962 WaterBase 900+ Series Mica Green

Product code : 9962

Product description : Not available.

Product type : Liquid.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Professional spray painting, near-industrial setting

Use in coatings - Basecoat

#### **Uses advised against**

Not applicable.

#### 1.3 Details of the supplier of the safety data sheet

Valspar b.v.

Zuiveringweg 89

8243 PE Lelystad

The Netherlands

tel: +31 (0)320 292200

e-mail address of person

: msds@valspar.com

responsible for this SDS

#### **National contact**

Sherwin-Williams UK Limited

Avenue One Station Lane, Witney, United Kingdom

Oxfordshire OX28 4XR

#### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : UK: 0-800-014-8126

CALL: +(44)-870-8200418 (Hours of operation - 24 hours)

<u>Supplier</u>

**Telephone number** : Call: +31 (0)320 292200 (8:30AM - 5PM)

#### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Skin Sens. 1, H317

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms



Signal word : Warning

Date of issue/Date of revision : 10/25/2023 Date of previous issue : 2/7/2023 Version : 1 1/17

#### **SECTION 2: Hazards identification**

**Hazard statements** 

: May cause an allergic skin reaction.

**Precautionary statements** 

**Prevention** 

: Wear protective gloves. Avoid breathing vapour or spray.

Response

: Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.

Storage : Not applicable.

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Supplemental label elements

entai label

: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

#### **Special packaging requirements**

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification

: None known.

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

| Product/ingredient name                   | Identifiers   | %     | Classification  | Type    |
|---|---|-------|---|---------|
| 2-butoxyethanol                           | REACH #:<br>01-2119475108-36<br>EC: 203-905-0<br>CAS: 111-76-2<br>Index: 603-014-00-0 | <10   | Acute Tox. 4, H302<br>Acute Tox. 3, H331<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319   | [1] [2] |
| 2,4,7,9-tetramethyldec-5-yne-<br>4,7-diol | REACH #:<br>01-2119954390-39<br>EC: 204-809-1<br>CAS: 126-86-3                        | ≤0.3  | Eye Dam. 1, H318<br>Skin Sens. 1B, H317<br>Aquatic Chronic 3,<br>H412   | [1]     |
| (2-methoxymethylethoxy)propanol           | REACH #:<br>01-2119450011-60<br>EC: 252-104-2<br>CAS: 34590-94-8                      | ≤0.3  | Not classified.   | [2]     |
| tin dioxide                               | REACH #:<br>01-2119946062-44<br>EC: 242-159-0<br>CAS: 18282-10-5                      | ≤0.1  | Not classified.   | [2]     |
| 3(2H)-Isothiazolone, 2-methyl-            | REACH #:<br>01-2120764690-50<br>EC: 220-239-6<br>CAS: 2682-20-4                       | <0.01 | Acute Tox. 3, H301<br>Acute Tox. 3, H311<br>Acute Tox. 2, H330<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1A, H317<br>Aquatic Acute 1, H400<br>(M=10)<br>Aquatic Chronic 1, | [1]     |

Date of issue/Date of revision : 10/25/2023 Date of previous issue : 2/7/2023 Version : 1 2/17

| MM 962 WaterBase 900+ Series Mica Green |  |
|---|--|
| SECTION 3: Composition/information      | on on ingredients  |
|   | H410 (M=1)<br>EUH071   |
|   | See Section 16 for the full text of the H statements declared above. |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### **Over-exposure signs/symptoms**

**Eye contact** : No specific data. **Inhalation** : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

Date of issue/Date of revision : 10/25/2023 Date of previous issue : 2/7/2023 Version : 1 3/17

# SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide metal oxide/oxides

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

# **6.2 Environmental precautions**

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# 6.4 Reference to other sections

See Section 1 for emergency contact information.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 13 for additional waste treatment information.

Date of issue/Date of revision : 10/25/2023 Date of previous issue : 2/7/2023 Version : 1 4/17

# SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

# SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name         | Exposure limit values                                  |  |  |  |
|---------------------------------|--|--|--|--|
| 2-butoxyethanol                 | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed |  |  |  |
| ,                               | through skin.  |  |  |  |
|                                 | STEL: 50 ppm 15 minutes.                               |  |  |  |
|                                 | TWA: 25 ppm 8 hours.                                   |  |  |  |
|                                 | STEL: 246 mg/m³ 15 minutes.                            |  |  |  |
|                                 | TWA: 123 mg/m³ 8 hours.                                |  |  |  |
| (2-methoxymethylethoxy)propanol | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed |  |  |  |
|                                 | through skin.  |  |  |  |
|                                 | TWA: 308 mg/m³ 8 hours.                                |  |  |  |
|                                 | TWA: 50 ppm 8 hours.                                   |  |  |  |
| tin dioxide                     | EH40/2005 WELs (United Kingdom (UK), 1/2020). [tin     |  |  |  |
|                                 | compounds, inorganic except SnH4 as Sn]                |  |  |  |
|                                 | STEL: 4 mg/m³, (as Sn) 15 minutes.                     |  |  |  |
|                                 | TWA: 2 mg/m³, (as Sn) 8 hours.                         |  |  |  |

Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Date of issue/Date of revision: 10/25/2023Date of previous issue: 2/7/2023Version: 15/17

# SECTION 8: Exposure controls/personal protection

| Product/ingredie        | ent name T        | Гуре         | Exposure                               | Value  | Population                          | Effects           |
|-------------------------|-------------------|--------------|--|--|-------------------------------------|-------------------|
| 2-butoxyethanol         | D                 | NEL          | Long term Oral                         | 6.3 mg/kg  | General                             | Systemic          |
|                         | D                 | NEL          | Short term Oral                        | bw/day<br>26.7 mg/                               | population<br>General               | Systemic          |
|                         | D                 | NEL          | Long term                              | kg bw/day<br>59 mg/m³                            | population<br>General               | Systemic          |
|                         | D                 | NEL          | Inhalation<br>Long term                | 98 mg/m³   | population<br>Workers               | Systemic          |
|                         | D                 | NEL          | Inhalation<br>Short term<br>Inhalation | 147 mg/m³  | General population                  | Local             |
|                         | D                 | NEL          | Short term<br>Inhalation               | 246 mg/m³  | Workers                             | Local             |
|                         | D                 | NEL          | Short term<br>Inhalation               | 426 mg/m³  | General population                  | Systemic          |
|                         | D                 | NEL          | Short term<br>Inhalation               | 1091 mg/<br>m³                                   | Workers                             | Systemic          |
| 2,4,7,9-tetramethyldec  | -5-yne-4,7-diol D | NEL          | Long term Oral                         | 0.25 mg/   | General                             | Systemic          |
|                         | D                 | NEL          | Long term Dermal                       | kg bw/day<br>0.25 mg/<br>kg bw/day               | population<br>General<br>population | Systemic          |
|                         | D                 | NEL          | Long term<br>Inhalation                | 0.43 mg/m <sup>3</sup>                           | General population                  | Systemic          |
|                         |                   | NEL          | Long term Dermal                       | 0.5 mg/kg<br>bw/day                              | Workers                             | Systemic          |
|                         |                   | NEL  <br>NEL | Short term Oral                        | 0.75 mg/<br>kg bw/day                            | General<br>population<br>General    | Systemic          |
|                         |                   |              | Short term Dermal                      | 0.75 mg/<br>kg bw/day                            | population                          | Systemic          |
|                         |                   | NEL          | Short term<br>Inhalation               | 1.29 mg/m³                                       | General population                  | Systemic          |
|                         |                   | NEL          | Short term Dermal                      | 1.5 mg/kg<br>bw/day                              | Workers                             | Systemic          |
|                         |                   | NEL NEL      | Long term<br>Inhalation<br>Short term  | 1.76 mg/m <sup>3</sup><br>5.28 mg/m <sup>3</sup> |                                     | Systemic Systemic |
| (2 mothov/mothylotho    |                   |              | Inhalation Long term Oral              | 36 mg/kg   | General                             |                   |
| (2-methoxymethyletho    | ху)ргорапог Б     | /INLL        | Long term Oral                         | bw/day   | population<br>[Consumers]           | Systemic          |
|                         |                   |              | Long term Oral                         | 36 mg/kg<br>bw/day                               | General population                  | Systemic          |
|                         |                   |              | Long term<br>Inhalation                | 37.2 mg/m³                                       | General population                  | Systemic          |
|                         |                   |              | Long term Dermal                       | 121 mg/kg<br>bw/day                              | General population                  | Systemic          |
|                         |                   |              | Long term Dermal                       | 283 mg/kg<br>bw/day                              | Workers                             | Systemic          |
|                         |                   | NEL          | Long term<br>Inhalation                | 308 mg/m³  | Workers                             | Systemic          |
| 3(2H)-Isothiazolone, 2- |                   | NEL          | Long term<br>Inhalation                | 0.021 mg/<br>m³                                  | Workers                             | Local             |
|                         |                   | NEL          | Short term<br>Inhalation               | 0.043 mg/<br>m³                                  | Workers                             | Local             |
|                         | D                 | NEL          | Long term<br>Inhalation                | 0.021 mg/<br>m³                                  | General population                  | Local             |
|                         | D                 | NEL          | Short term<br>Inhalation               | 0.043 mg/<br>m³                                  | [Consumers] General population      | Local             |
|                         | D                 | NEL          | Long term Oral                         | 0.027 mg/<br>kg bw/day                           | [Consumers] General population      | Systemic          |
|                         | D                 | NEL          | Short term Oral                        | 0.053 mg/  | [Consumers]<br>General              | Systemic          |

Date of issue/Date of revision : 10/25/2023 Date of previous issue : 2/7/2023 Version : 1 6/17

## **SECTION 8: Exposure controls/personal protection**

|  |  | kg bw/day | population  | - |
|--|--|-----------|-------------|---|
|  |  |           | [Consumers] |   |

#### **PNECs**

| Product/ingredient name               | Compartment Detail        | Value           | Method Detail            |
|---------------------------------------|---------------------------|-----------------|--------------------------|
| 2-butoxyethanol                       | Fresh water               | 8.8 mg/l        | -                        |
| -                                     | Marine water              | 0.88 mg/l       | -                        |
|                                       | Sewage Treatment Plant    | 463 mg/l        | -                        |
|                                       | Fresh water sediment      | 34.6 mg/kg dwt  | -                        |
|                                       | Marine water sediment     | 3.46 mg/kg dwt  | -                        |
|                                       | Soil                      | 2.33 mg/kg dwt  | -                        |
|                                       | Secondary Poisoning       | 20 mg/kg        | -                        |
| 2,4,7,9-tetramethyldec-5-yne-4,7-diol | Fresh water               | 0.04 mg/l       | -                        |
|                                       | Marine water              | 0.004 mg/l      | -                        |
|                                       | Sewage Treatment          | 7 mg/l          | -                        |
|                                       | Plant                     |                 |                          |
|                                       | Fresh water sediment      | 0.32 mg/kg dwt  | -                        |
|                                       | Marine water sediment     | 0.032 mg/kg dwt | -                        |
|                                       | Soil                      | 0.028 mg/kg dwt | -                        |
| (2-methoxymethylethoxy)propanol       | Fresh water               | 19 mg/l         | Assessment Factors       |
|                                       | Marine water              | 1.9 mg/l        | Assessment Factors       |
|                                       | Sewage Treatment<br>Plant | 4168 mg/l       | Assessment Factors       |
|                                       | Fresh water sediment      | 70.2 mg/kg dwt  | Equilibrium Partitioning |
|                                       | Marine water sediment     | 7.02 mg/kg dwt  | Equilibrium Partitioning |
|                                       | Soil                      | 2.74 mg/kg dwt  | Equilibrium Partitioning |
| tin dioxide                           | Fresh water               | 0.1 mg/l        | Assessment Factors       |
|                                       | Marine water              | 0.01 mg/l       | Assessment Factors       |
|                                       | Sewage Treatment          | 100 mg/l        | Assessment Factors       |
|                                       | Plant                     |                 |                          |
| 3(2H)-Isothiazolone, 2-methyl-        | Fresh water               | 3.39 µg/l       | Assessment Factors       |
| •                                     | Marine water              | 3.39 µg/l       | Assessment Factors       |
|                                       | Sewage Treatment          | 0.23 mg/l       | Assessment Factors       |
|                                       | Plant                     |                 |                          |
|                                       | Soil                      | 0.047 mg/kg dwt | Assessment Factors       |

#### 8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: chemical splash goggles and/or face shield.

# Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Recommended EN 374 foil butyl rubber fluor rubber

Date of issue/Date of revision : 10/25/2023 Date of previous issue : 2/7/2023 Version : 1 7/17

# SECTION 8: Exposure controls/personal protection

>= 0.7 mm

< 1 hour (breakthrough time): Conditionally suitable materials for protective gloves; EN 374: Nitrile rubber - NBR (>= 0.35 mm). Only suitable as splash protection. Only suitable for brief exposure. In the event of contamination, change protective gloves

immediately.

Personal protective equipment for the body should be selected based on the task **Body protection** 

being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Cotton or cotton/synthetic overalls or

coveralls are normally suitable.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

**Respiratory protection** Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a

respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: EN 405:2001 + A1:2009 organic vapour (Type A)

and particulate filter FFA2P3 R D

**Environmental exposure** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment

will be necessary to reduce emissions to acceptable levels.

# SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Colour Green.

: Characteristic. Odour **Odour threshold** Not available. **Melting point/freezing point** : Not applicable. Initial boiling point and boiling : 100°C (212°F)

range

Flammability (solid, gas) : Not available. Upper/lower flammability or Lower: 1.1% explosive limits Upper: 10.6%

Flash point : Closed cup: >93.3°C (>199.9°F)

**Auto-ignition temperature** : 230°C (446°F) **Decomposition temperature** : Not applicable.

pН : 7.9 to 8.1 [Conc. (% w/w): 100%] **Viscosity** : Kinematic (40°C): >20.5 mm<sup>2</sup>/s

Solubility(ies)

| Media                   | Result                 |
|-------------------------|------------------------|
| cold water<br>hot water | Soluble Easily soluble |

Solubility in water : Not applicable.

Miscible with water : Yes.

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure : 2.3 kPa (17.5 mm Hg) **Evaporation rate** : 89 (butyl acetate = 1)

**Relative density** : 1.053

: 1.053 g/cm<sup>3</sup> Density Vapour density : 1 [Air = 1]

Date of issue/Date of revision : 10/25/2023 Date of previous issue : 2/7/2023 Version: 1 8/17

## **SECTION 9: Physical and chemical properties**

Explosive properties : Not available.

Oxidising properties : Not available.

**Particle characteristics** 

**Median particle size** : Not applicable.

9.2 Other information

**Heat of combustion** : 3.086 kJ/g

# **SECTION 10: Stability and reactivity**

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

**10.5 Incompatible materials**: No specific data.

**10.6 Hazardous** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

| Product/ingredient name | Result               | Species | Dose        | Exposure |
|-------------------------|----------------------|---------|-------------|----------|
| 2-butoxyethanol         | LC50 Inhalation Gas. | Rat     | 450 ppm     | 4 hours  |
|                         | LD50 Dermal          | Rabbit  | 220 mg/kg   | -        |
|                         | LD50 Dermal          | Rat     | >2000 mg/kg | -        |
|                         | LD50 Oral            | Rat     | 250 mg/kg   | -        |
| 2,4,7,9-tetramethyldec- | LD50 Dermal          | Rabbit  | >2000 mg/kg | -        |
| 5-yne-4,7-diol          |                      |         |             |          |
|                         | LD50 Oral            | Rat     | >1860 mg/kg | -        |
| tin dioxide             | LD50 Oral            | Rat     | >20 g/kg    | -        |
| 3(2H)-Isothiazolone,    | LD50 Oral            | Rat     | 2131 mg/kg  | -        |
| 2-methyl-               |                      |         |             |          |

Conclusion/Summary : Not available.

#### **Acute toxicity estimates**

| Product/ingredient name                 | Oral (mg/<br>kg) | Dermal<br>(mg/kg) | Inhalation<br>(gases)<br>(ppm) | Inhalation<br>(vapours)<br>(mg/l) | Inhalation<br>(dusts<br>and mists)<br>(mg/l) |
|---|------------------|-------------------|--------------------------------|-----------------------------------|--|
| MM 962 WaterBase 900+ Series Mica Green | 13381.7          | N/A               | N/A                            | 33.5                              | N/A  |
| 2-butoxyethanol                         | 1200             | N/A               | N/A                            | 3                                 | N/A  |
| 3(2H)-Isothiazolone, 2-methyl-          | 100              | 300               | N/A                            | 0.5                               | N/A  |

**Irritation/Corrosion** 

Date of issue/Date of revision : 10/25/2023 Date of previous issue : 2/7/2023 Version : 1 9/17

# **SECTION 11: Toxicological information**

| Product/ingredient name       | Result                   | Species | Score | Exposure     | Observation |
|-------------------------------|--------------------------|---------|-------|--------------|-------------|
| 2-butoxyethanol               | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 100 | -           |
|                               |                          |         |       | mg           |             |
|                               | Eyes - Severe irritant   | Rabbit  | -     | 100 mg       | -           |
|                               | Skin - Mild irritant     | Rabbit  | -     | 500 mg       | -           |
| 2,4,7,9-tetramethyldec-5-yne- | Eyes - Severe irritant   | Rabbit  | -     | 0.1 MI       | -           |
| 4,7-diol                      |                          |         |       |              |             |
|                               | Skin - Mild irritant     | Rabbit  | -     | 0.5 gm       | -           |
| (2-methoxymethylethoxy)       | Eyes - Mild irritant     | Human   | -     | 8 mg         | -           |
| propanol                      |                          |         |       |              |             |
|                               | Eyes - Mild irritant     | Rabbit  | -     | 24 hours 500 | -           |
|                               |                          |         |       | mg           |             |
|                               | Skin - Mild irritant     | Rabbit  | -     | 500 mg       | -           |

**Conclusion/Summary** 

: Not available.

**Sensitisation** 

**Conclusion/Summary**: Not available.

**Mutagenicity** 

**Conclusion/Summary**: Not available.

**Carcinogenicity** 

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

**Conclusion/Summary**: Not available.

**Reproductive toxicity** 

Conclusion/Summary : Not available.

**Teratogenicity** 

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

**Aspiration hazard** 

Not available.

Information on likely routes

of exposure

: Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion** : No specific data.

<u>Delayed and immediate effects as well as chronic effects from short and long-term exposure</u>

<u>Short term exposure</u>

Date of issue/Date of revision: 10/25/2023Date of previous issue: 2/7/2023Version: 110/17

## **SECTION 11: Toxicological information**

**Potential immediate** 

effects

: Not available.

Potential delayed effects

: Not available.

**Long term exposure** 

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

| Product/ingredient name          | Result                              | Species   | Exposure |
|----------------------------------|-------------------------------------|---|----------|
| 2-butoxyethanol                  | Acute EC50 911 mg/l                 | Algae - Pseudokrichneriella                         | 72 hours |
|                                  |                                     | subcapitata   |          |
|                                  | Acute EC50 1550 mg/l                | Daphnia - <i>Daphnia magna</i>                      | 48 hours |
|                                  | Acute LC50 800000 µg/l Marine water | Crustaceans - Common shrimp,                        | 48 hours |
|                                  |                                     | sand shrimp - Crangon crangon                       |          |
|                                  | Acute LC50 1250 ppm Marine water    | Fish - Inland silverside - <i>Menidia</i> beryllina | 96 hours |
|                                  | Chronic NOEC 100 mg/l               | Daphnia - <i>Daphnia magna</i>                      | 21 days  |
|                                  | Chronic NOEC >100 mg/l              | Fish - Brachydanio rerio                            | 21 days  |
| 2,4,7,9-tetramethyldec-          | Acute EC50 82 mg/l                  | Algae - Selenastrum                                 | 72 hours |
| 5-yne-4,7-diol                   |                                     | capricornutum                                       |          |
|                                  | Acute EC50 91 mg/l                  | Daphnia - <i>Daphnia magna</i>                      | 48 hours |
|                                  | Acute LC50 36 mg/l                  | Fish - Elrits Pimephales                            | 96 hours |
| (2-methoxymethylethoxy) propanol | Acute EC50 >1000 mg/l               | Daphnia   | 48 hours |
|                                  | Acute LC50 >1000 mg/l               | Fish  | 96 hours |
| tin dioxide                      | Acute EC50 >100 mg/l                | Daphnia - Daphnia magna                             | 48 hours |
|                                  | Acute NOEC >100 mg/l                | Daphnia - <i>Daphnia magna</i>                      | 48 hours |
| 3(2H)-Isothiazolone,             | Acute EC50 0.157 mg/l               | Algae - pseudokirchneriella                         | 72 hours |
| 2-methyl-                        |                                     | subcapitata   |          |
| ,                                | Acute EC50 1.68 mg/l                | Daphnia   | 48 hours |
|                                  | Acute LC50 6 mg/l                   | Fish  | 96 hours |
|                                  | Chronic NOEC 0.03 mg/l              | Algae - pseudokirchneriella                         | 72 hours |
|                                  |                                     | subcapitata   |          |
|                                  | Chronic NOEC 0.55 mg/l              | Daphnia   | 21 days  |
|                                  | Chronic NOEC 2.38 mg/l              | Fish  | 28 days  |

**Conclusion/Summary** : Not available.

#### 12.2 Persistence and degradability

| Product/ingredient name | Test | Result                     | Dose | Inoculum |
|-------------------------|------|----------------------------|------|----------|
| 2-butoxyethanol         | -    | 90.4 % - Readily - 28 days | -    | -        |

Conclusion/Summary : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| 2-butoxyethanol         | -                 | -          | Readily          |

Date of issue/Date of revision : 10/25/2023 Date of previous issue : 2/7/2023 Version : 1 11/17

# **SECTION 12: Ecological information**

#### 12.3 Bioaccumulative potential

| Product/ingredient name                                | LogPow        | BCF | Potential |
|--|---------------|-----|-----------|
| 2-butoxyethanol<br>(2-methoxymethylethoxy)<br>propanol | 0.81<br>0.004 | -   | Low       |

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### **Product**

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

<u>Packaging</u>

**Methods of disposal** 

: The classification of the product may meet the criteria for a hazardous waste.

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

|                                  | ADR/RID        | ADN            | IMDG           | IATA           |
|----------------------------------|----------------|----------------|----------------|----------------|
| 14.1 UN number                   | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name     | -              | -              | -              | -              |
| 14.3 Transport hazard class(es)  | -              | -              | -              | -              |
| 14.4 Packing group               | -              | -              | -              | -              |
| 14.5<br>Environmental<br>hazards | No.            | No.            | No.            | No.            |

Date of issue/Date of revision : 10/25/2023 Date of previous issue : 2/7/2023 Version : 1 12/17

## **SECTION 14: Transport information**

14.6 Special precautions for user

: **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

**Prior Informed Consent (PIC)** 

Not listed.

**Persistent Organic Pollutants** 

Not listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

**EU regulations** 

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Air

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

<u>International regulations</u>

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Date of issue/Date of revision: 10/25/2023Date of previous issue: 2/7/2023Version: 113/17

# **SECTION 15: Regulatory information**

Not listed.

**Inventory list** 

**New Zealand** 

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

**Eurasian Economic Union**: Russian Federation inventory: Not determined.

Japan : Japan inventory (CSCL): At least one component is not listed.

apair inventory (OUL). At least one component is not in

Japan inventory (ISHL): Not determined.: All components are listed or exempted.

Philippines : Not determined.

**Republic of Korea** : All components are listed, exempted, or notified.

Taiwan : Not determined.
Thailand : Not determined.
Turkey : Not determined.
United States : Not determined.
Viet Nam : Not determined.

15.2 Chemical safety :

assessment req

: This product contains substances for which Chemical Safety Assessments are still

required.

#### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate

GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and

Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019

No. 720 and amendments

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = GB CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification

| Classification     | Justification      |  |
|--------------------|--------------------|--|
| Skin Sens. 1, H317 | Calculation method |  |

#### Full text of abbreviated H statements

| H301   | Toxic if swallowed.                                   |  |
|--------|---|--|
| H302   | Harmful if swallowed.                                 |  |
| H311   | Toxic in contact with skin.                           |  |
| H314   | Causes severe skin burns and eye damage.              |  |
| H315   | Causes skin irritation.                               |  |
| H317   | May cause an allergic skin reaction.                  |  |
| H318   | Causes serious eye damage.                            |  |
| H319   | Causes serious eye irritation.                        |  |
| H330   | Fatal if inhaled.                                     |  |
| H331   | Toxic if inhaled.                                     |  |
| H400   | Very toxic to aquatic life.                           |  |
| H410   | Very toxic to aquatic life with long lasting effects. |  |
| H412   | Harmful to aquatic life with long lasting effects.    |  |
| EUH071 | Corrosive to the respiratory tract.                   |  |

#### **Full text of classifications**

Date of issue/Date of revision: 10/25/2023Date of previous issue: 2/7/2023Version: 114/17

#### **SECTION 16: Other information**

Acute Tox. 2
Acute Tox. 3
Acute Tox. 4
Aquatic Acute 1
Aquatic Chronic 1

ACUTE TOXICITY - Category 2
ACUTE TOXICITY - Category 3
ACUTE TOXICITY - Category 4
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category

Aquatic Chronic 1
Aquatic Chronic 1
Aquatic Chronic 3
Eye Dam. 1
Eye Irrit. 2

SHOKT-TERM (ACOTE) AQUATIC HAZARD - Category 1
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2

Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2

Skin Sens. 1 SKIN SENSITISATION - Category 1
Skin Sens. 1A SKIN SENSITISATION - Category 1A
Skin Sens. 1B SKIN SENSITISATION - Category 1B

Date of printing : 10/31/2023 Date of issue/ Date of : 10/25/2023

revision

Date of previous issue : 2/7/2023

Version : 1

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 10/25/2023 Date of previous issue : 2/7/2023 Version : 1 15/17

# SUMI Safe Use of Mixtures Information for end-users



Title : Professional spray painting, near-industrial setting

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

## General description of the process covered

Indoor spray painting by professionals with efficient ventilation such as spray booth or local exhaust ventilation

# **Operational conditions**

Place of use : Indoor use

## Risk management measures (RMM)

| Contributing activity   | Process category (ies) | Maximum duration   | Ventilation                             |                                       |
|---|------------------------|--|---|---------------------------------------|
|   |                        |  | Туре                                    | ach (air changes per hour)            |
| Preparation of material for application                                     | PROC05                 | More than 4 hours  | Enhanced (mechanical) room ventilation  | 5 - 10                                |
| Loading of application equipment and handling of coated parts before curing | PROC08a                | More than 4 hours  | Enhanced (mechanical) room ventilation  | 5 - 10                                |
| Professional application of coatings and inks by spraying                   | PROC11                 | More than 4 hours  | Local exhaust ventilation               | Refer to relevant technical standards |
| Film formation - force drying, stoving and other technologies               | PROC04                 | More than 4 hours  | Enhanced (mechanical) room ventilation  | Refer to relevant technical standards |
| Cleaning  | PROC05                 | More than 4 hours  | Enhanced (mechanical) room ventilation  | 5 - 10                                |
| Waste management  | PROC08a                | More than 4 hours  | Enhanced (mechanical) room ventilation  | 5 - 10                                |
| Contributing activity   | Process category (ies) | Respiratory  | Eye                                     | Hands                                 |
| Preparation of material for application                                     | PROC05                 | None   | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Loading of application equipment and handling of coated parts before curing | PROC08a                | None   | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Professional application of coatings and inks by spraying                   | PROC11                 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Film formation - force drying, stoving and other technologies               | PROC04                 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | None                                    | None                                  |
| Cleaning  | PROC05                 | None   | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Waste management  | PROC08a                | None   | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |

See chapter 8 of this Safety Data Sheet for specifications.

CEPE\_PW\_01 Version: 1 Date of issue: 2/1/2017







#### **Disclaimer**

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.