



# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product identifier** : AM63  
**Product name** : Centari® Mastertint® Transparent Magenta  
**Product type** : Liquid.  
**Other means of identification** : 1250073557; 1250091831  
**Date of issue/ Date of revision** : 24 April 2024  
**Version** : 1.03  
**Date of previous issue** : 3 November 2023

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** : Coating component.  
**Uses advised against** : Not for sale to or use by consumers.

### 1.3 Details of the supplier of the safety data sheet

Axalta Coating Systems Germany GmbH & Co. KG  
Christbusch 25  
DE 42285 Wuppertal  
+49 (0)202 529-0

**e-mail address of person responsible for this SDS** : sds-competence@axalta.com

Axalta Coating Systems UK Ltd.  
Unit 1, Quadrant Park, Mundells  
GB Welwyn Garden City, Hertfordshire, AL7 1FS  
+44 (0)1707 518 000

### 1.4 Emergency telephone number

#### Supplier

**Telephone number** : +(44)-870-8200418  
**Hours of operation** :

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to UK CLP/GHS

Flam. Liq. 3, H226  
STOT SE 3, H336  
Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

## SECTION 2: Hazards identification

**Ingredients of unknown toxicity** :  percent of the mixture consists of component(s) of unknown acute oral toxicity  
 1 percent of the mixture consists of component(s) of unknown acute dermal toxicity  
 1 percent of the mixture consists of component(s) of unknown acute inhalation toxicity


**Ingredients of unknown ecotoxicity** :  Contains 1% of components with unknown hazards to the aquatic environment

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning

**Contains** : -butyl acetate

**Hazard statements** : H226 - Flammable liquid and vapour.  
 H336 - May cause drowsiness or dizziness.  
 H412 - Harmful to aquatic life with long lasting effects.

#### Precautionary statements

**Prevention** : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P273 - Avoid release to the environment.  
 P261 - Avoid breathing vapour.

**Response** : P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

**Storage** : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

**Disposal** :  Not applicable.

**Supplemental label elements** : EUH066 - Repeated exposure may cause skin dryness or cracking.  
 EUH208 - Contains 2-ethylhexyl methacrylate and 2-hydroxyethyl methacrylate. May produce an allergic reaction.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

**SECTION 3: Composition/information on ingredients**

Product/ingredient name	Identifiers	%	Classification	Type
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4	≥10 - ≤25	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[1] [2]
Hydrocarbons, C9, aromatics	REACH #: 01-2119455851-35 EC: 918-668-5	≤10	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1]
Reaction mass of ethylbenzene and xylene	REACH #: 01-2119539452-40 EC: 905-588-0	≤9.7	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	[1]
ethyl 3-ethoxypropionate	REACH #: 01-2119463267-34 EC: 212-112-9 CAS: 763-69-9	≤5	Flam. Liq. 3, H226 EUH066	[1]
2-ethylhexyl methacrylate	REACH #: 01-2119490166-35 EC: 211-708-6 CAS: 688-84-6	<1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT SE 3, H335 Aquatic Chronic 3, H412	[1]
2-hydroxyethyl methacrylate	REACH #: 01-2119490169-29 EC: 212-782-2 CAS: 868-77-9	≤0.3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	[1]
cetrimonium chloride	Index: 607-124-00-X REACH #: 01-2119970558-23 EC: 203-928-6 CAS: 112-02-7	<0.1	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1) <b>See Section 16 for the full text of the H statements declared above.</b>	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

**Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.

**Unsuitable extinguishing media** : Do not use water jet.

**5.2 Special hazards arising from the substance or mixture**

**Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

**5.3 Advice for firefighters**

**Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

**6.3 Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

**SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**7.1 Precautions for safe handling**

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Centari® Mastertint® Transparent Magenta

## SECTION 7: Handling and storage

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

### Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### Seveso Directive - Reporting thresholds

#### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonne	50000 tonne

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
n-butyl acetate	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> STEL: 966 mg/m <sup>3</sup> 15 minutes. STEL: 200 ppm 15 minutes. TWA: 724 mg/m <sup>3</sup> 8 hours. TWA: 150 ppm 8 hours.

#### Biological exposure indices

No exposure indices known.

**Recommended monitoring procedures** : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
n-butyl acetate	DNEL	Short term Dermal	11 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3.4 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	7 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	11 mg/kg	Workers	Systemic

**SECTION 8: Exposure controls/personal protection**

Hydrocarbons, C9, aromatics	DNEL	Long term Inhalation	bw/day 12 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Inhalation	35.7 mg/m <sup>3</sup>	General population	Local	
	DNEL	Long term Inhalation	48 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Local	
	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Inhalation	300 mg/m <sup>3</sup>	Workers	Local	
	DNEL	Short term Inhalation	600 mg/m <sup>3</sup>	Workers	Local	
	DNEL	Short term Inhalation	600 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Inhalation	150 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Dermal	25 mg/kg	Workers	Systemic	
	Reaction mass of ethylbenzene and xylene	DNEL	Long term Dermal	bw/day 212 mg/kg	Workers	Systemic
		DNEL	Long term Inhalation	bw/day 221 mg/m <sup>3</sup>	Workers	Systemic
ethyl 3-ethoxypropionate	DNEL	Long term Inhalation	100.6 ppm	Workers	Systemic	
	DNEL	Long term Oral	1.2 mg/kg	General population	Systemic	
	DNEL	Long term Dermal	3.1 mg/kg	General population	Systemic	
2-ethylhexyl methacrylate	DNEL	Long term Dermal	bw/day 8.85 mg/kg	Workers	Systemic	
	DNEL	Long term Inhalation	bw/day 72.6 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Inhalation	610 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Inhalation	0.3 ppm	Workers	Systemic	
	DNEL	Long term Inhalation	2.5 mg/m <sup>3</sup>	Workers	Systemic	
2-hydroxyethyl methacrylate	DNEL	Long term Dermal	5 mg/kg	Workers	Systemic	
	DNEL	Long term Inhalation	bw/day 0.908 ppm	Workers	Systemic	
	DNEL	Long term Oral	0.83 mg/kg	General population	Systemic	
	DNEL	Long term Dermal	0.83 mg/kg	General population	Systemic	
	DNEL	Long term Dermal	1.39 mg/kg	Workers	Systemic	
	DNEL	Long term Inhalation	bw/day 1.45 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Inhalation	4.9 mg/m <sup>3</sup>	Workers	Systemic	

**PNECs**

**SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Compartment Detail	Value	Method Detail	
n-butyl acetate	Soil	0.09 mg/kg	-	
	Fresh water	0.18 mg/l	-	
	Sewage Treatment Plant	35.6 mg/l	-	
	Marine water	0.018 mg/l	-	
	Fresh water sediment	0.981 mg/kg	-	
	Marine water sediment	0.098 mg/kg	-	
	Reaction mass of ethylbenzene and xylene	Fresh water	0.327 mg/l	-
		Marine water	0.327 mg/l	-
		Sewage Treatment Plant	6.58 mg/l	-
		Fresh water sediment	12.46 mg/kg dwt	-
ethyl 3-ethoxypropionate	Marine water sediment	12.46 mg/kg dwt	-	
	Soil	2.31 mg/kg	-	
	Marine water	0.00609 mg/l	-	
	Fresh water	0.0609 mg/l	-	
2-ethylhexyl methacrylate	Sediment	0.0419 mg/l	-	
	Soil	0.446 mg/kg	-	
	Sewage Treatment Plant	10 mg/l	-	
2-hydroxyethyl methacrylate	Fresh water	0.00348 mg/l	-	
	Sediment	2.24 mg/kg	-	
	Fresh water	0.482 mg/l	-	
	Marine water	0.482 mg/l	-	
	Sewage Treatment Plant	10 mg/l	-	
	Fresh water sediment	3.79 mg/kg	-	
cetrimonium chloride	Marine water sediment	3.79 mg/kg	-	
	Soil	0.476 mg/kg	-	
	Fresh water	0.42 µg/l	Assessment Factors	
	Sewage Treatment Plant	0.4 mg/l	Assessment Factors	
	Fresh water sediment	68 mg/kg	-	
	Marine water sediment	6.8 mg/kg	-	
	Marine water	0.042 µg/l	-	

**8.2 Exposure controls**

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.

**Skin protection**

**Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.



## SECTION 8: Exposure controls/personal protection

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : Duration / breakthrough time: <1 hour,  
 Glove material: NBR, nitrile rubber, material thickness as splash protection: at least 0.2 mm, (EN374)  
 Glove material: NBR, nitrile rubber Material thickness for short-term contact: at least 0.5 mm, (EN374)  
 The recommendation for the type or types of glove to use when handling this product is based on information from the following source:  
 Expert judgment  
 The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

**Environmental exposure controls** : Do not allow to enter drains or watercourses.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.  
**Colour** : Red.  
**Odour** : Not available.  
**Odour threshold** : Not available.  
**Melting point/freezing point** : Technically not possible to measure  
**Initial boiling point and boiling range** : 125 to 250°C (257 to 482°F)  
**Flammability (solid, gas)** : Not available.  
**Upper/lower flammability or explosive limits** : Lower: 0.7%  
 Upper: 7.5%  
 Not available.  
**Flash point** : Closed cup: 32°C (89.6°F)  
**Auto-ignition temperature** : 280°C (536°F)  
**Decomposition temperature** : Not applicable.  
**pH** : Not applicable.  
**Viscosity** : Dynamic: 41 mPa·s  
 Kinematic: 39 mm<sup>2</sup>/s  
**Solubility(ies)** :

Media	Result
cold water	Very slightly soluble

Centari® Mastertint® Transparent Magenta

## SECTION 9: Physical and chemical properties

<b>Solubility in water</b>	: Not available.	
<b>Miscible with water</b>	: No.	
<b>Partition coefficient: n-octanol/ water</b>	: Not applicable.	
<b>Vapour pressure</b>	: 0.48 kPa (3.6 mm Hg)	
<b>Relative density</b>	: Not available.	
<b>Density</b>	: 1.051 g/cm <sup>3</sup>	
<b>Vapour density</b>	: Not available.	
<b>Explosive properties</b>	: Not available.	
<b>Oxidising properties</b>	: Not available.	
<b>Weight volatiles</b>	: 45.9 % (w/w)	
<b>VOC content</b>	: 44.4 % (w/w)	(2010/75/EU)

### 9.2 Other information

#### 9.2.1 Information with regard to physical hazard classes

**Flow time (ISO 2431)** : 33 s (room temperature) [Jet diameter: 4 mm]

Further information Not available.

#### 9.2.2 Other safety characteristics

**Miscible with water** : No.

Further information Not available.

*room temperature (=20°C)*

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: Stable under recommended storage and handling conditions (see Section 7).
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: When exposed to high temperatures may produce hazardous decomposition products.
<b>10.5 Incompatible materials</b>	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
<b>10.6 Hazardous decomposition products</b>	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.  Not applicable

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

**SECTION 11: Toxicological information**

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-ethylhexyl methacrylate, 2-hydroxyethyl methacrylate. May produce an allergic reaction.

**Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LC50 Inhalation Vapour	Rat	21.1 mg/l	4 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
Hydrocarbons, C9, aromatics	LD50 Dermal	Rabbit	>3160 mg/kg	-
	LD50 Oral	Rat - Female	3492 mg/kg	-
Reaction mass of ethylbenzene and xylene	LC50 Inhalation Vapour	Rat	6350 to 6700 ppm	4 hours
	LD50 Dermal	Rabbit	121236 mg/kg	-
	LD50 Oral	Rat	3523 to 4000 mg/kg	-
ethyl 3-ethoxypropionate	LD50 Dermal	Rat - Male	4080 mg/kg	-
	LD50 Oral	Rat	3200 mg/kg	-
2-hydroxyethyl methacrylate	LD50 Oral	Rat	5050 mg/kg	-
	LD50 Oral	Rat - Female	1550 mg/kg	-

**Acute toxicity estimates**

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Mixture	N/A	11900.6	N/A	119.0	N/A
n-butyl acetate	10768	N/A	N/A	21.1	N/A
Hydrocarbons, C9, aromatics	3492	N/A	N/A	N/A	N/A
Reaction mass of ethylbenzene and xylene	N/A	1100	N/A	11	N/A
ethyl 3-ethoxypropionate	3200	4080	N/A	N/A	N/A
2-hydroxyethyl methacrylate	5050	N/A	N/A	N/A	N/A
cetrimonium chloride	1550	N/A	N/A	N/A	N/A

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethyl 3-ethoxypropionate	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
2-hydroxyethyl methacrylate cetrimonium chloride	Skin - Irritant	Rabbit	-	-	-
	Skin - Visible necrosis	Rabbit	-	4 hours	10 days

**Sensitisation****Mutagenicity****Carcinogenicity****Reproductive toxicity****Teratogenicity****Specific target organ toxicity (single exposure)**

## SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
n-butyl acetate	Category 3	-	Narcotic effects
Hydrocarbons, C9, aromatics	Category 3	-	Respiratory tract irritation
Reaction mass of ethylbenzene and xylene	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
2-ethylhexyl methacrylate	Category 3	-	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Reaction mass of ethylbenzene and xylene	Category 2	-	-

### Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9, aromatics	ASPIRATION HAZARD - Category 1
Reaction mass of ethylbenzene and xylene	ASPIRATION HAZARD - Category 1

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking
- Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

**SECTION 11: Toxicological information**

Not available.

<b>Conclusion/Summary</b>	: Not available.
<b>General</b>	: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
<b>Carcinogenicity</b>	: No known significant effects or critical hazards.
<b>Mutagenicity</b>	: No known significant effects or critical hazards.
<b>Reproductive toxicity</b>	: No known significant effects or critical hazards.

Other information : Not available.

**SECTION 12: Ecological information****12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
n-butyl acetate	Acute LC50 185 ppm Marine water	Fish - Inland silverside - <i>Menidia beryllina</i>	96 hours
Hydrocarbons, C9, aromatics	Acute LC50 9.2 mg/l	Fish - Trout - <i>Oncorhynchus mykiss</i>	96 hours
Reaction mass of ethylbenzene and xylene	Acute EC50 2.2 mg/l	Algae - Algae - <i>Selenastrum capricornutum</i>	73 hours
	Acute LC50 1 mg/l	Daphnia - Daphnia - <i>Daphnia magna</i>	24 hours
	Acute LC50 2.6 mg/l	Fish - Trout - <i>Oncorhynchus mykiss</i>	96 hours
ethyl 3-ethoxypropionate	Chronic NOEC 16 mg/l	Micro-organism - Activated sludge - <i>Activated sludge</i>	28 days
	Acute LC50 45.3 to 55.3 mg/l	Fish	96 hours
2-hydroxyethyl methacrylate	Acute LC50 227000 µg/l Fresh water	Fish - Fathead minnow - <i>Pimephales promelas</i> - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
cetrimonium chloride	Acute EC50 0.0149 mg/l Fresh water	Daphnia - Water flea - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 100 µg/l Fresh water	Crustaceans - Scud, Amphipod - <i>Gammarus sp.</i>	48 hours
	Acute LC50 100 µg/l Fresh water	Fish - Bluegill - <i>Lepomis macrochirus</i>	96 hours
	Chronic NOEC 0.007 mg/l Fresh water	Daphnia	21 days
	Chronic NOEC 0.032 mg/l	Fish - <i>Pimephales promelas</i>	28 days

Conclusion/Summary : Not available.

**12.2 Persistence and degradability**

Product/ingredient name	Test	Result	Dose	Inoculum
ethyl 3-ethoxypropionate	OECD 301B Ready Biodegradability - CO2 Evolution Test	80 % - Readily - 13 days	-	-

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
ethyl 3-ethoxypropionate	-	-	Readily
cetrimonium chloride	-	-	Readily

**12.3 Bioaccumulative potential**

## SECTION 12: Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
n-butyl acetate	2.3	-	Low
Reaction mass of ethylbenzene and xylene	3.16	-	Low
ethyl 3-ethoxypropionate	1.47	-	Low
2-ethylhexyl methacrylate	4.95	37	Low
2-hydroxyethyl methacrylate	0.42	-	Low
cetrimonium chloride	3.23	160	Low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

#### Waste catalogue

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

#### Packaging





**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue
	15 01 10* packaging containing residues of or contaminated by hazardous substances

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Centari® Mastertint® Transparent Magenta

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	Yes.	No.	No.

### Additional information

ADR/RID : **Tunnel code** (D/E)

ADN : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### UK (GB)/REACH

#### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### Seveso Directive

This product is controlled under the Seveso Directive.

#### Danger criteria

Category

P5c

### National regulations

Centari® Mastertint® Transparent Magenta

## SECTION 15: Regulatory information

Product/ingredient name	List name	Name on list	Classification	Notes

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

🔍 Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** :

- ATE = Acute Toxicity Estimate
- GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = GB CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification

Classification	Justification
Flam. Liq. 3, H226 STOT SE 3, H336 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method

### Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### Full text of classifications



## SECTION 16: Other information

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of issue/ Date of revision** : 4/24/2024

**Version** : 1.03

**Date of previous issue** : 11/3/2023

### Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.