

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : A-U-86 1L 1L Steel drums

Product code : 000000000050857922

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Spraying
Substance/Mixture : Coatings and related products

1.3 Details of the supplier of the safety data sheet

Company:

BASF Coatings GmbH
Postfach 6123
48136 Münster
Deutschland

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
United Kingdom

Telephone: +44 161 475 3000
E-mail address: product-safety-uk-and-ireland@basf.com

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

1.4 Emergency telephone

International emergency number:
Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

| | |
|--|---|
| Flammable liquids, Category 2 | H225: Highly flammable liquid and vapor. |
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Eye irritation, Category 2 | H319: Causes serious eye irritation. |
| Skin sensitization, Category 1 | H317: May cause an allergic skin reaction. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. |
| Long-term (chronic) aquatic hazard, | H411: Toxic to aquatic life with long lasting |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Category 2

effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI
2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal Word : Danger

| | | | |
|-------------------|---|------|--|
| Hazard Statements | : | H225 | Highly flammable liquid and vapor. |
| | | H315 | Causes skin irritation. |
| | | H317 | May cause an allergic skin reaction. |
| | | H319 | Causes serious eye irritation. |
| | | H336 | May cause drowsiness or dizziness. |
| | | H411 | Toxic to aquatic life with long lasting effects. |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Precautionary Statements

:

Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
- P391 Collect spillage.

Hazardous ingredients which must be listed on the label:
acetone

tripropylene glycol diacrylate

(OLIGOMER) 4,4'-Isopropylidenediphenol, oligomeric reactionproducts with 1-

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

chloro-2,3-epoxypropane, esters with acrylic acid

Neopentyl glycol, propoxylated, esters with acrylic acid

Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2- p

2,4,6-trimethylbenzoylphenylphosphinic acid ethyl ester

2-hydroxyethyl acrylate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : unsaturated acrylic resin
fillers

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

pigment

organic compounds

organic solvent

inorganic compounds

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|-----------------------------|--|---|-----------------------|
| polymeric urethane acrylate | 123904-10-9 | Skin Irrit. 2; H315 Eye Irrit. 2; H319 | >= 15 - < 20 |
| acetone | 67-64-1 200-662-2 | Flam. Liq. 2; H225 Eye Irrit. 2; H319 | >= 15 - < 20 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | | | |
|-------------------|---|--|-------------|
| | 606-001-00-8 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 | STOT SE 3; H336 (Central nervous system) | |
| Methylethylketone | 78-93-3 201-159-0 606-002-00-3 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- | Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) | >= 7 - < 10 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | | | |
|--------------------------------|--|--|------------|
| | 0000 | | |
| tripropylene glycol diacrylate | 42978-66-5 256-032-2 607-249-00-X UK-20- 0537843089-5- 0000 | Eye Irrit. 2; H319 Skin Sens. 1A; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 _____ specific concentration limit STOT SE 3; H335 ≥ 10 % | ≥ 7 - < 10 |
| (OLIGOMER) 4,4'- | 55818-57-0 | Skin Sens. 1; | ≥ 5 - < 7 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | | | |
|---|---|--|------------|
| Isopropylidenediphenol, oligomeric reactionproducts with 1-chloro-2,3-epoxypropane, esters with acrylic acid | 500-130-2 | H317 Aquatic Chronic 2; H411 | |
| Neopentyl glycol, propoxylated, esters with acrylic acid | 84170-74-1 01-2119970213-43 | Skin Sens. 1; H317 Aquatic Chronic 2; H411 | >= 3 - < 5 |
| zinc phosphate | 7779-90-0 231-944-3 030-011-00-6 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- | Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 | >= 3 - < 5 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | | | |
|--|---|--|--------------|
| | 0000 | | |
| Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)- | 162881-26-7 423-340-5 015-189-00-5 UK-20- 0537843089-5- 0000 | Skin Sens. 1A; H317 Aquatic Chronic 4; H413 | >= 2.5 - < 3 |
| 2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction | 1187441-10-6 | Eye Dam. 1; H318 Skin Sens. 1; H317 | >= 1 - < 2 |
| Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2- p | 28961-43-5 500-066-5 01-2119489900-30 | Eye Irrit. 2; H319 Skin Sens. 1; H317 | >= 1 - < 2 |
| 2,4,6-trimethylbenzoylphenylphosphinic acid ethyl ester | 84434-11-7 282-810-6 UK-20- 0537843089-5- | Skin Sens. 1B; H317 Aquatic Chronic 2; H411 | >= 0.5 - < 1 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | | | |
|-------------------------|---|--|---------------------|
| | 0000 | | |
| 2-hydroxyethyl acrylate | 818-61-1 212-454-9 607-072-00-8 UK-20- 9642318150-0- 0000 UK-20- 0537843089-5- 0000 | Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 3; H412 _____ specific concentration limit | >= 0.025 - < 0.1 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | | | |
|--|---|--------------------------------------|---------------|
| | | Skin Sens. 1; H317 ≥ 0.2 % | |
| Substances with a workplace exposure limit : | | | |
| talc | 14807-96-6 238-877-9 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 | | ≥ 10 - < 12.5 |
| Kaolin | 1332-58-7 310-194-1 | | ≥ 5 - < 7 |
| Silicon dioxide | 7631-86-9 | | ≥ 2.5 - < 3 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | | | |
|------------------|---|--|------------------|
| | 231-545-4 UK-20- 2749242067-7- 0000 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000 | | |
| Titanium dioxide | 13463-67-7 236-675-5 UK-20- 2749242067-7- 0000 UK-20- | | $\geq 2 - < 2.5$ |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | | | |
|--|---------------------------------|--|--|
| | 9702550300-0- 0000 | | |
| | UK-20- 0537843089-5- 0000 | | |
| | UK-20- 9642318150-0- 0000 | | |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own safety.

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

In all cases of doubt, or when symptoms persist, seek medical attention.

Move out of dangerous area.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Never give anything by mouth to an unconscious person.

| | |
|-------------------------|---|
| If inhaled | : If symptoms persist, call a physician. If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. |
| In case of skin contact | : In case of skin contact avoid direct exposure to sunlight or other UV radiation since this would increase sensitisation of the skin. If symptoms persist, call a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Do NOT use solvents or thinners. |
| In case of eye contact | : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

eye specialist.

Call a physician immediately.

If easy to do, remove contact lens, if worn.

In case of accidental eye contact avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of eye.

If swallowed : If symptoms persist, call a physician.

Do NOT induce vomiting.

Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Risks : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Dry powder
Alcohol-resistant foam
Carbon dioxide (CO₂)

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Hazardous combustion products : Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : In the event of fire, cool tanks with water spray.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

regulations.

Collect contaminated fire extinguishing water separately.

This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

Advice on product handling can be found in sections 7
and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined
areas.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on : Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

storage conditions

upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.

Advice on common storage : Keep away from free radical initiators, peroxides, strong alkalis and reactive materials to avoid exothermic polymerization.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Recommended storage : 5.00 °C
temperature

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Packaging material : Suitable material: tinned carbon steel (Tinplate), Carbon steel (Iron), Polypropylene, Polyethylenetherephtalate (PET), Low density polyethylene (LDPE), High density polyethylene (HDPE), Stove-lacquer C222A/C221A, Standard interior paint, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X, Stove-lacquer EHD0022, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer R 78433, Stove-lacquer RDL 50

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|------------|---------|-------------------------------------|--------------------|-------|
| | | | | |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

Version 1.0 Revision Date: 25.04.2025 SDS Number: 000000000050857922 Date of last issue: -
Date of first issue: 25.04.2025

| | | | | |
|--|------------|--------------------------|--------------------------|------------|
| acetone | 67-64-1 | TWA | 500 ppm 1,210 mg/m3 | GB EH40 |
| | | STEL | 1,500 ppm 3,620 mg/m3 | GB EH40 |
| | | TWA | 500 ppm 1,210 mg/m3 | 2000/39/EC |
| Further information: Indicative | | | | |
| talc | 14807-96-6 | TWA (Respirable dust) | 1 mg/m3 | GB EH40 |
| Methylethylketone | 78-93-3 | TWA | 200 ppm 600 mg/m3 | GB EH40 |
| Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | | |
| | | STEL | 300 ppm | GB EH40 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | | | | |
|--------|--|--------------------------|----------------------|------------|
| | | | 899 mg/m3 | |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| | | STEL | 300 ppm 900 mg/m3 | 2000/39/EC |
| | Further information: Indicative | | | |
| | | TWA | 200 ppm 600 mg/m3 | 2000/39/EC |
| | Further information: Indicative | | | |
| Kaolin | 1332-58-7 | TWA (Respirable dust) | 2 mg/m3 | GB EH40 |
| | | TWA (Respirable dust) | 0.1 mg/m3 | 2004/37/EC |
| | Further information: Carcinogens or mutagens | | | |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | | | | |
|------------------|------------|--------------------------|-----------------------|---------|
| Silicon dioxide | 7631-86-9 | TWA (inhalable dust) | 6 mg/m3 (Silica) | GB EH40 |
| | | TWA (Respirable dust) | 2.4 mg/m3 (Silica) | GB EH40 |
| Titanium dioxide | 13463-67-7 | TWA (inhalable dust) | 10 mg/m3 | GB EH40 |
| | | TWA (Respirable dust) | 4 mg/m3 | GB EH40 |

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|-------------------|---------|---|---------------|----------------|
| Methylethylketone | 78-93-3 | butan-2-one: 70 micromol per litre (Urine) | After shift | GB EH40 BAT |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Required when there is a risk of eye contact.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

indication of degradation or chemical breakthrough.
Preventive skin protection Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Skin and body protection : Wear chemical-resistant disposable coverall and boots.

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | |
|---------------------|---|
| Protective measures | : In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. |
| | : Do not breathe vapour/spray. |
| | Eye wash fountains and safety showers must be easily accessible. |
| | If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. |
| | Avoid contact with the skin, eyes and clothing. |
| | Handle in accordance with good industrial hygiene and safety practice. |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|----------------|---|
| Appearance | : liquid |
| Color | : gray |
| Odor | : ketone-like |
| Odor Threshold | : not determined |
| pH | : substance/mixture is non-soluble (in water) |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | | |
|---|---|--|
| Melting point/ range | : | not determined |
| Flash point | : | 56.00 - 66.00 °C -12 °C Method: ISO 3679 |
| Evaporation rate | : | not determined |
| Lower explosion limit / Lower flammability limit | : | > 35.0 g/m3 |
| Vapor pressure | : | 203.0000 hPa (20 °C) 682.0000 hPa (50 °C) |
| Relative vapor density | : | Heavier than air. |
| Density | : | 1.266 g/cm3 (20 °C) |
| Solubility(ies) | : | |
| Water solubility | : | not determined |
| Partition coefficient: n- octanol/water | : | not applicable for mixtures |
| Autoignition temperature | : | > 200 °C |
| Decomposition temperature | : | No decomposition if stored and handled as prescribed/indicated. |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | | |
|----------------------|---|--|
| Viscosity | | |
| Viscosity, kinematic | : | not determined (40 °C) |
| | | 36.0 mm ² /s (23 °C) |
| Flow time | : | > 30 s |
| | | Cross section: 4 mm |
| Explosive properties | : | Not explosive |
| Oxidizing properties | : | The substance or mixture is not classified as oxidizing. |

9.2 Other information

| | | |
|-------------------------|---|--|
| Flammability (liquids) | : | Highly flammable liquid and vapour. |
| Self-heating substances | : | The substance or mixture is not classified as self heating. |
| Metal corrosion rate | : | Not corrosive to metals. |
| Particle size | : | The substance / product is marketed or used in a non solid or granular form. |

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.
Protect from frost.
Ultraviolet rays
Heat, flames and sparks.
Heat.

10.5 Incompatible materials

Materials to avoid : Keep away from free radical initiators, peroxides, strong alkalis and reactive materials to avoid exothermic polymerization.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Components:

acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Methylethylketone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Components:

zinc phosphate:

M-Factor (Acute aquatic) : 1

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

toxicity)

M-Factor (Chronic aquatic : 1
toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

acetone:

Partition coefficient: n- : log Pow: -0.24 (25 °C)
octanol/water

Methylethylketone:

Partition coefficient: n- : log Pow: 0.29
octanol/water

GLP: No information available.

Remarks: Information taken from reference works and
the literature.

tripropylene glycol diacrylate:

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Partition coefficient: n-
octanol/water : log Pow: 2.0 (25 °C)
GLP: no

log Pow: 2 (25 °C)

Method: OECD Test Guideline 117

GLP: yes

log Pow: 2.77 (25 °C)

Method: OECD Test Guideline 117

GLP: yes

log Pow: 2.1 (25 °C)

Method: OECD Test Guideline 117

GLP: yes

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

log Pow: 2.5 - 2.7 (23 °C)

pH: 6.7

Method: OECD Test Guideline 117

GLP: yes

(OLIGOMER) 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid:

Partition coefficient: n- : log Pow: ca. 1.6 - 3.8 (23 °C)
octanol/water

Method: OECD Test Guideline 117

GLP: yes

log Pow: 1.6 - 3.8 (23 °C)

pH: 6.4

Method: OECD Test Guideline 117

GLP: yes

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

log Pow: 1.6 - 3 (23 °C)

pH: 6.4

Method: OECD Test Guideline 117

GLP: yes

log Pow: 3 - 3.8 (23 °C)

pH: 6.4

Method: OECD Test Guideline 117

GLP: yes

Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-:

Partition coefficient: n-
octanol/water

: log Pow: 5.8 (22 °C)

pH: 8.3

Method: OECD Test Guideline 117

GLP: yes

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction:

Partition coefficient: n- : Pow: 2 - 5,200 (23.3 °C)
octanol/water
log Pow: 0.3 - 3.7 (23.3 °C)
Method: OECD Test Guideline 117
GLP: yes

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2- p:

Partition coefficient: n- : log Pow: 2.89 (23 °C)
octanol/water
pH: 8.1
Method: OECD Test Guideline 107
GLP: no

2,4,6-trimethylbenzoylphenylphosphinic acid ethyl ester:

Partition coefficient: n- : log Pow: 2.91 (25 °C)
octanol/water
pH: 4.4

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

GLP: yes

2-hydroxyethyl acrylate:

Partition coefficient: n-
octanol/water : log Pow: -0.17 (25 °C)
Method: OECD Test Guideline 107
GLP: no

talc:

Partition coefficient: n-
octanol/water : log Pow: -9.4 (25 °C)
pH: 7
GLP: no

Silicon dioxide:

Partition coefficient: n-
octanol/water : Remarks: Not applicable

Titanium dioxide:

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Partition coefficient: n- : Remarks: Not applicable
octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Product : Do not discharge into drains/surface
waters/groundwater.

Observe national and local legal requirements.

Contaminated packaging : Containers which are not properly emptied must be
disposed pursuant to Directive 2008/98/EC

Packaging that is not properly emptied must be disposed
of as the unused product.

SECTION 14: Transport information

14.1 UN number

| | |
|-----|-----------|
| ADN | : UN 1263 |
| ADR | : UN 1263 |
| RID | : UN 1263 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

IMDG : UN 1263

IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT

ADR : PAINT

RID : PAINT

IMDG : PAINT

(ZINC PHOSPHATE, TRIPROPYLENEGLYCOL DIACRYLATE)

IATA : PAINT

14.3 Transport hazard class(es)

| | Class | Subsidiary risks |
|------------|-------|------------------|
| ADN | : 3 | |
| ADR | : 3 | |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

RID : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADN

Packing group : II

Classification Code : F1

Hazard Identification
Number : 33

Labels : 3

Remarks : Special Provision 640D

ADR

Packing group : II

Classification Code : F1

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Hazard Identification : 33
Number
Labels : 3
Tunnel restriction code : (D/E)
Remarks : Special Provision 640D

RID

Packing group : II
Classification Code : F1
Hazard Identification : 33
Number
Labels : 3
Remarks : Special Provision 640D

IMDG

Packing group : II
Labels : 3

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo : 364
aircraft)

Packing instruction (LQ) : Y341

Packing group : II

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction : 353
(passenger aircraft)

Packing instruction (LQ) : Y341

Packing group : II

Labels : Flammable liquid

14.5 Environmental hazards

ADN

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Environmentally : yes
hazardous

ADR

Environmentally : yes
hazardous

RID

Environmentally : yes
hazardous

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:

Number on list 72, 3

Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

The Persistent Organic Pollutants Regulations
(retained Regulation (EU) 2019/1021 as amended
for Great Britain) : Not applicable

Regulation (EC) on substances that deplete the
ozone layer : Not applicable

Regulation (EU) 2019/1148 on the marketing and
use of explosives precursors : acetone

UK REACH List of substances subject to
authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards
Regulations 2015 (COMAH) E2 ENVIRONMENTAL HAZARDS

P5c FLAMMABLE LIQUIDS

Volatile organic
compounds : Directive 2010/75/EU of 24 November 2010 on
industrial emissions (integrated pollution prevention and
control)

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Volatile organic compounds (VOC) content: 27.59 %

Volatile organic compounds (VOC) content: 349.28 g/l

VOC content excluding water

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999
(requirements relating to new and expectant mothers at work contained in Regulation
16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999
(requirements relating to protection of young people at work contained in Regulation
19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

c

Limit value for maximum VOC content as specified in Annex IIB:

540 g/l

VOC content of the ready-for-use product according to ISO 11890-2:

539 g/l

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in
section 7 and 8 of the SDS

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

SECTION 16: Other information

Full text of H-Statements

| | |
|------|---|
| H225 | : Highly flammable liquid and vapor. |
| H302 | : Harmful if swallowed. |
| H311 | : Toxic in contact with skin. |
| H314 | : Causes severe skin burns and eye damage. |
| H315 | : Causes skin irritation. |
| H317 | : May cause an allergic skin reaction. |
| H318 | : Causes serious eye damage. |
| H319 | : Causes serious eye irritation. |
| H335 | : May cause respiratory irritation. |
| H336 | : May cause drowsiness or dizziness. |
| H400 | : Very toxic to aquatic life. |
| H410 | : Very toxic to aquatic life with long lasting effects. |
| H411 | : Toxic to aquatic life with long lasting effects. |
| H412 | : Harmful to aquatic life with long lasting effects. |
| H413 | : May cause long lasting harmful effects to aquatic life. |

Full text of other abbreviations

| | |
|-----------------|--------------------------------------|
| Acute Tox. | : Acute toxicity |
| Aquatic Acute | : Short-term (acute) aquatic hazard |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard |
| Eye Dam. | : Serious eye damage |
| Eye Irrit. | : Eye irritation |
| Flam. Liq. | : Flammable liquids |
| Skin Corr. | : Skin corrosion |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

| | |
|-------------------|---|
| Skin Irrit. | : Skin irritation |
| Skin Sens. | : Skin sensitization |
| STOT SE | : Specific target organ toxicity - single exposure |
| 2000/39/EC | : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values |
| 2004/37/EC | : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work |
| GB EH40 | : UK. EH40 WEL - Workplace Exposure Limits |
| GB EH40 BAT | : UK. Biological monitoring guidance values |
| 2000/39/EC / TWA | : Limit Value - eight hours |
| 2000/39/EC / STEL | : Short term exposure limit |
| 2004/37/EC / TWA | : Long term exposure limit |
| GB EH40 / TWA | : Long-term exposure limit (8-hour TWA reference period) |
| GB EH40 / STEL | : Short-term exposure limit (15-minute reference period) |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data sheets of all components.
Restricted to professional users.

Classification of the mixture:

| | |
|---------------|------|
| Flam. Liq. 2 | H225 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2 | H319 |
| Skin Sens. 1 | H317 |
| STOT SE 3 | H336 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-86 1L 1L Steel drums

| | | | |
|---------|----------------|------------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 25.04.2025 | 000000000050857 922 | Date of first issue: 25.04.2025 |

Aquatic Chronic 2

H411

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN