# **SAFETY DATA SHEET**



Date of issue/Date of revision

: 31 October 2023

**Version** : 1.01

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: AquaMax Extra Fuoco Artico
Product code	: 1.550.CS33/E0.25
Product description	:
Product type	: Liquid.
Other means of identification	: Not available.
1.2 Relevant identified us	es of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.

#### 1.3 Details of the supplier of the safety data sheet

PPG Industries Italia S.r.l., Via Comasina, 121, 20161 Milano, Italy Tel: +39 02 6404.1 PPG Industries (UK) Ltd., Needham Road, Stowmarket, Suffolk, IP14 2AD, UK Tel: +44 (0) 1449 773 338

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

#### 1.4 Emergency telephone number

#### **Supplier**

Company emergency telephone number : +39 02 6404.1 (0800-1700)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to UK CLP/GHS Not classified.

The product is not classified as hazardous according to UK CLP Regulation SI 2019/720 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	No signal word.	
Hazard statements	No known significant effects or critical hazards.	
Precautionary statements		
Prevention	Not applicable.	
Response	Not applicable.	
Storage	Not applicable.	
Disposal	Dispose of contents and container in accordance with all local, regional, nation and international regulations. P501	nal
Supplemental label elements	Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reacti Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do no preathe spray or mist.	

Code	: 1.550.CS33/E0.25	Date of issue/Date of revision	: 31 October 2023
AquaMax E	Extra Fuoco Artico		

#### **SECTION 2: Hazards identification**

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	<u>ents</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

#### **SECTION 3: Composition/information on ingredients**

Mixture

3.2 Mixtures ÷ **Product/ingredient name Identifiers** % **Classification** Type 2-butoxyethanol REACH #: ≥5.0 - <10 Acute Tox. 4, H302 [1] [2] 01-2119475108-36 Acute Tox. 3, H331 EC: 203-905-0 Skin Irrit. 2, H315 CAS: 111-76-2 Eye Irrit. 2, H319 Index: 603-014-00-0 2,4,7,9-tetramethyldec-5-yne-<1.0 REACH #: Eye Dam. 1, H318 [1] Skin Sens. 1B, H317 4,7-diol 01-2119954390-39 EC: 204-809-1 Aquatic Chronic 3, CAS: 126-86-3 H412 See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains  $\geq$  1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

#### SUB codes represent substances without registered CAS Numbers.

#### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures Eye contact Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

English (GB)

United Kingdom (UK)

Code	: 1.550.CS33/E0.25	Date of issue/Date of revision	: 31 October 2023
AquaMax	c Extra Fuoco Artico		
SECTION 4: Eirot aid magauraa			

SECTION 4: First a	id measures
Skin contact	: Remove contaminated clothing and sh

Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water
	or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/syn</u>	<u>nptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

## **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising fr	om	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon oxides metal oxide/oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Code	: 1.550.CS33/E0.25	Date of issue/Date of revision	: 31 October 2023
AquaMax Ex	tra Fuoco Artico		

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

#### **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
	Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Storage temperature: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

English (GB)

#### Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

Code : 1.550.CS33/E0.25

AquaMax Extra Fuoco Artico

Date of issue/Date of revision

: 31 October 2023

#### **SECTION 7: Handling and storage**

See Section 1.2 for Identified uses.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
2-butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m <sup>3</sup> 15 minutes. TWA: 123 mg/m <sup>3</sup> 8 hours.

#### **Biological exposure indices**

Product/ingredient name	Exposure indices
2-butoxyethanol	2-BUTOXY ETHANOL
Recommended monitoring : Reference shou	d be made to appropriate monitoring standards. Reference to

Recommended monitoring	- 2	Reference should be made to appropriate monitoring standards. Reference to
procedures		national guidance documents for methods for the determination of hazardous
		substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2-butoxyethanol	DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	26.7 mg/kg bw/day	General population	
	DNEL	Long term Inhalation	59 mg/m <sup>3</sup>	General population	
	DNEL	Long term Inhalation	98 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	147 mg/m <sup>3</sup>	General population	
	DNEL	Short term Inhalation	246 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	426 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	1091 mg/m <sup>3</sup>	Workers	Systemic
2,4,7,9-tetramethyldec-5-yne- 4,7-diol	DNEL	Long term Oral	0.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.43 mg/m <sup>3</sup>	General population	
	DNEL	Long term Dermal	0.5 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	0.75 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.75 mg/kg bw/day	General population	
	DNEL	Short term Inhalation	1.29 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Dermal	1.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.76 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	5.28 mg/m <sup>3</sup>	Workers	Systemic

#### **PNECs**

Product/ingredient name	Compartment Detail	Value	Method Detail
2-butoxyethanol	Fresh water	8.8 mg/l	Assessment Factors
	Marine water	0.88 mg/l	Assessment Factors
	Fresh water sediment	34.6 mg/kg	Equilibrium Partitioning
	Marine water sediment	3.46 mg/kg	Equilibrium Partitioning
	Soil	3.13 mg/kg	Equilibrium Partitioning
	Sewage Treatment Plant	463 mg/l	Assessment Factors
2,4,7,9-tetramethyldec-5-yne-4,7-diol	Fresh water	0.04 mg/l	Assessment Factors
	Marine water	0.004 mg/l	Assessment Factors
	Sewage Treatment Plant	7 mg/l	Assessment Factors
	Fresh water sediment	0.32 mg/kg dwt	Equilibrium Partitioning
English (GB)	United Kingdom (UK	<u> </u>	5/12

Code	: 1.550.CS33/E0.25	Date of issue/Date of revision	: 31 October 2023
AquaMax Ex	tra Fuoco Artico		

# **SECTION 8: Exposure controls/personal protection**

	-		
	Marine water sediment	0.032 mg/kg dwt	Equilibrium Partitioning
	Soil	0.028 mg/kg dwt	Equilibrium Partitioning

#### 8.2 Exposure controls

Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measured	res	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	:	Safety glasses with side shields.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Gloves	1	For prolonged or repeated handling, use the following type of gloves:
		Recommended: butyl rubber, nitrile rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Yellow.
Odour	: Faint odour.
Odour threshold	: Not available.
Melting point/freezing point	<ul> <li>May start to solidify at the following temperature: 0°C (32°F) This is based on data for the following ingredient: water. Weighted average: -7.83°C (17.9°F)</li> </ul>
Initial boiling point and boiling range	: >37.78°C (>100°F)
Flammability (solid, gas)	: liquid
Upper/lower flammability or explosive limits	: Not applicable.

English (GB)

Code	: 1.550.CS33/E0.25	Date of issue/Date of revision	: 31 October 2023
AquaMax	Extra Fuoco Artico		

# SECTION 9: Physical and chemical properties

Flash point	: Clo	sed cup: 100°C	(212°F) [Product d	oes not sustain combustion.]	
Auto-ignition temperature	:				
Ingredient name		°C	°F	Method	
2-butoxyethanol		230	446	DIN 51794	
Decomposition temperature	:		ł		
рН	: Not	t available.			
Viscosity	: Kin	ematic (40°C): >	21 mm²/s		
looolig					
Solubility(ies)	:				
		tesult			

Partition coefficient: n-octanol/ : Not applicable. water

#### Vapour pressure

	V	apour Pres	our Pressure at 20°C		Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
Relative density	: 1.03	3	Į				
/apour density	: Hig	hest known	value: 4.1 (Air =	1) (2-butoxyeth	nanol).		
Explosive properties	: Not	available.					
Oxidising properties Particle characteristics	: Pro	duct does r	not present an oxic	lizing hazard.			
Median particle size	: Not	applicable					

# SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Code : 1.550.CS33/E0.25 Date of issue/Date of revision

: 31 October 2023

AquaMax Extra Fuoco Artico

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LC50 Inhalation Vapour LD50 Dermal	Rat Rat	3 mg/l >2000 mg/kg	4 hours -
2,4,7,9-tetramethyldec- 5-yne-4,7-diol	LD50 Oral LC50 Inhalation Dusts and mists	Rat Rat	1200 mg/kg >20 mg/l	- 1 hours
	LD50 Dermal LD50 Oral	Rabbit Rat	>2000 mg/kg 4.6 g/kg	-

**Conclusion/Summary** Acute toxicity estimates : There are no data available on the mixture itself.

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
AquaMax Extra Fuoco Artico	15081.6	N/A	339824.2	36.6	N/A
2-butoxyethanol	1200	N/A	N/A	3	N/A
2,4,7,9-tetramethyldec-5-yne-4,7-diol	4600	N/A	N/A	N/A	N/A

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-butoxyethanol	Eyes - Irritant Skin - Moderate irritant	Rabbit Rabbit	-	24 hours 4 hours	21 days 28 days
2,4,7,9-tetramethyldec-5-yne- 4,7-diol	Eyes - Severe irritant	Rabbit	-	0.1 Mililiters	-
,	Skin - Mild irritant	Rabbit	-	0.5 Grams	-
Conclusion/Summary	Not available.				

Skin	: There are no data available on the mixture itself.		
Eyes	: There are no data available on the mixture itself.		

Respiratory	: There are no data available on the mixture itself
-------------	---

Sensitisation	
<b>Conclusion/Summary</b>	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
<b>Mutagenicity</b>	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Carcinogenicity	

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Reproductive toxicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Teratogenicity	
<b>Conclusion/Summary</b>	- 1

There are no data available on the mixture itself.

Specific target organ toxicity (single exposure) Not available.

#### Specific target organ toxicity (repeated exposure) Not available.

#### **Aspiration hazard**

English (GB)

Code : 1.550.CS33/E0.25	Date of issue/Date of revision	: 31 October 2023
AquaMax Extra Fuoco Artico		

# **SECTION 11: Toxicological information**

Not available.

Information on likely routes of exposure	:	Not available.	
Potential acute health effects	2		
Eye contact	:	No known significant effects or critical hazards.	
Inhalation	:	No known significant effects or critical hazards.	
Skin contact	:	No known significant effects or critical hazards.	
Ingestion	:	No known significant effects or critical hazards.	
Symptoms related to the phy	sic	cal, chemical and toxicological characteristics	
Eye contact	:	No specific data.	
Inhalation	:	No specific data.	
Skin contact	:	No specific data.	
Ingestion	:	No specific data.	
Delayed and immediate effec	ts	as well as chronic effects from short and long-term exposure	
Short term exposure			
		as well as chronic effects from short and long-term exposure Not available.	
Short term exposure Potential immediate	:		
Short term exposure Potential immediate effects	:	Not available.	
Short term exposure Potential immediate effects Potential delayed effects	:	Not available.	
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate	:	Not available.	
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects		Not available. Not available. Not available.	
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects		Not available. Not available. Not available.	
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential delayed effects	: : : ect	Not available. Not available. Not available.	
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential delayed effects Potential chronic health effe Not available.	: : : ect	Not available. Not available. Not available. S	
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effects Not available. Conclusion/Summary	: : : ect	Not available. Not available. Not available. S Not available. S Not available. No known significant effects or critical hazards.	
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential delayed effects Potential chronic health effe Not available. Conclusion/Summary General	: : : ect	Not available. Not available. Not available. S Not available. S Not available. No known significant effects or critical hazards.	

#### Other information

: Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-butoxyethanol	Acute LC50 1474 mg/l Chronic NOEC >100 mg/l	Fish Fish	96 hours 21 days
Conclusion/Summary	: Not available.		

#### **Conclusion/Summary**

#### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-butoxyethanol	-	-	Readily

Code	: 1.550.CS33/E0.25	Date of issue/Date of revision	: 31 October 2023
AguaMa	x Extra Fuoco Artico		

#### **SECTION 12: Ecological information**

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-butoxyethanol	0.81	-	Low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

#### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### **13.1 Waste treatment methods**

Product		
Methods of disposal	:	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	:	Yes.

W	aste	cata	loque	

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
Packaging	

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue
Container	15 01 02 plastic packaging
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

#### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	9003	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	SUBSTANCES WITH A FLASH-POINT ABOVE 60 °C AND NOT MORE THAN 100 °C (2-butoxyethanol)	-	-
English (0	GB)	United Kingdom	(UK)	10/12

Code	: 1.550.CS33/E0.25	Date of issue/Date of revision	: 31 October 2023
AquaMax Ex	tra Fuoco Artico		

#### **SECTION 14: Transport information**

	manoportimori			
		(2-butoxyethanol)		
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.
ADR/RID :	None identified.	-	•	-
ADN :	The product is only regu	lated as a dangerous good	l when transported in tank	vessels.
IMDG :	None identified.			

IATA : None identified.

# **14.6 Special precautions for user**: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

# 14.7 Transport in bulk: Not available.according to IMOinstruments

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB)/REACH

#### Annex XIV - List of substances subject to authorisation

#### Annex XIV

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

#### **Ozone depleting substances**

Not listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

#### Seveso Directive

This product is not controlled under the Seveso Directive.

#### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling Packaging of Substances and Mixtures as amended by (EU Exit) Reg No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic</li> </ul>	

United Kingdom (UK)

Code : 1.550.CS33/E0.25

Date of issue/Date of revision

: 31 October 2023

AquaMax Extra Fuoco Artico

#### **SECTION 16: Other information**

PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification

Not classified.

#### Full text of abbreviated H statements

<mark>⊮</mark> 302 H315	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H412	Harmful to aquatic life with long lasting effects.

: 1.01

#### Full text of classifications

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1B	SKIN SENSITISATION - Category 18
History Date of issue/ Date of revision Date of previous issue Prepared by	SKIN SENSITISATION - Category 1B : 31 October 2023 : 9 November 2022 : EHS

Version

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.