

MULTI ECO PUTTY - UNIVERSAL 1.8kg MME1.8

v.01-11.2014

Features:

This Eco Multi putty is a multifunctional polyester putty. Ideal for application on steel, aluminum, as well as galvanized and polyester surfaces. Thanks to its low viscosity and consistency, this product is very easy to apply. It can be used as a finishing filler, providing a smooth and clean result. Ideal for filling irregularities, particularly on galvanized aluminum surfaces. If your surface requires multiple coats, this filler may be the perfect solution.

Application : The surface to be treated must be thoroughly cleaned, dry, degreased, and matted. Add 2-3% hardener (included) and apply within 5 minutes. Can be machine or hand sanded from P150 to P320 grit.

Note : *Be careful not to use too much hardener, as this may cause discoloration of the topcoat. It is not recommended to use the filler at temperatures below 15°C.*

Technical data :

VOC content : 2004/42/IIIB(b)(250) <250

Shelf life : 12 months

Density: 1,97 - 1,99 g/cm³

Color : beige



Cleaning



Hardener addition

Putty 100 g

BPO hardener 2-3 g



body filling

4 - 6 min.



Drying time

20 min.



Hand sanding/ dry

P150 - P320



machine sanding / dry

P150 - P320



Store in cold place