

A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	: A-R-130 5L 5L Steel jerricans
Product code	: 0000000050675485
1.2 Relevant identified uses of the	e substance or mixture and uses advised against
Use of the	: Spraying
Substance/Mixture	Thinner
1.3 Details of the supplier of the	safety data sheet
<u>Company:</u>	<u>Contact address:</u>
BASF Coatings GmbH	BASF plc
Postfach 6123	4th and 5th Floors, 2 Stockport Exchange
48136 Münster	Railway Road, Stockport, SK1 3GG
Deutschland	United Kingdom

Telephone: +44 161 475 3000 E-mail address: product-safety-uk-and-ireland@basf.com



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :		
Signal Word :	Danger	
Hazard Statements :	H226	Flammable liquid and vapor.
	H304	May be fatal if swallowed and enters airways.
	H336	May cause drowsiness or dizziness.
	H412	Harmful to aquatic life with long lasting effects.
Precautionary : Statements	Prevention P210	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

smoking.

P261	Avoid breathing mist or vapors.
P273	Avoid release to the environment.
Response:	
P301 + P31	0 IF SWALLOWED: Immediately call a
	POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P370 + P37	8 In case of fire: Use dry sand, dry chemical
	or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

2-heptanone

n-Butyl acetate

Hydrocarbons, C9, aromatics

Naphtha (petroleum), hydrotreated light, Kp > 140oC

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature :

: organic solvent

Components

Chemical name	CAS-No.	Classification	Concentratio
	EC-No.		n (% w/w)
	Index-No.		
	Registration		
	number		
2-heptanone	110-43-0	Flam. Liq. 3; H226	>= 25 - < 50
	203-767-1	Acute Tox. 4;	
	606-024-00-3	H302	
	UK-20-	Acute Tox. 4;	



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

	0537843089-5- 0000	H332 STOT SE 3; H336 (Central nervous system)	
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 20 - < 25
Hydrocarbons, C9, aromatics	64742-95-6	Flam. Liq. 3; H226	>= 12.5 - < 15



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

	265-199-0 UK-20- 0537843089-5- 0000	STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	
Naphtha (petroleum),hydrotreated light, Kp > 140oC	64742-52-5 265-155-0 649-465-00-7 01-2119471843-32	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 7 - < 10
2-butoxyethyl acetate	112-07-2	Acute Tox. 4;	>= 5 - < 7



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

203-933-3	H302	
607-038-00-2 UK-20- 0537843089-5- 0000	Acute Tox. 4; H332 Acute Tox. 4; H312	
UK-20- 9642318150-0- 0000		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice	: First aid personnel should pay attention to their own
	safety.
	Immediately remove contaminated clothing.
	In case of intoxication, call a poison control center or
	physician for treatment advice, taking the packaging or
	the label of the product.
	Symptoms of poisoning may occur even after several
	hours, continue medical observation for at least 48



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

	hours after the accident. Never give anything by mouth to an unconscious p Keep patient warm and at rest.	erson.
If inhaled	If breathed in, move person into fresh air.	
	Call a physician or poison control center immediat	ely.
	If breathing is irregular or stopped, administer arti respiration.	ficial
In case of skin contact	If symptoms persist, call a physician.	
	Wash off immediately with soap and plenty of wat while removing all contaminated clothes and shoe	
	Do NOT use solvents or thinners.	
In case of eye contact	If symptoms persist, call a physician.	
	In case of eye contact, remove contact lens and rir immediately with plenty of water, also under the e	



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

for at least 15 minutes.

If swallowed	: Do not induce vomiting due to aspiration hazard.
	Keep at rest.
	If symptoms persist, call a physician or Poison Control Center immediately.
	Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
Risks	: May be fatal if swallowed and enters airways.
	May cause drowsiness or dizziness.



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment

: No known specific antidote. Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing	:	W
media		_

Water spray jet Dry powder Alcohol-resistant foam Carbon dioxide (CO2)



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Unsuitable extinguishing	: High volume water jet
media	

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire :	Fire will produce dense black smoke containing
fighting	hazardous combustion products (see section 10).

5.3 Advice for firefighters

Special protective	:	Appropriate breathing apparatus may be required.
equipment for fire-fighters		

Further information : In the event of fire, cool tanks with water spray.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Avoid breathing vapours.
		Keep away from sources of ignition.
		Advice on product handling can be found in sections 7 and 8 of this safety data sheet.
		For non-emergency personnel:
		For emergency responders:
		Use personal protective equipment.
		Ensure adequate ventilation, especially in confined areas.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Provide good ventilation of working area (local exhaust
		ventilation if necessary).



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Do not return residues to the storage containers.

	Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
	When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
	The workplace should be equipped with an emergency shower and eye-rinsing facility.
	Avoid contact with the skin, eyes and clothing.
	Handle in accordance with good industrial hygiene and safety practice.
	Do not breathe vapors or spray mist.
Advice on protection :	Avoid all sources of ignition: heat, sparks, open flame.



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

against fire and explosion	Product may charge electrostatically: always use
	earthing leads when transferring from one container to
	another and earth containers. It is recommended that
	operators should wear antistatic clothing and footwear.
	The relevant fire protection measures should be noted.
	Use explosion-proof equipment. Vapors are heavier than
	air and may spread along floors. Vapors may form
	explosive mixtures with air.

Hygiene measures: Remove contaminated clothing immediately and dispose
of safely. Wash hands before breaks and at the end of
workday. Keep away from food, drink and animal
feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on	:	Avoid direct sunlight. Close containers carefully once
storage conditions		opened and store them upright in order to prevent any
		leakage. No smoking. No admission for unauthorised
		personnel. Always keep in containers of same material
		as the original one. Observe label precautions. Keep in a
		dry, cool and well-ventilated place.



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Advice on common storage :	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
7.3 Specific end use(s)	
Specific use(s) :	Please refer to the technical leaflet for further

information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-heptanone	110-43-0	STEL	100 ppm 475 mg/m3	GB EH40



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

	substances a		sorbed through the skin. T there are concerns that d c toxicity.	-
		TWA	50 ppm	GB EH40
			237 mg/m3	
	Further info	mation: Can be ab	sorbed through the skin. T	he assigned
	substances a	ire those for which	there are concerns that d	ermal
	absorption v	absorption will lead to systemic toxicity.		
		TWA	50 ppm	2000/39/EC
			238 mg/m3	
	Further information: Identifies the possibility of significant uptake			
	through the skin, Indicative			
		STEL	100 ppm	2000/39/EC
			475 mg/m3	
	Further infor	mation: Identifies	the possibility of significar	nt uptake
	through the	through the skin, Indicative		
n-Butyl acetate	123-86-4	TWA	150 ppm	GB EH40



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

			724 mg/m3	
		STEL	200 ppm	GB EH40
			966 mg/m3	
		STEL	150 ppm	2019/1831/
			723 mg/m3	EU
	Further info	rmation: Indicative		
		TWA	50 ppm	2019/1831/
			241 mg/m3	EU
	Further info	rmation: Indicative		
2-butoxyethyl	112-07-2	TWA	20 ppm	GB EH40
acetate			133 mg/m3	
	Further info	rmation: Can be ab	sorbed through the skin.	The assigned
	substances a	are those for which	there are concerns that d	ermal
	absorption v	will lead to systemi	c toxicity.	
		STEL	50 ppm	GB EH40



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

		332 mg/m3		
Further info	rmation: Can be a	bsorbed through the skin.	The assigned	
substances	are those for whicl	n there are concerns that o	lermal	
absorption	will lead to system	ic toxicity.		
	STEL	50 ppm	2000/39/EC	
		333 mg/m3		
Further info	Further information: Identifies the possibility of significant uptake			
through the	skin, Indicative			
	TWA	20 ppm	2000/39/EC	
		133 mg/m3		
Further info	rmation: Identifies	the possibility of significa	nt uptake	
through the	skin, Indicative			

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles (splash goggles) (e.g. EN 166)



A-R-130 5L 5L Steel jerricans

VersionRevision Date:SDS Number:Date of last issue: 13.09.20242.020.01.202500000000050675
485Date of first issue: 22.08.2024

Required when there is a risk of eye contact.

Hand protection

Remarks

: Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for shortterm contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

		index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)
Skin and body protection	:	Anti-static protective clothing
		Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.
Respiratory protection	:	Suitable respiratory equipment:
		half-mask with A1P2 class combination filter
		When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
		In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Protective measures	:	Do not breathe vapour/spray.
		Eye wash fountains and safety showers must be easily



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	No data available
рН	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Boiling point/boiling range	:	124 °CMethod: calculated
Flash point	:	31 °C Method: ISO 3679
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35 g/m3
Vapor pressure	:	11.0000 hPa (20 °C) Method: other (calculated)
		(50 °C)



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

- Relative vapor density : Heavier than air.
- Density : 0.868 g/cm3 (20 °C) Method: calculated
- Solubility(ies) Water solubility : not determined
- Partition coefficient: n- : not applicable for mixtures octanol/water Autoignition temperature : > 200 °C
- Decomposition: No decomposition if stored and handled astemperatureprescribed/indicated.



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Viscosity Viscosity, kinematic	: 0.9 mm2/s (40 °C)
	411.6 mm2/s (23 °C)
Flow time	: > 60 s at 23 °C
	Cross section: 6 mm
	Method: ISO 2431
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
9.2 Other information Flammability (liquids)	: Flammable liquid and vapour.



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid: Keep away from oxidizing agents, strongly alkaline and
strongly acid materials in order to avoid exothermic
reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Exposure	time:	4 h
LAPOSUIC	unic.	

Test atmosphere: vapor

Method: Calculation method

Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg
		Method: Calculation method

- Acute oral toxicity : LD50 (Rat): 1,600 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 16.7 mg/l Exposure time: 4 h

Test atmosphere: vapor

2-butoxyethyl acetate:



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Acute oral toxicity	: LD50 (Rat): 1,880 mg/kg
---------------------	---------------------------

Acute dermal toxicity	:	LD50 (Rabbit): 1,500 mg/kg
-----------------------	---	----------------------------

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Components:

n-Butyl acetate:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Carcinogenicity
Based on available data, the classification criteria are not met.
Reproductive toxicity
Based on available data, the classification criteria are not met.
STOT-single exposure
May cause drowsiness or dizziness.
STOT-repeated exposure
Based on available data, the classification criteria are not met.
Aspiration toxicity
May be fatal if swallowed and enters airways.
SECTION 12: Ecological information
12.1 Toxicity
12.1 Toxicity No data available
12.2 Persistence and degradability
No data available
12.3 Bioaccumulative potential
Components:
2-heptanone:
Partition coefficient: n- : log Pow: 2.26 (30 °C)
octanol/water
pH: 7
Method: Regulation (EC) No. 440/2008, Annex, A.8
I



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

	GLP: yes
n-Butyl acetate: Partition coefficient: n- : octanol/water	Pow: 200 (25 °C) log Pow: 2.3 (25 °C)
	рН: 7 Method: OECD Test Guideline 117 GLP: yes
Hydrocarbons, C9, aromatics: Partition coefficient: n- : octanol/water	
2-butoxyethyl acetate: Partition coefficient: n- : octanol/water	log Pow: 1.51 (25 °C) pH: 7



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

		Method: OECD Test Guideline 107 GLP: no
	Mobility in soil No data available	
12.5	Results of PBT and vPvB asses	ssment
	Product:	
	Assessment :	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
12.6	Other adverse effects	
	Product:	
	Endocrine disrupting : potential	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

SECTION 13: Disposal considerations

13.1 Waste treatment methods		
Product	uct :	Do not discharge into drains/surface waters/groundwater.
		Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC
		Packaging that is not properly emptied must be disposed of as the unused product.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263
ΙΑΤΑ	: UN 1263

14.2 UN proper shipping name

ADN	: PAINT RELATED MATER	IAL
ADR	: PAINT RELATED MATER	IAL
RID	: PAINT RELATED MATER	IAL
IMDG	: PAINT RELATED MATER	IAL
ΙΑΤΑ	: PAINT RELATED MATER	IAL

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

ADR	:	3
RID	:	3
IMDG	:	3
ΙΑΤΑ	:	3

14.4 Packing group

ADN

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
ADR		
Packing group	:	Ш
Classification Code	:	F1



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Hazard Identification Number	:	30
Labels	:	3
Tunnel restriction code	:	(D/E)
RID		
Packing group	:	Ш
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
IMDG		
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
IATA (Cargo)		



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

	Packing instruction (cargo aircraft)	:	366
	Packing instruction (LQ)	:	Y344
	Packing group	:	111
	Labels	:	Flammable Liquids
	IATA (Passenger)		
	Packing instruction (passenger aircraft)	:	355
	Packing instruction (LQ)	:	Y344
	Packing group	:	III
	Labels	:	Flammable liquid
14.5	Environmental hazards		
	ADN		
	Environmentally hazardous	:	no



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

ADR

Environmentally hazardous	:	no
RID		
Environmentally hazardous	:	no
IMDG		
Marine pollutant	:	no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

UK REACH List of restrictions (Annex 17)

: Conditions of restriction for the following entries should be considered:

Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

P5c

Control of Major Accident Hazards Regulations 2015 (COMAH) P5c FLAMMABLE LIQUIDS

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
		Volatile organic compounds (VOC) content: 100 %
		Volatile organic compounds (VOC) content: 868.00 g/l
		VOC content excluding water

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:	
Subcategory as indicated in Annex IIB:	dropped
Limit value for maximum VOC content as specified in Annex IIB:	dropped



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements		
H226	:	Flammable liquid and vapor.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations



Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Flam. Liq.	:	Flammable liquids
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675	Date of first issue: 22.08.2024
		485	Dute of mist 1550c. 22.00.2024

GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight: CLP - Classification Labelling Packaging Regulation: Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information Other information	: For multi-pack system sheets of all compon Restricted to professi	
Classification of the mixture:		Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a



A-R-130 5L 5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	20.01.2025	00000000050675 485	Date of first issue: 22.08.2024

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN