

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Page 1/18

Printing date 09.09.2025

V- 1.0

Revision: 02.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: CARROSS VERNIS SUPREME GLOSS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use: professional use.

Application of the substance / the mixture Clear coating material, Varnish

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

CARROSS SAS
16 rue de Serrières
69540, Irigny, France
Tel +33 (0)1 60 27 20 19
contact@carross.eu

Further information obtainable from: contact@carross.eu

1.4 Emergency telephone number:

+33 (0)1 60 27 20 19 (8:30-18:00 du lundi au jeudi, 9:30-17 le vendredi)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

n-butyl acetate

heptan-2-one

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

pentaerythritol tetrakis(3-mercaptopropionate)

triisotridecyl phosphite

dibutyltin dilaurate

Hazard statements

H225 Highly flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 1)

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Determination of endocrine-disrupting properties

78-93-3	butanone	List II
---------	----------	---------

* **SECTION 3: Composition/information on ingredients**

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	10-<25%
CAS: 110-43-0 EINECS: 203-767-1 Reg.nr.: 01-2119902391-49	heptan-2-one Flam. Liq. 3, H226; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H336	2.5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	2.5-<10%
List no.: 918-668-5 Reg.nr.: 01-2119455851-35	hydrocarbons, C9, aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	1-5%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	1-5%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	1-5%
CAS: 127519-17-9 EINECS: 407-000-3 Reg.nr.: 01-0000015648-61	reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl] propionates Aquatic Chronic 2, H411	0.1-<2%
List no.: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate Repr. 2, H361f; Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317	0.1-<0.5%
CAS: 77745-66-5 EINECS: 278-758-9 Reg.nr.: 01-2119487302-40	triisotridecyl phosphite Skin Sens. 1, H317; Aquatic Chronic 4, H413	0.1-<0.5%

(Contd. on page 3)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 2)

CAS: 77-99-6 EINECS: 201-074-9 Reg.nr.: 01-2119486799-10	propylidynetrimethanol ⚠ Repr. 2, H361fd	0.1-<1%
CAS: 77-58-7 EINECS: 201-039-8 Reg.nr.: 01-2119496068-27	dibutyltin dilaurate ⚠ Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT RE 1, H372; ⚠ Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1); ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317	0.1-<0.3%
CAS: 7575-23-7 EINECS: 231-472-8 Reg.nr.: 01-2119486981-23	pentaerythritol tetrakis(3-mercaptopropionate) ⚠ Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1); ⚠ Acute Tox. 4, H302; Skin Sens. 1A, H317	0.1-<0.5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	0-<1%
List no.: 905-588-0 Reg.nr.: 01-2119539452-40	reaction mass of ethylbenzene and xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	0-<1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out of danger area and lay down.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.

(Contd. on page 4)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 3)

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents.

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Do not allow to enter sewers/ surface or ground water.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

7.3 Specific end use(s) No further relevant information available.

*

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:	
123-86-4 n-butyl acetate	
WEL (Great Britain)	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
IOELV (EU)	Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm
110-43-0 heptan-2-one	
WEL (Great Britain)	Short-term value: 475 mg/m ³ , 100 ppm Long-term value: 237 mg/m ³ , 50 ppm Sk

(Contd. on page 5)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 4)

IOELV (EU)	Short-term value: 475 mg/m ³ , 100 ppm Long-term value: 238 mg/m ³ , 50 ppm Skin
1330-20-7 xylene	
WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
78-93-3 butanone	
WEL (Great Britain)	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
IOELV (EU)	Short-term value: 900 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm
112-07-2 2-butoxyethyl acetate	
WEL (Great Britain)	Short-term value: 332 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Sk
IOELV (EU)	Short-term value: 333 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Skin
77-58-7 dibutyltin dilaurate	
WEL (Great Britain)	Short-term value: 0.2 mg/m ³ Long-term value: 0.1 mg/m ³ as Sn; Sk
108-65-6 2-methoxy-1-methylethyl acetate	
WEL (Great Britain)	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
IOELV (EU)	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin
reaction mass of ethylbenzene and xylene	
WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin

Regulatory information

WEL (Great Britain): EH40/2020

IOELV (EU): (EU) 2019/1831

DNELs		
123-86-4 n-butyl acetate		
Dermal	DNEL	7 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	960 mg/m ³ (acute - systemic effects, workers) 960 mg/m ³ (acute - local effects, workers) 480 mg/m ³ (long-term - systemic effects, workers)

(Contd. on page 6)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 5)

		480 mg/m3 (long-term - local effects, workers)
110-43-0 heptan-2-one		
Dermal	DNEL	54.27 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	1,516 mg/m3 (acute - systemic effects, workers) 394.25 mg/m3 (long-term - systemic effects, workers)
1330-20-7 xylene		
Dermal	DNEL	212 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	442 mg/m3 (acute - systemic effects, workers) 442 mg/m3 (acute - local effects, workers) 221 mg/m3 (long-term - systemic effects, workers) 221 mg/m3 (long-term - local effects, workers)
hydrocarbons, C9, aromatics		
Dermal	DNEL	25 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	150 mg/m3 (long-term - systemic effects, workers)
78-93-3 butanone		
Dermal	DNEL	1,161 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	600 mg/m3 (long-term - systemic effects, workers)
112-07-2 2-butoxyethyl acetate		
Dermal	DNEL	102 mg/kg bw/day (acute - systemic effects, workers) 102 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	775 mg/m3 (acute - systemic effects, workers) 333 mg/m3 (acute - local effects, workers) 133 mg/m3 (long-term - local effects, workers)
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates		
Dermal	DNEL	0.83 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	7 mg/m3 (long-term - systemic effects, workers)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
Dermal	DNEL	1.8 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	1.27 mg/m3 (long-term - systemic effects, workers)
77-58-7 dibutyltin dilaurate		
Dermal	DNEL	2.08 mg/kg bw/day (acute - systemic effects, workers) 0.42 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	0.02 mg/m3 (long-term - systemic effects, workers)
7575-23-7 pentaerythritol tetrakis(3-mercaptopropionate)		
Dermal	DNEL	3.4 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	40.13 mg/m3 (acute - local effects, workers) 2.39 mg/m3 (long-term - systemic effects, workers) 40.13 mg/m3 (long-term - local effects, workers)
108-65-6 2-methoxy-1-methylethyl acetate		
Dermal	DNEL	153.5 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	275 mg/m3 (long-term - systemic effects, workers)

(Contd. on page 7)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 6)

PNECs	
123-86-4 n-butyl acetate	
PNEC	0.18 mg/l (freshwater environment) 0.018 mg/l (marine environment) 0.36 mg/l (intermittent releases) 35.6 mg/l (sewage treatment plants)
PNEC	0.981 mg/kg (freshwater sediment environment)
110-43-0 heptan-2-one	
PNEC	0.0982 mg/l (freshwater environment) 0.00982 mg/l (marine environment) 0.982 mg/l (intermittent releases) 12.5 mg/l (sewage treatment plants)
PNEC	1.89 mg/kg (freshwater sediment environment) 0.189 mg/kg (marine sediment environment) 0.321 mg/kg (soil)
1330-20-7 xylene	
PNEC	0.327 mg/l (freshwater environment) 0.327 mg/l (marine environment)
PNEC	12.46 mg/kg (freshwater sediment environment) 12.46 mg/kg (marine sediment environment)
78-93-3 butanone	
PNEC	55.8 mg/l (freshwater environment) 55.8 mg/l (marine environment) 55.8 mg/l (intermittent releases) 709 mg/l (sewage treatment plants)
PNEC	284.74 mg/kg (freshwater sediment environment) 284.7 mg/kg (marine sediment environment) 22.5 mg/kg (soil)
112-07-2 2-butoxyethyl acetate	
PNEC	0.304 mg/l (freshwater environment) 0.0304 mg/l (marine environment) 0.56 mg/l (intermittent releases) 90 mg/l (sewage treatment plants)
PNEC	2.03 mg/kg (freshwater sediment environment) 0.203 mg/kg (marine sediment environment) 0.68 mg/kg (soil)
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates	
PNEC	0.0425 mg/l (freshwater environment) 0.00425 mg/l (marine environment) 0.032 mg/l (intermittent releases) 10 mg/l (sewage treatment plants)
PNEC	3,520 mg/kg (freshwater sediment environment) 352 mg/kg (marine sediment environment)

(Contd. on page 8)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 7)

	701 mg/kg (soil)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
PNEC	0.0022 mg/l (freshwater environment) 0.00022 mg/l (marine environment) 0.009 mg/l (intermittent releases)
PNEC	1.05 mg/kg (freshwater sediment environment) 0.11 mg/kg (marine sediment environment) 0.21 mg/kg (soil)
77-58-7 dibutyltin dilaurate	
PNEC	100 mg/l (sewage treatment plants)
PNEC	0.05 mg/kg (freshwater sediment environment) 0.005 mg/kg (marine sediment environment) 0.0407 mg/kg (soil)
PNEC	0.463 µg/l (freshwater environment) 0.0463 µg/l (marine environment) 4.63 µg/l (intermittent releases)
7575-23-7 pentaerythritol tetrakis(3-mercaptopropionate)	
PNEC	2.39 mg/l (sewage treatment plants)
PNEC	0.03 µg/l (freshwater environment) 0.0034 µg/l (marine environment) 0.34 µg/l (intermittent releases)
PNEC	1.02 µg/kg (freshwater sediment environment) 0.102 µg/kg (marine sediment environment) 0.184 µg/kg (soil)
108-65-6 2-methoxy-1-methylethyl acetate	
PNEC	0.635 mg/l (freshwater environment) 0.0635 mg/l (marine environment) 6.35 mg/l (intermittent releases) 100 mg/l (sewage treatment plants)
PNEC	3.29 mg/kg (freshwater sediment environment) 0.329 mg/kg (marine sediment environment)
Ingredients with biological limit values:	
1330-20-7 xylene	
BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
78-93-3 butanone	
BMGV (Great Britain)	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
reaction mass of ethylbenzene and xylene	
BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

(Contd. on page 9)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 8)

Regulatory information BMGV (Great Britain): EH40/2020

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep ignition sources away - Do not smoke.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

A2/P2 filter (EN 14387)

Hand protection



Protective gloves

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

When choosing protective gloves, the breakthrough time, rate of penetration and degradation (EN 374) should be taken into account.

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

PVA gloves

Recommended material thickness: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Permeation level and breakthrough time: level 6 ≥ 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles (EN 166 / EN 170)

Body protection: Protective work clothing (EN 14325)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Liquid

Colour:

Colourless/light yellow

Odour:

Characteristic

Odour threshold:

Not determined.

(Contd. on page 10)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 9)

Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Decomposition temperature: pH Viscosity: Kinematic viscosity Dynamic: Solubility water: Partition coefficient n-octanol/water (log value) Vapour pressure at 20 °C: Vapour pressure at 50 °C: Density and/or relative density Density at 20 °C: Vapour density	Undetermined. 124-128 °C (123-86-4 n-butyl acetate) Highly flammable. 0.7 Vol % (hydrocarbons, C9, aromatics) 15 Vol % (123-86-4 n-butyl acetate) <23 °C Not determined. Not applicable. Not determined. Not determined. Not miscible or difficult to mix. Not determined. 105 hPa (78-93-3 butanone) 55 hPa 0.98-1 g/cm³ Not determined.
9.2 Other information Appearance: Form: Important information on protection of health and environment, and on safety. Ignition temperature: Explosive properties: Change in condition Evaporation rate	Fluid Not determined. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. Not determined.
Information with regard to physical hazard classes Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids Organic peroxides Corrosive to metals Desensitised explosives	Void Void Void Void Void Highly flammable liquid and vapour. Void Void Void Void Void Void Void Void Void

SECTION 10: Stability and reactivity

10.1 Reactivity No decomposition if used according to specifications.

(Contd. on page 11)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 10)

10.2 Chemical stability No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Reacts with alkali, amines and strong acids.

Reacts with oxidising agents.

Fumes can combine with air to form an explosive mixture.

10.4 Conditions to avoid Protect from heat and direct sunlight.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Formation of toxic gases is possible during heating or in case of fire.

* **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
123-86-4 n-butyl acetate		
Oral	LD50	10,760 mg/kg (rat)
Dermal	LD50	>14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	23.4 mg/l (rat)
110-43-0 heptan-2-one		
Oral	LD50	1,600 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	ATE	1.5 mg/l (dust/ mist)
1330-20-7 xylene		
Dermal	LD50	1,100 mg/kg (ATE)
Inhalative	ATE	1.5 mg/l (dust/ mist)
hydrocarbons, C9, aromatics		
Oral	LD50	3,592 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg
Inhalative	LC50/4 h	>6,193 mg/l (rat)
78-93-3 butanone		
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
112-07-2 2-butoxyethyl acetate		
Oral	LD50	1,880 mg/kg (rat)
Dermal	LD50	1,500 mg/kg (rabbit)
Inhalative	ATE	1.5 mg/l
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates		
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
Oral	LD50	3,230 mg/kg (rat)
Dermal	LD50	>3,170 mg/kg (rat)
77-99-6 propylidynetrimethanol		
Oral	LD50	14,700 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)

(Contd. on page 12)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 11)

77-58-7 dibutyltin dilaurate		
Oral	LD50	2,071 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
7575-23-7 pentaerythritol tetrakis(3-mercaptopropionate)		
Oral	LD50	1,000-2,000 mg/kg (rat)
Inhalative	LC50/4 h	>3,363 mg/l (rat)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/6 h	4,345 mg/l (rat)
reaction mass of ethylbenzene and xylene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties		
78-93-3	butanone	List II

* **SECTION 12: Ecological information**

12.1 Toxicity

Aquatic toxicity:	
123-86-4 n-butyl acetate	
LC50/96 h	18 mg/l (fish)
TT/16 h	115 mg/l (microorganisms)
EC50/48 h	44 mg/l (daphnia)
EC50/72 h	675 mg/l (algae)
110-43-0 heptan-2-one	
LC50/96 h	131 mg/l (fish)
EC50/72 h	98.2 mg/l (algae)
1330-20-7 xylene	
LC50/96 h	2.6 mg/l (Oncorhynchus mykiss) (OECD 203)
EC50/3 h	>157 mg/l (microorganisms)
EC50/48 h	>3.4 mg/l (Ceriodaphnia dubia) (OECD 202)
EC50/73h	2.2 mg/l (algae) (OECD 201)
hydrocarbons, C9, aromatics	
ErC50/96 h	9.2 mg/l (fish)

(Contd. on page 13)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 12)

EL50/48 h	3.2 mg/l (Daphnia magna)
ErL50/72 h	2.9 mg/l (algae)
EC50/48 h	6.14 mg/l (Daphnia magna)
EC50/10 min	>99 mg/l (microorganisms)
78-93-3 butanone	
EC50/7 d	>100 mg/l (Desmodesmus subspicatus)
EC50/48 h	>100 mg/l (Leuciscus idus melanotus)
	>100 mg/l (Daphnia magna)
112-07-2 2-butoxyethyl acetate	
EC50/72 h	>100 mg/l (Scenedesmus subspicatus)
EC50/24 h	>100 mg/l (Daphnia magna)
LC50/48 h	10-100 mg/l (Leuciscus idus melanotus)
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates	
LC50/96 h	>9.9 mg/l (fish)
EC20/30 min	>100 mg/l (microorganisms)
EC50/72 h	>2 mg/l (Scenedesmus subspicatus)
EC50/24 h	16.4 mg/l (invertebrates)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
LC50/96 h	0.9 mg/l (fish)
EC50/3 h	≥100 mg/l (microorganisms)
EC50/72 h	1.68 mg/l (Desmodesmus subspicatus)
EC50/24 h	20 mg/l (Daphnia magna)
77-58-7 dibutyltin dilaurate	
LC50/96 h	3.1 mg/l (fish)
EC50/48 h	0.463 mg/l (Daphnia magna) (OECD 202)
EC50/72 h	>1 mg/l (Desmodesmus subspicatus) (OECD 201)
EC50/48h	0.463 µg/l (Daphnia magna) (OECD 202)
7575-23-7 pentaerythritol tetrakis(3-mercaptopropionate)	
LC50/96 h	0.034 mg/l (Oncorhynchus mykiss) (OECD 203)
EC50/48 h	>0.35 mg/l (Daphnia magna)
EC50	>0.65 mg/l (Desmodesmus subspicatus)
108-65-6 2-methoxy-1-methylethyl acetate	
LC50/96 h	>100 mg/l (fish)
EC50/48 h	>500 mg/l (Daphnia magna)
EC20/30 min	>1,000 mg/l (microorganisms)
EC50/72 h	>1,000 mg/l (algae)
EC50	>100 mg/l (algae)
	>100 mg/l (fish)
	>100 mg/l (Daphnia magna)
12.2 Persistence and degradability	
123-86-4 n-butyl acetate	
Biodegradation	83 % (readily biodegradable) (OECD 301 D, 28 d, aerobic)

(Contd. on page 14)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 13)

110-43-0 heptan-2-one	
Biodegradation	69 % (readily biodegradable) (OECD 310, 28 d, aerobic)
1330-20-7 xylene	
Biodegradation	>60 % (readily biodegradable)
hydrocarbons, C9, aromatics	
Biodegradation	78 % (readily biodegradable) (OECD 301 F, 28 d, aerobic)
78-93-3 butanone	
Biodegradation	98 % (readily biodegradable) (OECD 301 D, 28 d)
112-07-2 2-butoxyethyl acetate	
Biodegradation	>70 % (readily biodegradable) (OECD 301C, 28d)
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates	
Biodegradation	9 % (not readily biodegradable)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
Biodegradation	38 % (not readily biodegradable) (OECD 301 F, 28 d, aerobic)
77-58-7 dibutyltin dilaurate	
Biodegradation	23 % (not readily biodegradable)
7575-23-7 pentaerythritol tetrakis(3-mercaptopropionate)	
Biodegradation	26 % (not readily biodegradable) (OECD 301 B, 28 d, aerobic)
108-65-6 2-methoxy-1-methylethyl acetate	
Biodegradation	100 % (readily biodegradable) (OECD 302 B, 8 d, aerobic)
12.3 Bioaccumulative potential	
123-86-4 n-butyl acetate	
BCF	15.3 (-)
log Pow	2.3
1330-20-7 xylene	
BCF	25.9
log Kow	<3.2
78-93-3 butanone	
log Pow	0.3
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates	
BCF	<0.24
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
BCF	<9.7
77-58-7 dibutyltin dilaurate	
BCF	2.91 (-)
7575-23-7 pentaerythritol tetrakis(3-mercaptopropionate)	
BCF	23.7
log Pow	3.03
108-65-6 2-methoxy-1-methylethyl acetate	
log Pow	0.56

(Contd. on page 15)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 14)

12.4 Mobility in soil	
123-86-4 n-butyl acetate	
log Koc	1.27
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates	
log Koc	5.9177
Koc	827,300
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
log Koc	5.31
Koc	204,400
7575-23-7 pentaerythritol tetrakis(3-mercaptopropionate)	
log Koc	2.54
Koc	347
108-65-6 2-methoxy-1-methylethyl acetate	
Koc	1.7

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	1263 PAINT
IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
	
Class	3

(Contd. on page 16)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 15)

Label	3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code): 33 EMS Number: F-E, S-E Stowage Category B	Warning: Flammable liquids.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	1L
UN "Model Regulation":	UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act

Regulated explosives precursors
None of the ingredients is listed.
Regulated poisons
None of the ingredients is listed.
Reportable explosives precursors
None of the ingredients is listed.
Reportable poisons
None of the ingredients is listed.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 20

Regulation (EU) No 649/2012		
77-58-7	dibutyltin dilaurate	Annex I Part 1

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
None of the ingredients is listed.

(Contd. on page 17)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 16)

Annex II - REPORTABLE EXPLOSIVES PRECURSORS		
None of the ingredients is listed.		
Regulation (EC) No 273/2004 on drug precursors		
78-93-3	butanone	3
Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors		
78-93-3	butanone	3

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

* **SECTION 16: Other information**

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

The above information is based on currently available data characterising the product. They do not constitute a guarantee or quality specification. It should be regarded as a guideline for safe use, storage, transport, disposal in case of release into the environment. It is the responsibility of the user to create conditions for the safe use of the product and the user accepts responsibility for any consequences resulting from improper use of this product.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H360FD May damage fertility. May damage the unborn child.
- H361f Suspected of damaging fertility.
- H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
- H370 Causes damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008	
Flammable liquids	Bridging principles
Skin sensitisation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 18)

Trade name: CARROSS VERNIS SUPREME GLOSS

(Contd. of page 17)

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: chemical number assigned to the chemical in the Chemical Abstracts Service list

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration

LC50: median lethal concentration

LD50: lethal dose 50%

PBT: persistent, bioaccumulative and toxic

vPvB: very persistent and very bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 2: Flammable liquid substance. Hazard category 2

Flam. Liq. 3: Flammable liquid substance. Hazard category 3

Acute Tox. 4: Acute toxicity. Hazard category 4

Skin Irrit. 2: Skin corrosion/irritation. Hazard category 2

Eye Irrit. 2: Serious eye damage/eye irritation. Hazard category 2

Skin Sens. 1: Skin sensitisation. Hazard category 1

Skin Sens. 1A: Skin sensitisation. Hazard category 1A

Muta. 2: Mutagenic effect on germ cells. Hazard category 2

Repr. 1B: Reproductive toxicity. Hazard category 1B

Repr. 2: Reproductive toxicity. Hazard category 2

Repr. 2: Reproductive toxicity. Hazard category 2

STOT SE 1: Toxic effects on target organs - single exposure. Hazard category 1

STOT SE 3: Toxic effects on target organs - single exposure. Hazard category 3

STOT RE 1: Toxic effects on target organs - repeated exposure. Hazard category 1

STOT RE 2: Toxic effects on target organs - repeated exposure. Hazard category 2

Asp. Tox. 1: Aspiration hazard. Hazard category 1

Aquatic Acute 1: Presenting a hazard to the aquatic environment - acute hazard, Category 1

Aquatic Chronic 1: Presenting a hazard to the aquatic environment. Chronic hazard, Category 1

Aquatic Chronic 2: Presenting a hazard to the aquatic environment. Chronic hazard, Category 2

Aquatic Chronic 3: Presenting a hazard to the aquatic environment. Chronic hazard, Category 3

Aquatic Chronic 4: Presenting a hazard to the aquatic environment. Chronic hazard, Category 4

Sources European Chemicals Agency, <http://echa.europa.eu/>

*** Data compared to the previous version altered.**