According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : A-H-410 2,5L 2,5L Steel jerricans A-H-410 2,5L 2,5L Steel

jerricans

Product code : 00000000050794091

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Spraying

Substance/Mixture

hardener

1.3 Details of the supplier of the safety data sheet

Company:Contact address:BASF Coatings GmbHBASF plc

BASF Coatings GmbH Postfach 6123 48136 Münster

Deutschland

4th and 5th Floors, 2 Stockport Exchange Railway Road, Stockport, SK1 3GG

United Kingdom

Telephone: +44 161 475 3000

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

E-mail address: product-safety-uk-and-ireland@basf.com

1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

Acute toxicity, Category 4 H332: Harmful if inhaled.

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single

exposure, Category 3, Respiratory

system

H335: May cause respiratory irritation.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :





Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Prevention:

Precautionary

Statements

P210

Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

P261 Avoid breathing mist or vapors.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection/ hearing

protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/ doctor if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label: HDI-Oligomer(Trimer)

isophorone diisocyanate (IPDI) polymer

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

2-heptanone

1,6-hexamethylene diisocyanate

Additional Labeling

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : organic solvent

polyisocyanate

Components

Chemical name	CAS-No.	Classification	Concentratio

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

	EC-No.		n (% w/w)
	Registration number		
HDI-Oligomer(Trimer)	28182-81-2	Acute Tox. 4;	>= 75 - <= 100
	500-060-2	H332	
	01-2119485796-17	Skin Sens. 1; H317	
		STOT SE 3; H335	
		(Respiratory system)	
isophorone diisocyanate (IPDI)	53880-05-0	Skin Sens. 1;	>= 5 - < 7
polymer	500-125-5	H317	
	01-2119488734-24	STOT SE 3; H335	
		(Respiratory	
		system)	
2-heptanone	110-43-0	Flam. Liq. 3; H226	>= 5 - < 7

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

	203-767-1 606-024-00-3 UK-20- 0537843089-5- 0000	Acute Tox. 4; H302 Acute Tox. 4; H332 STOT SE 3; H336 (Central nervous system)	
Naphtha (petroleum),hydrotreated light, Kp > 140oC	64742-52-5 265-155-0 649-465-00-7 01-2119471843-32	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 3 - < 5
xylene	1330-20-7 215-535-7 601-022-00-9	Flam. Liq. 3; H226 Acute Tox. 4; H332	>= 2.5 - < 3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

	UK-20- 2749242067-7- 0000 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Kidney, Liver, Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
1-methoxy-2-propylacetate	108-65-6 203-603-9 607-195-00-7	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous	>= 1 - < 2

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

	UK-20- 9702550300-0- 0000	system)	
	UK-20- 0537843089-5- 0000		
	UK-20- 9642318150-0- 0000		
1,6-hexamethylene diisocyanate	822-06-0 212-485-8 615-011-00-1 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Acute Tox. 4; H302 Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317	< 0.1

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

1	I	STOT SE 3; H335	
		3101 SE 3; H335	
		(Respiratory	
		system)	
		specific	
		concentration	
		limit	
		Resp. Sens. 1;	
		H334	
		>= 0.5 %	
		>= 0.5 %	
		Skin Sens. 1;	
		H317	
		>= 0.5 %	
		3.3 /0	

For explanation of abbreviations see section 16.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own

safety.

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

Immediately remove contaminated clothing.

In all cases of doubt, or when symptoms persist, seek

medical attention.

Move out of dangerous area.

Never give anything by mouth to an unconscious person.

If inhaled : If symptoms persist, call a physician.

If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Call a physician immediately.

In case of contact, immediately flush skin with plenty of

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

water for at least 15 minutes while removing

contaminated clothing and shoes.

In case of eye contact : Immediately wash affected eyes for at least 15 minutes

under running water with eyelids held open, consult an

eye specialist.

Call a physician immediately.

If easy to do, remove contact lens, if worn.

If swallowed : Do not induce vomiting due to aspiration hazard.

Keep at rest.

If symptoms persist, call a physician or Poison Control

Center immediately.

Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Symptoms : Information, i.e. additional information on symptoms

and effects may be included in the GHS labeling phrases

available in Section 2 and in the Toxicological

assessments available in Section 11.

Risks : May cause an allergic skin reaction.

Harmful if inhaled.

May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing : Water spray jet

media

Dry powder

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Alcohol-resistant foam

Carbon dioxide (CO2)

Unsuitable extinguishing : High volume water jet

media

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire : Fire will produce dense black smoke containing

fighting hazardous combustion products (see section 10).

Hazardous combustion : Nitrogen oxides (NOx)

products

5.3 Advice for firefighters

Special protective : Appropriate breathing apparatus may be required.

equipment for fire-fighters

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Further information : In the event of fire, cool tanks with water spray.

Fire residues and contaminated fire extinguishing water

must be disposed of in accordance with local

regulations.

Collect contaminated fire extinguishing water separately.

This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

Advice on product handling can be found in sections 7

and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

areas.

6.2 Environmental precautions

Environmental precautions: Do not allow uncontrolled discharge of product into the

environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains

inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible

absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth. Place in a suitable container. The contaminated area should be cleaned up immediately

with a suitable decontaminant. One possible

(flammable) decontaminant comprises (by volume):

ethanol or isopropyl alcohol (50 parts); water (45 parts);

concentrated ammonia solution (5 parts). A non-

flammable alternative is: sodium carbonate (5 parts);

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13).

Ensure adequate ventilation.

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust

ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in

application area. For personal protection see section 8.

Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Open drum carefully as content may be under pressure.

Do not breathe vapors or spray mist.

Protect from moisture.

Advice on protection against fire and explosion

: Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

Hygiene measures : Remove contaminated clothing immediately and dispose

of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal

feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions

: Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Exercise caution when opening to allow pressure release. Precautions should be taken to minimise exposure to atmospheric humidity or water: carbon dioxide will be formed which in closed containers can result pressurisation. Always keep in containers of same material as the original one. Observe label

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

precautions. Store protected against freezing.

Advice on common storage: Keep away from oxidising agents, strongly alkaline and

strongly acidic materials, amines, alcohols and water.
Uncontrolled exothermic reactions occur with amines
and alcohols. The product reacts with water resulting in

evolution of carbon dioxide. In closed containers,

pressure build up could result in distortion, blowing and

in extreme cases bursting of the container.

Recommended storage

temperature

: 5.00 - 35.00 °C

Packaging material : Suitable material: Carbon steel (Iron), tinned carbon

steel (Tinplate)

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further

information.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
HDI-	28182-81-2	TWA	0.02 mg/m3	GB EH40	
Oligomer(Trimer)			(NCO)		
	Further information: Capable of causing occupational asthma.				
		STEL	0.07 mg/m3	GB EH40	
			(NCO)		
	Further information: Capable of causing occupational asthma.				
2-heptanone	110-43-0	STEL	100 ppm	GB EH40	
			475 mg/m3		
	Further information: Can be absorbed through the skin. The assigned				

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. TWA 50 ppm GB EH40 237 mg/m3 Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. 2000/39/EC TWA 50 ppm 238 mg/m3 Further information: Identifies the possibility of significant uptake through the skin, Indicative STEL 100 ppm 2000/39/EC 475 mg/m3 Further information: Identifies the possibility of significant uptake through the skin, Indicative xylene 1330-20-7 TWA 50 ppm GB EH40

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

		220 mg/m3			
Furth	Further information: Can be absorbed through the skin. The assigned				
subst	ances are those for w	which there are concerns	that dermal		
absor	ption will lead to sys	temic toxicity.			
	STEL	100 ppm	GB EH40		
		441 mg/m3			
Furth	er information: Can l	oe absorbed through the	skin. The assigned		
subst	ances are those for w	which there are concerns	that dermal		
absor	ption will lead to sys	temic toxicity.			
	TWA 50 ppm 2000/39/				
		221 mg/m3			
Furth	er information: Ident	tifies the possibility of sig	gnificant uptake		
throu	gh the skin, Indicativ	e			
	STEL	100 ppm	2000/39/EC		
		442 mg/m3			
Furth	er information: Ident	tifies the possibility of sig	nificant uptake		
throu	through the skin, Indicative				

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

1-methoxy-2- propylacetate	108-65-6	TWA	50 ppm	GB EH40		
' '			274 mg/m3			
	Further info	Further information: Can be absorbed through the skin. The assigned				
	substances a	substances are those for which there are concerns that dermal				
	absorption v	vill lead to systemi	c toxicity.			
		STEL	100 ppm	GB EH40		
			548 mg/m3			
	Further info	Further information: Can be absorbed through the skin. The assigned				
	substances a	re those for which	there are concerns that d	ermal		
	absorption v	vill lead to systemi	c toxicity.			
		STEL	100 ppm	2000/39/EC		
			550 mg/m3			
	Further info	rmation: Identifies	the possibility of significar	nt uptake		
	through the	through the skin, Indicative				
		TWA	50 ppm	2000/39/EC		
			275 mg/m3			
	Further info	Further information: Identifies the possibility of significant uptake				

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

through the skin, Indicative

1,6hexamethylene
diisocyanate

Further information: Capable of causing occupational asthma.

STEL

0.07 mg/m3
(NCO)

Further information: Capable of causing occupational asthma.

Biological occupational exposure limits

	-			
Substance name	CAS-No.	Control	Sampling time	Basis
		parameters		
HDI-Oligomer(Trimer)	28182-81-2	isocyanate-	At the end of the	GB EH40
		derived diamine	period of	BAT
		(Isocyanates): 1	exposure	
		μmol/mol		
		creatinine		
		(Urine)		
	1	1	1	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT
1,6-hexamethylene diisocyanate	822-06-0	isocyanate- derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Required when there is a risk of eye contact.

Hand protection

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Remarks

: Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for shortterm contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

time according to EN ISO 374-1)

Skin and body protection : chemical-resistant disposable coveralls

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant

synthetic fibres.

Respiratory protection : Suitable respiratory equipment:

full face mask with AB2P3 class combination filter

When workers are facing concentrations above the exposure limit they must use appropriate certified

respirators.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily

accessible.

Under cool dry conditions, it is possible for the

isocyanate to remain unreacted in the paint film for up

to 30 hours after application.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Respiratory protective equipment should be worn by

spray booth operatives.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and

safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Color : colorless

Odor : ketone-like

pH : substance/mixture reacts with water

Melting point/ range : not determined

Boiling point/boiling range : 116.00 °C

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date:

SDS Number: 000000000050794

Date of last issue: 14.11.2024

3.0 02.03.2025

091

Date of first issue: 03.05.2024

Flash point : 42 °C

Method: ISO 3679

Evaporation rate : not determined

Upper explosion limit /

Upper flammability limit

: not determined

Lower explosion limit /

Lower flammability limit

: > 35.0 g/m3

Vapor pressure : 20.0000 hPa (20 °C)

(50 °C)

not determined

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Relative vapor density : Heavier than air.

Density : 1.090 g/cm3

Solubility(ies)

Water solubility : not determined

Partition coefficient: n-

octanol/water

: not applicable for mixtures

Autoignition temperature : > 200 °C

Decomposition : No decomposition if stored and handled as

temperature prescribed/indicated.

Viscosity

Viscosity, dynamic : No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Viscosity, kinematic : 195.5 mm2/s (23 °C)

(40 °C)

not determined

Flow time : > 30 s

Cross section: 6 mm

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids) : Flammable liquid and vapour.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

Particle size : The substance / product is marketed or used in a non

solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazardous reactions when stored and handled

according to instructions.

10.4 Conditions to avoid

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Conditions to avoid : Avoid direct contact with water.

Avoid direct sunlight.

Protect from frost.

Heat, flames and sparks.

Heat.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidising agents, strongly alkaline and

strongly acidic materials, amines, alcohols and water.
Uncontrolled exothermic reactions occur with amines
and alcohols. The product reacts with water resulting in

evolution of carbon dioxide. In closed containers,

pressure build up could result in distortion, blowing and

in extreme cases bursting of the container.

10.6 Hazardous decomposition products

Nitrogen oxides (NOx) Hydrogen cyanide (hydrocyanic acid) Isocyanates

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 12.85 mg/l

Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Components:

2-heptanone:

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 16.7 mg/l

Exposure time: 4 h

Test atmosphere: vapor

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Based on available data, the classification criteria are not met.

Product:

No aspiration toxicity classification

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

HDI-Oligomer(Trimer):

Partition coefficient: n- : log Pow: 9.81 (25 °C)

octanol/water

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

2-heptanone:

Partition coefficient: n- :

octanol/water

: log Pow: 2.26 (30 °C)

pH: 7

Method: Regulation (EC) No. 440/2008, Annex, A.8

GLP: yes

xylene:

Partition coefficient: n-

octanol/water

: log Pow: 3.12 - 3.20 (25 °C)

GLP: no

Remarks: Information taken from reference works and

the literature.

1-methoxy-2-propylacetate:

Partition coefficient: n-

: log Pow: 1.2 (20 °C)

octanol/water

pH: 6.8

Method: OECD Test Guideline 117

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components

considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative

(vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting

potential

: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Product : Dispose of isocyanate waste in dry containers and never

mix together with other wastes (reaction, dangerous

pressure build up).

Do not discharge into drains/surface

waters/groundwater.

Observe national and local legal requirements.

Contaminated packaging : Containers which are not properly emptied must be

disposed pursuant to Directive 2008/98/EC

Residues in empty containers should be neutralised with

decontaminant (see section 6).

Packaging that is not properly emptied must be disposed

of as the unused product.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263

ADR : UN 1263

RID : UN 1263

IMDG : UN 1263

IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT

ADR : PAINT

RID : PAINT

IMDG : PAINT

IATA : PAINT

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date:

3.0

SDS Number: 0000000000050794

Date of last issue: 14.11.2024

02.03.2025 0000 091

Date of first issue: 03.05.2024

14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 3

ADR : 3

RID : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADN

Packing group : III

Classification Code : F1

Hazard Identification : 30

Number

Labels : 3

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794 Date of first issue: 03.05.2024

ADR

Packing group : III

Classification Code : F1

Hazard Identification : 30

Number

Labels : 3

Tunnel restriction code : (D/E)

RID

Packing group : III

Classification Code : F1

Hazard Identification : 30

Number

Labels : 3

IMDG

Packing group : III

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Labels : 3

EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction : 355

(passenger aircraft)

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable liquid

14.5 Environmental hazards

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

ADN

Environmentally : no

hazardous

ADR

Environmentally : no

hazardous

RID

Environmentally : no

hazardous

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the

following entries should be

considered:

Number on list 72, 3

Number on list 3

UK REACH Candidate list of substances of very high : Not applicable

concern (SVHC) for Authorisation

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

The Persistent Organic Pollutants Regulations : Not applicable

(retained Regulation (EU) 2019/1021 as amended

for Great Britain)

Regulation (EC) on substances that deplete the : Not applicable

ozone layer

UK REACH List of substances subject to : Not applicable

authorisation (Annex XIV)

P5c

Control of Major Accident Hazards P5c FLAMMABLE LIQUIDS

Regulations 2015 (COMAH)

Volatile organic : Volatile organic compounds (VOC) content: 161.1 g/l

compounds

Directive 2010/75/EU of 24 November 2010 on

industrial emissions (integrated pollution prevention and

control)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

Volatile organic compounds (VOC) content: 14.21 %

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB: dropped Limit value for maximum VOC content as specified in Annex IIB: dropped

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapor.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H319 : Causes serious eye irritation.

H330 : Fatal if inhaled.

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 : May cause respiratory irritation.

H336 : May cause drowsiness or dizziness.

H373 : May cause damage to organs through prolonged or

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

repeated exposure.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard

Eye Irrit. : Eye irritation

Flam. Liq. : Flammable liquids

Resp. Sens. : Respiratory sensitization

Skin Irrit. : Skin irritation

Skin Sens. : Skin sensitization

STOT RE : Specific target organ toxicity - repeated exposure

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a

first list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

GB EH40 BAT : UK. Biological monitoring guidance values

2000/39/EC / TWA : Limit Value - eight hours

2000/39/EC / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road: AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

SDS Number: Version **Revision Date:** Date of last issue: 14.11.2024

00000000050794 3.0 02.03.2025

Date of first issue: 03.05.2024 091

Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data

sheets of all components.

Restricted to professional users.

Classification of the mixture:		Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Acute Tox. 4	H332	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-H-410 2,5L 2,5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 14.11.2024

3.0 02.03.2025 00000000050794

091 Date of first issue: 03.05.2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB/EN