

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Product identifier	: 6800
Product name	: STANDOX PRECLEANER 6800?
Product type	: Liquid.
Other means of identification	: 4024669801323
Date of issue/ Date of revision	: 8 May 2024
Version	: 1.11
Date of previous issue	: 13 March 2024

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	: Solvent.	
Uses advised against	: Not for sale to or use by consum	iers.

1.3 Details of the supplier of the safety data sheet

Axalta Coating Systems Gerr	nany GmbH & Co. KG
Christbusch 25	
DE 42285 Wuppertal	
+49 (0)202 529-0	
e-mail address of person responsible for this SDS	: sds-competence@axalta.com

1.4 Emergency telephone number

<u>Supplier</u>	
Telephone number	: +(44)-870-8200418
Hours of operation	:

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to UK CLP/GHS

Flam. Liq. 3, H226 Eye Irrit. 2, H319

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

SECTION 2: Hazards identification

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	H226 - Flammable liquid and vapour. H319 - Causes serious eye irritation.
Precautionary statements		
Prevention	:	P280 - Wear eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Response	:	P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Туре
Isopropyl alcohol	REACH #: 01-2119457558-25 EC: 200-661-7 CAS: 67-63-0	≥10 - <20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 See Section 16 for	[1] [2]
			the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

4.1 Description of first aid n	neasures
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	pain or irritation watering redness
Inhalation	: No specific data.
Skin contact Ingestion	No specific data.No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Recommended: alcohol-resistant foam, CO ₂ , powders, water spray.
Unsuitable extinguishing media	:	Do not use water jet.
5.2 Special hazards arising	from	the substance or mixture
Hazards from the substance or mixture	:	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Substance of mixture		cause a health hazaru.

5.3 Advice for firefighters

Date	of	issue/Date	of revision
------	----	------------	-------------

: 5/8/2024

SECTION 5: Firefighting measures

Special protective actions for fire-fighters	:	Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other	: See Section 1 for emergency contact information.
sections	See Section 8 for information on appropriate personal protective equipment.
	See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Seveso Directive - Reporting thresholds

Date of issue/Date of revision	: 5/8/2024	Date of previous issue	: 3/13/2024	Version : 1.11 4/13
--------------------------------	------------	------------------------	-------------	---------------------

SECTION 7: Handling and storage

Danger criteriaCategoryNotification and MAPP
thresholdSafety report thresholdP5c5000 tonne50000 tonne

7.3 Specific end use(s) Recommendations

Not	availa	hla
 INOL	avalla	DIE.

Industrial sector specific : Not available. solutions

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Isopropyl alcohol	EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 1250 mg/m ³ 15 minutes. STEL: 500 ppm 15 minutes. TWA: 999 mg/m ³ 8 hours. TWA: 400 ppm 8 hours.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Isopropyl alcohol	DNEL	Long term Inhalation	500 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	888 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	26 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	51 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	89 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	178 mg/m³	General population	Systemic
	DNEL	Long term Dermal	319 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	1000 mg/ m ³	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
Isopropyl alcohol	Fresh water	140.9 mg/l	-
	Marine water	140.9 mg/l	-
	Fresh water sediment	552 mg/kg	-
	Marine water sediment	552 mg/kg	-
	Soil	28 mg/kg	-
	Sewage Treatment Plant	2251 mg/kg	-

8.2 Exposure controls

Date of issue/Date of revision

SECTION 8: Exposure controls/personal protection

 Appropriate engineering controls Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn. Individual protection measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated clothing Wash contaminated clothing before reusing. Ensure that eyewash stations and 	
Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working perio Appropriate techniques should be used to remove potentially contaminated clothi	
before eating, smoking and using the lavatory and at the end of the working perio Appropriate techniques should be used to remove potentially contaminated clothi	
safety showers are close to the workstation location.	
Eye/face protection : Use safety eyewear designed to protect against splash of liquids.	
Skin protection	
Hand protection	
There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product.	r
The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.	
Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly.	
The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.	
Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.	;
Gloves : Duration / breakthrough time: <1 hour, Glove material: NBR, nitrile rubber, material thickness as splash protection: at lea 0.2 mm, (EN374) Glove material: NBR, nitrile rubber Material thickness for short-term contact: at lea 0.5 mm, (EN374)	
The recommendation for the type or types of glove to use when handling this product is based on information from the following source: Expert judgment	
The user must check that the final choice of type of glove selected for handling thi product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.	
Body protection: Personnel should wear antistatic clothing made of natural fibres or of high- temperature-resistant synthetic fibres.	
Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	9
Respiratory protection : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.	e
Environmental exposure : Do not allow to enter drains or watercourses. controls	

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Clear.
Odour	: Not available.
Odour threshold	: Not available.
Melting point/freezing point	: Technically not possible to measure

Date of issue/D	ate of revision
-----------------	-----------------

SECTION 9: Physical and chemical properties

Initial boiling point and boiling range	: 8	82.5 to 100.1°C (180.5 to 212.2°F)	
Flammability (solid, gas)	: 1	Not available.	
Upper/lower flammability or explosive limits		Lower: 2% Upper: 12%	
	1	Not available.	
Flash point	: (Closed cup: 29°C (84.2°F)	
Auto-ignition temperature	: 4	456°C (852.8°F)	
Decomposition temperature	: 1	Not applicable.	
рН	: 7	7.5 to 8.5	
Viscosity	: 1	Not available.	
Solubility(ies)	:		
Media		Result	
cold water		Easily soluble	
Solubility in water	: 1	Not available.	
Miscible with water	: `	Yes.	
Partition coefficient: n-octanol/	: 1	Not applicable.	
water			
Vapour pressure	: 2	2.7 kPa (20.6 mm Hg)	
Relative density	: 1	Not available.	
Density	: (0.946 g/cm³	
Vapour density	: 1	Not available.	
Explosive properties	: Not available.		
Oxidising properties	: Not available.		
Weight volatiles	: 9	99.9 % (w/w)	
VOC content	: `	19.9 % (w/w) (2010/75/EU)	

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Further information Not available.

9.2.2 Other safety characteristics

Miscible with water : Yes.

Further information Not available.

room temperature (=20°C)

SECTION 10: Stabil	ity and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.

Date of issue/Date of revision

SECTION 10: Stability and reactivity

10.5 Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	:	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen. Not applicable

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Isopropyl alcohol	LC50 Inhalation Vapour	Rat - Male, Female	37.5 mg/l	4 hours
	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	(vapours)	Inhalation (dusts and mists) (mg/l)
Isopropyl alcohol	5000	12800	N/A	37.5	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Isopropyl alcohol	Eyes - Moderate irritant	Rabbit	-	10 mg	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

Sensitisation

<u>Mutagenicity</u>

<u>Carcinogenicity</u> <u>Reproductive toxicity</u>

Teratogenicity

<u>Specific target organ toxicity (single exposure)</u>

Product/ingredient name			Category	Route of exposure	Target organ
Isopropyl alcohol			Category 3	-	Narcotic effects
Specific target organ toxicit	ty (repeated exposure)		I	
Not available.					
Aspiration hazard					
Not available.					
nformation on likely routes f exposure	:	Not available.			
otential acute health effects	5				
Eye contact	:	Causes serious eye irritati	ion.		
Inhalation	:	No known significant effect	cts or critical hazards	i.	
Skin contact	:	No known significant effect	cts or critical hazards	i.	
Ingestion	:	No known significant effec	cts or critical hazards		
ymptoms related to the phy	vsic	al, chemical and toxicolo	gical characteristic	<u>:s</u>	
Eye contact	:	Adverse symptoms may in pain or irritation watering redness	nclude the following:		
Inhalation	:	No specific data.			
Skin contact	:	No specific data.			
Ingestion	:	No specific data.			
elayed and immediate effec	ts a	as well as chronic effects	from short and lor	ng-term exposur	<u>.</u> e
<u>Short term exposure</u>					
Potential immediate effects	:	Not available.			
Potential delayed effects	:	Not available.			
Long term exposure					
Potential immediate effects	:	Not available.			
Potential delayed effects	:	Not available.			
Potential chronic health effe	ect	<u>S</u>			
Not available.					
Conclusion/Summary	:	Not available.			
General	:	No known significant effect	cts or critical hazards	i.	
Carcinogenicity	:	No known significant effect	cts or critical hazards	i.	
Mutagenicity	:	No known significant effect	cts or critical hazards	i.	
Reproductive toxicity	:	No known significant effec	cts or critical hazards	i.	
other information		Not available.			

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Isopropyl alcohol	Acute EC50 7550 mg/l Fresh water	Daphnia - Water flea - <i>Daphnia</i> <i>magna</i> - Neonate	48 hours
	Acute LC50 1400000 µg/l Marine water	Crustaceans - Common shrimp, sand shrimp - <i>Crangon crangon</i>	48 hours
	Acute LC50 4200 mg/l Fresh water	Fish - Harlequinfish, red rasbora - <i>Rasbora</i> <i>heteromorpha</i>	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Isopropyl alcohol	0.05	-	Low

12.4 Mobility in soil	
Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

Waste catalogue

Waste code	Waste designation
08 01 19*	aqueous suspensions containing paint or varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 13: Disposal considerations

Type of packaging		Waste catalogue
	15 01 10*	packaging containing residues of or contaminated by hazardous substances
Special precautions	taken when l Empty conta residues ma container. D thoroughly in	I and its container must be disposed of in a safe way. Care should be handling emptied containers that have not been cleaned or rinsed out. iners or liners may retain some product residues. Vapour from product y create a highly flammable or explosive atmosphere inside the to not cut, weld or grind used containers unless they have been cleaned ternally. Avoid dispersal of spilt material and runoff and contact with ays, drains and sewers.

SECTION 14: Transport information

	-			
	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	111	111	III	111
14.5 Environmental hazards	No.	No.	No.	No.

Additional information

ADR/RID

: Tunnel code (D/E)

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk	: Not available.
according to IMO	
instruments	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>UK (GB)/REACH</u>

Annex XIV - List of substances subject to authorisation

<u>Annex XIV</u>

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

SECTION 15: Regulatory information

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

P5c

National regulations

Γ	Product/ingredient name	List name	Name on list	Classification	Notes	

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

15.2 Chemical safety	:	This product contains substances for which Chemical Safety Assessments are still
assessment		required.

SECTION 16: Other information

✓ Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and
-	Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019
	No. 720 and amendments
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = GB CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Flam. Liq. 3, H226	On basis of test data
Eye Irrit. 2, H319	Calculation method

Full text of abbreviated H statements

	nmable liquid and vapour.
H319 Cau	ses serious eye irritation.
H336 May	cause drowsiness or dizziness.

Full text of classifications

Eye Irrit. 2 Flam. Liq. 2 Flam. Liq. 3 STOT SE 3	 FLAMMABLE LIQUIDS - Category 2 FLAMMABLE LIQUIDS - Category 3 	
Date of issue/ Date of revision	: 5/8/2024	
Version	: 1.11	

SECTION 16: Other information

Date of previous issue : 3/13/2024

Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.