

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** 4CR 4330 1K-Kunststoff-Primer
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Filler and surfacer
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
4CR Vertriebsgesellschaft mbH  
Oberer Sommerfeldweg 2  
D-94469 Deggendorf  
Tel.: +49 (0) 40 69 60 99 315  
Fax: +49 (0) 40 69 60 99 316  
E-Mail: [Info@4CR.com](mailto:Info@4CR.com)  
[www.4CR.com](http://www.4CR.com)
- **1.4 Emergency telephone number:** +49(0)700 24112112 (CRM)

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



Flam. Liq. 2      H225      Highly flammable liquid and vapour.

---



STOT RE 2      H373      May cause damage to organs through prolonged or repeated exposure.  
Asp. Tox. 1      H304      May be fatal if swallowed and enters airways.

---



Skin Irrit. 2      H315      Causes skin irritation.  
Eye Irrit. 2      H319      Causes serious eye irritation.  
STOT SE 3      H335-H336      May cause respiratory irritation. May cause drowsiness or dizziness.  
Aquatic Chronic 3      H412      Harmful to aquatic life with long lasting effects.

---

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02    GHS07    GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**  
*Xylene*  
*ethyl acetate*

**Trade name: 4CR 4330 1K-Kunststoff-Primer**

(Contd. of page 1)

Solvent naphtha (petroleum), light arom.  
ethylbenzene

· **Hazard statements**

- H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H304 May be fatal if swallowed and enters airways.  
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P321 Specific treatment (see on this label).  
P331 Do NOT induce vomiting.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.  
· **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

|  |  |          |
|--|--|----------|
| CAS: 141-78-6<br>EINECS: 205-500-4<br>Reg.nr.: 01-2119475103-46  | ethyl acetate<br>⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336   | 25-50%   |
| CAS: 1330-20-7<br>EINECS: 215-535-7<br>Reg.nr.: 01-2119488216-32 | Xylene<br>⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304;<br>⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315;<br>Eye Irrit. 2, H319; STOT SE 3, H335 | 25-50%   |
| CAS: 64742-95-6<br>EINECS: 265-199-0                             | Solvent naphtha (petroleum), light arom.<br>⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304  | 2.5-<10% |
| CAS: 123-42-2<br>EINECS: 204-626-7<br>Reg.nr.: 01-2119473975-21  | 4-hydroxy-4-methylpentan-2-one<br>⚠ Flam. Liq. 3, H226; ⚠ Eye Irrit. 2, H319; STOT SE 3, H335  | 2.5-<10% |
| CAS: 100-41-4<br>EINECS: 202-849-4<br>Reg.nr.: 01-2119489370-35  | ethylbenzene<br>⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304;<br>⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;<br>Aquatic Chronic 3, H412       | 2.5-<10% |
| CAS: 95-63-6<br>EINECS: 202-436-9                                | 1,2,4-trimethylbenzene<br>⚠ Flam. Liq. 3, H226; ⚠ Aquatic Chronic 2, H411; ⚠ Acute<br>Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3,<br>H335                | 2.5-<10% |

(Contd. on page 3)

**Trade name: 4CR 4330 1K-Kunststoff-Primer**

(Contd. of page 2)

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Seek immediate medical advice.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

#### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

(Contd. on page 4)

**Trade name: 4CR 4330 1K-Kunststoff-Primer**

(Contd. of page 3)

Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Store away from foodstuffs.

· **Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Storage class:** 3

· **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

· **8.1 Control parameters**

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

**141-78-6 ethyl acetate**

|     |  |
|-----|--|
| WEL | Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm<br>Long-term value: 734 mg/m <sup>3</sup> , 200 ppm |
|-----|--|

**1330-20-7 Xylene**

|     |  |
|-----|--|
| WEL | Short-term value: 441 mg/m <sup>3</sup> , 100 ppm<br>Long-term value: 220 mg/m <sup>3</sup> , 50 ppm<br>Sk; BMGV |
|-----|--|

**123-42-2 4-hydroxy-4-methylpentan-2-one**

|     |   |
|-----|---|
| WEL | Short-term value: 362 mg/m <sup>3</sup> , 75 ppm<br>Long-term value: 241 mg/m <sup>3</sup> , 50 ppm |
|-----|---|

**100-41-4 ethylbenzene**

|     |   |
|-----|---|
| WEL | Short-term value: 552 mg/m <sup>3</sup> , 125 ppm<br>Long-term value: 441 mg/m <sup>3</sup> , 100 ppm<br>Sk |
|-----|---|

**95-63-6 1,2,4-trimethylbenzene**

|     |  |
|-----|--|
| WEL | Long-term value: 125 mg/m <sup>3</sup> , 25 ppm<br>ILV |
|-----|--|

· **Ingredients with biological limit values:**

**1330-20-7 Xylene**

|      |  |
|------|--|
| BMGV | 650 mmol/mol creatinine<br>Medium: urine<br>Sampling time: post shift<br>Parameter: methyl hippuric acid |
|------|--|

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)

**Trade name: 4CR 4330 1K-Kunststoff-Primer**

(Contd. of page 4)

· **Respiratory protection:**



*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.*

· **Protection of hands:**

*Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*



*Protective gloves (EN 374)*

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.*

· **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

· **Breakthrough time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

· **Eye protection:**



*Tightly sealed goggles*

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Fluid  
**Colour:** According to product specification  
**Odour:** Characteristic  
**Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

**Melting point/freezing point:** Undetermined.  
**Initial boiling point and boiling range:** 77 °C

· **Flash point:** 10 °C (DIN 53213)

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 430 °C (DIN 51794)

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

(Contd. on page 6)

**Trade name: 4CR 4330 1K-Kunststoff-Primer**

(Contd. of page 5)

|  |   |
|--|---|
| · <b>Explosive properties:</b>                   | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · <b>Explosion limits:</b>                       |   |
| <b>Lower:</b>                                    | 1.1 Vol %   |
| <b>Upper:</b>                                    | 11.5 Vol %  |
| · <b>Vapour pressure at 20 °C:</b>               | 97 hPa  |
| · <b>Density at 20 °C:</b>                       | 0.912 g/cm <sup>3</sup> (DIN 53217)   |
| · <b>Relative density</b>                        | Not determined.   |
| · <b>Vapour density</b>                          | Not determined.   |
| · <b>Evaporation rate</b>                        | Not determined.   |
| · <b>Solubility in / Miscibility with water:</b> | Not miscible or difficult to mix.   |
| · <b>Partition coefficient: n-octanol/water:</b> | Not determined.   |
| · <b>Viscosity:</b>                              |   |
| <b>Dynamic:</b>                                  | Not determined.   |
| <b>Kinematic at 20 °C:</b>                       | 13 s (DIN 53211/4)  |
| · <b>Solvent content:</b>                        |   |
| <b>VOC (EC)</b>                                  | 95.54 %   |
| <b>Solids content (weight-%):</b>                | 4.3 %   |
| · <b>9.2 Other information</b>                   | No further relevant information available.  |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

|  |          |                       |
|--|----------|-----------------------|
| <b>1330-20-7 Xylene</b>                                    |          |                       |
| Oral   | LD50     | 5,251 mg/kg (rat)     |
| Dermal   | LD50     | >5,000 mg/kg (rabbit) |
| Inhalative   | LC50/4 h | 29 mg/l (rat)         |
| <b>64742-95-6 Solvent naphtha (petroleum), light arom.</b> |          |                       |
| Oral   | LD50     | >6,800 mg/kg (rat)    |
| Dermal   | LD50     | >3,400 mg/kg (rab)    |

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.

(Contd. on page 7)

**Trade name: 4CR 4330 1K-Kunststoff-Primer**

(Contd. of page 6)

- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure**  
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) : hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |                                       |              |
|---------------------------------------|--------------|
| · <b>14.1 UN-Number</b>               |              |
| · <b>ADR, IMDG, IATA</b>              | UN1263       |
| · <b>14.2 UN proper shipping name</b> |              |
| · <b>ADR</b>                          | UN1263 PAINT |
| · <b>IMDG, IATA</b>                   | PAINT        |

(Contd. on page 8)



**Trade name: 4CR 4330 1K-Kunststoff-Primer**

(Contd. of page 7)

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 3 (F1) Flammable liquids.  
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids.  
· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):** 33

· **EMS Number:** F-E,S-E

· **Stowage Category** B

· **14.7 Transport in bulk according to Annex II of**

**Marpol and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 5L

· **Transport category** 2

· **Tunnel restriction code** D/E

· **IMDG**

· **Limited quantities (LQ)** 5L

· **UN "Model Regulation":** UN 1263 PAINT, 3, II

**SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials, Annex II:**

| Class | Share in % |
|-------|------------|
| NK    | 50-100     |

(Contd. on page 9)



**Trade name: 4CR 4330 1K-Kunststoff-Primer**

(Contd. of page 8)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**