SAFETY DATA SHEET



Date of issue/Date of revision

: 12 March 2024

Version : 1.02

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: AQUAMAX EXTRA ROSSO OSSIDO B.C.
Product code	: 1.550.5520/E0.5
Product type	: Liquid.
Other means of identification	: Not available.
1.2 Relevant identified use	es of the substance or mixture and uses advised against
Product use	: P rofessional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Industries Italia S.r.l., Via Comasina, 121, 20161 Milano, Italy Tel: +39 02 6404.1 PPG Industries (UK) Ltd., Needham Road, Stowmarket, Suffolk, IP14 2AD, UK Tel: +44 (0) 1449 773 338

e-mail address of person : Product.Stewardship.EMEA@ppg.com responsible for this SDS

1.4 Emergency telephone number

Supplier

Company emergency telephone number : +39 02 6404.1 (0800-1700)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Product definition : Mixture <u>Classification according to UK CLP/GHS</u>

Not classified.

The product is not classified as hazardous according to UK CLP Regulation SI 2019/720 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

2.2 Laber elements		
Signal word	:	No signal word.
Hazard statements	1	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	1	Not applicable.
Storage	1	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
		P501
Supplemental label elements	:	Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction. Safety data sheet available on request.

Code	: 1.550.5520/E0.5	Date of issue/Date of revision	: 12 March 2024
	X EXTRA ROSSO OSSIDO B C		

SECTION 2: Hazards identification

: Not applicable.
ents
: Not applicable.
: Not applicable.
: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
: None known.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Туре
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≥5.0 - <10	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
2,4,7,9-tetramethyldec-5-yne- 4,7-diol	REACH #: 01-2119954390-39 EC: 204-809-1 CAS: 126-86-3	<1.0	Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

English (GB)	United Kingdom (UK) 2/12
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Code AQUAMAX	: 1.550.5520/E0.5 EXTRA ROSSO OSSIDO B.C.	Date of issue/Date of revision	: 12 March 2024

SECTION 4: First aid measures

Potential acute health effects

Eye contact

4.2 Most important symptoms and effects, both acute and delayed

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

: No known significant effects or critical hazards.

Lyc contact	
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>toms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
4.3 Indication of any immed	ate medical attention and special treatment needed
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
SECTION 5: Firefigh	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident i there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

SECTION 6: Accidental release measures

mode.

6.1 Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	

Conforms to Regulation (E	=C) NO. 1907/2006 (F	REACH), Annex II, as amended by UK REAC	A Regulation SI 2019/758
Code : 1.550.55 AQUAMAX EXTRA ROS		Date of issue/Date of revision	: 12 March 2024
SECTION 6: Acci	dental release	measures	
6.2 Environmental precautions	and sewers	ersal of spilt material and runoff and contact v s. Inform the relevant authorities if the produc ewers, waterways, soil or air).	
6.3 Methods and materi	al for containment a	and cleaning up	
Small spill	up if water-	without risk. Move containers from spill area soluble. Alternatively, or if water-insoluble, a d place in an appropriate waste disposal con	bsorb with an inert dry

	licensed waste disposal contractor.
Large spill :	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4 Reference to other : sections	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.
--------------------------------------	---

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
	Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Code

: 1.550.5520/E0.5 AQUAMAX EXTRA ROSSO OSSIDO B.C. Date of issue/Date of revision

: 12 March 2024

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.
	STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m³ 15 minutes. TWA: 123 mg/m³ 8 hours.

Biological exposure indices

Product/ingredient name	Exposure indices		
2-butoxyethanol	2-BUTOXY ETHANOL		

Recommended monitoring : Reference should be made to appropriate monitoring standards. Reference to procedures

national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2-butoxyethanol	DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	26.7 mg/kg bw/day	General population	
	DNEL	Long term Inhalation	59 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	98 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	147 mg/m ³	General population	Local
	DNEL	Short term Inhalation	246 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	426 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	1091 mg/m ³	Workers	Systemic
2,4,7,9-tetramethyldec-5-yne-	DNEL	Long term Oral	0.25 mg/kg bw/day	General population	Systemic
4,7-diol					
	DNEL	Long term Dermal	0.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.43 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	0.5 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	0.75 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.75 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	1.29 mg/m ³	General population	Systemic
	DNEL	Short term Dermal	1.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.76 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	5.28 mg/m ³	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
2-butoxyethanol	Fresh water	8.8 mg/l	Assessment Factors
-	Marine water	0.88 mg/l	Assessment Factors
	Fresh water sediment	34.6 mg/kg	Equilibrium Partitioning
	Marine water sediment	3.46 mg/kg	Equilibrium Partitioning
	Soil	3.13 mg/kg	Equilibrium Partitioning
	Sewage Treatment Plant	463 mg/l	Assessment Factors
2,4,7,9-tetramethyldec-5-yne-4,7-diol	Fresh water	0.04 mg/l	Assessment Factors
	Marine water	0.004 mg/l	Assessment Factors
	Sewage Treatment Plant	7 mg/l	Assessment Factors
	Fresh water sediment	0.32 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	0.032 mg/kg dwt	Equilibrium Partitioning
	Soil	0.028 mg/kg dwt	Equilibrium Partitioning

8.2 Exposure controls

English (GB)

Code	: 1.550.5520/E0.5	Date of issue/Date of revision	: 12 March 2024
AQUAMAX	EXTRA ROSSO OSSIDO B.C.		

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measu	res
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Safety glasses with side shields.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Gloves	: For prolonged or repeated handling, use the following type of gloves:
	Recommended: butyl rubber
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>					
Physical state	: Liqui	d.			
Colour	: Colo	urless.			
Odour	: Fain	t odour.			
Odour threshold	: Not a	available.			
Melting point/freezing point				mperature: 0°C (32°F) This is base ighted average: -7.94°C (17.7°F)	d on data
Initial boiling point and boiling range	: >37.	78°C (>100°F)			
Flammability (solid, gas)	: liquio	k			
Upper/lower flammability or explosive limits	: Not a	applicable.			
Flash point	: Clos	ed cup: 100°C	(212°F) [Product of	loes not sustain combustion.]	
Auto-ignition temperature	:				
Ingredient name		°C	°F	Method	
2-butoxyethanol		230	446	DIN 51794	

English (GB)

Code	: 1.550.5520/E0.5	Date of issue/Date of revision	: 12 March 2024
AQUAMAX E	EXTRA ROSSO OSSIDO B.C.		

SECTION 9: Physical and chemical properties

	Not available. Kinematic (40°C): >21 mm²/s
Media	Result
cold water	Partially soluble
Miscible with water :	Yes.

Partition coefficient: n-octanol/ : Not applicable. water

Vapour pressure

	Vapour Pressure at 20°C			V	Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
Relative density	: 1.02	2					
/apour density	: Hig	hest knowr	value: 4.1 (Air =	1) (2-butoxyet	nanol).		
Explosive properties	: Not	available.					
Oxidising properties	: Pro	duct does r	not present an oxid	dizing hazard.			
Particle characteristics							

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LC50 Inhalation Vapour	Rat	3 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
2,4,7,9-tetramethyldec-	LC50 Inhalation Dusts and	Rat	>20 mg/l	1 hours
5-yne-4,7-diol	mists		_	
-	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	4.6 g/kg	-
Conclusion/Summary Acute toxicity estimates	: There are no data available o	on the mixture itse	elf.	

Code	: 1.550.5520/E0.5	Date of issue/Date of revision	: 12 March 2024
AQUAMAX	EXTRA ROSSO OSSIDO B.C.		

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
AQUAMAX EXTRA ROSSO OSSIDO B.C.	14090.0	N/A	382680.6	34.4	N/A
2-butoxyethanol	1200	N/A	N/A	3	N/A
2,4,7,9-tetramethyldec-5-yne-4,7-diol	4600	N/A	N/A	N/A	N/A

Irritation/Corrosion

		i		i	ii
Product/ingredient name	Result	Species	Score	Exposure	Observation
2-butoxyethanol 2,4,7,9-tetramethyldec-5-yne- 4,7-diol	Eyes - Irritant Skin - Moderate irritant Eyes - Severe irritant Skin - Mild irritant	Rabbit Rabbit Rabbit Rabbit	- - -	24 hours 4 hours 0.1 Mililiters 0.5 Grams	21 days 28 days -
		Rabbit	-	0.5 Grams	-
Conclusion/Summary Skin	: Not available.	the neiver ite	- If		
	There are no data available on				
Eyes	There are no data available on				
Respiratory	: There are no data available on	the mixture its	elf.		
<u>Sensitisation</u> Conclusion/Summary					
Skin	: There are no data available on	the mixture its	elf		
Respiratory	: There are no data available on				
Mutagenicity					
Conclusion/Summary	: There are no data available on	the mixture its	elf.		
<u>Carcinogenicity</u>					
Conclusion/Summary	: There are no data available on	the mixture its	elf.		
Reproductive toxicity					
Conclusion/Summary	: There are no data available on	the mixture its	elf.		
<u>Teratogenicity</u>					
Conclusion/Summary	: There are no data available on	the mixture its	elf.		
Specific target organ toxicity	<u>r (single exposure)</u>				
Not available.					
Specific target organ toxicity Not available.	<u>r (repeated exposure)</u>				
Aspiration hazard Not available.					
Information on likely routes of exposure	: Not available.				
Potential acute health effects					
Eye contact	: No known significant effects or	critical hazard	s.		
Inhalation	: No known significant effects or	critical hazard	s.		
Skin contact	: No known significant effects or	critical hazard	s.		
Ingestion	: No known significant effects or	critical hazard	S.		
Symptoms related to the phys	ical, chemical and toxicologica	I characteristi	<u>cs</u>		
Eye contact	: No specific data.				
Inhalation	: No specific data.				
Skin contact	: No specific data.				

English (GB)

United Kingdom (UK)

Code : 1	1.550.5520/E0.5	Date of issue/Date of revision	: 12 March 2024
AQUAMAX EXTI	RA ROSSO OSSIDO B.C.		

SECTION 11: Toxicological information

Ingestion

: No specific data.

Delayed and immediate effect	ts as well as chronic effects from short and long-term exposure			
Short term exposure				
Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
<u>Long term exposure</u>				
Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
Potential chronic health effects				
Not available.				
Conclusion/Summary	: Not available.			
General	: No known significant effects or critical hazards.			
Carcinogenicity	: No known significant effects or critical hazards.			
Mutagenicity	: No known significant effects or critical hazards.			
Reproductive toxicity	: No known significant effects or critical hazards.			
Other information	: Not available.			

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-butoxyethanol	Acute LC50 1474 mg/l Chronic NOEC >100 mg/l		96 hours 21 days

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-butoxyethanol	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-butoxyethanol	0.81	-	Low

12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

English	(GR)
LIIGUSU	

Code	: 1.550.5520/E0.5	Date of issue/Date of revision	: 12 March 2024
AQUAMA	X EXTRA ROSSO OSSIDO B.C.		

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment metho	ods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

Waste catalogue

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
Packaging	
Methods of disposal	• The generation of waste should be avoided or minimised wherever possible. Waste

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue
Container	15 01 02 plastic packaging
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	9003	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	SUBSTANCES WITH A FLASH-POINT ABOVE 60 °C AND NOT MORE THAN 100 °C (2-butoxyethanol)	-	-
		(2-butoxyethanol)		
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.
ADR/RID :	None identified.			
	The product is only reguneration None identified.	lated as a dangerous good	when transported in tar	k vessels.

ΙΑΤΑ : None identified.

Code	: 1.550.5520/E0.5	Date of issue/Date of revision	: 12 March 2024
AQUAMAX E	XTRA ROSSO OSSIDO B.C.		

SECTION 14: Transport information

14.6	S	р	ec	ia
user				

precautions for : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk : Not available. according to IMO

instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Seveso Directive

This product is not controlled under the Seveso Directive.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and
	Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019
	No. 720 and amendments
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = GB CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Not classified.

Full text of abbreviated H statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications

Code : 1.550.5520/E0.5	Date of issue/Date of revision	: 12 March 2024
AQUAMAX EXTRA ROSSO OSSIDO B.C.		

SECTION 16: Other information

Acute Tox. 3	ACUTE TOXICITY - Category 3	
Acute Tox. 4	ACUTE TOXICITY - Category 4	
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
Skin Sens. 1B	SKIN SENSITISATION - Category 1B	
History		
Date of issue/ Date of revision	: 12 March 2024	
Date of previous issue	e : 31 October 2023	
Prepared by	: EHS	
Version	: 1.02	

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.