

A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	: A-A-10 1L 1L Steel drums A-A-10 1L 1L Steel drums			
Product code	: 0000000050794272			
1.2 Relevant identified uses of the substance or mixture and uses advised against Use of the : Spraying Substance/Mixture Clearcoat product				
1.3 Details of the supplier of the safety data sheetContact address:Company:BASF Coatings GmbHBASF plcBASF Coatings GmbHBASF plc4th and 5th Floors, 2 Stockport ExchangePostfach 61234th and 5th Floors, 2 Stockport, SK1 3GG48136 MünsterBailway Road, Stockport, SK1 3GGDeutschlandUnited Kingdom				

Telephone: +44 161 475 3000 E-mail address: product-safety-uk-and-ireland@basf.com



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:		
Signal Word	:	Danger	
Hazard Statements	:	H226	Flammable liquid and vapor.
		H304	May be fatal if swallowed and enters airways.
		H336	May cause drowsiness or dizziness.
		H412	Harmful to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH066	Repeated exposure may cause skin dryness or cracking.



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

Precautionary Statements	Preventi P210	on: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P261	Avoid breathing mist or vapors.
	P273	Avoid release to the environment.
	Respons P301 + F	se: 2310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
	P331	Do NOT induce vomiting.
	P370 + F	2378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

n-Butyl acetate

Hydrocarbons, C9, aromatics



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

1-methoxy-2-propylacetate

isobutyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : organic solvent

Components

Chemical name	CAS-No.	Classification	Concentratio
	EC-No. Index-No. Registration		n (% w/w)
	number		



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

n-Butyl acetate	123-86-4	Flam. Liq. 3; H226	>= 50 - < 75
	204-658-1	STOT SE 3; H336 (Central nervous system)	
	607-025-00-1		
	UK-20- 9702550300-0- 0000		
	UK-20- 0537843089-5- 0000		
	UK-20- 9642318150-0- 0000		
Hydrocarbons, C9, aromatics	64742-95-6	Flam. Liq. 3; H226	>= 15 - < 20
	265-199-0	STOT SE 3; H336	
	UK-20- 0537843089-5-	(Central nervous system)	
	0000	STOT SE 3; H335	
		(Respiratory	



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

1-methoxy-2-propylacetate	108-65-6	system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 Flam. Liq. 3; H226	>= 5 - < 7
	203-603-9 607-195-00-7 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	STOT SE 3; H336 (Central nervous system)	
isobutyl acetate	110-19-0	Flam. Liq. 2; H225	>= 3 - < 5



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

203-745-1	STOT SE 3; H336	
607-026-00-7 UK-20- 0537843089-5- 0000	(Central nervous system)	
UK-20- 9642318150-0- 0000		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice	: First aid personnel should pay attention to their own
	safety.
	Immediately remove contaminated clothing.
	In case of intoxication, call a poison control center or
	physician for treatment advice, taking the packaging or
	the label of the product.
	Symptoms of poisoning may occur even after several
	hours, continue medical observation for at least 48



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

	hours after the accident. Never give anything by mouth to an unconscious p Keep patient warm and at rest.	erson.
If inhaled	If breathed in, move person into fresh air.	
	Call a physician or poison control center immediate	ely.
	If breathing is irregular or stopped, administer artities respiration.	ficial
In case of skin contact	If symptoms persist, call a physician.	
	Wash off immediately with soap and plenty of wat while removing all contaminated clothes and shoe	
	Do NOT use solvents or thinners.	
In case of eye contact	If symptoms persist, call a physician.	
	In case of eye contact, remove contact lens and rin immediately with plenty of water, also under the e	



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

for at least 15 minutes.

If swallowed	: Do not induce vomiting due to aspiration hazard.
	Keep at rest.
	If symptoms persist, call a physician or Poison Control Center immediately.
	Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	and ava	ormation, i.e. additional information on symptoms d effects may be included in the GHS labeling phrases ailable in Section 2 and in the Toxicological sessments available in Section 11.
Risks	: Ma	ay be fatal if swallowed and enters airways.
	Ma	ay cause drowsiness or dizziness.



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

Repeated exposure may cause skin dryness or cracking.

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	:	No known specific antidote.
		Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing	:	Water spray jet
media		Dry powder
		Alcohol-resistant foam
		Carbon dioxide (CO2)



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

	Unsuitable extinguishing media	:	High volume water jet
5.2	Special hazards arising from	the	e substance or mixture
	Specific hazards during fire	:	Fire will produce dense black smoke containing
	fighting		hazardous combustion products (see section 10).
5.3	Advice for firefighters		
	Special protective	:	Appropriate breathing apparatus may be required.
	equipment for fire-fighters		
	Further information	:	In the event of fire, cool tanks with water spray.
			Fire residues and contaminated fire extinguishing water
			must be disposed of in accordance with local
			regulations.
			Collect contaminated fire extinguishing water separately.



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined areas.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning u	: qu	Ensure adequate ventilation.
		Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

Advice on safe handling :	:	Provide good ventilation of working area (local exhaust ventilation if necessary).
		Do not return residues to the storage containers.
		Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
		When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
		The workplace should be equipped with an emergency shower and eye-rinsing facility.
		Avoid contact with the skin, eyes and clothing.
		Handle in accordance with good industrial hygiene and safety practice.



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

Do not breathe vapors or spray mist.

Advice on protection : against fire and explosion	Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.
Hygiene measures :	Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.
7.2 Conditions for safe storage, in	cluding any incompatibilities
Further information on storage conditions	Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised

personnel. Always keep in containers of same material



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

	as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.
Advice on common storage :	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
7.3 Specific end use(s)	
Specific use(s) :	Please refer to the technical leaflet for further information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type	Control parameters	Basis
		(Form of		
		exposure)		



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

n-Butyl acetate	123-86-4	TWA	150 ppm	GB EH40	
			724 mg/m3		
		STEL	200 ppm	GB EH40	
			966 mg/m3		
		STEL	150 ppm	2019/1831/	
			723 mg/m3	EU	
	Further information: Indicative				
		TWA	50 ppm	2019/1831/	
			241 mg/m3	EU	
	Further information: Indicative				
1-methoxy-2-	108-65-6	TWA	50 ppm	GB EH40	
propylacetate			274 mg/m3		
	Further information: Can be absorbed through the skin. The assigned				
	substances are those for which there are concerns that dermal				
	absorption will lead to systemic toxicity.				



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

		STEL	100 ppm	GB EH40			
			548 mg/m3				
	Further info	Further information: Can be absorbed through the skin. The assigned					
	substances a	are those for which	there are concerns that d	ermal			
	absorption v	vill lead to systemi	c toxicity.				
		STEL	100 ppm	2000/39/EC			
			550 mg/m3				
	Further information: Identifies the possibility of significant uptake						
	through the skin, Indicative						
		TWA	50 ppm	2000/39/EC			
			275 mg/m3				
	Further information: Identifies the possibility of significant uptake						
	through the skin, Indicative						
isobutyl acetate	110-19-0	TWA	150 ppm	GB EH40			
			724 mg/m3				
		STEL	187 ppm	GB EH40			



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

		903 mg/m3				
	TWA	50 ppm	2019/1831/			
		241 mg/m3	EU			
Further	Further information: Indicative					
	STEL	150 ppm	2019/1831/			
		723 mg/m3	EU			
Further	Further information: Indicative					

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection

: Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Required when there is a risk of eye contact.

Hand protection



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for shortterm contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

		time according to EN ISO 374-1)
Skin and body protection	:	Anti-static protective clothing
		Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.
Respiratory protection	:	Suitable respiratory equipment:
		half-mask with A1P2 class combination filter
		When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
		In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Protective measures	:	Do not breathe vapour/spray.
		Eye wash fountains and safety showers must be easily accessible.
		If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid	
Color	: color	ess
Odor	: of gly	col
рН	: substa	ance/mixture is non-polar/aprotic
Melting point/ range	: not d	etermined
	: 114.0	0 - 185.00 °C
Flash point	: 25 °C	
	Meth	od: ISO 3679



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

Upper explosion limit / Upper flammability limit	: not determined
Lower explosion limit / Lower flammability limit	: > 35.0 g/m3
Vapor pressure	: 12.0000 hPa (20 °C)
	(50 °C)
	not determined
Relative vapor density	: Heavier than air.
Density	: 0.867 g/cm3 (20 °C)



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

Solubility(ies) Water solubility	:	not determined
Partition coefficient: n- octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, kinematic	:	6.0 mm2/s (23 °C)
		(40 °C)
		not determined



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

Flow time	: < 30 s		
	Cross section: 3 mm		
Explosive properties	: Not explosive		
Oxidizing properties	: The substance or mixture is not classified as oxidizing.		
9.2 Other information			
Flammability (liquids)	: Flammable liquid and vapour.		
Colf booting substances	The substance or minture is not classified as solf besting		
Self-heating substances	: The substance or mixture is not classified as self heating.		
Metal corrosion rate	: Not corrosive to metals.		
Particle size	: The substance / product is marketed or used in a non		
	solid or granular form.		
	26 / 44		
207 ++			



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight. Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

n-Butyl acetate:

Result

: Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

Carcinogenicity Not classified due to lack of data. **Reproductive toxicity** Not classified due to lack of data. **STOT-single exposure** May cause drowsiness or dizziness. STOT-repeated exposure Not classified due to lack of data. Aspiration toxicity May be fatal if swallowed and enters airways. **SECTION 12: Ecological information** 12.1 Toxicity No data available 12.2 Persistence and degradability No data available 12.3 Bioaccumulative potential **Components:** n-Butyl acetate: Partition coefficient: n-: Pow: 200 (25 °C) octanol/water log Pow: 2.3 (25 °C) pH: 7



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

	Method: OECD Test Guideline 117
	GLP: yes
Hydrocarbons, C9, aromatics:	
Partition coefficient: n- :	log Pow: 3.17
octanol/water	GLP: no
1-methoxy-2-propylacetate:	
Partition coefficient: n- :	log Pow: 1.2 (20 °C)
octanol/water	рН: 6.8
	Method: OECD Test Guideline 117
	GLP: yes
isobutyl acetate:	
	log Pow: 2.3 (25 °C)
octanol/water	рН: 7



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

		Method: OECD Test Guideline 117
		GLP: yes
12.4	l I Mobility in soil	
	No data available	
12.5	Results of PBT and vPvB asse	essment
	Product:	
	Assessment :	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
12.6	Other adverse effects	
	Product:	
	Endocrine disrupting : potential	This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

SECTION 13: Disposal considerations

13.1 Waste treatment methods		
Product		Do not discharge into drains/surface waters/groundwater.
		Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC
		Packaging that is not properly emptied must be disposed of as the unused product.

SECTION 14: Transport information

14.1	14.1 UN number				
	ADN	:	UN 1263		
	ADR	:	UN 1263		



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

RID	: UN 1263
IMDG	: UN 1263
ΙΑΤΑ	: UN 1263

14.2 UN proper shipping name

Т

ADN	:	PAINT RELATED MATERIAL
ADR	:	PAINT RELATED MATERIAL
RID	:	PAINT RELATED MATERIAL
IMDG	:	PAINT RELATED MATERIAL
ΙΑΤΑ	:	PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

		Class	Subsidiary risks
A	DN :	3	
A	DR :	3	



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

	RID	:	3
	IMDG	:	3
	ΙΑΤΑ	:	3
14.4	Packing group		
	ADN		
	Packing group	:	Ш
	Classification Code	:	F1
	Hazard Identification Number	:	30
	Labels	:	3
	ADR		
	Packing group	:	Ш
	Classification Code	:	F1
	Hazard Identification Number	:	30



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

Labels	:	3
Tunnel restriction code	:	(D/E)
RID		
Packing group	:	Ш
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
IMDG		
Packing group	:	Ш
Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
IATA (Cargo)		
Packing instruction (cargo aircraft)	:	366



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

	Packing instruction (LQ)	:	Y344
	Packing group	:	Ш
	Labels	:	Flammable Liquids
	IATA (Passenger)		
	Packing instruction (passenger aircraft)	:	355
	Packing instruction (LQ)	:	Y344
	Packing group	:	III
	Labels	:	Flammable liquid
14.5	i 5 Environmental hazards		
	ADN		
	Environmentally hazardous	:	no

ADR

Environmentally : no



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

hazardous

RID

Environmentally	:	no
hazardous		
IMDG		

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Conditions of restriction for the

following entries should be



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

considered:

Number on list 3

UK REACH Candidate list of substances of ve concern (SVHC) for Authorisation	n : Not applicable		
The Persistent Organic Pollutants Regulatio (retained Regulation (EU) 2019/1021 as am for Great Britain)	: Not applicable		
Regulation (EC) on substances that deplete ozone layer	the	: Not applicable	
UK REACH List of substances subject to authorisation (Annex XIV)		: Not applicable	
Control of Major Accident Hazards Regulations 2015 (COMAH)	P5c	FLAMMABLE LIQUIDS	
	34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels),



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

(c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds	:	Volatile organic compounds (VOC) content: 870 g/l
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
		Volatile organic compounds (VOC) content: 99.08 %



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:	
Subcategory as indicated in Annex IIB:	dropped
Limit value for maximum VOC content as specified in Annex IIB:	dropped

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements		
H225	:	Highly flammable liquid and vapor.
H226	:	Flammable liquid and vapor.
H304	:	May be fatal if swallowed and enters airways.



Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H411	:	Toxic to aquatic life with long lasting effects.
Full text of other abbreviati	ons	
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Flam. Liq.	:	Flammable liquids
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

(EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information	:	For multi-pack systems observe material safety data	
		sheets of all components.	
		Restricted to professional users.	

Classification of the mi	Classification procedure:	
Flam. Liq. 3	H226	Based on product data or assessment
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 3	H412	Calculation method



A-A-10 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	00000000050794 272	Date of first issue: 18.10.2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN