

Safety Data Sheet

MACROFAN POWER ADDITIVE

Safety Data Sheet dated 13/11/2023 version 4



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: MACROFAN POWER ADDITIVE

Trade code: L0MT0405

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Coatings and paints, thinners, paint removers

Coating additive

Liquid solution

Professional uses

Uses advised against: N.A.

1.3. Details of the supplier of the safety data sheet

Company: Lechler SpA - Via Cecilio, 17 - 22100 Como - CO - Italy

Telephone: +39031586111

First Email: safety@lechler.eu

1.4. Emergency telephone number

UNITED KINGDOM: Emergency Number 0044 1606738600 - This telephone number is available during office hours only (8.45-16.45).

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Flam. Liq. 3	Flammable liquid and vapour.
Skin Irrit. 2	Causes skin irritation.
Eye Irrit. 2	Causes serious eye irritation.
Skin Sens. 1A	May cause an allergic skin reaction.
Muta. 2	Suspected of causing genetic defects.
Repr. 1B	May damage fertility or the unborn child.
STOT SE 2	May cause damage to organs.
STOT SE 3	May cause respiratory irritation.
STOT SE 3	May cause drowsiness or dizziness.
STOT RE 2	May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 2	Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Danger

Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P370+P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.
P403+P235	Store in a well-ventilated place. Keep cool.

Contains

n-butyl acetate
xylene
ethylene bis(3-mercaptopropionate)
2-ethoxy-1-methylethyl acetate
dibutyltin dilaurate
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
ethylene di(S-thioacetate)
pentaerythritol tetrakis(3-mercaptopropionate)

Special provisions according to Annex XVII of REACH and subsequent amendments:

Restricted to professional users.

2.3. Other hazards

Results of PBT and vPvB assessment Not a PBT, vPvB substance as per the criteria of the REACH Regulation.
Endocrine disrupting properties-Toxicity The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Endocrine disrupting properties-Ecotoxicity The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: MACROFAN POWER ADDITIVE

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥50 - ≤55 %	n-butyl acetate	CAS:123-86-4 EC:204-658-1 Index:607-025-00-1	Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	01-2119485493-29

≥25 - ≤30 %	xylene	CAS:1330-20-7 EC:215-535-7 Index:601-022-00-9	Flam. Liq. 3, H226; Acute Tox. 4, H332; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 3, H412; STOT SE 3, H335	01-2119488216-32
≥10 - ≤12.5 %	2-butoxyethyl acetate	CAS:112-07-2 EC:203-933-3 Index:607-038-00-2	Acute Tox. 4, H302; Acute Tox. 4, H332; Acute Tox. 4, H312	01-2119475112-47
≥5 - ≤7 %	2-ethoxy-1-methylethyl acetate	CAS:54839-24-6 EC:259-370-9 Index:603-177-00-8	Flam. Liq. 3, H226; STOT SE 3, H336	01-2119475116-39
≥1 - ≤2.5 %	ethylene bis(3-mercaptopropionate)	CAS:22504-50-3 EC:245-044-3	Acute Tox. 4, H302; Skin Sens. 1A, H317; Aquatic Acute 1, H400; Aquatic Chronic 1, H410	01-2120775145-52
≥1 - ≤2.5 %	dibutyltin dilaurate	CAS:77-58-7 EC:201-039-8 Index:050-030-00-3	STOT SE 1, H370; STOT RE 1, H372; Skin Sens. 1, H317; Eye Irrit. 2, H319; Muta. 2, H341; Repr. 1B, H360FD; Aquatic Acute 1, H400; Aquatic Chronic 1, H410, M-Chronic:1, M-Acute:1	01-2119496068-27
≥1 - ≤2.5 %	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	CAS:1065336-91-5 EC:915-687-0	Skin Sens. 1A, H317; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Repr. 2, H361f, M-Acute:1	01-2119491304-40-0000
≥0.3 - ≤0.5 %	ethylene di(S-thioacetate)	CAS:123-81-9 EC:204-653-4	Acute Tox. 4, H302; Acute Tox. 4, H332; Acute Tox. 4, H312; Eye Irrit. 2, H319; Skin Sens. 1A, H317; STOT SE 3, H335	01-2120775150-61
≥0.1 - ≤0.25 %	pentaerythritol tetrakis(3-mercaptopropionate)	CAS:7575-23-7 EC:231-472-8	Acute Tox. 4, H302; Skin Sens. 1A, H317; Aquatic Acute 1, H400; Aquatic Chronic 1, H410, M-Chronic:10, M-Acute:10	01-2119486981-23
≥0.1 - ≤0.25 %	bis(isopropyl)naphthalene	CAS:38640-62-9 EC:254-052-6	Asp. Tox. 1, H304; Aquatic Chronic 1, H410	01-2119565150-48-0000

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
n-butyl acetate CAS: 123-86-4	EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 724 mg/m ³ - 150 ppm; Short Term: 966 mg/m ³ - 200 ppm
	EU		Long Term: 241 mg/m ³ - 50 ppm; Short Term: 723 mg/m ³ - 150 ppm Behaviour Indicative 2019/1831/EU
	ACGIH		Long Term: 50 ppm; Short Term: 150 ppm Eye and URT irr
xylene CAS: 1330-20-7	ACGIH		Long Term: 20 ppm A4, BEI - URT and eye irr; hematologic eff; CNS impair
	EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 220 mg/m ³ - 50 ppm; Short Term: 441 mg/m ³ - 100 ppm Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to
	EU		Long Term: 221 mg/m ³ - 50 ppm; Short Term: 442 mg/m ³ - 100 ppm Behaviour Indicative 2000/39/EC
2-butoxyethyl acetate CAS: 112-07-2	EU		Identifies the possibility of significant uptake through the skin
	ACGIH		Long Term: 20 ppm A3 - Hemolysis
	EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 133 mg/m ³ - 20 ppm; Short Term: 332 mg/m ³ - 50 ppm Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to
dibutyltin dilaurate CAS: 77-58-7	EU		Long Term: 133 mg/m ³ - 20 ppm; Short Term: 333 mg/m ³ - 50 ppm Behaviour Indicative 2000/39/EC
	EU		Identifies the possibility of significant uptake through the skin
	EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 0.1 mg/m ³ ; Short Term: 0.2 mg/m ³ Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to
	ACGIH		Long Term: 0.1 mg/m ³
	ACGIH		Short Term: 0.2 mg/m ³ LEC-TD-95133

Biological limit values

xylene
CAS: 1330-20-7
Biological Indicator: xylene; Sampling Period: End of turn
Value: 1.5 mg/L; Medium: Blood
Remark: Croatia. Biological Exposure Limits

Biological Indicator: Methylhippuric acid; Sampling Period: End of turn
Value: 1.5 g/l; Medium: Urine
Remark: New Zealand. Biological Exposure Indices

Biological Indicator: xylene; Sampling Period: End of turn
Value: 1.5 mg/L; Medium: Blood
Remark: Slovakia. Biological Limit Values

Biological Indicator: sum of 2,3,4-methylhippuric acid; Sampling Period: End of turn
Value: 2000 mg/L; Medium: Urine

Remark: Slovakia. Biological Limit Values

Biological Indicator: methylhypuric acid; Sampling Period: End of turn
Value: 3 g/l; Medium: Urine
Remark: Romania. Biological limit values

Biological Indicator: methylhippuric acid (all isomers); Sampling Period: End of turn
Value: 2 g/l; Medium: Urine
Remark: Slovenia. BAT-values

Biological Indicator: xylene; Sampling Period: Immediately after exposure or after working hours
Value: 1.5 mg/L; Medium: Blood
Remark: TRGS 903 - Biological limit values

Biological Indicator: methylhippuric acid (all isomers); Sampling Period: Immediately after exposure or after working hours
Value: 2 g/l; Medium: Urine
Remark: TRGS 903 - Biological limit values

Biological Indicator: Methylhippuric acid; Sampling Period: Last 4 hours of shift
Value: 2 mg/L; Medium: Urine
Remark: South Africa. Hazardous Chemical Substances Regulations, Biological Exposure Indices.

Biological Indicator: total (o-, m-, p-)methylhippuric acid; Sampling Period: End of turn; End of working week
Value: 800 mg/L; Medium: Urine
Remark: Occupational exposure limits based on biological monitoring (JSOH).

Biological Indicator: methyl hippuric acid; Sampling Period: At the end of a work week / at the end of a work day / at the end of a shift
Value: 1.5 g/l; Medium: Urine
Remark: Austria. Regulation on health surveillance in the workplace 2014

Biological Indicator: xylene; Sampling Period: End of workday
Value: 1 mg/L; Medium: Blood
Remark: Austria. Regulation on health surveillance in the workplace 2014

Biological Indicator: Methylhippuric acid; Sampling Period: At the end of exposure, in 4 hours
Value: 2 mg/L; Medium: Urine
Remark: Kenya. Occupational Safety and Health Act (CAP.514), Schedule I, Table 3 Biological Exposure Limits

Biological Indicator: methyl hippuric acid; Sampling Period: After shift
Value: 5 Millimoles per liter; Medium: Urine
Remark: Finland. Biological limit values

Biological Indicator: methyl hippuric acid; Sampling Period: Immediately after exposure or after working hours
Value: 2 g/l; Medium: Urine
Remark: Svizzera. Lista di valori BAT

2-butoxyethyl acetate
CAS: 112-07-2

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: End of turn; End of working week
Value: 200 mg/g Creatinine; Medium: Urine
Remark: Czech Republic. Biological Exposure Indices

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: End of turn; End of working week
Value: 17 mmol/mmol creatinine; Medium: Urine
Remark: Czech Republic. Biological Exposure Indices

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: In case of long-term exposure: after more than one shift
Value: 200 mg/L; Medium: Urine
Remark: TRGS 903 - Biological limit values

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: In case of long-term exposure: after more than one shift
Value: 100 mg/L; Medium: Urine
Remark: TRGS 903 - Biological limit values

Biological Indicator: total butoxy acetic acid; Sampling Period: In case of long-term exposure: after more than one shift
Value: 200 mg/L; Medium: Urine
Remark: Svizzera. Lista di valori BAT

Biological Indicator: total butoxy acetic acid; Sampling Period: In case of long-term exposure: after more than one shift
Value: 15134 micromol per litre; Medium: Urine
Remark: Svizzera. Lista di valori BAT

Biological Indicator: 2-butoxy acetic acid; Sampling Period: Immediately after exposure or after working hours

Value: 100 mg/L; Medium: Urine
Remark: Svizzera. Lista di valori BAT

Biological Indicator: 2-butoxy acetic acid; Sampling Period: In case of long-term exposure: after more than one shift

Value: 7567 micromol per litre; Medium: Urine
Remark: Svizzera. Lista di valori BAT

Sampling Period: Immediately after exposure or after working hours

Sampling Period: In case of long-term exposure: after more than one shift

Predicted No Effect Concentration (PNEC) values

n-butyl acetate
CAS: 123-86-4

Exposure Route: Fresh Water; PNEC Limit: 0.18 mg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.36 mg/l

Exposure Route: Marine water; PNEC Limit: 0.01 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 0.98 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 0.09 mg/kg

Exposure Route: Soil; PNEC Limit: 0.09 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 35.6 mg/l

Exposure Route: Fresh Water; PNEC Limit: 0.32 mg/l

xylene
CAS: 1330-20-7

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.32 mg/l

Exposure Route: Marine water; PNEC Limit: 0.32 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 12.46 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 12.46 mg/kg

Exposure Route: Soil; PNEC Limit: 2.31 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 6.58 mg/l

2-butoxyethyl acetate
CAS: 112-07-2

Exposure Route: Fresh Water; PNEC Limit: 0.304 mg/l

Exposure Route: Marine water; PNEC Limit: 0.03 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 2.03 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 0.203 mg/kg

Exposure Route: Soil; PNEC Limit: 0.415 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 90 mg/l

2-ethoxy-1-methylethyl acetate
CAS: 54839-24-6

Exposure Route: Fresh Water; PNEC Limit: 2 mg/l

Exposure Route: Marine water; PNEC Limit: 0.2 mg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 2 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 8.2 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 0.67 mg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 62.5 mg/l

Exposure Route: Oral; PNEC Limit: 117 mg/l

dibutyltin dilaurate
CAS: 77-58-7

Exposure Route: Fresh Water; PNEC Limit: 0.463 µg/L

Exposure Route: Freshwater sediments; PNEC Limit: 0.05 µg/L

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 4.63 µg/L

Exposure Route: Marine water; PNEC Limit: 0.0463 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 0.005 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l

Exposure Route: Soil; PNEC Limit: 0.0407 mg/kg

Reaction mass of
Bis(1,2,2,6,6-
pentamethyl-4-piperidyl)
sebacate and Methyl
1,2,2,6,6-pentamethyl-4-
piperidyl sebacate

Exposure Route: Fresh Water; PNEC Limit: 0.002 mg/l

Exposure Route: Marine water; PNEC Limit: 0 mg/l
 Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.009 mg/l
 Exposure Route: Freshwater sediments; PNEC Limit: 1.05 mg/kg
 Exposure Route: Marine water sediments; PNEC Limit: 0.11 mg/kg
 Exposure Route: Soil; PNEC Limit: 0.21 mg/kg
 Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 1 mg/l

Derived No Effect Level (DNEL) values

n-butyl acetate
 CAS: 123-86-4

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Worker Industry: 300 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
 Worker Industry: 600 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
 Worker Industry: 300 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
 Worker Industry: 600 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
 Worker Industry: 11 mg/kg dry weight (d.w.)

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
 Worker Industry: 11 mg/kg dry weight (d.w.)

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Consumer: 35.7 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
 Consumer: 300 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
 Consumer: 35.7 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
 Consumer: 300 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
 Consumer: 6 mg/kg dry weight (d.w.)

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
 Consumer: 6 mg/kg dry weight (d.w.)

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
 Consumer: 2 mg/kg dry weight (d.w.)

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
 Consumer: 2 mg/kg dry weight (d.w.)

xylene
 CAS: 1330-20-7

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Consumer: 65.3 mg/m³

Exposure Route: Oral; Exposure Frequency: Long Term, systemic effects
 Consumer: 12.5 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
 Worker Professional: 442 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 212 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Worker Professional: 221 mg/m³

2-butoxyethyl acetate
 CAS: 112-07-2

Exposure Route: Human Inhalation; Exposure Frequency: Short Term (acute)
 Consumer: 200 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
 Consumer: 72 mg/kg

Exposure Route: Oral; Exposure Frequency: Short Term, systemic effects
 Consumer: 36 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
 Consumer: 80 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Consumer: 102 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term (acute)
Worker Professional: 333 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 133 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 169 mg/kg

2-ethoxy-1-methylethyl acetate
CAS: 54839-24-6

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Industry: 2366 mg/m³; Worker Professional: 2366 mg/kg; Consumer: 1420 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 152 mg/m³; Worker Professional: 152 mg/m³; Consumer: 181 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 103 mg/kg; Worker Professional: 103 mg/kg; Consumer: 62 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 13.1 mg/kg

dibutyltin dilaurate
CAS: 77-58-7

Exposure Route: Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 0.0031 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Consumer: 0.5 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Consumer: 0.16 mg/kg

Exposure Route: Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 0.02 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 0.43 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Professional: 2.05 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 0.0046 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Consumer: 0.04 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 0.02 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 0.059 mg/m³

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
CAS: 1065336-91-5

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 1.27 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 1.8 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 0.31 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Consumer: 0.9 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 0.18 mg/kg

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State: Liquid

Colour: Colourless

Odour: N.A.

pH: Not Relevant

Kinematic viscosity: > 20,5 mm²/sec (40 °C)

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Flash point: 23°C / 60°C

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 0.89 g/cm³

Solubility in water: N.A.

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Flammability: The product is classified Flam. Liq. 3 H226

Kinematic viscosity m²/s (40°C) > 20,5 mm²/sec (40 °C)

Viscosity: = 14.00 s - Method: ISO/DIN 2431 84 - Section: 6.00 mm

Particle characteristics:

Particle size: N.A.

9.2. Other information

Evaporation rate: N.A.

Miscibility: N.A.

Conductivity: N.A.

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity

Not classified

	Based on available data, the classification criteria are not met
	ATEmix - Oral : 10150.3 mg/kg bw
	ATEmix - Dermal : 3300.66 mg/kg bw
	ATEmix - Inhalation (Vapours) : 30.4709 mg/l
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1A(H317)
e) germ cell mutagenicity	The product is classified: Muta. 2(H341)
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	The product is classified: Repr. 1B(H360)
h) STOT-single exposure	The product is classified: STOT SE 2(H371), STOT SE 3(H335), STOT SE 3(H336)
i) STOT-repeated exposure	The product is classified: STOT RE 2(H373)
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

n-butyl acetate	a) acute toxicity	LD50 Oral Rat = 10760 mg/kg LC50 Inhalation > 20 mg/l 4h LD50 Skin Rabbit > 14112 mg/kg	OECD Test Guideline 423 OECD Test Guideline 402
xylene	a) acute toxicity	LD50 Oral Mouse = 5627 mg/kg LC50 Inhalation Rat = 6700 Ppm 4h LD50 Skin Rabbit > 5000 mg/kg	
2-butoxyethyl acetate	a) acute toxicity	LD50 Oral Rat = 1880 mg/kg ATE Skin = 1100 mg/kg LD50 Skin Rabbit = 1500 mg/kg LC0 Inhalation Rat = 400 Ppm 4h	Converted acute toxicity p estimate
2-ethoxy-1-methylethyl acetate	a) acute toxicity	LD50 Oral Rat > 5000 LC50 Inhalation Mist Rat > 6.99 4h	OECD Test Guideline 401 OECD Test Guideline 403
dibutyltin dilaurate	a) acute toxicity	LD50 Oral Rat = 2071 mg/kg	OECD Test Guideline 401
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	a) acute toxicity	LD50 Oral Rat = 3230 mg/kg LD50 Skin Rat = 3170 mg/kg	

11.2. Information on other hazards

Endocrine disrupting properties:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Toxic to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 2(H411)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
n-butyl acetate	CAS: 123-86-4 - EINECS: 204- 658-1 - INDEX: 607-025-00-1	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas (fathead minnow) = 18 mg/L 96 H OECD Test Guideline 203 a) Aquatic acute toxicity : EC50 Invertebrates Daphnia magna (Water flea) = 44 mg/L 48 H OECD Test Guideline 202 e) Plant toxicity : EC50 Algae Selenastrum capricornutum (green algae) = 397 mg/L 72 H OECD Test Guideline 201 c) Bacteria toxicity : IC50 Microorganisms Tetrahymena pyriformis = 356 mg/L 40 H
xylene	CAS: 1330-20-7 - EINECS: 215- 535-7 - INDEX: 601-022-00-9	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss (rainbow trout) = 2.6 mg/L 96 H a) Aquatic acute toxicity : IC50 Invertebrates Daphnia magna (Water flea) = 1 mg/L 24 H e) Plant toxicity : EC0 Algae Pseudokirchneriella subcapitata (green algae) = 0.44 mg/L 72 H b) Aquatic chronic toxicity : NOEC Fish Oncorhynchus mykiss (rainbow trout) > 1.3 mg/L 56 D e) Plant toxicity : Algae Pseudokirchneriella subcapitata (green algae) = 4.36 mg/L 72 H
2-butoxyethyl acetate	CAS: 112-07-2 - EINECS: 203- 933-3 - INDEX: 607-038-00-2	a) Aquatic acute toxicity : EC50 Invertebrates Daphnia magna (Water flea) = 145 mg/L 24 H e) Plant toxicity : EC50 Algae = 1570 mg/L 72 H a) Aquatic acute toxicity : LC50 Fish = 20 mg/L 96h
2-ethoxy-1-methylethyl acetate	CAS: 54839-24- 6 - EINECS: 259-370-9 - INDEX: 603- 177-00-8	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss (rainbow trout) = 140 mg/L 96 H OECD Test Guideline 203 a) Aquatic acute toxicity : EC50 Invertebrates Daphnia magna (Water flea) = 110 mg/L 48 H OECD Test Guideline 202 e) Plant toxicity : EC50 Algae Desmodesmus subspicatus (green algae) > 100 mg/L 72 H OECD Test Guideline 201 c) Bacteria toxicity : EC10 Microorganisms Pseudomonas putida = 560 mg/L 16 H b) Aquatic chronic toxicity : NOEC Invertebrates Daphnia magna (Water flea) >= 100 mg/L 21 D a) Aquatic acute toxicity : NOEC Fish Oryzias latipes (Orange-red killifish) = 47.5 mg/L 96 H e) Plant toxicity : NOEC Algae Desmodesmus subspicatus (green algae) >= 100 mg/L 72 H
dibutyltin dilaurate	CAS: 77-58-7 - EINECS: 201- 039-8 - INDEX: 050-030-00-3	a) Aquatic acute toxicity : EC50 Invertebrates Daphnia magna (Water flea) = 0.463 mg/L 48 H e) Plant toxicity : EC50 Algae Desmodesmus subspicatus (green algae) = 1 mg/L 72 H
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	CAS: 1065336- 91-5 - EINECS: 915-687-0	e) Plant toxicity : EC50 Algae Desmodesmus subspicatus (green algae) = 1.68 mg/L 72 H

a) Aquatic acute toxicity : LC50 Fish Brachydanio rerio (zebrafish) = 0.9 mg/L 96 H

a) Aquatic acute toxicity : NOEC Invertebrates Daphnia magna = 1 mg/L 21 Days

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration \geq 0.1%

12.6. Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number or ID number

1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT RELATED MATERIAL
IATA-Technical name: PAINT RELATED MATERIAL
IMDG-Technical name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR-Class: 3
IATA-Class: 3
IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: III
IATA-Packing group: III
IMDG-Packing group: III

14.5. Environmental hazards

Most important toxic component: ethylene bis(3-mercaptopropionate)
Toxic ingredients quantity: 0.00
Very toxic ingredients quantity: 4.44
Marine pollutant: Yes
Environmental Pollutant: Yes
IMDG-EMS: F-E, S-E

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: 3
ADR - Hazard identification number: -
ADR-Special Provisions: 163 367 650
ADR-Transport category (Tunnel restriction code): 3 (E)

Air (IATA):

IATA-Passenger Aircraft: 355
IATA-Cargo Aircraft: 366
IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisions: A3 A72 A192

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 163 223 367 955

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2020/878

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40

Restrictions related to the substances contained: 30, 75

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1	Lower-tier threshold (tonnes)	Upper-tier threshold (tonnes)
--	-------------------------------	-------------------------------

Product belongs to category: P5c	5000	50000
----------------------------------	------	-------

Product belongs to category: E2	200	500
---------------------------------	-----	-----

Regulation (EU) No 649/2012 (PIC regulation)

Substances listed in Annex V to the PIC regulation:

No substances listed

Substances listed in Annex I to the PIC regulation:

dibutyltin dilaurate Part 1

German Water Hazard Class.

3: Severe hazard to waters

German Lagerklasse according to TRGS 510:

LGK 3

SVHC Substances:

No SVHC substances present in concentration \geq 0.1%

Dir. 2010/75/EC (VOC directive)

Volatile Organic compounds - VOCs = 95.56 %

Volatile Organic compounds - VOCs = 850.48 g/L

Estimated Total Content of Water 0.00 %

Estimated Total Solid Content 4.44 %

Flammable liquid substances

Classification according to VbF

Classification according to VbF A II - Flash point 21 °C to 55 °C, at 15 °C not miscible in water

Mal-Code (Denmark)

Mal-Code (Denmark)	Mal Factor	Unit of Measure	Revision Status / Number	Regulatory Base
4 - 6	3.038	m3 air/10 g	1993	Administrative determined MAL-Factors

Biocides

REGULATION (EC) No 528/2012

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H360FD	May damage fertility. May damage the unborn child.
H361f	Suspected of damaging fertility.
H370	Causes damage to organs (thymus).
H371	May cause damage to organs.
H372	Causes damage to organs (thymus) through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.5/2	Muta. 2	Germ cell mutagenicity, Category 2
3.7/1B	Repr. 1B	Reproductive toxicity, Category 1B
3.7/2	Repr. 2	Reproductive toxicity, Category 2

3.8/1	STOT SE 1	Specific target organ toxicity — single exposure, Category 1
3.8/2	STOT SE 2	Specific target organ toxicity — single exposure, Category 2
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category 1
3.9/2	STOT RE 2	Specific target organ toxicity — repeated exposure, Category 2
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008 Classification procedure

Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1A, H317	Calculation method
Muta. 2, H341	Calculation method
Repr. 1B, H360	Calculation method
STOT SE 2, H371	Calculation method
STOT SE 3, H335	Calculation method
STOT SE 3, H336	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Chronic 2, H411	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
IRCCS: Scientific Institute for Research, Hospitalization and Health Care
KAFH: KAFH
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LDLo: Leathal Dose Low
N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information