according to 1907/2006/EC, Article 31




GB

Printing date 09.09.2021

Version number 14

# SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: 4CR 2355 Multi Soft Spachtel 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Knife filler/ Surfacer · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: 4CR Vertriebsgesellschaft mbH **Oberer Sommerfeldweg 2** D-94469 Deggendorf Tel.: +49 (0) 40 69 60 99 315 Fax: +49 (0) 40 69 60 99 316 E-Mail: Info@4CR.com www.4CR.com · 1.4 Emergency telephone number: +49(0)700 24112112 (CRM) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 flame Flam. Liq. 3 H226 Flammable liquid and vapour. health hazard Repr. 2 H361d Suspected of damaging the unborn child. STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure. Skin Irrit. 2 H315 Causes skin irritation. H319 Causes serious eye irritation. Eye Irrit. 2 Skin Sens. 1 H317 May cause an allergic skin reaction. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labelling: styrene maleic anhydride (Contd. on page 2)

Version number 14



### Trade name: 4CR 2355 Multi Soft Spachtel



(Contd. of page 1)

| 2 21 (m tobuling | inoldiothanol   |
|------------------|---|
| 2,2'-(m-tolylim  |   |
|                  | [phenyl)imino] bisethanol   |
| • Hazard statem  |   |
|                  | able liquid and vapour.   |
| H315 Causes      |   |
|                  | serious eye irritation.   |
| H317 May ca      | use an allergic skin reaction.  |
| H361d Suspect    | ted of damaging the unborn child.   |
| H372 Causes      | damage to the hearing organs through prolonged or repeated exposure.  |
| H412 Harmfi      | I to aquatic life with long lasting effects.  |
| · Precautionary  | statements  |
| P210             | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  |
| P260             | Do not breathe dust/fume/gas/mist/vapours/spray.  |
| P280             | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.   |
| P303+P361+I      | P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].                         |
| P305+P351+I      | P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P403+P235        |   |
| · 2.3 Other haza | urds  |
| · Results of PB1 | T and vPvB assessment   |
|                  | 1. 11   |

- *PBT:* Not applicable. *vPvB:* Not applicable.


# SECTION 3: Composition/information on ingredients

#### · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components:  |   |                      |
|--|---|----------------------|
| CAS: 100-42-5<br>EINECS: 202-851-5<br>Reg.nr.: 01-2119457861-32  | styrene<br>Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372;<br>Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315;<br>Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3,<br>H412 | <i>≥10-≤20%</i>      |
| CAS: 91-99-6<br>EINECS: 202-114-8                                | 2,2'-(m-tolylimino)diethanol<br>STOT RE 2, H373; Eye Dam. 1, H318; Acute Tox. 4,<br>H302; Skin Irrit. 2, H315; Skin Sens. 1B, H317  | <i>≥</i> 0.1-<1%     |
| CAS: 3077-12-1<br>EINECS: 221-359-1<br>Reg.nr.: 01-2120791684-40 | 2,2'-[(4-methylphenyl)imino]bisethanol<br>Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1,<br>H317; Aquatic Chronic 3, H412  | <i>≥</i> 0.1-<1%     |
| CAS: 38668-48-3<br>EINECS: 254-075-1                             | 1,1'-(p-tolylimino)dipropan-2-ol<br>Acute Tox. 2, H300;   | <1%                  |
| CAS: 117-80-6<br>EINECS: 204-210-5                               | <i>dichlone (ISO)</i>   | <i>≥</i> 0.025-<0.1% |
| CAS: 108-31-6<br>EINECS: 203-571-6<br>Reg.nr.: 01-2119472428-31  | maleic anhydride<br>Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. IB,<br>H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens.<br>1A, H317  | <i>≥</i> 0.001-<0.1% |
|  |   | (Contd. on page      |

according to 1907/2006/EC, Article 31



Version number 14



Trade name: 4CR 2355 Multi Soft Spachtel

• Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 2)

### **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- *Protective equipment: Mouth respiratory protective device.*

### **SECTION 6:** Accidental release measures


- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
   6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

# SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke.*

(Contd. on page 4)

according to 1907/2006/EC, Article 31



Version number 14



Trade name: 4CR 2355 Multi Soft Spachtel

(Contd. of page 3)

Protect against electrostatic charges.

Keep respiratory protective device available.

- $\cdot$  7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.

· Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

**SECTION 8: Exposure controls/personal protection** 

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

#### · Ingredients with limit values that require monitoring at the workplace:

#### 100-42-5 styrene

WEL Short-term value: 1080 mg/m<sup>3</sup>, 250 ppm

Long-term value: 430 mg/m<sup>3</sup>, 100 ppm

108-31-6 maleic anhydride

WEL Short-term value: 3 mg/m<sup>3</sup>

Long-term value: 1 mg/m<sup>3</sup>

Sen

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.* • *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

G₿ ∙



Printing date 09.09.2021

Version number 14

# Trade name: 4CR 2355 Multi Soft Spachtel

(Contd. of page 4)

· Breakthrough time of glove material

- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be
- observed.

· Eye protection:



×

Tightly sealed goggles

| 9.1 Information on basic physical and ch | nemical properties   |
|--|--|
| General Information<br>Appearance:       |  |
| Form:                                    | Fluid  |
| Colour:                                  | According to product specification   |
| Odour:                                   | Characteristic   |
| Odour threshold:                         | Not determined.  |
| pH-value:                                | Not determined.  |
| Change in condition                      |  |
| Melting point/freezing point:            | Undetermined.  |
| Initial boiling point and boiling range: | 145 °C   |
| Flash point:                             | 33 °C (DIN 53213)  |
| Flammability (solid, gas):               | Not applicable.  |
| Ignition temperature:                    | 480 °C (DIN 51794)   |
| Decomposition temperature:               | Not determined.  |
| Auto-ignition temperature:               | Product is not selfigniting.   |
| Explosive properties:                    | Product is not explosive. However, formation of explosive ai vapour mixtures are possible. |
| Explosion limits:                        |  |
| Lower:                                   | 1.2 Vol %  |
| Upper:                                   | 8.9 Vol %  |
| Vapour pressure at 20 °C:                | 6 hPa  |
| Density at 20 °C:                        | 1.556 g/cm <sup>3</sup> (DIN 53217)  |
| Relative density                         | Not determined.  |
| Vapour density                           | Not determined.  |
| Evaporation rate                         | Not determined.  |
| Solubility in / Miscibility with         |  |
| water:                                   | Not miscible or difficult to mix.  |
| Partition coefficient: n-octanol/water:  | Not determined.  |
| Viscosity:                               |  |
| Dynamic at 20 °C:                        | 9,000 mPas   |
| Kinematic:                               | Not determined.  |
| Solvent content:                         |  |
| VOC (EC)                                 | 0.46 %   |

according to 1907/2006/EC, Article 31



Printing date 09.09.2021

Version number 14

Trade name: 4CR 2355 Multi Soft Spachtel

 Solids content (weight-%):
 83.2 %

 • 9.2 Other information
 No further relevant information available.

# SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide

## **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

| 100-42-5 styrene |          |   |  |
|------------------|----------|---|--|
| Oral             | LD50     | 5,000 mg/kg (rat)                       |  |
|                  | LD50     | 5,000 mg/kg (rat)<br>>2,000 mg/kg (rat) |  |
| Inhalative       | LC50/4 h | 11.8 mg/l (rat)                         |  |

Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

- Causes serious eye irritation.
- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- *Carcinogenicity* Based on available data, the classification criteria are not met.
- · Reproductive toxicity
- Suspected of damaging the unborn child.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure
- Causes damage to the hearing organs through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.


### **SECTION 12: Ecological information**

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish

(Contd. on page 7)

GB



#### Version number 14



### Trade name: 4CR 2355 Multi Soft Spachtel

(Contd. of page 6)

### • Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

# · 12.5 Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

#### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

### **SECTION 14: Transport information** · 14.1 UN-Number · ADR, IMDG, IATA UN3269 • 14.2 UN proper shipping name UN3269 POLYESTER RESIN KIT · ADR POLYESTER RESIN KIT · IMDG, IATA · 14.3 Transport hazard class(es) ·ADR · Class 3 (F3) Flammable liquids. · Label \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ · IMDG, IATA · Class 3 Flammable liquids. · Label 3 · 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): EMS Number: F-E, S-D

(Contd. on page 8)

GB

according to 1907/2006/EC, Article 31



Printing date 09.09.2021

Version number 14


Trade name: 4CR 2355 Multi Soft Spachtel

|  | (Cont                                 | d. of page 7 |
|--|---------------------------------------|--------------|
| · Stowage Category   | Α                                     |              |
| · 14.7 Transport in bulk according to A<br>Marpol and the IBC Code | <b>Annex II of</b><br>Not applicable. |              |
| · Transport/Additional information:                                |                                       |              |
| · ADR  |                                       |              |
| · Limited quantities (LQ)  | 5L                                    |              |
| Transport category   | 3                                     |              |
| • Tunnel restriction code  | E                                     |              |
| · IMDG   |                                       |              |
| · Limited quantities (LQ)  | 5L                                    |              |
| · UN "Model Regulation":   | UN 3269 POLYESTER RESIN KIT, 3, III   |              |

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II:



· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H226 Flammable liquid and vapour.
- H300 Fatal if swallowed.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- *H400 Very toxic to aquatic life.*
- H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 9)

GB

**CCR** *Revision: 09.09.2021* 

Printing date 09.09.2021

Version number 14

### Trade name: 4CR 2355 Multi Soft Spachtel

|   | (Contd. of page 8) |
|---|--------------------|
| H412 Harmful to aquatic life with long lasting effects.   |                    |
| Classification according to Regulation (EC) No 1272/2008  |                    |
| The classification of the mixture is generally based on the calculation method using substance of               | data according     |
| to Regulation (EC) No 1272/2008.  | aala accoraing     |
|   |                    |
| Abbreviations and acronyms:   | <i>a</i>           |
| RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulation | ns Concerning th   |
| International Transport of Dangerous Goods by Rail)   |                    |
| IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)                   |                    |
| ICAO: International Civil Aviation Organisation   |                    |
| ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)                       | . Como comito e di |
| ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreemen        | it Concerning th   |
| International Carriage of Dangerous Goods by Road)  |                    |
| IMDG: International Maritime Code for Dangerous Goods<br>IATA: International Air Transport Association          |                    |
| GHS: Globally Harmonised System of Classification and Labelling of Chemicals                                    |                    |
| EINECS: European Inventory of Existing Commercial Chemical Substances   |                    |
| ELINECS: European List of Notified Chemical Substances  |                    |
| CAS: Chemical Abstracts Service (division of the American Chemical Society)                                     |                    |
| VOC: Volatile Organic Compounds (USA, EU)   |                    |
| LC50: Lethal concentration, 50 percent  |                    |
| LD50: Lethal dose, 50 percent   |                    |
| PBT: Persistent, Bioaccumulative and Toxic  |                    |
| vPvB: very Persistent and very Bioaccumulative  |                    |
| Flam. Liq. 3: Flammable liquids – Category 3  |                    |
| Acute Tox. 2: Acute toxicity – Category 2   |                    |
| Acute Tox. 4: Acute toxicity – Category 4   |                    |
| Skin Corr. 1B: Skin corrosion/irritation – Category 1B  |                    |
| Skin Irrit. 2: Skin corrosion/irritation – Category 2   |                    |
| Eye Dam. 1: Serious eye damage/eye irritation – Category 1  |                    |
| Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  |                    |
| Resp. Sens. 1: Respiratory sensitisation – Category 1   |                    |
| Skin Sens. 1: Skin sensitisation – Category I   |                    |
| Skin Sens. 1A: Skin sensitisation – Category 1A   |                    |
| Skin Sens. 1B: Skin sensitisation – Category 1B   |                    |
| Repr. 2: Reproductive toxicity – Category 2   |                    |
| STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  |                    |
| STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1                                      |                    |
| STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2                                      |                    |
| Asp. Tox. 1: Aspiration hazard – Category 1   |                    |
| Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1                       |                    |
| Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1                 |                    |
| Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3                 |                    |
| * Data compared to the previous version altered.  |                    |
|   |                    |