



Art.-No.:6.5200.0500

5200

## Underbody Protection Bitumen Spray

### Characteristics

4CR 5200 Underbody Protection Bitumen Spray is a durable elastic underbody protection based on rubber-bitumen. Provides a long-term protection against water, salt, corrosion on corners, edges or for repair work.

### Tech Tip

- Abrasion resistant, durable elasticity
- Anti-corrosive
- Not overcoatable!
- Excellent anti-noise characteristics

### Application

Substrate: The substrate must be clean from rust, grease, and polishing agents and sanded. If necessary primed.

Pretreatment / Cleansing: Pre-cleansing with 4CR Silikonentferner.

Processing Conditions: Can be processed at any temperature.

Do not spray on the motor, gears, brakes etc.

All substrates must be clean, dry and free from grease. Shake can vigorously for approx. 3 mins. prior to use. Spraying distance approx. 20 - 30 cm. Apply several thin layers, with a flash-off period of approx. 3 - 5 Minuten between each coating.

After use, turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

### Technical Data

Colour	black
Content	500 ml
Full hardness	Dry after 5 h / 20°C

### Storage and Transportation

The product may not be stored under +10°C and above +30°C the packaging must be protected from direct sunlight and heat. Cool and moisture free stored the product is tenable for a minimum of 2 years in the unopened original packaging.