



Art.-No.:6.1200.5000

1200

## Foam Masking Tape

### Characteristics

4CR 1200 Foam Masking Tape is designed for Masking Door Apertures to stop the ingress of spray paint whilst being sprayed, during repair.

### Tech Tip

The fast and sure way to mask door apertures and other gaps.  
 Making previously unmaskable gaps simple and easy to protect.  
 Uniquely positioned adhesive allows material to be adjusted in-situ eliminating hard edges due to painting up to an adhesive barrier.  
 Eliminates unnecessary rework due to unwanted paint edges.  
 Just one size to choose for every occasion.

### Application

1. Choose aperture to be masked.
2. Apply tape behind the door edge taking care to place the adhesive behind the panel. Leave the adhesive free portion extending beyond the door edge.
3. Close the door. Smooth the tape into the gap to the required depth. Mask up the rest of the vehicle.
4. Paint the vehicle.
5. Once the paint is dry remove all the masking materials.
6. Once the tape is removed, inspect edges and polish if necessary. The result is no extra rework.

### Technical Data

Foam	White
Adhesive	Rubber
Thickness	9mm (+/- 1mm)
Width	20mm (+/- 2mm)
Length	50m (+/- .5m)
Density	30 kg/m <sup>3</sup> (+/- 4 kg/m <sup>3</sup> )
Peel adhesion N/25mm	6
Shear adhesion h/23°C	>10
UV resistance	Limited
Temperature resistance	1h/°C 95