

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : A-H-600 1L 1L Steel drums

Product code : 000000000050732241

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : hardener
Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company:

BASF Coatings GmbH
Postfach 6123
48136 Münster
Deutschland

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
United Kingdom

Telephone: +44 161 475 3000
E-mail address: product-safety-uk-and-ireland@basf.com

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

1.4 Emergency telephone

International emergency number:
Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal Word : Warning

Hazard Statements	:	H226	Flammable liquid and vapor.
		H317	May cause an allergic skin reaction.
		H332	Harmful if inhaled.
		H335	May cause respiratory irritation.
		H336	May cause drowsiness or dizziness.

Supplemental Hazard Statements	:	EUH066	Repeated exposure may cause skin dryness or cracking.
--------------------------------	---	--------	---

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

Precautionary Statements

:

Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing mist or vapors.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

Hazardous ingredients which must be listed on the label:

Hexamethylen-1,6-diisocyanat Homopolymer

n-Butyl acetate

IPDI Homopolymer

xylene

Additional Labeling

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : polyisocyanate

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

polyurethane
organic solvent

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hexamethylen-1,6-diisocyanat Homopolymer	28182-81-2 500-060-2 01-2119485796-17	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 25 - < 50

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 25 - < 50
IPDI Homopolymer	53880-05-0 500-125-5 01-2119980716-25	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory	>= 7 - < 10

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

		system)	
xylene	1330-20-7	Flam. Liq. 3; H226	>= 2.5 - < 3
	215-535-7	Acute Tox. 4;	
	601-022-00-9	H332	
	UK-20-	Acute Tox. 4;	
	2749242067-7-	H312	
	0000	Skin Irrit. 2; H315	
	UK-20-	Eye Irrit. 2; H319	
	9702550300-0-	STOT SE 3; H335	
	0000	(Respiratory	
	UK-20-	system)	
	0537843089-5-	STOT RE 2; H373	
	0000	(Kidney, Liver,	
	UK-20-	Central nervous	
	9642318150-0-	system)	
	0000	Asp. Tox. 1; H304	
		Aquatic	

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

		Chronic 3; H412	
1-methoxy-2-propylacetate	108-65-6	Flam. Liq. 3; H226	>= 2.5 - < 3
	203-603-9	STOT SE 3; H336	
	607-195-00-7	(Central nervous system)	
	UK-20-9702550300-0-0000		
	UK-20-0537843089-5-0000		
	UK-20-9642318150-0-0000		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own safety.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).
Immediately remove contaminated clothing.
In all cases of doubt, or when symptoms persist, seek medical attention.
Move out of dangerous area.
Never give anything by mouth to an unconscious person.

If inhaled : If symptoms persist, call a physician.

If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Call a physician immediately.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

In case of eye contact : If symptoms persist, call a physician.

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If swallowed : Do not induce vomiting due to aspiration hazard.

Keep at rest.

If symptoms persist, call a physician or Poison Control Center immediately.

Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

Risks : May cause an allergic skin reaction.
Harmful if inhaled.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Dry powder
Alcohol-resistant foam
Carbon dioxide (CO₂)

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

Unsuitable extinguishing : High volume water jet
media

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire : Fire will produce dense black smoke containing
fighting hazardous combustion products (see section 10).

Hazardous combustion : Nitrogen oxides (NO_x)
products

5.3 Advice for firefighters

Special protective : Appropriate breathing apparatus may be required.
equipment for fire-fighters

Further information : In the event of fire, cool tanks with water spray.
Fire residues and contaminated fire extinguishing water

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

must be disposed of in accordance with local
regulations.

Collect contaminated fire extinguishing water separately.
This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

Advice on product handling can be found in sections 7
and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined
areas.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth. Place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): ethanol or isopropyl alcohol (50 parts); water (45 parts); concentrated ammonia solution (5 parts). A non-flammable alternative is: sodium carbonate (5 parts); water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13).

Ensure adequate ventilation.

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Open drum carefully as content may be under pressure.

Do not breathe vapors or spray mist.

Protect from moisture.

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Exercise caution when opening to allow pressure release. Precautions should be taken to minimise exposure to atmospheric humidity or water: carbon dioxide will be formed which in closed containers can result in pressurisation. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing.

Advice on common storage : Keep away from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result in distortion, blowing and

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

in extreme cases bursting of the container.

Recommended storage : 5.00 - 30.00 °C
temperature

Packaging material : Suitable material: Aluminum, glass, High density
polyethylene (HDPE), Low density polyethylene (LDPE),
tinned carbon steel (Tinplate), Carbon steel (Iron),
Stainless steel 1.4301 (V2), Polypropylene,
Polyethylenetherephtalate (PET)

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further
information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version 3.0 Revision Date: 14.03.2025 SDS Number: 000000000050732
241 Date of last issue: 20.01.2025 Date of first issue: 09.04.2024

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hexamethylen-1,6-diisocyanat Homopolymer	28182-81-2	TWA	0.02 mg/m ³ (NCO)	GB EH40
	Further information: Capable of causing occupational asthma.			
		STEL	0.07 mg/m ³ (NCO)	GB EH40
	Further information: Capable of causing occupational asthma.			
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40
		STEL	200 ppm 966 mg/m ³	GB EH40
		STEL	150 ppm 723 mg/m ³	2019/1831/ EU

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

	Further information: Indicative			
		TWA	50 ppm 241 mg/m3	2019/1831/ EU
	Further information: Indicative			
xylene	1330-20-7	TWA	50 ppm 220 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 221 mg/m3	2000/39/EC

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
1-methoxy-2-propylacetate	108-65-6	TWA	50 ppm 274 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 548 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm	2000/39/EC

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

			550 mg/m3	
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Hexamethylen-1,6-diisocyanat Homopolymer	28182-81-2	isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT
xylene	1330-20-7	methyl hippuric acid: 650	After shift	GB EH40 BAT

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

		Millimoles per mole creatinine (Urine)		
--	--	--	--	--

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166
Required when there is a risk of eye contact.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Skin and body protection : chemical-resistant disposable coveralls

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

respirators.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Suitable respiratory equipment:

full face mask with AB2P3 class combination filter

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

Under cool dry conditions, it is possible for the isocyanate to remain unreacted in the paint film for up to 30 hours after application.

Respiratory protective equipment should be worn by spray booth operatives.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Color	:	yellow
Odor	:	ester-like
pH	:	substance/mixture reacts with water
Melting point/ range	:	not determined
Boiling point/boiling range	:	128 - 138 °CMethod: calculated
Flash point	:	29 °C Method: ISO 3679
Upper explosion limit / Upper flammability limit	:	not determined

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

Lower explosion limit /
Lower flammability limit : > 35.0 g/m³

Vapor pressure : 10 hPa (20 °C)

48 hPa (50 °C)

Relative vapor density : Heavier than air.

Density : 1.047 g/cm³ (20 °C)

Solubility(ies)
Water solubility : not determined

Partition coefficient: n- : not applicable for mixtures

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

octanol/water

Autoignition temperature : > 200 °C

Decomposition : No decomposition if stored and handled as
temperature prescribed/indicated.

Viscosity
Viscosity, kinematic : (40 °C)
not determined

411.6 mm²/s (23 °C)

Flow time : > 60 s
Cross section: 6 mm

Explosive properties : Not explosive

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids) : Flammable liquid and vapour.

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

Particle size : The substance / product is marketed or used in a non solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct contact with water.

Avoid direct sunlight.

Protect from frost.

Heat, flames and sparks.

Heat.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts with water resulting in evolution of carbon dioxide. In closed containers,

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

pressure build up could result in distortion, blowing and
in extreme cases bursting of the container.

10.6 Hazardous decomposition products

Nitrogen oxides (NO_x)
Hydrogen cyanide (hydrocyanic acid)
Isocyanates

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

Product:

Acute inhalation toxicity : Acute toxicity estimate: 2.79 mg/l
Exposure time: 4 h

Test atmosphere: dust/mist

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

n-Butyl acetate:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

STOT-single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

Product:

No aspiration toxicity classification

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Hexamethylen-1,6-diisocyanat Homopolymer:

Partition coefficient: n- : log Pow: 9.81 (25 °C)
octanol/water

n-Butyl acetate:

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

Partition coefficient: n-
octanol/water

: Pow: 200 (25 °C)

log Pow: 2.3 (25 °C)

pH: 7

Method: OECD Test Guideline 117

GLP: yes

xylene:

Partition coefficient: n-
octanol/water

: log Pow: 3.12 - 3.20 (25 °C)

GLP: no

Remarks: Information taken from reference works and
the literature.

1-methoxy-2-propylacetate:

Partition coefficient: n-
octanol/water

: log Pow: 1.2 (20 °C)

pH: 6.8

Method: OECD Test Guideline 117

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

Product : Dispose of isocyanate waste in dry containers and never mix together with other wastes (reaction, dangerous pressure build up).

Do not discharge into drains/surface waters/groundwater.

Observe national and local legal requirements.

Contaminated packaging : Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

Residues in empty containers should be neutralised with decontaminant (see section 6).

Packaging that is not properly emptied must be disposed of as the unused product.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

SECTION 14: Transport information

14.1 UN number

ADN	:	UN 1866
ADR	:	UN 1866
RID	:	UN 1866
IMDG	:	UN 1866
IATA	:	UN 1866

14.2 UN proper shipping name

ADN	:	RESIN SOLUTION
ADR	:	RESIN SOLUTION
RID	:	RESIN SOLUTION
IMDG	:	RESIN SOLUTION
IATA	:	RESIN SOLUTION

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

ADR

Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
Tunnel restriction code	: (D/E)

RID

Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3

IMDG

Packing group	: III
---------------	-------

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

Labels : 3

EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo : 366
aircraft)

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction : 355
(passenger aircraft)

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable liquid

14.5 Environmental hazards

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

ADN

Environmentally : no
hazardous

ADR

Environmentally : no
hazardous

RID

Environmentally : no
hazardous

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 liters, not
goods/merchandise of Class 3

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Conditions of restriction for the following entries should be considered: Number on list 3
--	---

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	: Not applicable
---	------------------

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	: Not applicable
---	------------------

Regulation (EC) on substances that deplete the	: Not applicable
--	------------------

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

ozone layer

UK REACH List of substances subject to
authorisation (Annex XIV) : Not applicable

P5c

Control of Major Accident Hazards
Regulations 2015 (COMAH) P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on
industrial emissions (integrated pollution prevention and
control)

Volatile organic compounds (VOC) content: 35.02 %

Volatile organic compounds (VOC) content: 366.65 g/l

VOC content excluding water

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

dropped

Limit value for maximum VOC content as specified in Annex IIB:

dropped

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of other abbreviations

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

exposure limit values

GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization;

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data sheets of all components.
Restricted to professional users.

Classification of the mixture:

Flam. Liq. 3

H226

Classification procedure:

Based on product data or

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-H-600 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 20.01.2025
3.0	14.03.2025	000000000050732 241	Date of first issue: 09.04.2024

		assessment
Acute Tox. 4	H332	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method
STOT SE 3	H335	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN