

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : A-U-87 1L 1L Steel drums

Product code : 000000000050857906

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Spraying
Substance/Mixture : Coatings and related products

1.3 Details of the supplier of the safety data sheet

Company:

BASF Coatings GmbH
Postfach 6123
48136 Münster
Deutschland

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
United Kingdom

Telephone: +44 161 475 3000
E-mail address: product-safety-uk-and-ireland@basf.com

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

1.4 Emergency telephone

International emergency number:
Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard,	H411: Toxic to aquatic life with long lasting

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Category 2

effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI
2019/720, and UK SI 2020/1567)

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H225	Highly flammable liquid and vapor.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Precautionary Statements

:

Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
- P391 Collect spillage.

Hazardous ingredients which must be listed on the label:
acetone

tripropylene glycol diacrylate

(OLIGOMER) 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

chloro-2,3-epoxypropane, esters with acrylic acid

Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-

Neopentyl glycol, propoxylated, esters with acrylic acid

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2- p

2-hydroxyethyl acrylate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : unsaturated acrylic resin
fillers
pigment

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

organic solvent

inorganic compounds

organic compounds

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
polymeric urethane acrylate	123904-10-9	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 15 - < 20
acetone	67-64-1 200-662-2 606-001-00-8 UK-20-	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous	>= 15 - < 20

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

	9702550300-0-0000 UK-20-0537843089-5-0000	system)	
Methylethylketone	78-93-3 201-159-0 606-002-00-3 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 7 - < 10
tripropylene glycol diacrylate	42978-66-5	Eye Irrit. 2; H319	>= 7 - < 10

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

	256-032-2 607-249-00-X UK-20- 0537843089-5- 0000	Skin Sens. 1A; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 _____ specific concentration limit STOT SE 3; H335 ≥ 10 %	
(OLIGOMER) 4,4'- Isopropylidenediphenol, oligomeric reactionproducts with 1-chloro-2,3-epoxypropane,	55818-57-0 500-130-2	Skin Sens. 1; H317 Aquatic	≥ 5 - < 7

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

esters with acrylic acid		Chronic 2; H411	
Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-	162881-26-7 423-340-5 015-189-00-5 UK-20- 0537843089-5- 0000	Skin Sens. 1A; H317 Aquatic Chronic 4; H413	>= 3 - < 5
Neopentyl glycol, propoxylated, esters with acrylic acid	84170-74-1 01-2119970213-43	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 3 - < 5
zinc phosphate	7779-90-0 231-944-3 030-011-00-6 UK-20- 9702550300-0- 0000	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity):	>= 3 - < 5

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

	UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	1 M-Factor (Chronic aquatic toxicity): 1	
2-Propenoic acid, 2-methyl-, 2- hydroxyethyl ester, reaction	1187441-10-6	Eye Dam. 1; H318 Skin Sens. 1; H317	>= 1 - < 2
Poly(oxy-1,2-ethanediyl), .alpha.- hydro-.omega.-[(1-oxo-2- p	28961-43-5 500-066-5 01-2119489900-30	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 2
2-hydroxyethyl acrylate	818-61-1 212-454-9 607-072-00-8 UK-20- 9642318150-0- 0000	Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1B; H314	>= 0.025 - < 0.1

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

	UK-20- 0537843089-5- 0000	Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 3; H412 _____ specific concentration limit Skin Sens. 1; H317 >= 0.2 %	
Substances with a workplace exposure limit :			
talc	14807-96-6		>= 10 - < 12.5

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

	238-877-9 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000		
Kaolin	1332-58-7 310-194-1		$\geq 5 - < 7$
Silicon dioxide	7631-86-9 231-545-4 UK-20- 2749242067-7- 0000 UK-20- 9702550300-0- 0000		$\geq 2.5 - < 3$

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

	UK-20- 0537843089-5- 0000		
	UK-20- 9642318150-0- 0000		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own safety.

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

In all cases of doubt, or when symptoms persist, seek medical attention.

Move out of dangerous area.

Never give anything by mouth to an unconscious person.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

- If inhaled : If symptoms persist, call a physician.
- If breathed in, move person into fresh air.
- If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : In case of skin contact avoid direct exposure to sunlight or other UV radiation since this would increase sensitisation of the skin.
- If symptoms persist, call a physician.
- Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
- Do NOT use solvents or thinners.
- In case of eye contact : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- Call a physician immediately.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

If easy to do, remove contact lens, if worn.

In case of accidental eye contact avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of eye.

If swallowed : If symptoms persist, call a physician.

Do NOT induce vomiting.

Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Risks : Causes skin irritation.

May cause an allergic skin reaction.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Causes serious eye irritation.

May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Dry powder
Alcohol-resistant foam
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire : Fire will produce dense black smoke containing
fighting hazardous combustion products (see section 10).

Hazardous combustion : Oxides of phosphorus
products

5.3 Advice for firefighters

Special protective : Appropriate breathing apparatus may be required.
equipment for fire-fighters

Further information : In the event of fire, cool tanks with water spray.

Fire residues and contaminated fire extinguishing water
must be disposed of in accordance with local
regulations.

Collect contaminated fire extinguishing water separately.
This must not be discharged into drains.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

Advice on product handling can be found in sections 7
and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined
areas.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the
environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

application area. For personal protection see section 8.
Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Advice on protection : Avoid all sources of ignition: heat, sparks, open flame.
against fire and explosion : Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

operators should wear antistatic clothing and footwear.
The relevant fire protection measures should be noted.
Use explosion-proof equipment. Vapors are heavier than
air and may spread along floors. Vapors may form
explosive mixtures with air.

Hygiene measures : Remove contaminated clothing immediately and dispose
of safely. Wash hands before breaks and at the end of
workday. Keep away from food, drink and animal
feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Keep away from heat. Avoid direct sunlight. Close
containers carefully once opened and store them
upright in order to prevent any leakage. No smoking. No
admission for unauthorised personnel. Always keep in
containers of same material as the original one. Observe
label precautions. Store protected against freezing. Keep
in a dry, cool and well-ventilated place.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Advice on common storage : Keep away from free radical initiators, peroxides, strong alkalis and reactive materials to avoid exothermic polymerization.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Recommended storage : 5.00 - 30.00 °C
temperature

Packaging material : Suitable material: tinned carbon steel (Tinplate), Carbon steel (Iron), Polypropylene, Polyethylenetherephthalate (PET), Low density polyethylene (LDPE), High density polyethylene (HDPE), Stove-lacquer C222A/C221A, Standard interior paint, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X, Stove-lacquer EHD0022, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer R 78433, Stove-lacquer RDL 50

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
acetone	67-64-1	TWA	500 ppm 1,210 mg/m ³	GB EH40
		STEL	1,500 ppm 3,620 mg/m ³	GB EH40
		TWA	500 ppm 1,210 mg/m ³	2000/39/EC
Further information: Indicative				

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

talc	14807-96-6	TWA (Respirable dust)	1 mg/m3	GB EH40
Methylethylketone	78-93-3	TWA	200 ppm 600 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	300 ppm 899 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	300 ppm 900 mg/m3	2000/39/EC
	Further information: Indicative			
		TWA	200 ppm	2000/39/EC

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version 1.0 Revision Date: 25.04.2025 SDS Number: 000000000050857906 Date of last issue: -
Date of first issue: 25.04.2025

			600 mg/m3	
	Further information: Indicative			
Kaolin	1332-58-7	TWA (Respirable dust)	2 mg/m3	GB EH40
		TWA (Respirable dust)	0.1 mg/m3	2004/37/EC
	Further information: Carcinogens or mutagens			
Silicon dioxide	7631-86-9	TWA (inhalable dust)	6 mg/m3 (Silica)	GB EH40
		TWA (Respirable dust)	2.4 mg/m3 (Silica)	GB EH40

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Methylethylketone	78-93-3	butan-2-one: 70 micromol per litre (Urine)	After shift	GB EH40 BAT
-------------------	---------	---	-------------	----------------

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Required when there is a risk of eye contact.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Skin and body protection : Wear chemical-resistant disposable coverall and boots.

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Respiratory protection : Suitable respiratory equipment:
half-mask with A1P2 class combination filter

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Color	:	gray
Odor	:	ketone-like
Odor Threshold	:	not determined
pH	:	substance/mixture is non-soluble (in water)
Melting point/ range	:	not determined
Flash point	:	56.00 - 66.00 °C -12 °C Method: ISO 3679
Evaporation rate	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35.0 g/m3
Vapor pressure	:	203.0000 hPa (20 °C) 682.0000 hPa (50 °C)
Relative vapor density	:	Heavier than air.
Density	:	1.216 g/cm3 (20 °C)

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Solubility(ies)

Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C

Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
---------------------------	---	---

Viscosity

Viscosity, kinematic	:	not determined (40 °C)
		36.0 mm ² /s (23 °C)

Flow time	:	> 30 s
		Cross section: 4 mm

Explosive properties	:	Not explosive
----------------------	---	---------------

Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
----------------------	---	--

9.2 Other information

Flammability (liquids)	:	Highly flammable liquid and vapour.
------------------------	---	-------------------------------------

Self-heating substances	:	The substance or mixture is not classified as self heating.
-------------------------	---	---

Metal corrosion rate	:	Not corrosive to metals.
----------------------	---	--------------------------

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Particle size : The substance / product is marketed or used in a non solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.
Protect from frost.
Ultraviolet rays
Heat, flames and sparks.
Heat.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

10.5 Incompatible materials

Materials to avoid : Keep away from free radical initiators, peroxides, strong alkalis and reactive materials to avoid exothermic polymerization.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Components:

acetone:

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Assessment : Repeated exposure may cause skin dryness or cracking.

Methylethylketone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Aspiration toxicity

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Components:

zinc phosphate:

M-Factor (Acute aquatic : 1
toxicity)

M-Factor (Chronic aquatic : 1
toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

acetone:

Partition coefficient: n- : log Pow: -0.24 (25 °C)
octanol/water

Methylethylketone:

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Partition coefficient: n- : log Pow: 0.29
octanol/water

GLP: No information available.

Remarks: Information taken from reference works and
the literature.

tripropylene glycol diacrylate:

Partition coefficient: n- : log Pow: 2.0 (25 °C)
octanol/water

GLP: no

log Pow: 2 (25 °C)

Method: OECD Test Guideline 117

GLP: yes

log Pow: 2.77 (25 °C)

Method: OECD Test Guideline 117

GLP: yes

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

log Pow: 2.1 (25 °C)

Method: OECD Test Guideline 117

GLP: yes

log Pow: 2.5 - 2.7 (23 °C)

pH: 6.7

Method: OECD Test Guideline 117

GLP: yes

(OLIGOMER) 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid:

Partition coefficient: n- : log Pow: ca. 1.6 - 3.8 (23 °C)
octanol/water

Method: OECD Test Guideline 117

GLP: yes

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

log Pow: 1.6 - 3.8 (23 °C)

pH: 6.4

Method: OECD Test Guideline 117

GLP: yes

log Pow: 1.6 - 3 (23 °C)

pH: 6.4

Method: OECD Test Guideline 117

GLP: yes

log Pow: 3 - 3.8 (23 °C)

pH: 6.4

Method: OECD Test Guideline 117

GLP: yes

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-:

Partition coefficient: n-
octanol/water

: log Pow: 5.8 (22 °C)

pH: 8.3

Method: OECD Test Guideline 117

GLP: yes

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction:

Partition coefficient: n-
octanol/water

: Pow: 2 - 5,200 (23.3 °C)

log Pow: 0.3 - 3.7 (23.3 °C)

Method: OECD Test Guideline 117

GLP: yes

Poly(oxy-1,2-ethanediyl), .alpha.-hydro.-omega.-[(1-oxo-2- p:

Partition coefficient: n-
octanol/water

: log Pow: 2.89 (23 °C)

pH: 8.1

Method: OECD Test Guideline 107

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

GLP: no

2-hydroxyethyl acrylate:

Partition coefficient: n- : log Pow: -0.17 (25 °C)
octanol/water
Method: OECD Test Guideline 107
GLP: no

talc:

Partition coefficient: n- : log Pow: -9.4 (25 °C)
octanol/water
pH: 7
GLP: no

Silicon dioxide:

Partition coefficient: n- : Remarks: Not applicable
octanol/water

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Observe national and local legal requirements.

Contaminated packaging : Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

Packaging that is not properly emptied must be disposed of as the unused product.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263

ADR : UN 1263

RID : UN 1263

IMDG : UN 1263

IATA : UN 1263

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

14.2 UN proper shipping name

ADN : PAINT

ADR : PAINT

RID : PAINT

IMDG : PAINT

(TRIPROPYLENEGLYCOL DIACRYLATE)

IATA : PAINT

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

IATA : 3

14.4 Packing group

ADN

Packing group	: II
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3
Remarks	: Special Provision 640D

ADR

Packing group	: II
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Tunnel restriction code : (D/E)

Remarks : Special Provision 640D

RID

Packing group : II

Classification Code : F1

Hazard Identification
Number : 33

Labels : 3

Remarks : Special Provision 640D

IMDG

Packing group : II

Labels : 3

EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo : 364

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

aircraft)

Packing instruction (LQ) : Y341

Packing group : II

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction : 353
(passenger aircraft)

Packing instruction (LQ) : Y341

Packing group : II

Labels : Flammable liquid

14.5 Environmental hazards

ADN

Environmentally : yes
hazardous

ADR

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Environmentally : yes
hazardous

RID

Environmentally : yes
hazardous

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:

Number on list 72, 3

Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1148 on the marketing and : Listed

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

use of explosives precursors

UK REACH List of substances subject to
authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards E2 ENVIRONMENTAL HAZARDS
Regulations 2015 (COMAH)

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on
industrial emissions (integrated pollution prevention and
control)

Volatile organic compounds (VOC) content: 27.48 %

Volatile organic compounds (VOC) content: 334.15 g/l

VOC content excluding water

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

Limit value for maximum VOC content as specified in Annex IIB:

VOC content of the ready-for-use product according to ISO 11890-2:

c

540 g/l

539 g/l

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapor.
H302	: Harmful if swallowed.
H311	: Toxic in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2004/37/EC / TWA	: Long term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025

Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data sheets of all components.
Restricted to professional users.

Classification of the mixture:

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H336
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

A-U-87 1L 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	25.04.2025	000000000050857 906	Date of first issue: 25.04.2025
