

# Safety data sheet

Page: 1/20

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: **\*11-E 820 0,125L BROWN PEARL**

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

---

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**\*11-E 820 0,125L BROWN PEARL**

UFI: S7YT-A6WA-9002-GKNY

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Basecoat product

### 1.3. Details of the supplier of the safety data sheet

Company:

BASF Coatings GmbH  
Postfach 6123  
48136 Muenster  
Deutschland

Contact address:

BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
UNITED KINGDOM

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

### 1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

---

## SECTION 2: Hazards Identification

### 2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: **\*11-E 820 0,125L BROWN PEARL**

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Skin Corr./Irrit. 2	H315 Causes skin irritation.
Eye Dam./Irrit. 1	H318 Causes serious eye damage.
Skin Sens. 1B	H317 May cause an allergic skin reaction.
STOT SE 3	H336 May cause drowsiness or dizziness.
Flam. Liq. 3	H226 Flammable liquid and vapour.

For the classifications not written out in full in this section the full text can be found in section 16.

## 2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
--------------------	--

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
-------------	--

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Labeling of special preparations (GHS):

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: \*11-E 820 0,125L BROWN PEARL

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Hazard determining component(s) for labelling: 1-methoxy-2-propanol, 2-dimethylaminoethanol, 2-methoxy-1-methylethyl acetate, 2,4,7,9-Tetramethyldec-5-yne-4,7-diol

### 2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

---

## SECTION 3: Composition/Information on Ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

#### Chemical nature

organic solvent, pigment, polyurethane

#### Hazardous ingredients (GHS)

1-methoxy-2-propanol

Content (W/W):  $\geq 15\%$  -  $< 20\%$

CAS Number: 107-98-2

EC-Number: 203-539-1

REACH registration number: 01-2119457435-35

INDEX-Number: 603-064-00-3

Flam. Liq. 3

STOT SE 3 (drowsiness and dizziness)

H226, H336

2-methoxy-1-methylethyl acetate

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: \*11-E 820 0,125L BROWN PEARL

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

Content (W/W): $\geq 12.5\%$ - $< 15\%$	Flam. Liq. 3
CAS Number: 108-65-6	STOT SE 3 (drowsiness and dizziness)
EC-Number: 203-603-9	H226, H336
REACH registration number: 01-2119475791-29	
INDEX-Number: 607-195-00-7	

## titanium dioxide

Content (W/W): $\geq 12.5\%$ - $< 15\%$	Carc. 2 (by inhalation)
CAS Number: 13463-67-7	H351
EC-Number: 236-675-5	
REACH registration number: 01-2119489379-17	
INDEX-Number: 022-006-002	

## Naphtha (petroleum), heavy alkylate

Content (W/W): $\geq 3\%$ - $< 5\%$	Asp. Tox. 1
CAS Number: 64741-65-7	Flam. Liq. 3
EC-Number: 918-167-1	Aquatic Chronic 4
REACH registration number: 01-2119472146-39	H413, H226, H304
	EUH066

## 2-butoxyethanol

Content (W/W): $\geq 1\%$ - $< 2\%$	Acute Tox. 4 (Inhalation - vapour)
CAS Number: 111-76-2	Acute Tox. 4 (oral)
EC-Number: 203-905-0	Skin Corr./Irrit. 2
REACH registration number: 01-2119475108-36	Eye Dam./Irrit. 2
INDEX-Number: 603-014-00-0	H319, H315, H302 + H332

## 2-dimethylaminoethanol

Content (W/W): $\geq 1\%$ - $< 2\%$	Flam. Liq. 3
CAS Number: 108-01-0	Acute Tox. 3 (Inhalation - vapour)
EC-Number: 203-542-8	Acute Tox. 4 (oral)
REACH registration number: 01-2119492298-24	Acute Tox. 4 (dermal)
INDEX-Number: 603-047-00-0	Skin Corr./Irrit. 1B
	Eye Dam./Irrit. 1
	STOT SE 3 (irr. to respiratory syst.)
	H226, H331, H335, H314, H302 + H312

Specific concentration limit:STOT SE 3, irr. to respiratory syst.:  $\geq 5\%$

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: \*11-E 820 0,125L BROWN PEARL

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

2,4,7,9-Tetramethyldec-5-yne-4,7-diol

Content (W/W):  $\geq 1\%$  -  $< 2\%$

CAS Number: 126-86-3

EC-Number: 204-809-1

REACH registration number: 01-2119954390-39

Eye Dam./Irrit. 1

Skin Sens. 1B

Aquatic Chronic 3

H318, H317, H412

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

---

## SECTION 4: First-Aid Measures

### 4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms: allergic symptoms, dazed state, skin irritation, dizziness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions).

Antidote: No known specific antidote.

---

## SECTION 5: Fire-Fighting Measures

### 5.1. Extinguishing media

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: \*11-E 820 0,125L BROWN PEARL

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

---

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

### **5.2. Special hazards arising from the substance or mixture**

Advice: Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

### **5.3. Advice for fire-fighters**

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

---

## **SECTION 6: Accidental Release Measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

### **6.4. Reference to other sections**

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

---

## **SECTION 7: Handling and Storage**

### **7.1. Precautions for safe handling**

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: **\*11-E 820 0,125L BROWN PEARL**

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate), High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephthalate (PET), Polypropylene (PP)

Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing.

## 7.3. Specific end use(s)

Please refer to the technical leaflet for further information.

---

## SECTION 8: Exposure Controls/Personal Protection

### 8.1. Control parameters

Components with occupational exposure limits

107-98-2: 1-methoxy-2-propanol

TWA value 375 mg/m<sup>3</sup> ; 100 ppm (WEL/EH 40 (UK))

Skin Designation (WEL/EH 40 (UK))

The substance can be absorbed through the skin.

STEL value 568 mg/m<sup>3</sup> ; 150 ppm (OEL (EU))

indicative

Skin Designation (OEL (EU))

The substance can be absorbed through the skin.

TWA value 375 mg/m<sup>3</sup> ; 100 ppm (OEL (EU))

indicative

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: \*11-E 820 0,125L BROWN PEARL

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

- 108-01-0: 2-dimethylaminoethanol  
 STEL value 560 mg/m<sup>3</sup> ; 150 ppm (WEL/EH 40 (UK))  
 Ceiling limit value/factor: 15 min
- 108-65-6: 2-methoxy-1-methylethyl acetate  
 TWA value 7.4 mg/m<sup>3</sup> ; 2 ppm (WEL/EH 40 (UK))  
 STEL value 22 mg/m<sup>3</sup> ; 6 ppm (WEL/EH 40 (UK))  
 Ceiling limit value/factor: 15 min
- 111-76-2: 2-butoxyethanol  
 Skin Designation (WEL/EH 40 (UK))  
 The substance can be absorbed through the skin.  
 TWA value 123 mg/m<sup>3</sup> ; 25 ppm (WEL/EH 40 (UK))  
 Skin Designation (OEL (EU))  
 The substance can be absorbed through the skin.  
 STEL value 246 mg/m<sup>3</sup> ; 50 ppm (OEL (EU))  
 indicative  
 TWA value 98 mg/m<sup>3</sup> ; 20 ppm (OEL (EU))  
 indicative  
 STEL value 246 mg/m<sup>3</sup> ; 50 ppm (WEL/EH 40 (UK))  
 Ceiling limit value/factor: 15 min
- 13463-67-7: titanium dioxide  
 TWA value 4 mg/m<sup>3</sup> (WEL/EH 40 (UK)), Respirable  
 TWA value 10 mg/m<sup>3</sup> (WEL/EH 40 (UK)), Inhalable

#### Components with biological limit values

- 111-76-2: 2-butoxyethanol  
 UKEH40BMGV  
 Determinant: butoxyacetic acid  
 Biological Specimen: Creatinine in urine  
 Sampling time: End of shift  
 Concentration: 240 mmol/mol

#### Components with PNEC

- 107-98-2: 1-methoxy-2-propanol  
 freshwater: 10 mg/l  
 marine water: 1 mg/l



BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: **\*11-E 820 0,125L BROWN PEARL**

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

intermittent release: 100 mg/l  
STP: 100 mg/l  
sediment (freshwater): 41.6 mg/kg  
soil: 2.47 mg/kg  
sediment (marine water): 4.17 mg/kg

108-01-0: 2-dimethylaminoethanol

freshwater: 0.066 mg/l  
marine water: 0.004 mg/l  
intermittent release: 0.661 mg/l  
sediment (freshwater): 0.246 mg/kg  
sediment (marine water): 0.015 mg/kg  
soil: 0.01 mg/kg  
STP: 10 mg/l  
oral (secondary poisoning):  
No PNEC oral derived, as accumulation in organisms is not to be expected.

108-65-6: 2-methoxy-1-methylethyl acetate

freshwater: 0.635 mg/l  
marine water: 0.0635 mg/l  
intermittent release: 6.35 mg/l  
sediment (freshwater): 3.29 mg/kg  
sediment (marine water): 0.329 mg/kg  
soil: 0.29 mg/kg  
STP: 100 mg/l

111-76-2: 2-butoxyethanol

freshwater: 8.8 mg/l  
marine water: 0.88 mg/l  
intermittent release: 9.1 mg/l  
sediment (freshwater): 34.6 mg/kg  
sediment (marine water): 3.46 mg/kg  
soil: 2.33 mg/kg  
STP: 463 mg/l  
oral (secondary poisoning): 20 mg/kg

126-86-3: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol

freshwater: 0.04 mg/l  
marine water: 0.004 mg/l  
intermittent release: 0.4 mg/l  
STP: 7 mg/l  
sediment (freshwater): 0.32 mg/kg  
sediment (marine water): 0.032 mg/kg  
soil: 0.028 mg/kg  
oral (secondary poisoning):  
No PNEC value available.

13463-67-7: titanium dioxide

marine water: 1 mg/l  
intermittent release: 0.61 mg/l

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: \*11-E 820 0,125L BROWN PEARL

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

sediment (freshwater): 1000 mg/kg  
oral (secondary poisoning): 1667 mg/kg  
freshwater: 0.127 mg/l  
sediment (marine water): 100 mg/kg  
soil: 100 mg/kg  
STP: 100 mg/l

#### Components with DNEL

##### 107-98-2: 1-methoxy-2-propanol

worker: Short-term exposure - systemic and local effects, Inhalation: 553.5 mg/m<sup>3</sup>  
worker: Long-term exposure- systemic effects, dermal: 183 mg/kg  
worker: Long-term exposure- systemic effects, Inhalation: 369 mg/m<sup>3</sup>  
consumer: Long-term exposure- systemic effects, dermal: 78 mg/kg  
consumer: Long-term exposure- systemic effects, Inhalation: 43.9 mg/m<sup>3</sup>  
consumer: Long-term exposure- systemic effects, oral: 33 mg/kg

##### 108-01-0: 2-dimethylaminoethanol

worker: Long-term exposure - systemic and local effects, Inhalation: 1.76 mg/m<sup>3</sup>  
worker: Short-term exposure - systemic effects, Inhalation: 5.28 mg/m<sup>3</sup>  
worker: Short-term exposure - local effects, Inhalation: 13.53 mg/m<sup>3</sup>  
worker: Long-term exposure- systemic effects, dermal: 0.25 mg/kg  
worker: Short-term exposure - systemic effects, dermal: 1.2 mg/kg  
worker: Short-term exposure - local effects, dermal: 100 µg/cm<sup>2</sup>  
consumer: Long-term exposure- systemic effects, Inhalation: 0.43 mg/m<sup>3</sup>  
consumer: Long-term exposure- systemic effects, oral: 0.126 mg/kg

##### 108-65-6: 2-methoxy-1-methylethyl acetate

worker: Long-term exposure- systemic effects, Inhalation: 275 mg/m<sup>3</sup>  
worker: Long-term exposure- systemic effects, dermal: 796 mg/kg  
consumer: Long-term exposure- systemic effects, oral: 36 mg/kg  
consumer: Long-term exposure - systemic and local effects, Inhalation: 33 mg/m<sup>3</sup>  
consumer: Long-term exposure- systemic effects, dermal: 320 mg/kg  
worker: Short-term exposure - local effects, Inhalation: 550 mg/m<sup>3</sup>  
consumer: Short-term exposure - systemic effects, oral: 500 mg/kg

##### 111-76-2: 2-butoxyethanol

worker: Long-term exposure- systemic effects, Inhalation: 98 mg/m<sup>3</sup>, 20 ppm  
worker: Short-term exposure - systemic effects, Inhalation: 1091 mg/m<sup>3</sup>  
worker: Short-term exposure - local effects, Inhalation: 246 mg/m<sup>3</sup>  
consumer: Long-term exposure- systemic effects, oral: 6.3 mg/kg  
consumer: Short-term exposure - systemic effects, oral: 26.7 mg/kg  
consumer: Long-term exposure- systemic effects, Inhalation: 59 mg/m<sup>3</sup>  
consumer: Short-term exposure - systemic effects, Inhalation: 426 mg/m<sup>3</sup>  
consumer: Short-term exposure - local effects, Inhalation: 147 mg/m<sup>3</sup>

##### 126-86-3: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: **\*11-E 820 0,125L BROWN PEARL**

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

worker: Long-term exposure- systemic effects, Inhalation: 1.76 mg/m<sup>3</sup>  
worker: Short-term exposure - systemic effects, Inhalation: 5.28 mg/m<sup>3</sup>  
worker: Long-term exposure- systemic effects, dermal: 0.5 mg/kg  
worker: Short-term exposure - systemic effects, dermal: 1.5 mg/kg  
consumer: Long-term exposure- systemic effects, Inhalation: 0.43 mg/m<sup>3</sup>  
consumer: Short-term exposure - systemic effects, Inhalation: 1.29 mg/m<sup>3</sup>  
consumer: Long-term exposure- systemic effects, dermal: 0.25 mg/kg  
consumer: Short-term exposure - systemic effects, dermal: 0.75 mg/kg  
consumer: Long-term exposure- systemic effects, oral: 0.25 mg/kg  
consumer: Short-term exposure - systemic effects, oral: 0.75 mg/kg

## 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

### Personal protective equipment

Respiratory protection:

Suitable respiratory protection: e.g. half-mask with A1P2 class combination filter When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. Use A1P2 breathing-protection half mask in case of contact with aerosols.

Hand protection:

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.

butyl rubber gloves - material thickness: 0.5 mm

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166), Required when there is a risk of eye contact.

Body protection:

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: \*11-E 820 0,125L BROWN PEARL

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

Anti-static protective clothing, Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

#### General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

#### Environmental exposure controls

For information regarding environmental exposure controls, see Section 6.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Form:	liquid
Colour:	brown
Odour:	specific
pH value:	7.0 - 9.0 (500.00000 g/l)
Melting point:	not determined
onset of boiling:	not determined
Flash point:	> 51 °C
Flammability:	Flammable liquid and vapour.
Lower explosion limit:	36 g/m <sup>3</sup>
Ignition temperature:	> 200.00 °C
Vapour pressure:	(20 °C) not determined
	(50 °C) not determined
	No applicable information available.
Density:	No applicable information available. 1.260 g/cm <sup>3</sup> (20 °C)
Relative vapour density (air):	Heavier than air.
Partitioning coefficient n-octanol/water (log Kow):	not applicable for mixtures
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, kinematic:	691.3 mm <sup>2</sup> /s (20 °C)

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: \*11-E 820 0,125L BROWN PEARL

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

---

Explosion hazard: (40 °C)  
not determined  
not explosive  
Fire promoting properties: not fire-propagating

## 9.2. Other information

Burning rate: The material doesn't meet the criteria (UN Test N.1 (ready specified in paragraph 33.2.4.4 of UN manual of tests and criteria. combustible solids))

Self heating ability: It is not a material capable of spontaneous heating

Miscibility with water: miscible

Flow time: > 100 s (DIN EN ISO 2431; 6 mm)

---

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

### 10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### 10.3. Possibility of hazardous reactions

Vapours may form ignitable mixture with air.

### 10.4. Conditions to avoid

Avoid heat. Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing.

### 10.5. Incompatible materials

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermic reactions.

### 10.6. Hazardous decomposition products

When exposed to high temperatures hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

---

## SECTION 11: Toxicological Information

### 11.1. Information on toxicological effects

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: **\*11-E 820 0,125L BROWN PEARL**

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

---

### Acute toxicity

Assessment of acute toxicity:

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The mixture has been assessed following regulation (EC) No 1272/2008. See sections 2 and 3 for details.

Based on available data, the classification criteria are not met.

### Irritation

Assessment of irritating effects:

The liquid splashed in the eyes may cause irritation and reversible damage. Skin contact causes irritation. May cause severe damage to the eyes.

### Respiratory/Skin sensitization

Assessment of sensitization:

Sensitization after skin contact possible.

### Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

### Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

### Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

### Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: \*11-E 820 0,125L BROWN PEARL

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

---

#### Specific target organ toxicity (single exposure)

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available data, the classification criteria are not met.

#### Aspiration hazard

No aspiration hazard expected.

---

## SECTION 12: Ecological Information

### 12.1. Toxicity

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways. The mixture has been assessed following regulation (EC) No 1272/2008 and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details.

### 12.2. Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O):

Biological degradability of hazardous substances mentioned in section 3:

*Information on: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol*

*Elimination information:*

*< 10 % CO<sub>2</sub> formation relative to the theoretical value (28 d) (OECD 301B; ISO 9439; 92/69/EEC, C.4-C) (aerobic, activated sludge, domestic)*

*< 20 % CO<sub>2</sub> formation relative to the theoretical value (60 d) (ISO DIS 9439) (aerobic, activated sludge)*

*25.4 % DOC reduction (57 d) (OECD Guideline 302 A) (aerobic, activated sludge, domestic)*

*< 10 % (28 d) (OECD Guideline 302 B) (aerobic, activated sludge, domestic)*

*Information on: Naphtha (petroleum), heavy alkylate*

-----

### 12.3. Bioaccumulative potential

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: \*11-E 820 0,125L BROWN PEARL

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

---

Bioaccumulation potential:  
No data available.

#### 12.4. Mobility in soil

Assessment transport between environmental compartments:  
Adsorption in soil: No data available.

#### 12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

#### 12.6. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

---

### SECTION 13: Disposal Considerations

#### 13.1. Waste treatment methods

Do not discharge into drains/surface waters/groundwater.  
Observe national and local legal requirements.

Dispose of the substance/product as special waste in accordance with Directive 2008/98/EC.

Waste key:

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

Contaminated packaging:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

---

### SECTION 14: Transport Information

#### Land transport

ADR

UN number or ID number: UN1263

UN proper shipping name: PAINT

Transport hazard class(es): 3



BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: \*11-E 820 0,125L BROWN PEARL

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

Packing group: III  
Environmental hazards: no  
Special precautions for user: Tunnel code: D/E

#### RID

UN number or ID number: UN1263  
UN proper shipping name: PAINT  
Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no  
Special precautions for user: None known

#### **Inland waterway transport**

##### ADN

UN number or ID number: UN1263  
UN proper shipping name: PAINT  
Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no  
Special precautions for user: None known

#### Transport in inland waterway vessel

Not evaluated

#### **Sea transport**

##### IMDG

UN number or ID number: UN 1263  
UN proper shipping name: PAINT  
Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no  
Special precautions for user: Marine pollutant: NO

#### **Air transport**

IATA/ICAO

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: \*11-E 820 0,125L BROWN PEARL

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

---

UN number or ID number: UN 1263  
UN proper shipping name: PAINT  
Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: No Mark as dangerous for the environment is needed  
Special precautions for user: None known

#### **14.1. UN number or ID number**

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

#### **14.2. UN proper shipping name**

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

#### **14.3. Transport hazard class(es)**

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

#### **14.4. Packing group**

See corresponding entries for "Packing group" for the respective regulations in the tables above.

#### **14.5. Environmental hazards**

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

#### **14.6. Special precautions for user**

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

#### **14.7. Maritime transport in bulk according to IMO instruments**

Maritime transport in bulk is not intended.

#### **Further information**

Not dangerous goods of class 3 in packages up to 450 litres capacity (valid for ADR, ADNR, RID, TDG and USDOT).

---

## **SECTION 15: Regulatory Information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Directive 2010/75/EU of the European Parliament and of the Council of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

VOC content: 36.0 % organic solvents

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: \*11-E 820 0,125L BROWN PEARL

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

VOC content:	37.2 %	calculated
VOC content:	468.5 g/l	calculated

### Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 28, 29, 3, 40, 75

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):  
Listed in above regulation: Flammable liquids, Categories 2 or 3 not covered by P5a and P5b

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:	d
Limit value for maximum VOC content as specified in Annex IIB:	420 g/l
VOC content of the ready-for-use product according to ISO 11890-2:	419 g/l

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

## 15.2. Chemical Safety Assessment

Chemical Safety Assessment not required

---

## SECTION 16: Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity — single exposure
Flam. Liq.	Flammable liquids
Carc.	Carcinogenicity
Asp. Tox.	Aspiration hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic
Acute Tox.	Acute toxicity
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer by inhalation.
H413	May cause long lasting harmful effects to aquatic life.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H302 + H332	Harmful if swallowed or if inhaled

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 17.03.2023

Version: 6.0

Date previous version: 19.07.2022

Previous version: 5.0

Date / First version: 27.10.2020

Product: **\*11-E 820 0,125L BROWN PEARL**

(ID no. 53163387/SDS\_GEN\_GB/EN)

Date of print 18.03.2023

H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H314	Causes severe skin burns and eye damage.
H302 + H312	Harmful if swallowed or in contact with skin
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.  
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

---

Vertical lines in the left hand margin indicate an amendment from the previous version.