



Art.-No.: 6.1140.1850 6.1140.4850
 6.1140.2450
 6.1140.3050
 6.1140.3650

1140

Trillennium Masking Tape

Characteristics

A quality, smooth crepe pressure-sensitive masking tape with good quick stick and holding properties. This product is designed for paint masking requiring clean and easy removal from a variety of surfaces. Can be exposed to oven temperatures up to 121 °C (250 °F) for 30 minutes. Waterproof and IR resistant. Excellent for masking rubber trim and plastic parts.

Application

Automotive, truck, bus and marine paint masking. Recommend warm removal, although can be removed cold.

Technical Data

Backing	Coarse crepe paper
Colour	Dark blue
Adhesive	Rubber / Resin
Adhesion to steel (oz/in of width)	26 (7.1 N/25mm)
Quick stick to kraft (oz/in of width)	5 (1.4 N/25mm)
Quick Stick to steel (oz/in of width)	12 (3.3 N/25mm)
Tensile strength (lbs/in of width)	23 (100 N/25mm)
Elongation (% at break)	8
Thickness (mils)	6.7 (0.17mm)

Storage and Transportation

Store in a clean, dry place. Temperature of 21 °C and 40% to 50% relative humidity are recommended. 12 months shelf life, when stored under suggested storage conditions.