

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerricans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	000000000050675818	Date of first issue: 05.09.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : A-H-440 2,5L 2,5L Steel jerricans

Product code : 000000000050675818

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Spraying hardener

1.3 Details of the supplier of the safety data sheet

Company:

BASF Coatings GmbH
Postfach 6123
48136 Münster
Deutschland

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
United Kingdom

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

1.4 Emergency telephone

International emergency number:

Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3
Acute toxicity, Category 4
Skin sensitization, Category 1
Specific target organ toxicity - single exposure, Category 3, Respiratory system

H226: Flammable liquid and vapor.
H332: Harmful if inhaled.
H317: May cause an allergic skin reaction.
H335: May cause respiratory irritation.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerri-cans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal Word :

Warning

Hazard Statements :

H226	Flammable liquid and vapor.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

Precautionary Statements :

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing mist or vapors.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

HDI-Oligomer(Trimer)
2-butoxyethyl acetate
isophorone diisocyanate (IPDI) polymer
1,6-hexamethylene diisocyanate

Additional Labeling

EUH204 Contains isocyanates. May produce an allergic reaction.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerri-cans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : organic solvent
polyisocyanate

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
HDI-Oligomer(Trimer)	28182-81-2 500-060-2 01-2119485796-17	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 75 - <= 100
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312	>= 5 - < 7
Naphtha (petroleum),hydrotreated light, Kp > 140oC	64742-52-5 265-155-0 649-465-00-7 01-2119471843-32	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 3 - < 5
2-heptanone	110-43-0 203-767-1 606-024-00-3 UK-20-0537843089-5-0000	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332 STOT SE 3; H336 (Central nervous	>= 2.5 - < 3

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerrycans

Version 2.0 Revision Date: 09.11.2024 SDS Number: 0000000000506758 Date of last issue: 13.09.2024
Date of first issue: 05.09.2024
18

isophorone diisocyanate (IPDI) polymer	53880-05-0 500-125-5 01-2119488734-24	system) Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	$\geq 2.5 - < 3$
1,6-hexamethylene diisocyanate	822-06-0 212-485-8 615-011-00-1 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Acute Tox. 4; H302 Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) specific concentration limit Resp. Sens. 1; H334 $\geq 0.5\%$ Skin Sens. 1; H317 $\geq 0.5\%$	< 0.1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : First aid personnel should pay attention to their own safety.
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).
Immediately remove contaminated clothing.
In all cases of doubt, or when symptoms persist, seek medical attention.
Move out of dangerous area.
Never give anything by mouth to an unconscious person.
- If inhaled : If breathed in, move person into fresh air.
If breathing is irregular or stopped, administer artificial respiration.
If symptoms persist, call a physician.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerri-cans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758 18	Date of first issue: 05.09.2024

- | | |
|-------------------------|--|
| In case of skin contact | : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Call a physician immediately. |
| In case of eye contact | : Call a physician immediately.
Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
If easy to do, remove contact lens, if worn. |
| If swallowed | : Rinse mouth with water.
Do not induce vomiting due to aspiration hazard.
Keep at rest.
If symptoms persist, call a physician or Poison Control Center immediately. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|----------|---|
| Symptoms | : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. |
| Risks | : May cause an allergic skin reaction.
Harmful if inhaled.
May cause respiratory irritation. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|---|
| Treatment | : Treat symptomatically.
No known specific antidote. |
|-----------|---|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|--------------------------------|--|
| Suitable extinguishing media | : Water spray jet
Dry powder
Alcohol-resistant foam
Carbon dioxide (CO ₂) |
| Unsuitable extinguishing media | : High volume water jet |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerri-cans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758 18	Date of first issue: 05.09.2024

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Hazardous combustion products : Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : In the event of fire, cool tanks with water spray.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.
For non-emergency personnel:
Use personal protective equipment.
Ensure adequate ventilation, especially in confined areas.
Keep away from sources of ignition.
For emergency responders:
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
Avoid subsoil penetration.
Do not allow uncontrolled discharge of product into the environment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.
Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth.
Place in a suitable container. The contaminated area should

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerri-cans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): ethanol or isopropyl alcohol (50 parts); water (45 parts); concentrated ammonia solution (5 parts). A non-flammable alternative is: sodium carbonate (5 parts); water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
Handle in accordance with good industrial hygiene and safety practice.
Do not breathe vapors or spray mist.
Provide good ventilation of working area (local exhaust ventilation if necessary).
Do not return residues to the storage containers.
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
The workplace should be equipped with an emergency shower and eye-rinsing facility.
Avoid contact with the skin, eyes and clothing.
Protect from moisture.
- Advice on protection against fire and explosion : Open drum carefully as content may be under pressure.
Avoid all sources of ignition: heat, sparks, open flame. The relevant fire protection measures should be noted. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Use explosion-proof equipment. Vapors

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerrycans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Avoid direct sunlight.

Keep in a cool, well-ventilated place. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Exercise caution when opening to allow pressure release. Observe label precautions. Always keep in containers of same material as the original one. Precautions should be taken to minimise exposure to atmospheric humidity or water: carbon dioxide will be formed which in closed containers can result in pressurisation.

Advice on common storage : Keep away from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
HDI-Oligomer(Trimer)	28182-81-2	TWA	0.02 mg/m ³ (NCO)	GB EH40
Further information: Capable of causing occupational asthma.				
		STEL	0.07 mg/m ³	GB EH40

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerri-cans

Version 2.0 Revision Date: 09.11.2024 SDS Number: 0000000000506758 Date of last issue: 13.09.2024
Date of first issue: 05.09.2024
18

			(NCO)	
	Further information: Capable of causing occupational asthma.			
2-butoxyethyl acetate	112-07-2	TWA	20 ppm 133 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm 332 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm 333 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	20 ppm 133 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
2-heptanone	110-43-0	STEL	100 ppm 475 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 237 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 238 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 475 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
1,6-hexamethylene diisocyanate	822-06-0	TWA	0.02 mg/m3 (NCO)	GB EH40
	Further information: Capable of causing occupational asthma.			
		STEL	0.07 mg/m3 (NCO)	GB EH40
	Further information: Capable of causing occupational asthma.			

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerri-cans

Version 2.0 Revision Date: 09.11.2024 SDS Number: 0000000000506758 Date of last issue: 13.09.2024
Date of first issue: 05.09.2024
18

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
HDI-Oligomer(Trimer)	28182-81-2	isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT
1,6-hexamethylene diisocyanate	822-06-0	isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166
Required when there is a risk of eye contact.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Skin and body protection : chemical-resistant disposable coveralls
Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerrycans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

Respiratory protection : Suitable respiratory equipment:
full face mask with AB2P3 class combination filter
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Protective measures : Respiratory protective equipment should be worn by spray booth operatives.
Under cool dry conditions, it is possible for the isocyanate to remain unreacted in the paint film for up to 30 hours after application.
Eye wash fountains and safety showers must be easily accessible.
Avoid contact with the skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.
Do not breathe vapour/spray.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Color	: colorless
Odor	: No data available
pH	: substance/mixture reacts with water
Melting point/range	: not determined
Boiling point/boiling range	: 140 °CMethod: calculated
Flash point	: 46 °C Method: ISO 3679
Upper explosion limit / Upper flammability limit	: not determined
Lower explosion limit / Lower flammability limit	: > 35 g/m3
Vapor pressure	: 6.0000 hPa (20 °C) Method: other (calculated)
	not determined

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerri-cans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

Relative vapor density	:	Heavier than air.
Density	:	1.0979 g/cm ³ (20 °C) Method: calculated
Solubility(ies)	:	
Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity	:	
Viscosity, kinematic	:	not determined 411.6 mm ² /s (23 °C)
Flow time	:	> 60 s at 23 °C Cross section: 6 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids)	:	Flammable liquid and vapour.
Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle size	:	The substance / product is marketed or used in a non solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerrycans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758 18	Date of first issue: 05.09.2024

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.
Heat.
Protect from frost.
Heat, flames and sparks.
Avoid direct contact with water.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.

10.6 Hazardous decomposition products

Nitrogen oxides (NO_x)
Hydrogen cyanide (hydrocyanic acid)
Isocyanates

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 12.34 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerrycans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

2-butoxyethyl acetate:

Acute oral toxicity : LD50 (Rat): 1,880 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 1,500 mg/kg

2-heptanone:

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 16.7 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerrycans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

Aspiration toxicity

Based on available data, the classification criteria are not met.

Product:

No aspiration toxicity classification

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

HDI-Oligomer(Trimer):

Partition coefficient: n-octanol/water : log Pow: 9.81 (25 °C)

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1.51 (25 °C)
pH: 7
Method: OECD Test Guideline 107
GLP: no

2-heptanone:

Partition coefficient: n-octanol/water : log Pow: 2.26 (30 °C)
pH: 7
Method: Regulation (EC) No. 440/2008, Annex, A.8
GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerrycans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: Observe national and local legal requirements. Do not discharge into drains/surface waters/groundwater. Dispose of isocyanate waste in dry containers and never mix together with other wastes (reaction, dangerous pressure build up).
Contaminated packaging	: Packaging that is not properly emptied must be disposed of as the unused product. Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC Residues in empty containers should be neutralised with decontaminant (see section 6).

SECTION 14: Transport information

14.1 UN number

ADN	: UN 1263
ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263
IATA	: UN 1263

14.2 UN proper shipping name

ADN	: PAINT
-----	---------

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerri-cans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT
IATA	:	PAINT

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
ADR	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
Tunnel restriction code	: (D/E)
RID	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
IMDG	
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
IATA (Cargo)	
Packing instruction (cargo aircraft)	: 366
Packing instruction (LQ)	: Y344

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerri-cans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable liquid

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 liters, not goods/merchandise of Class 3

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Conditions of restriction for the following entries should be considered: Number on list 3 xylene (Number on list 3) benzene (Number on list 72, 5, 29, 28)
--	--

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerrycans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH) P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Volatile organic compounds (VOC) content: 165 g/l

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 15.06 %

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

dropped

Limit value for maximum VOC content as specified in Annex IIB:

dropped

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapor.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerrycans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Resp. Sens.	: Respiratory sensitization
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - Interna-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

A-H-440 2,5L 2,5L Steel jerrycans

Version	Revision Date:	SDS Number:	Date of last issue: 13.09.2024
2.0	09.11.2024	0000000000506758	Date of first issue: 05.09.2024
		18	

tional Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : Restricted to professional users.
For multi-pack systems observe material safety data sheets of all components.

Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 4	H332
Skin Sens. 1	H317
STOT SE 3	H335

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN