

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
		GB / EN	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code : Please see section 16 for detailed data

Trade name : MOBIHEL Base MIX

Unique Formula Identifier (UFI) : 4221-G07J-Y000-H682

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : PC9a Coatings and paints, thinners, paint removers

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Helios TBLUS d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383
productsafety@helios.si

1.4 Emergency telephone number

Call 999 for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892 0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
		GB / EN	

Skin sensitisation, Category 1
Reproductive toxicity, Category 2

H317: May cause an allergic skin reaction.
H361: Suspected of damaging fertility or the unborn child.
H336: May cause drowsiness or dizziness.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

n-butyl acetate
butan-1-ol
butyl glycolate
Fatty acids, C14-18 and C16-18-unsatd., maleated
formaldehyde
maleic anhydride

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version
1.0

Revision Date:
05.10.2021

SDS Number:
MAT0GA05_007
GB / EN

Date of last issue: -
Date of first issue: 05.10.2021

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 30 - < 50
butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 3 - < 10
reaction mixture of ethylbenzene, m-xylene and p-xylene	- 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 1 - < 10
butyl glycollate	7397-62-8 230-991-7 01-2119514685-36	Eye Dam. 1; H318 Repr. 2; H361	>= 3 - < 10
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312	>= 1 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version
1.0

Revision Date:
05.10.2021

SDS Number:
MAT0GA05_007
GB / EN

Date of last issue: -
Date of first issue: 05.10.2021

	01-2119475112-47		
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics	- 01-2119471843-32	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	$\geq 1 - < 2,5$
2-methylpropan-1-ol	78-83-1 201-148-0 603-108-00-1 01-2119484609-23	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	$\geq 1 - < 3$
fatty acids, C14-18 and C16-18-unsatd., maleated	85711-46-2 288-306-2 01-2119976378-19	Skin Irrit. 2; H315 Skin Sens. 1; H317	$\geq 0,1 - < 1$
formaldehyde	50-00-0 200-001-8 605-001-00-5 01-2119488953-20	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Muta. 2; H341 Carc. 1B; H350 STOT SE 3; H335 (Respiratory system) specific concentration limit Skin Corr. 1B; H314 $\geq 25\%$ Skin Irrit. 2; H315 $5 - < 25\%$ Eye Irrit. 2; H319 $5 - < 25\%$ STOT SE 3; H335 $\geq 5\%$ Skin Sens. 1; H317 $\geq 0,2\%$	$< 0,1$
maleic anhydride	108-31-6 203-571-6 607-096-00-9 01-2119472428-31	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Inhalation, Respiratory system) EUH071	$\geq 0,001 - < 0,1$

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
GB / EN			

		specific concentration limit Skin Sens. 1A; H317 ≥ 0,001 %	
Substances with a workplace exposure limit :			
(2-Methoxymethylethoxy)propanol	34590-94-8 252-104-2 01-2119450011-60		≥ 1 - < 10

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
GB / EN			

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
		GB / EN	

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version
1.0

Revision Date:
05.10.2021

SDS Number:
MAT0GA05_007
GB / EN

Date of last issue: -
Date of first issue: 05.10.2021

sheet.

Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40
		STEL	200 ppm 966 mg/m ³	GB EH40
		STEL	150 ppm 723 mg/m ³	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m ³	2019/1831/E U
	Further information: Indicative			
butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 220 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
2-butoxyethyl acetate	112-07-2	TWA	20 ppm 133 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version
1.0

Revision Date:
05.10.2021

SDS Number:
MAT0GA05_007
GB / EN

Date of last issue: -
Date of first issue: 05.10.2021

	skin, Indicative			
		STEL	50 ppm 333 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	20 ppm 133 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm 332 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
(2-Methoxymethylethoxy)propanol	34590-94-8	TWA	50 ppm 308 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 308 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m ³	GB EH40
		TWA (Respirable dust)	4 mg/m ³	GB EH40
2-methylpropan-1-ol	78-83-1	TWA	50 ppm 154 mg/m ³	GB EH40
		STEL	75 ppm 231 mg/m ³	GB EH40
formaldehyde	50-00-0	TWA	2 ppm 2,5 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
		STEL	2 ppm 2,5 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
		TWA	0,3 ppm 0,37 mg/m ³	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			
		STEL	0,6 ppm 0,74 mg/m ³	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			
maleic anhydride	108-31-6	TWA	1 mg/m ³	GB EH40
	Further information: Capable of causing occupational asthma.			
		STEL	3 mg/m ³	GB EH40
	Further information: Capable of causing occupational asthma.			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version
1.0

Revision Date:
05.10.2021

SDS Number:
MAT0GA05_007
GB / EN

Date of last issue: -
Date of first issue: 05.10.2021

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	48 mg/m3
	Workers	Inhalation	Long-term local effects	300 mg/m3
	Consumers	Inhalation	Acute systemic effects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	12 mg/m3
	Consumers	Inhalation	Long-term local effects	35,7 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
butan-1-ol	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	310 mg/m3
	Consumers	Inhalation	Long-term systemic effects	55,357 mg/m3
	Consumers	Inhalation	Long-term local effects	155 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1,562 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	77 mg/m3
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
	Consumers	Inhalation	Long-term local effects	65,3 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version
1.0

Revision Date:
05.10.2021

SDS Number:
MAT0GA05_007
GB / EN

Date of last issue: -
Date of first issue: 05.10.2021

	Workers	Inhalation	Acute systemic effects	442 mg/m3
	Workers	Inhalation	Acute local effects	289 mg/m3
	Consumers	Inhalation	Acute systemic effects	260 mg/m3
	Workers	Inhalation	Long-term local effects	221 mg/m3
	Consumers	Inhalation	Long-term systemic effects	14,8 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
butyl glycollate	Workers	Inhalation	Long-term systemic effects	58,8 mg/m3
	Consumers	Inhalation	Long-term systemic effects	17,4 mg/m3
	Consumers	Inhalation	Long-term local effects	17,4 mg/m3
	Consumers	Dermal	Long-term local effects	0,11 mg/cm2
	Consumers	Oral	Long-term systemic effects	4,2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	41,7 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	25 mg/kg bw/day
2-butoxyethyl acetate	Workers	Inhalation	Long-term systemic effects	333 mg/m3
	Consumers	Oral	Long-term systemic effects	86 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	169 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	120 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	102 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	72 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	36 mg/kg bw/day
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics	Workers	Inhalation	Long-term systemic effects	871 mg/m3
	Consumers	Inhalation	Long-term systemic effects	185 mg/m3
	Workers	Dermal	Long-term systemic effects	208 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version
1.0

Revision Date:
05.10.2021

SDS Number:
MAT0GA05_007
GB / EN

Date of last issue: -
Date of first issue: 05.10.2021

	Consumers	Dermal	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	125 mg/kg bw/day
(2-Methoxymethylethoxy)propanol	Workers	Inhalation	Long-term systemic effects	308 mg/m3
	Consumers	Inhalation	Long-term systemic effects	37,2 mg/m3
	Workers	Dermal	Long-term systemic effects	283 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	121 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
Fatty acids, C14-18 and C16-18-unsatd., maleated	Workers	Dermal	Long-term systemic effects	3,33 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	1,67 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1,67 mg/kg bw/day
formaldehyde	Workers	Inhalation	Long-term systemic effects	9 mg/m3
	Consumers	Inhalation	Long-term systemic effects	3,2 mg/m3
	Workers	Dermal	Long-term systemic effects	240 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	102 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	4,1 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Soil	0,0903 mg/kg dry weight (d.w.)
	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l
	Marine sediment	0,0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35,6 mg/l
	Intermittent use/release	0,36 mg/l
butan-1-ol	Soil	0,0166 mg/kg dry weight (d.w.)
	Marine water	0,0082 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version
1.0

Revision Date:
05.10.2021

SDS Number:
MAT0GA05_007
GB / EN

Date of last issue: -
Date of first issue: 05.10.2021

	Fresh water	0,082 mg/l
	Marine sediment	0,0324 mg/kg dry weight (d.w.)
	Fresh water sediment	0,324 mg/kg dry weight (d.w.)
	Sewage treatment plant	2476 mg/l
	Intermittent use/release	2,25 mg/l
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2,31 mg/kg dry weight (d.w.)
	Marine water	0,327 mg/l
	Fresh water	0,327 mg/l
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Intermittent use/release	0,327 mg/l
butyl glycollate	Soil	0,0112 mg/kg dry weight (d.w.)
	Marine water	0,005 mg/l
	Fresh water	0,05 mg/l
	Marine sediment	0,0203 mg/kg dry weight (d.w.)
	Fresh water sediment	0,203 mg/kg dry weight (d.w.)
	Sewage treatment plant	232 mg/l
	Intermittent use/release	0,5 mg/l
2-butoxyethyl acetate	Soil	0,415 mg/kg dry weight (d.w.)
	Marine water	0,0304 mg/l
	Fresh water	0,304 mg/l
	Marine sediment	0,203 mg/kg dry weight (d.w.)
	Fresh water sediment	2,03 mg/kg dry weight (d.w.)
	Sewage treatment plant	90 mg/l
	Intermittent use/release	0,56 mg/l
(2-Methoxymethylethoxy)propanol	Soil	2,74 mg/kg dry weight (d.w.)
	Marine water	1,9 mg/l
	Fresh water	19 mg/l
	Marine sediment	7,02 mg/kg dry weight (d.w.)
	Fresh water sediment	70,2 mg/kg dry weight (d.w.)
	Sewage treatment plant	4168 mg/l
	Intermittent use/release	190 mg/l
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water	0,184 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version
1.0

Revision Date:
05.10.2021

SDS Number:
MAT0GA05_007
GB / EN

Date of last issue: -
Date of first issue: 05.10.2021

	Marine sediment	100 mg/kg dry weight (d.w.)
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,193 mg/l
2-methylpropan-1-ol	Soil	0,0765 mg/kg dry weight (d.w.)
	Marine water	0,04 mg/l
	Fresh water	0,4 mg/l
	Marine sediment	0,156 mg/kg dry weight (d.w.)
	Fresh water sediment	1,56 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Intermittent use/release	11 mg/l
Fatty acids, C14-18 and C16-18-unsatd., maleated	Sewage treatment plant	100 mg/l
formaldehyde	Marine water	0,44 mg/l
	Fresh water	0,44 mg/l
	Marine sediment	2,3 mg/kg dry weight (d.w.)
	Fresh water sediment	2,3 mg/kg dry weight (d.w.)
	Sewage treatment plant	0,19 mg/l
	Intermittent use/release	4,44 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Gloves : | Viton® (> 0,6 mm; < 240 min); DIN EN374 | | PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Equipment should conform to EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
		GB / EN	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: Different colour shades
Odour	: solvent-like
Odour Threshold	: No data available
Melting point/freezing point	: -78,0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	: 118 °C (calculation method (principal components, lowest value))
Flammability	: Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	: 11,3 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	: 1,2 %(V) (calculation method (principal components, highest value))
Flash point	: 26 °C Method: ISO 3679, closed cup
Ignition temperature	: 343 °C (calculation method (principal components, highest value))
Decomposition temperature	
Decomposition temperature	: No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
pH	: Not applicable
Viscosity	
Viscosity, kinematic	: > 20,5 mm ² /s (40 °C)
Flow time	: 80 - 90 s at 20 °C Cross section: 4 mm Method: DIN 53211
Solubility(ies)	
Water solubility	: immiscible, partly soluble
Solubility in other solvents	: Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	: log Pow: 1,81 (calculation method (principal components, highest value))

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
		GB / EN	

Vapour pressure : < 1.100 hPa (calculation method (principal components, highest value))
(50 °C)

Relative density : No data available

Density : 0,915 - 1,145 g/cm³

Relative vapour density : No data available

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Sustains combustion

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

Adequate ventilation is required.

Heating can release vapours which can be ignited.

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
		GB / EN	

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2.000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2.000 mg/kg Method: Calculation method

Components:

n-butyl acetate:

Acute oral toxicity	:	LD50 Oral (Rat): >= 10.760 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): >= 5.000 mg/kg

butan-1-ol:

Acute oral toxicity	:	Assessment: The component/mixture is moderately toxic after single ingestion. LD50 Oral (Rat): > 2.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Test atmosphere: vapour
Acute dermal toxicity	:	LD50 (Rabbit): > 2.000 mg/kg

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity	:	LD50 Oral (Rat): >= 8.700 mg/kg
Acute inhalation toxicity	:	Test atmosphere: vapour Assessment: The component/mixture is moderately toxic after short term inhalation.
Acute dermal toxicity	:	Assessment: The component/mixture is moderately toxic after single contact with skin.

2-butoxyethyl acetate:

Acute oral toxicity	:	Assessment: The component/mixture is moderately toxic after single ingestion. LD50 Oral (Rat): >= 2.400 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): >= 50 mg/l Exposure time: 2 h Test atmosphere: vapour

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
GB / EN			

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

LD50 (Rabbit): ≥ 1.500 mg/kg

2-methylpropan-1-ol:

Acute oral toxicity : LD50 Oral (Rat): ≥ 2.460 mg/kg

Acute dermal toxicity : LD50 (Rabbit): ≥ 3.400 mg/kg

formaldehyde:

Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicity : Test atmosphere: vapour
Assessment: The component/mixture is highly toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.

maleic anhydride:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

(2-Methoxymethylethoxy)propanol:

Acute oral toxicity : Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

butan-1-ol:

Result : irritating

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version
1.0

Revision Date:
05.10.2021

SDS Number:
MAT0GA05_007
GB / EN

Date of last issue: -
Date of first issue: 05.10.2021

2-methylpropan-1-ol:

Result : irritating

Fatty acids, C14-18 and C16-18-unsatd., maleated:

Result : irritating

formaldehyde:

Result : Corrosive after 3 minutes to 1 hour of exposure

maleic anhydride:

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

butan-1-ol:

Result : Corrosive

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

butyl glycollate:

Result : Corrosive

2-methylpropan-1-ol:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version
1.0

Revision Date:
05.10.2021

SDS Number:
MAT0GA05_007
GB / EN

Date of last issue: -
Date of first issue: 05.10.2021

Components:

Fatty acids, C14-18 and C16-18-unsatd., maleated:

Result : Probability or evidence of skin sensitisation in humans

formaldehyde:

Result : Probability or evidence of skin sensitisation in humans

maleic anhydride:

Result : Probability of respiratory sensitisation in humans based on animal testing

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

formaldehyde:

Germ cell mutagenicity- Assessment : In vitro tests showed mutagenic effects

Carcinogenicity

Not classified based on available information.

Components:

formaldehyde:

Carcinogenicity - Assessment : Possible human carcinogen

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

butyl glycollate:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

butan-1-ol:

Assessment : May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
GB / EN			

Assessment : May cause respiratory irritation.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

2-methylpropan-1-ol:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

formaldehyde:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

maleic anhydride:

Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
GB / EN			

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

butan-1-ol:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l
Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1.000 mg/l
Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l
Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 1 - 10 mg/l
Toxicity to microorganisms : EC50 (Bacteria): >= 1 - 100 mg/l

2-butoxyethyl acetate:

Toxicity to fish : LC50 (Fish): >= 31 mg/l
Exposure time: 96 h
Toxicity to daphnia and other : LC50 (Daphnia (water flea)): >= 142,5 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
GB / EN			

aquatic invertebrates Exposure time: 48 h

Toxicity to microorganisms : EC50 (Bacteria): ≥ 2.800 mg/l

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

2-methylpropan-1-ol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

maleic anhydride:

Toxicity to fish : LC50 : 75 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Components:

n-butyl acetate:

Biodegradability : Result: Biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d
pH: 8
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Biodegradability : Readily biodegradable.

Photodegradation : Decomposes rapidly in contact with light.

2-butoxyethyl acetate:

Biodegradability : Result: Biodegradable

2-methylpropan-1-ol:

Biodegradability : Result: Biodegradable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
		GB / EN	

maleic anhydride:

Biodegradability : Result: Biodegradable
Biodegradation: 90 %
Exposure time: 25 d
Method: OECD Test Guideline 301B

Stability in water : Hydrolyses readily.

Photodegradation :

12.3 Bioaccumulative potential

Components:

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1,81

butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 0,785

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25,9
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1,51

2-methylpropan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 0,79

formaldehyde:

Partition coefficient: n-octanol/water : log Pow: 0,35

maleic anhydride:

Bioaccumulation : Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: -2,61 (20 °C)

(2-Methoxymethylethoxy)propanol:

Partition coefficient: n-octanol/water : log Pow: -0,064

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
		GB / EN	

12.4 Mobility in soil

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Distribution among environmental compartments : Koc: 537, log Koc: 2,73
Moderately mobile in soils
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d
Percentage dissipation: 50 % (DT50)

maleic anhydride:

Mobility : Medium: Water
Content: 100 %

: Medium: Soil
Content: 0 %

Distribution among environmental compartments : Koc: 42, log Koc: 1,63

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
		GB / EN	

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 00 00, WASTES FROM THE MANUFACTURE,
FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS
(PAINTS, VARNISHES AND VITREOUS ENAMELS),
ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00, wastes from MFSU and removal of paint and var-
nish
08 01 11*, waste paint and varnish containing organic sol-
vents or other hazardous substances
15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING
CLOTHS, FILTER MATERIALS AND PROTECTIVE
CLOTHING NOT OTHERWISE SPECIFIED
15 01 00, packaging (including separately collected municipal
packaging waste)
15 01 10*, packaging containing residues of or contaminated
by hazardous substances
HP3, Flammable
HP4, Irritant - skin irritation and eye damage
HP10, Toxic for reproduction
HP13, Sensitising

SECTION 14: Transport information

14.1 UN number or ID number

ADN	: UN 1263
ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263
IATA	: UN 1263

14.2 UN proper shipping name

ADN	: PAINT
ADR	: PAINT
RID	: PAINT
IMDG	: PAINT
IATA	: Paint

14.3 Transport hazard class(es)

ADN	: 3
ADR	: 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
		GB / EN	

RID	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADN

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3

ADR

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
Tunnel restriction code	:	(D/E)

RID

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3

IMDG

Packing group	:	III
Labels	:	3
EmS Code	:	F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo aircraft)	:	366
Packing instruction (LQ)	:	Y344
Packing group	:	III
Labels	:	Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft)	:	355
Packing instruction (LQ)	:	Y344
Packing group	:	III
Labels	:	Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous	:	no
---------------------------	---	----

ADR

Environmentally hazardous	:	no
---------------------------	---	----

RID

Environmentally hazardous	:	no
---------------------------	---	----

IMDG

Marine pollutant	:	no
------------------	---	----

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
		GB / EN	

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3 formaldehyde (Number on list 72, 28)
--	---	---

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
---	---	----------------

REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
---	---	----------------

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
---	---	----------------

Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	:	Not applicable
---	---	----------------

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	:	Not applicable
--	---	----------------

Fire Hazard Class	:	Exempt
-------------------	---	--------

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	P5c	FLAMMABLE LIQUIDS
---	-----	-------------------

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226	:	Flammable liquid and vapour.
------	---	------------------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
GB / EN			

H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H311	: Toxic in contact with skin.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H341	: Suspected of causing genetic defects.
H350	: May cause cancer.
H361	: Suspected of damaging fertility or the unborn child.
H372	: Causes damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.
EUH071	: Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Muta.	: Germ cell mutagenicity
Repr.	: Reproductive toxicity
Resp. Sens.	: Respiratory sensitisation
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
		GB / EN	

2000/39/EC / STEL	:	Short term exposure limit
2004/37/EC / STEL	:	Short term exposure limit
2004/37/EC / TWA	:	Long term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
Repr. 2	H361
STOT SE 3	H336

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

Material codes (bulk) for 366923; 366935; 400207; 400262; 401108; 401924; 401951;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MOBIHEL Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05.10.2021	MAT0GA05_007	Date of first issue: 05.10.2021
GB / EN			

which the SDS is valid

401983; 418200; 418201; 418202; 418203; 418204; 418205;
418206; 418207; 418208; 418209; 418210; 418211; 418212;
418213; 418214; 418215; 418216; 418217; 418218; 418219;
418220; 418221; 418222; 418223; 418224; 418225; 418226;
418227; 418228; 418229; 418230; 418231; 418232; 418233;
418234; 418235; 418236; 418237; 418238; 418239; 418241;
418242; 418243; 418244; 418245; 418246; 418247; 418248;
418249; 418250; 418251; 418252; 418253; 418255; 418445;
418446; 418479; 418480; 418481; 418482; 418485; 418486;
418923; 418924; 419220; 419223; 419593; 419844; 419845;
419846; 419847; 419848; 419849; 478654; 478964; 478984;
479010; 479019; 479020; 480909; 481596; 481598;

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.