

## MULTI PLASTIC PUTTY - MPP1 1kg

v.01-09.2014

### Characteristics

Highly elastic multifunctional putty designed especially for application on plastic substrates including polypropylene. Easy application and modelling. It can be used as fill and as fine putty. Provides pore-free, easy to sand coating. Adheres also to metal substrates, including steel, galvanized steel and aluminium, as well as to polyester surfaces.

### Application

The surface must be clean, dry, degreased and matted with abrasives. Thoroughly mix putty by weight with 2-3% of BPO hardener. Apply within 3 - 5 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

**Note:** Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C. Do not apply over wash primers and one component acrylic products.

### Technical data

**VOC content:** 2004/42/II B(b)(250) < 250 g/l

Shelf life: 9 months

Density: 2 – 2,1 g/cm<sup>3</sup>

Colour: dark grey



### Cleaning



### Hardener addition

Putty 100 g

BPO Hardener 2-3 g



### Body filling

3 - 5 min.



### Drying time

20 - 30 min



### Hand sanding / dry

P150 - P320



### Machine sanding / dry

P150 - P320



### Store in cold place