

A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|-----------------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

| 1.1 Product identifier Trade name | : A-U-99 3L 3L Meta | l pail | | |
|---|---------------------|--------|--|--|
| Product code | : 00000000050731 | 702 | | |
| 1.2 Relevant identified uses of the substance or mixture and uses advised against Use of the : Spraying Substance/Mixture Coatings and related products | | | | |
| 1.3 Details of the supplier of the safety data sheetContact address:BASF Coatings GmbHBASF plcPostfach 61234th and 5th Floors, 2 Stockport Exchange48136 MünsterRailway Road, Stockport, SK1 3GGDeutschlandUnited Kingdom | | | | |

Telephone: +44 161 475 3000 E-mail address: product-safety-uk-and-ireland@basf.com



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

| Flammable liquids, Category 3 | H226: Flammable liquid and vapor. |
|--|--|
| Skin sensitization, Category 1 | H317: May cause an allergic skin reaction. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. |
| Long-term (chronic) aquatic hazard, Category 2 | H411: Toxic to aquatic life with long lasting effects. |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

| Hazard pictograms : | | |
|---------------------|------------|--|
| Signal Word : | Warning | |
| Hazard Statements : | H226 | Flammable liquid and vapor. |
| | H317 | May cause an allergic skin reaction. |
| | H336 | May cause drowsiness or dizziness. |
| | H411 | Toxic to aquatic life with long lasting effects. |
| Precautionary : | Preventior | |
| Statements | P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|-----------------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| P261 | Avoid breathing mist or vapors. | | |
|-----------|---|--|--|
| P273 | Avoid release to the environment. | | |
| P280 | Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. | | |
| Response | : | | |
| P370 + P3 | 78 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. | | |
| P391 | Collect spillage. | | |

Hazardous ingredients which must be listed on the label: n-Butyl acetate

Fatty acids C14-18 and C16-18 unsat., maleinated

alkylammonium salt

maleic anhydride

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|-----------------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

| Chemical nature | : | acrylic resin |
|-----------------|---|-----------------|
| | | organic solvent |
| | | fillers |
| | | nitrocellulose |
| | | pigment |
| | | |

Components

| Chemical name | CAS-No. | Classification | Concentratio |
|---------------|------------------------|----------------|--------------|
| | EC-No. | | n (% w/w) |
| | Index-No. | | |
| | Registration number | | |
| | number | | |



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| n-Butyl acetate | 123-86-4 | Flam. Liq. 3; H226 | >= 15 - < 20 |
|-----------------------------|---------------------------------|-----------------------------|----------------|
| | 204-658-1 | STOT SE 3; H336 | |
| | 607-025-00-1 | (Central nervous | |
| | UK-20- 9702550300-0- 0000 | system) | |
| | UK-20- 0537843089-5- 0000 | | |
| | UK-20- 9642318150-0- 0000 | | |
| Hydrocarbons, C9, aromatics | 64742-95-6 | Flam. Liq. 3; H226 | >= 10 - < 12.5 |
| | 265-199-0 | STOT SE 3; H336 | |
| | UK-20- 0537843089-5- | (Central nervous system) | |
| | 0000 | STOT SE 3; H335 | |
| | | (Respiratory | |



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|-----------------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| | | system) | |
|------------------------------------|---------------------------------|--|--------------|
| | | Asp. Tox. 1; H304 | |
| | | Aquatic Chronic 2; H411 | |
| zinc phosphate | 7779-90-0 | Aquatic Acute 1; | >= 5 - < 7 |
| | 231-944-3 | H400 | |
| | 030-011-00-6 | Aquatic Chronic 1; H410 | |
| | UK-20- | | |
| | 9702550300-0- 0000 | M Eactor (Acuto | |
| | UK-20- 0537843089-5- | M-Factor (Acute aquatic toxicity): 1 | |
| | 0000 | M-Factor (Chronic | |
| | UK-20- 9642318150-0- 0000 | aquatic toxicity): 1 | |
| Aluminum dihydrogentriphosphate | 13939-25-8 | Eye Irrit. 2; H319 | >= 2.5 - < 3 |



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| | 237-714-9 | | |
|-------------------------------|------------------|----------------------------|----------------|
| | 01-2119970565-28 | | |
| zinc oxide | 1314-13-2 | Aquatic Acute 1; | >= 0.1 - < 0.2 |
| | 215-222-5 | H400 | |
| | 030-013-00-7 | Aquatic Chronic 1; H410 | |
| | UK-20- | | |
| | 9702550300-0- | | |
| | 0000 | | |
| | UK-20- | | |
| | 0537843089-5- | | |
| | 0000 | | |
| | UK-20- | | |
| | 9642318150-0- | | |
| | 0000 | | |
| Fatty acids C14-18 and C16-18 | 85711-46-2 | Skin Irrit. 2; H315 | >= 0.1 - < 0.2 |
| unsat., maleinated | 288-306-2 | Skin Sens. 1; | |
| | | H317 | |
| | 01-2119976378-19 | | |
| | 1 | l | |



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| alkylammonium salt | 85711-55-3 | Eye Dam. 1; H318 | < 0.1 |
|--------------------|-------------------------|-------------------------|--------------|
| | 288-315-1 | Skin Sens. 1A; | |
| | 01-2119974148-28 | H317 | |
| | | STOT RE 2; H373 | |
| maleic anhydride | 108-31-6 | Acute Tox. 4; | >= 0.001 - < |
| | 203-571-6 | H302 | 0.1 |
| | 607-096-00-9 | Skin Corr. 1B; H314 | |
| | UK-20- 9702550300-0- | Eye Dam. 1; H318 | |
| | 0000 | Resp. Sens. 1; | |
| | UK-20- | H334 | |
| | 0537843089-5- | Skin Sens. 1A; | |
| | 0000 | H317 | |
| | UK-20- | STOT RE 1; H372 | |
| | 9642318150-0- 0000 | (Respiratory system) | |
| | | | |



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|-----------------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| | | specific concentration limit Skin Sens. 1A; H317 >= 0.001 % | |
|-------------------------|-----------------------|--|-------------|
| Substances with a workp | lace exposure limit : | | |
| Kaolin | 1332-58-7 | | >= 7 - < 10 |
| | 310-194-1 | | |
| Barium sulfate | 7727-43-7 | | >= 7 - < 10 |
| | 231-784-4 | | |
| | UK-20- | | |
| | 0537843089-5- | | |
| | 0000 | | |
| | UK-20- | | |
| | 9642318150-0- | | |



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| | 0000 | |
|--------------------|---------------------------------|-------------|
| talc | 14807-96-6 | >= 7 - < 10 |
| | 238-877-9 | |
| | UK-20- 9702550300-0- 0000 | |
| | UK-20- 0537843089-5- 0000 | |
| | | |
| Triiron tetraoxide | 1317-61-9 | >= 3 - < 5 |
| | 215-277-5 | |
| | UK-20- 9702550300-0- 0000 | |
| | UK-20- 0537843089-5- 0000 | |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| UK-20- | | |
|---------------|--|---|
| 9642318150-0- | | |
| 0000 | | |
| | | ł |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures General advice : First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Move out of dangerous area. Never give anything by mouth to an unconscious person. If inhaled If symptoms persist, call a physician. : If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial

12 / 50



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

respiration.

| In case of skin contact | : | If symptoms persist, call a physician. |
|-------------------------|---|---|
| | | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. |
| | | Do NOT use solvents or thinners. |
| _ | | |
| In case of eye contact | : | If symptoms persist, call a physician. |
| | | In case of eye contact, remove contact lens and rinse |
| | | immediately with plenty of water, also under the eyelids, |
| | | for at least 15 minutes. |
| | | |
| If swallowed | : | If symptoms persist, call a physician. |
| | | Do NOT induce vomiting. |
| | | Rinse mouth. |
| | | |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|-----------------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

4.2 Most important symptoms and effects, both acute and delayed

| Symptoms | : | Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. |
|----------|---|--|
| Risks | : | May cause an allergic skin reaction. May cause drowsiness or dizziness. |

4.3 Indication of any immediate medical attention and special treatment needed

| Treatment | : | No known specific antidote. |
|-----------|---|-----------------------------|
| | | Treat symptomatically. |

SECTION 5: Firefighting measures

| 5.1 Extinguishing media | | |
|-------------------------|---|------------------------|
| Suitable extinguishing | : | Water spray jet |
| media | | Dry powder |
| | | Alcohol-resistant foam |
| | | |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

Carbon dioxide (CO2)

| Unsuitable extinguishing | : High volume water jet |
|--------------------------|-------------------------|
| media | |

5.2 Special hazards arising from the substance or mixture

| Specific hazards during fire : | Fire will produce dense black smoke containing |
|--------------------------------|---|
| fighting | hazardous combustion products (see section 10). |

Hazardous combustion : Oxides of phosphorus products

5.3 Advice for firefighters

| Special protective | : | Appropriate breathing apparatus may be required. |
|-----------------------------|---|--|
| equipment for fire-fighters | | |

Further information : In the event of fire, cool tanks with water spray.



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

| Personal precautions | : | Avoid breathing vapours. |
|----------------------|---|--|
| | | Keep away from sources of ignition. |
| | | Advice on product handling can be found in sections 7 and 8 of this safety data sheet. |
| | | For non-emergency personnel: |
| | | For emergency responders: |
| | | Use personal protective equipment. |
| | | Ensure adequate ventilation, especially in confined areas. |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|-----------------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

6.2 Environmental precautions

| Environmental precautions : | Do not allow uncontrolled discharge of product into the environment. |
|-----------------------------|---|
| | Avoid subsoil penetration. |
| | If the product contaminates rivers and lakes or drains inform respective authorities. |

6.3 Methods and material for containment and cleaning up

| Methods for cleaning up : | Ensure | adequate ventilation. |
|---------------------------|--------|-----------------------|
|---------------------------|--------|-----------------------|

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

SECTION 7: Handling and storage

| 7.1 Precautions for safe handling | |
|-----------------------------------|--|
| Advice on safe handling : | Provide good ventilation of working area (local exhaust ventilation if necessary). |
| | Do not return residues to the storage containers. |
| | Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. |
| | When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. |
| | The workplace should be equipped with an emergency shower and eye-rinsing facility. |
| | Avoid contact with the skin, eyes and clothing. |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| | | Handle in accordance with good industrial hygiene and safety practice. |
|--|---|---|
| | | Do not breathe vapors or spray mist. |
| Advice on protection against fire and explosion | : | Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. |
| Hygiene measures | : | Remove contaminated clothing immediately and dispose of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs. |

7.2 Conditions for safe storage, including any incompatibilities

Further information on: Keep away from heat. Avoid direct sunlight. Close
containers carefully once opened and store them



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|-----------------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| storage conditions | upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place. |
|--|---|
| Advice on common storage : | Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. |
| Recommended storage : temperature | 5.00 - 35.00 °C |
| 7.3 Specific end use(s) Specific use(s) : | Please refer to the technical leaflet for further information. |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|-----------------|---------------------------------|-------------------------------------|----------------------|------------------|
| n-Butyl acetate | 123-86-4 | TWA | 150 ppm 724 mg/m3 | GB EH40 |
| | | STEL | 200 ppm 966 mg/m3 | GB EH40 |
| | | STEL | 150 ppm 723 mg/m3 | 2019/1831/ EU |
| | Further information: Indicative | | | |
| | | TWA | 50 ppm 241 mg/m3 | 2019/1831/ EU |
| | Further information: Indicative | | | |



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|-----------------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| Kaolin | 1332-58-7 | TWA (Respirable dust) | 2 mg/m3 | GB EH40 |
|--------------------|---------------|-----------------------------|-------------------|------------|
| | | TWA (Respirable dust) | 0.1 mg/m3 | 2004/37/EC |
| | Further infor | mation: Carcinoge | ns or mutagens | |
| Barium sulfate | 7727-43-7 | TWA (inhalable dust) | 10 mg/m3 | GB EH40 |
| | | TWA (Respirable dust) | 4 mg/m3 | GB EH40 |
| talc | 14807-96-6 | TWA (Respirable dust) | 1 mg/m3 | GB EH40 |
| Triiron tetraoxide | 1317-61-9 | TWA (Fumes) | 5 mg/m3 (Iron) | GB EH40 |
| | | STEL (Fumes) | 10 mg/m3 | GB EH40 |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| | | | (Iron) | | |
|------------------|--|------|---------|---------|--|
| maleic anhydride | 108-31-6 | TWA | 1 mg/m3 | GB EH40 | |
| | Further information: Capable of causing occupational asthma. | | | | |
| | | STEL | 3 mg/m3 | GB EH40 | |
| | Further information: Capable of causing occupational asthma. | | | | |

8.2 Exposure controls

| Engineering measures Ensure adequate ventilation. | | |
|--|----|---|
| Personal protective equipme | nt | |
| Eye/face protection | : | Safety glasses with side-shields conforming to EN166 |
| | | Required when there is a risk of eye contact. |
| Hand protection | | |
| Remarks | : | Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on |



A-U-99 3L 3L Metal pail

Version Revision Date: 3.0 20.02.2025

te: SDS Number: 000000000050731 702 Date of last issue: 03.01.2025 Date of first issue: 17.10.2023

information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for shortterm contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

synthetic fibres.

| Respiratory protection | : | Suitable respiratory equipment: |
|------------------------|---|---|
| | | half-mask with A1P2 class combination filter |
| | | When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. |
| | | In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. |
| Protective measures | : | Do not breathe vapour/spray. |
| | | Eye wash fountains and safety showers must be easily accessible. |
| | | If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. |
| | | Avoid contact with the skin, eyes and clothing. |
| | | Handle in accordance with good industrial hygiene and safety practice. |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

SECTION 9: Physical and chemical properties

| 9.1 | 9.1 Information on basic physical and chemical properties | | | | | |
|-----|---|---|---|--|--|--|
| | Appearance | : | liquid | | | |
| | Color | : | black | | | |
| | Odor | : | of acetate | | | |
| | рН | : | substance/mixture is non-soluble (in water) | | | |
| | Melting point/ range | : | not determined | | | |
| | Boiling point/boiling range | : | 129 - 139 °Cnot determined | | | |
| | Flash point | : | 30 °C Method: ISO 3679 | | | |
| | Upper explosion limit / | : | not determined | | | |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

Upper flammability limit

| Lower explosion limit / | : | > 35.0 g/m3 |
|--------------------------|---|-------------|
| Lower flammability limit | | |

Vapor pressure : 9.0000 hPa (20 °C)

45.0000 hPa (50 °C)

Relative vapor density : Heavier than air.

Density : 1.454 g/cm3 (20 °C)

Solubility(ies) Water solubility : not determined



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| Partition coefficient: n- octanol/water | : | not applicable for mixtures |
|--|---|---|
| Autoignition temperature | : | > 200 °C |
| Decomposition temperature | : | No decomposition if stored and handled as prescribed/indicated. |
| Viscosity Viscosity, kinematic | : | 411.6 mm2/s (23 °C) |
| | | 398.300 mm2/s (40 °C) |
| Flow time | : | > 60 s at 23 °C |
| | | Cross section: 6 mm |
| | | Method: ISO 2431 |



| Version 3.0 | n Revision Date: 20.02.2025 | SDS Number: 000000000050731 702 | Date of last issue: 03.01.2025 Date of first issue: 17.10.2023 |
|----------------|--|---------------------------------------|---|
| | | | |
| Ex | plosive properties | : Not explosive | |
| 0> | kidizing properties | : The substance | or mixture is not classified as oxidizing. |
| | er information ammability (liquids) | : Flammable liqu | uid and vapour. |
| Se | If-heating substances | : The substance | or mixture is not classified as self heating. |
| М | etal corrosion rate | : Not corrosive t | o metals. |
| Ра | rticle size | : The substance solid or granula | / product is marketed or used in a non ar form. |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight. Protect from frost. Heat, flames and sparks. Heat.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified due to lack of data.

Components:

maleic anhydride:

Acute oral toxicity : LD50 (Rat): 1,090 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Components:

n-Butyl acetate:

Result

: Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified due to lack of data.



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified due to lack of data.

Aspiration toxicity Not classified due to lack of data.

SECTION 12: Ecological information

12.1 Toxicity

Components:

zinc phosphate:

M-Factor (Acute aquatic : 1



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

toxicity)

M-Factor (Chronic aquatic : 1 toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

n-Butyl acetate:

Partition coefficient: n- : Pow: 200 (25 °C) octanol/water

log Pow: 2.3 (25 °C)

pH: 7

Method: OECD Test Guideline 117

GLP: yes

Hydrocarbons, C9, aromatics:

Partition coefficient: n- : log Pow: 3.17



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

octanol/water GLP: no

Fatty acids C14-18 and C16-18 unsat., maleinated:

| Partition coefficient: n- | : | log Pow: > 4 (23 °C) |
|---------------------------|---|----------------------|
| octanol/water | | GLP: yes |

alkylammonium salt:

| Partition coefficient: n- | : | log Pow: <= 2.6 (25 °C) |
|---------------------------|---|---------------------------------|
| octanol/water | | pH: 7 |
| | | Method: OECD Test Guideline 117 |
| | | GLP: yes |

maleic anhydride:Partition coefficient: n-:log Pow: -2.61 (19.8 °C)octanol/water

GLP: yes



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|-----------------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| Barium sulfate: | | |
|---------------------------|---|---------------|
| Partition coefficient: n- | : | Pow: 4.26 |
| octanol/water | | log Pow: 0.63 |

| talc: | |
|---------------------------|-------------------------|
| Partition coefficient: n- | : log Pow: -9.4 (25 °C) |
| octanol/water | pH: 7 |

GLP: no

| Triiron tetraoxide: | |
|---------------------------|---------------------------|
| Partition coefficient: n- | : Remarks: Not applicable |
| octanol/water | |

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

| Assessment | : | This substance/mixture contains no components |
|------------|---|---|
| | | considered to be either persistent, bioaccumulative and |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|-----------------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

| Product: | | |
|----------------------|---|--|
| Endocrine disrupting | : | This substance/mixture does not contain components |
| potential | | considered to have endocrine disrupting properties for |
| | | environment according to UK REACH Article 57(f). |

SECTION 13: Disposal considerations

| 13.1 Waste treatment methods | | |
|------------------------------|---|---|
| Product | : | Do not discharge into drains/surface waters/groundwater. |
| | | Observe national and local legal requirements. |
| Contaminated packaging | : | Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC Packaging that is not properly emptied must be disposed |
| | | |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

of as the unused product.

| SECTION 14: Transport information | | | |
|-----------------------------------|-----------|--|--|
| 14.1 UN number | | | |
| ADN | : UN 1263 | | |
| ADR | : UN 1263 | | |
| RID | : UN 1263 | | |
| IMDG | : UN 1263 | | |
| ΙΑΤΑ | : UN 1263 | | |
| 14.2 UN proper shipping name | | | |
| ADN | : PAINT | | |
| ADR | : PAINT | | |
| RID | : PAINT | | |
| | | | |



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| | IMDG | : | PAINT | |
|------|------------------------------|---|------------------|------------------|
| | | | (ZINC PHOSPHATE, | SOLVENT NAPHTHA) |
| | ΙΑΤΑ | : | PAINT | |
| 14.: | 3 Transport hazard class(es) | | | |
| | | | Class | Subsidiary risks |
| | ADN | : | 3 | |
| | ADR | : | 3 | |
| | RID | : | 3 | |
| | IMDG | : | 3 | |
| | ΙΑΤΑ | : | 3 | |
| 14.4 | 4 Packing group | | | |
| | ADN | | | |
| | Packing group | : | 111 | |



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| Classification Code | : | F1 |
|---------------------------------|---|-------|
| Hazard Identification Number | : | 30 |
| Labels | : | 3 |
| ADR | | |
| Packing group | : | III |
| Classification Code | : | F1 |
| Hazard Identification Number | : | 30 |
| Labels | : | 3 |
| Tunnel restriction code | : | (D/E) |
| RID | | |
| Packing group | : | III |
| Classification Code | : | F1 |
| Hazard Identification Number | : | 30 |



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| Labels | : | 3 |
|---|---|-------------------|
| IMDG | | |
| Packing group | : | III |
| Labels | : | 3 |
| EmS Code | : | F-E, <u>S-E</u> |
| IATA (Cargo) | | |
| Packing instruction (cargo aircraft) | : | 366 |
| Packing instruction (LQ) | : | Y344 |
| Packing group | : | Ш |
| Labels | : | Flammable Liquids |
| IATA (Passenger) | | |
| Packing instruction (passenger aircraft) | : | 355 |
| Packing instruction (LQ) | : | Y344 |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| Packing group | : | Ш |
|---------------|---|------------------|
| Labels | : | Flammable liquid |

14.5 Environmental hazards

ADN

| Environmentally | : | yes |
|-----------------|---|-----|
| hazardous | | |

ADR

| Environmentally | : | yes |
|-----------------|---|-----|
| hazardous | | |

RID

| Environmentally | : | yes |
|-----------------|---|-----|
| hazardous | | |

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|-----------------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)

: Conditions of restriction for the following entries should be considered:

Number on list 72, 3, 20

Number on list 3



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| | | | Number on list 30, 20 |
|--|----------|------|-----------------------|
| | | | |
| UK REACH Candidate list of substances of ve concern (SVHC) for Authorisation | ery high | : | Not applicable |
| The Persistent Organic Pollutants Regulation (retained Regulation (EU) 2019/1021 as amo for Great Britain) | | : | Not applicable |
| Regulation (EC) on substances that deplete to ozone layer | the | : | Not applicable |
| UK REACH List of substances subject to authorisation (Annex XIV) | | : | Not applicable |
| Control of Major Accident Hazards Regulations 2015 (COMAH) | E2 | ENV | IRONMENTAL HAZARDS |
| | P5c | FLAN | MMABLE LIQUIDS |
| | 34 | Petr | oleum products: (a) |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

| Volatile organic compounds | : Volatile organic compounds (VOC) content: 380 g/l |
|-------------------------------|--|
| | Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) |
| | Volatile organic compounds (VOC) content: 29.2 % |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|-----------------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:cSubcategory as indicated in Annex IIB:cLimit value for maximum VOC content as specified in Annex IIB:540 g/lVOC content of the ready-for-use product according to ISO 11890-2:535 g/l

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements

H226

: Flammable liquid and vapor.



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| H302 | : | Harmful if swallowed. |
|------|---|--|
| H304 | : | May be fatal if swallowed and enters airways. |
| H314 | : | Causes severe skin burns and eye damage. |
| H315 | : | Causes skin irritation. |
| H317 | : | May cause an allergic skin reaction. |
| H318 | : | Causes serious eye damage. |
| H319 | : | Causes serious eye irritation. |
| H334 | : | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | : | May cause respiratory irritation. |
| H336 | : | May cause drowsiness or dizziness. |
| H372 | : | Causes damage to organs through prolonged or repeated exposure if inhaled. |
| H373 | : | May cause damage to organs through prolonged or repeated exposure. |
| H400 | : | Very toxic to aquatic life. |



| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| H410 | : | Very toxic to aquatic life with long lasting effects. |
|---------------------------------|-----|---|
| H411 | : | Toxic to aquatic life with long lasting effects. |
| Full text of other abbreviation | ons | |
| Acute Tox. | : | Acute toxicity |
| Aquatic Acute | : | Short-term (acute) aquatic hazard |
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard |
| Asp. Tox. | : | Aspiration hazard |
| Eye Dam. | : | Serious eye damage |
| Eye Irrit. | : | Eye irritation |
| Flam. Liq. | : | Flammable liquids |
| Resp. Sens. | : | Respiratory sensitization |
| Skin Corr. | : | Skin corrosion |
| Skin Irrit. | : | Skin irritation |
| Skin Sens. | : | Skin sensitization |
| STOT RE | : | Specific target organ toxicity - repeated exposure |



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

| STOT SE | : | Specific target organ toxicity - single exposure |
|---------------------|---|---|
| 2004/37/EC | : | Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work |
| 2019/1831/EU | : | Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values |
| GB EH40 | : | UK. EH40 WEL - Workplace Exposure Limits |
| 2004/37/EC / TWA | : | Long term exposure limit |
| 2019/1831/EU / TWA | : | Limit Value - eight hours |
| 2019/1831/EU / STEL | : | Short term exposure limit |
| GB EH40 / TWA | : | Long-term exposure limit (8-hour TWA reference period) |
| GB EH40 / STEL | : | Short-term exposure limit (15-minute reference period) |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very **Bioaccumulative**

Further information

Other information

: For multi-pack systems observe material safety data sheets of all components.



A-U-99 3L 3L Metal pail

| Version | Revision Date: | SDS Number: | Date of last issue: 03.01.2025 |
|---------|----------------|-----------------------|---------------------------------|
| 3.0 | 20.02.2025 | 00000000050731 702 | Date of first issue: 17.10.2023 |

Restricted to professional users.

| Classification of the mix | Classification procedure: | |
|---------------------------|---------------------------|-------------------------------------|
| Flam. Liq. 3 | H226 | Based on product data or assessment |
| Skin Sens. 1 | H317 | Calculation method |
| STOT SE 3 | H336 | Calculation method |
| Aquatic Chronic 2 | H411 | Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN