Safety Data Sheet HYDROFAN BLUE BLACK

Safety Data Sheet dated 06/12/2023 version 4



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: HYDROFAN BLUE BLACK

Trade code: LNHF0186

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Coatings and paints, thinners, paint removers

Mono compound enamel - finish coat

Water pigmented dispersion

Professional uses

Uses advised against: N.A.

1.3. Details of the supplier of the safety data sheet

Company: Lechler SpA - Via Cecilio, 17 - 22100 Como - CO - Italy

Telephone: +39031586111 First Email: safety@lechler.eu

1.4. Emergency telephone number

UNITED KINGDOM: Emergency Number 0044 1606738600 - This telephone number is available during office hours only (8.45-16.45).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Aquatic Chronic 3 Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/ container to an approved waste disposal plant.

Special Provisions:

EUH208 Contains 2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

EUH208 Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1). May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

Results of PBT and vPvB assessment Not a PBT, vPvB substance as per the criteria of the REACH Regulation. Endocrine disrupting properties-Toxicity The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Endocrine disrupting properties-Ecotoxicity The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Date 04/09/2024 Production Name HYDROFAN BLUE BLACK Page n. 1 of 14

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: HYDROFAN BLUE BLACK

Hazardous components within the meaning of the CLP regulation and related classification:

	Qty Name Ident. Numb. Classification Registration Number				
Qty	Name		Classification	Registration Number	
≥5 - ≤/ %	2-butoxyethanol; ethylene glycol monobutyl ether	CAS:111-76-2 EC:203-905-0 Index:603-014- 00-0	Acute Tox. 3, H331 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319	01-21194/5108-36	
			Acute Toxicity Estimate: ATE - Oral: 1200mg/kg bw ATE - Inhalation (Vapours): 3mg/l		
≥1 - ≤2.5 %	Carbon black	CAS:1333-86-4 EC:215-609-9	Not classified as hazardous	01-2119384822-32	
≥0.5 - ≤1 %	Polymer with quaternized ammonium groups	CAS:1431957- 88-8	Aquatic Chronic 1, H410; Aquatic Acute 1, H400, M-Acute:1, M-Chronic:1		
≥0.1 - ≤0.25 %	2-dimethylaminoethanol	CAS:108-01-0 EC:203-542-8 Index:603-047- 00-0	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 3, H331 Acute Tox. 4, H312 Skin Corr. 1B, H314 STOT SE 3, H335	01-2119492298-24	
			Specific Concentration Limits: C ≥ 5%: STOT SE 3 H335		
≥0.1 - ≤0.25 %	triethylamine	CAS:121-44-8 EC:204-469-4 Index:612-004- 00-5	Flam. Liq. 2, H225 Acute Tox. 4, H302 Acute Tox. 3, H331 Acute Tox. 3, H311 Skin Corr. 1A, H314 STOT SE 3, H335	01-2119475467-26	
			Specific Concentration Limits: $C \ge 1\%$: STOT SE 3 H335		
≥0.1 - ≤0.25 %	(2-methoxymethylethoxy)propanol	CAS:34590-94-8 EC:252-104-2	Substance with a Union workplace exposure limit.	01-2119450011-60	
< 0,1 %	silicon dioxide	CAS:7631-86-9 EC:231-545-4	Substance with a Union workplace exposure limit.	01-2119379499-16	
< 0,1 %	1-methoxy-2-propanol	CAS:107-98-2 EC:203-539-1 Index:603-064- 00-3	Flam. Liq. 3, H226; STOT SE 3, H336	01-2119457435-35	
< 0,1 %	2-methylisothiazol-3(2H)-one	CAS:2682-20-4 EC:220-239-6 Index:613-326- 00-9	Acute Tox. 3, H301 Acute Tox. 2, H330 Acute Tox. 3, H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410, M-Chronic:1, M-Acute:10, EUH071		
			Specific Concentration Limits: $C \ge 0,0015\%$: Skin Sens. 1A H317		
< 0,1 %	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)		Acute Tox. 3, H301 Acute Tox. 2, H330 Acute Tox. 2, H310 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410, M-Chronic:100, M-Acute:100, EUH071		
			Specific Concentration Limits: $C \ge 0.6\%$: Skin Corr. 1C H314 $0.06\% \le C < 0.6\%$: Skin Irrit. 2		

Date 04/09/2024 Production Name HYDROFAN BLUE BLACK Page n. 2 of 14

H315

 $0.06\% \le C < 0.6\%$: Eye Irrit. 2

H319

 $C \ge 0,0015\%$: Skin Sens. 1A H317 $C \ge 0,6\%$: Eye Dam. 1 H318

Substances in nanoform:

Carbon black CAS:1333-86-4 Particle size distribution: D10: >= 18 nm <= 61 nm

EC:215-609-9

D50: >= 36 nm <= 101 nm D90: >= 66 nm <= 173 nm (Measurement technique: STEM)

Shape and aspect ratio: Spheres, (:1): < 3 (Measurement

technique: TEM)

Crystallinity: Amorphous: = 100% -

(Measurement technique: X-ray

Diffraction (XRD))

Surface Treatment - Agent: (No)

Specific surface area: >= 21m2/g <= 1200m2/g -

(Measurement technique: Brunaurer, Emmett and Teller (BET) method using Nitrogen)

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

N.A.

4.3. Indication of any immediate medical attention and special treatment needed

N.A.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Date 04/09/2024 Production Name HYDROFAN BLUE BLACK Page n. 3 of 14

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OFL)

Community Occupational Exposure Limits (OEL)			
	OEL Type	Country	Occupational Exposure Limit
2-butoxyethanol; ethylene glycol monobutyl ether CAS: 111-76-2	EU		Long Term: 98 mg/m3 - 20 ppm; Short Term: 246 mg/m3 - 50 ppm Behaviour Indicative 2000/39/EC
	EU		Identifies the possibility of significant uptake through the skin
	EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 25 ppm; Short Term: 50 ppm Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to
Carbon black CAS: 1333-86-4	EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 3,5 mg/m3; Short Term: 7 mg/m3
	ACGIH		Long Term: 3 mg/m3 I, A3 - Bronchitis
2-dimethylaminoethanol CAS: 108-01-0	EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 7,4 mg/m3 - 2 ppm; Short Term: 22 mg/m3 - 6 ppm
triethylamine CAS: 121-44-8	ACGIH		Long Term: 0,5 ppm; Short Term: 1 ppm Skin, A4 - Visual impair, URT irr

Date 04/09/2024 Production Name HYDROFAN BLUE BLACK Page n. 4 of 14

EH40 Long Term: 8 mg/m3 - 2 ppm; Short Term: 17 mg/m3 - 4 ppm UNITED

KINGDOM OF Can be absorbed through the skin. The assigned substances are those for which there

GREAT are concerns that dermal absorption will lead to

BRITAIN AND NORTHERN IRELAND

Long Term: 8,4 mg/m3 - 2 ppm; Short Term: 12,6 mg/m3 - 3 ppm EU

Behaviour Indicative

2000/39/EC

EU Identifies the possibility of significant uptake through the skin

Long Term: 308 mg/m3 - 50 ppm (2-ΕU methoxymethylethoxy)

Behaviour Indicative

2000/39/EC

EU Identifies the possibility of significant uptake through the skin

EH40 UNITED Long Term: 308 mg/m3 - 50 ppm

KINGDOM OF Where no specific short-term exposure limit is listed, a figure three times the long-term

exposure limit should be used. **GREAT**

BRITAIN AND NORTHERN IRELAND

ACGIH Long Term: 50 ppm

Liver & CNS eff

silicon dioxide FU Long Term: 0,1 mg/m3 CAS: 7631-86-9

2004/37/EC

FU Carcinogens or mutagens

EU Respirable dust **EH40** UNITED

Long Term: 6 mg/m3 KINGDOM OF The COSHH definition of a substance hazardous to health includes dust of any kind

GREAT when present at a concentration in air equal to or

BRITAIN AND NORTHERN **IRELAND**

EH40 UNITED Long Term: 2,4 mg/m3

KINGDOM OF Where no specific short-term exposure limit is listed, a figure three times the long-term

GREAT exposure limit should be used.

BRITAIN AND NORTHERN IRELAND

1-methoxy-2-propanol EU

CAS: 107-98-2

propanol

CAS: 34590-94-8

Long Term: 375 mg/m3 - 100 ppm; Short Term: 568 mg/m3 - 150 ppm

Behaviour Indicative

2000/39/EC

Identifies the possibility of significant uptake through the skin FU

Long Term: 375 mg/m3 - 100 ppm; Short Term: 560 mg/m3 - 150 ppm **EH40** UNITED

KINGDOM OF Can be absorbed through the skin. The assigned substances are those for which there

GREAT are concerns that dermal absorption will lead to

BRITAIN AND NORTHERN **IRELAND**

ACGIH Long Term: 50 ppm; Short Term: 100 ppm

A4 - Eye and URT irr

Biological limit values

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: End of turn 2-butoxvethanol:

ethylene glycol monobutyl Value: 200 mg/g Creatinine; Medium: Urine

Remark: Maximum allowable occupational exposure limits in the workplace - Table 3. Adopted Biological ether

CAS: 111-76-2 Exposu

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: End of turn; End of working week

Value: 200 mg/g Creatinine; Medium: Urine

Remark: Czech Republic. Biological Exposure Indices

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: End of turn; End of working week

Value: 17 mmol/mmol creatinine; Medium: Urine Remark: Czech Republic. Biological Exposure Indices

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: Immediately after exposure or after

Page n. 5 of 04/09/2024 **Production Name** HYDROFAN BLUE BLACK Date

working hours

Value: 150 mg/g Creatinine; Medium: Urine Remark: TRGS 903 - Biological limit values

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: In case of long-term exposure: after more

than one shift

Value: 100 mg/L; Medium: Urine

Remark: TRGS 903 - Biological limit values

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: End of turn

Value: 200 mg/g Creatinine; Medium: Urine

Remark: Official Mexican Norm NOM-047-SSA1-2011, Environmental Health - Biological exposure indices

for work

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: End of turn

Value: 200 mg/g Creatinine; Medium: Urine

Remark: Portuguese Norm 1796 - Biological Exposure Indices

Biological Indicator: methoxy acetic acid; Sampling Period: during long-term exposure: at the end of the

work shift after several consecutive workdays Value: 150 mg/g Creatinine; Medium: Urine

Remark: Slovenia. BAT-values

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: End of workday

Value: 200 mg/g Creatinine; Medium: Urine

Remark: Occupational Exposure Limits for Chemical Agents in Spain - Biological Exposure Values

Biological Indicator: 2-butoxy acetic acid; Sampling Period: Immediately after exposure or after working

hours

Value: 150 mg/g Creatinine; Medium: Urine Remark: Svizzera, Lista di valori BAT

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: After shift

Value: 240 Millimoles per mole Creatinine; Medium: Urine Remark: UK. Biological monitoring guidance values

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: End of turn

Value: 200 mg/g Creatinine; Medium: Urine

Remark: ACGIH - Indicatori di Esposizione Biologica (BEI)

Biological Indicator: Butoxyacetic acid (BAA); Sampling Period: End of workday

Value: 200 mg/g Creatinine; Medium: Urine Remark: VE.Biological Exposure Limits

Sampling Period: In case of long-term exposure: after more than one shift

Sampling Period: End of turn

Sampling Period: In case of long-term exposure: after more than one shift

1-methoxy-2-propanol

CAS: 107-98-2

Biological Indicator: 1-Methoxypropan-2-ol; Sampling Period: Immediately after exposure or after working

Value: 15 mg/L; Medium: Urine Remark: TRGS 903 - Biological limit values

Biological Indicator: 1-methoyxypropane-2-ol; Sampling Period: End of turn

Value: 15 mg/L; Medium: Urine Remark: Slovenia. BAT-values

Biological Indicator: 1-methoxypropanol-2; Sampling Period: Immediately after exposure or after working

hours

Value: 2219 micromol per litre; Medium: Urine

Remark: Svizzera. Lista di valori BAT

Biological Indicator: 1-methoxypropanol-2; Sampling Period: Immediately after exposure or after working

hours

Value: 20 mg/L; Medium: Urine Remark: Svizzera. Lista di valori BAT

Predicted No Effect Concentration (PNEC) values

2-butoxyethanol; Exposure Route: Fresh Water; PNEC Limit: 8,8 mg/l

ethylene glycol monobutyl

ether

CAS: 111-76-2

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 26,4 mg/l

Exposure Route: Marine water; PNEC Limit: 0,88 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 34,6 mg/kg dry weight (d.w.) Exposure Route: Marine water sediments; PNEC Limit: 3,46 mg/kg dry weight (d.w.)

Page n. 6 of 04/09/2024 HYDROFAN BLUE BLACK Date Production Name

Exposure Route: Soil; PNEC Limit: 2,33 mg/kg dry weight (d.w.)

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 436 mg/l

triethylamine CAS: 121-44-8 Exposure Route: Fresh Water; PNEC Limit: 0,064 mg/l

Exposure Route: Marine water; PNEC Limit: 0,006 mg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0,064 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 0,199 mg/kg

Exposure Route: Soil; PNEC Limit: 2,361 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l

Exposure Route: Fresh Water; PNEC Limit: 19 mg/l

methoxymethylethoxy)

propanol

(2-

CAS: 34590-94-8

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 190 mg/l

Exposure Route: Marine water; PNEC Limit: 1,9 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 70,2 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 7,02 mg/kg

Exposure Route: Soil; PNEC Limit: 2,74 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 4168 mg/l

Derived No Effect Level (DNEL) values

2-butoxyethanol; Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects

ethylene glycol monobutyl Consumer: 147 mg/m3

ether

CAS: 111-76-2

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects

Consumer: 426 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects

Consumer: 26,7 mg/kg dry weight (d.w.)

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Consumer: 59 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

Consumer: 6,3 mg/kg dry weight (d.w.)

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects

Worker Professional: 246 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects

Worker Professional: 1091 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Professional: 98 mg/m3

triethylamine CAS: 121-44-8

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects

Worker Professional: 12,6 mg/m3

Exposure Route: Human Inhalation: Exposure Frequency: Short Term (acute)

Worker Professional: 12,6 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Worker Professional: 12,1 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Professional: 8,4 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects

Worker Professional: 8,4 mg/m3

(2methoxymethylethoxy)

propanol CAS: 34590-94-8 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Consumer: 37,2 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Exposure Route: Oral; Exposure Frequency: Long Term, systemic effects

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Professional: 308 mg/m3

Page n. 7 of 04/09/2024 HYDROFAN BLUE BLACK Date Production Name

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Not needed for normal use.

Respiratory protection:

N.A.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State: Liquid

Colour: Black Odour: N.A. pH: Not Relevant

Kinematic viscosity: > 20,5 mm2/sec (40 °C)

Melting point / freezing point: N.A.
Initial boiling point and boiling range: N.A.

Flash point: > 93°C

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.
Vapour pressure: N.A.
Relative density: 1.01 g/cm3
Solubility in water: N.A.
Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Flammability: N.A.

Kinematic viscosity m2/s (40°C) > 20,5 mm2/sec (40 °C)

Viscosity: = 59.00 s - Method: ISO/DIN 2431 84 - Section: 6.00 mm

Particle characteristics:

Particle size: N.A.

Nanoforms: See Nanoform information in Section 3.

9.2. Other information

Evaporation rate: N.A. Miscibility: N.A. Conductivity: N.A.

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

Date 04/09/2024 Production Name HYDROFAN BLUE BLACK Page n. 8 of 14

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 **Toxicological Information of the Preparation**

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

ATEmix - Oral: 21806.6 mg/kg bw ATEmix - Dermal: 342167 mg/kg bw

ATEmix - Inhalation (Vapours): 275.774 mg/l

b) skin corrosion/irritation Not classified

Based on available data, the classification criteria are not met

c) serious eye damage/irritation Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

Not classified j) aspiration hazard

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

2-butoxyethanol; a) acute toxicity

ethylene glycol monobutyl

ether

ATE - Oral: 1200 mg/kg bw

ATE - Inhalation (Vapours): 3 mg/l

LD50 Oral Rat = 1746, mg/kg **OECD Test Guideline 401** OECD Test Guideline 402 LD50 Skin Rabbit > 2000, mg/kg

Carbon black a) acute toxicity LD50 Oral Rat > 8000, mg/kg

Polymer with quaternized a) acute toxicity

ammonium groups

LD50 Oral Rat > 2000 mg/kg

OECD Test Guideline 420

OECD Test Guideline 401

OECD Test Guideline 401 2-dimethylaminoethanol a) acute toxicity LD50 Oral Rat = 1183 mg/kg

> LC50 Inhalation Rat = 5,9 mg/l 4h **OECD Test Guideline 403** LD50 Skin Rabbit = 1219 mg/kg OECD Test Guideline 402

LD50 Oral Rat = 730 mg/kg triethylamine a) acute toxicity

> **OECD Test Guideline 403** LC50 Inhalation Rat = 3496 Ppm 1h LD50 Skin Rabbit = 580 mg/kg **OECD Test Guideline 402**

a) acute toxicity LD50 Oral Rat = 5350 mg/kgmethoxymethylethoxy)

propanol

LD50 Skin Rabbit > 2000 mg/kg

Page n. 9 of 04/09/2024 **Production Name** HYDROFAN BLUE BLACK Date

silicon dioxide a) acute toxicity LD50 Oral Rat > 5000 mg/kg

LC0 Inhalation Rat = 0,139 mg/l 4h - The product does not contain any substance classified for this

nazard

LD50 Skin Rabbit > 5000 mg/kg

1-methoxy-2-propanol a) acute toxicity LD50 Oral Rat = 4016 mg/kg

LC0 Inhalation Rat > 7000 Ppm 6h OECD Test Guideline 403

LD50 Skin Rat > 2000 mg/kg

11.2. Information on other hazards

Endocrine disrupting properties:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Harmful to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
2-butoxyethanol; ethylene glycol monobutyl ether	CAS: 111-76-2 - EINECS: 203- 905-0 - INDEX: 603-014-00-0	a) Aquatic acute toxicity: LC50 Fish Oncorhynchus mykiss (rainbow trout) = 1474 mg/L 96 H OECD Test Guideline 203
		a) Aquatic acute toxicity : EC50 Invertebrates Daphnia magna (Water flea) = $1550 \text{ mg/L} 48 \text{ H OECD Test Guideline 202}$
		e) Plant toxicity: EC50 Algae Pseudokirchneriella subcapitata (green algae) = 911 mg/L 72 H OECD Test Guideline 201
		b) Aquatic chronic toxicity : NOEC Fish Brachydanio rerio > 100 mg/L 21 D OECD Test Guideline 204 $$
Carbon black	CAS: 1333-86-4 - EINECS: 215- 609-9	a) Aquatic acute toxicity : LC10 Fish Brachydanio rerio (zebrafish) = 1000 mg/L 96h
		a) Aquatic acute toxicity : EC50 Invertebrates Daphnia magna (Water flea) > 5600 mg/L 48h
		a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus (green algae) $> 10000 \text{mg/L} 72 \text{h}$
Polymer with quaternized ammonium groups	CAS: 1431957- 88-8	e) Plant toxicity : Algae Pseudokirchneriella subcapitata (green algae) = 0,25 mg/L 72 H
(2-methoxymethylethoxy)propanol	CAS: 34590-94- 8 - EINECS: 252-104-2	a) Aquatic acute toxicity: LC50 Fish > 10000 mg/L 96 H
		a) Aquatic acute toxicity : EC50 Invertebrates Daphnia (water flea) > 85000 mg/L 48 H $$
1-methoxy-2-propanol	CAS: 107-98-2 - EINECS: 203- 539-1 - INDEX: 603-064-00-3	a) Aquatic acute toxicity: EC50 Invertebrates Daphnia magna (Water flea) 25900 mg/L 48 H
		e) Plant toxicity: EC50 Algae Selenastrum capricornutum (green algae) >

12.2. Persistence and degradability

N.A.

Date 04/09/2024 Production Name HYDROFAN BLUE BLACK Page n. 10 of 14

1000 mg/L 7 D

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration >= 0.1%

12.6. Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

N/A

14.2. UN proper shipping name

ADR-Shipping Name: N/A IATA-Technical name: N/A IMDG-Technical name: N/A

14.3. Transport hazard class(es)

ADR-Class: N/A
IATA-Class: N/A
IMDG-Class: N/A

14.4. Packing group

ADR-Packing Group: N/A IATA-Packing group: N/A IMDG-Packing group: N/A

14.5. Environmental hazards

Toxic ingredients quantity: 0.00 Very toxic ingredients quantity: 0.00

Marine pollutant: No

Environmental Pollutant: No

IMDG-EMS: N/A

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: N/A

ADR - Hazard identification number: N/A

ADR-Special Provisions: N/A

ADR-Transport category (Tunnel restriction code): N/A

Air (IATA):

IATA-Passenger Aircraft: N/A IATA-Cargo Aircraft: N/A

IATA-Label: N/A

IATA-Subsidiary hazards: N/A

IATA-Erg: N/A

IATA-Special Provisions: N/A

Sea (IMDG):

IMDG-Stowage Code: N/A
IMDG-Stowage Note: N/A
IMDG-Subsidiary hazards: N/A
IMDG-Special Provisions: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

Date 04/09/2024 Production Name HYDROFAN BLUE BLACK Page n. 11 of 14

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2020/878

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 40, 75

Provisions related to directive EU 2012/18 (Seveso III):

None

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

2: Hazard to waters

German Lagerklasse according to TRGS 510:

LGK 10

SVHC Substances:

No SVHC substances present in concentration >= 0.1%

Dir. 2010/75/EC (VOC directive)

Volatile Organic compounds - VOCs = 6.88 %

Volatile Organic compounds - VOCs = 69.52 g/L

Estimated Total Content of Water 75.08 %

Estimated Total Solid Content 18.04 %

Classification according to VbF

Classification according to VbF A III - Flash Point > 55 °C up to 100 °C, at 15 °C not miscible with water

Mal-Code (Denmark)

Mal-Code (Denmark) Mal Factor Unit of Measure Revision Status / Number Regulatory Base

1 - 6 222 m3 air/10 g 1993 Administrative determined MAL-Factors

Biocides

REGULATION (EC) No 528/2012

Substance Treated Article C(M)IT/MIT (3:1) In-can preservatives

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Date 04/09/2024 Production Name HYDROFAN BLUE BLACK Page n. 12 of 14

SECTION 16: Other information

Description

Code

H225	Highly flammable liquid and vapour.			
H226	Flammable liquid and vapour.			
H302	Harmful if swallowed.			
H311	Toxic in contact with skin.			
H312	Harmful in contact with skin.			
H314	Causes severe skin burns and eye damage.			
H315	Causes skin irritation.			
H319	Causes serious eye irritation.			
H331	Toxic if inhaled.			
H335	May cause respiratory irritation.			
H336	May cause drowsiness or dizziness.			
H400	Very toxic to aquatic life.			
H410	Very toxic to aquatic life with long lasting effects.			
H412	Harmful to aquatic life with long lasting effects.			
Code	Hazard class and hazard category	Description		
2.6/2	Flam. Liq. 2	Flammable liquid, Category 2		
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3		
3.1/3/Dermal	Acute Tox. 3	Acute toxicity (dermal), Category 3		
3.1/3/Inhal	Acute Tox. 3	Acute toxicity (inhalation), Category 3		
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4		
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4		
3.2/1A	Skin Corr. 1A	Skin corrosion, Category 1A		
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B		
3.2/2	Skin Irrit. 2	Skin irritation, Category 2		
3.3/2	Eye Irrit. 2	Eye irritation, Category 2		
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3		
4.1/A1		A suite a suite lease and a set a suite.		
,	Aquatic Acute 1	Acute aquatic hazard, category 1		
4.1/C1	Aquatic Acute 1 Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1		
•	•			

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation Classification procedure (EC) Nr. 1272/2008

Aquatic Chronic 3, H412 Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor BEI: Biological Exposure Index BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center CE: European Community

Date 04/09/2024 **Production Name** HYDROFAN BLUE BLACK Page n. 13 of 14 CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 3: Composition/information on ingredients

- SECTION 7: Handling and storage

- SECTION 8: Exposure controls/personal protection

- SECTION 9: Physical and chemical properties

- SECTION 11: Toxicological information

- SECTION 14: Transport information

- SECTION 15: Regulatory information

- SECTION 16: Other information

Date 04/09/2024 Production Name HYDROFAN BLUE BLACK Page n. 14 of 14