

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : 523-15 1L Racing Additive 1L Steel drums 523-15 1L
Racing Additive 1L Steel drums

Product code : 000000000050794263

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Spraying
Substance/Mixture Clearcoat product

1.3 Details of the supplier of the safety data sheet

Company:

BASF Coatings GmbH
Postfach 6123
48136 Münster
Deutschland

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
United Kingdom

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Telephone: +44 161 475 3000
E-mail address: product-safety-uk-and-ireland@basf.com

1.4 Emergency telephone

International emergency number:
Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Long-term (chronic) aquatic hazard,
Category 3

H412: Harmful to aquatic life with long lasting
effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI
2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal Word : Danger

Hazard Statements	:	H226	Flammable liquid and vapor.
		H304	May be fatal if swallowed and enters airways.
		H336	May cause drowsiness or dizziness.
		H412	Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Supplemental Hazard : EUH066 Repeated exposure may cause skin dryness or
Statements cracking.

Precautionary : **Prevention:**
Statements

P210 Keep away from heat, hot surfaces, sparks,
open flames and other ignition sources. No
smoking.

P261 Avoid breathing mist or vapors.

P273 Avoid release to the environment.

Response:

P301 + P310 IF SWALLOWED: Immediately call a
POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical
or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

n-Butyl acetate

Hydrocarbons, C9, aromatics

1-methoxy-2-propylacetate

isobutyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : organic solvent

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

**523-15 1L Racing Additive 1L Steel
drums**

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

	Index-No. Registration number		
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 50 - < 75
Hydrocarbons, C9, aromatics	64742-95-6	Flam. Liq. 3; H226	>= 15 - < 20

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

**523-15 1L Racing Additive 1L Steel
drums**

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

	265-199-0 UK-20- 0537843089-5- 0000	STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	
1-methoxy-2-propylacetate	108-65-6 203-603-9 607-195-00-7 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5-	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 5 - < 7

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

	0000 UK-20- 9642318150-0- 0000		
isobutyl acetate	110-19-0 203-745-1 607-026-00-7 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system)	>= 3 - < 5

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own safety.
Immediately remove contaminated clothing.
In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.
Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.
Never give anything by mouth to an unconscious person.
Keep patient warm and at rest.

If inhaled : If breathed in, move person into fresh air.
Call a physician or poison control center immediately.
If breathing is irregular or stopped, administer artificial respiration.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

In case of skin contact : If symptoms persist, call a physician.

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Do NOT use solvents or thinners.

In case of eye contact : If symptoms persist, call a physician.

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If swallowed : Do not induce vomiting due to aspiration hazard.

Keep at rest.

If symptoms persist, call a physician or Poison Control Center immediately.

Rinse mouth with water.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Risks : May be fatal if swallowed and enters airways.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Risk of product entering the lungs on vomiting after ingestion.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Dry powder
Alcohol-resistant foam
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing
hazardous combustion products (see section 10).

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : In the event of fire, cool tanks with water spray.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Collect contaminated fire extinguishing water separately.
This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Advice on product handling can be found in sections 7
and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined
areas.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the
environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains
inform respective authorities.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The workplace should be equipped with an emergency shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and safety practice.

Do not breathe vapors or spray mist.

Advice on protection against fire and explosion	:	Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that
--	---	--

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

operators should wear antistatic clothing and footwear.
The relevant fire protection measures should be noted.
Use explosion-proof equipment. Vapors are heavier than
air and may spread along floors. Vapors may form
explosive mixtures with air.

Hygiene measures : Remove contaminated clothing immediately and dispose
of safely. Wash hands before breaks and at the end of
workday. Keep away from food, drink and animal
feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Avoid direct sunlight. Close containers carefully once
opened and store them upright in order to prevent any
leakage. No smoking. No admission for unauthorised
personnel. Always keep in containers of same material
as the original one. Observe label precautions. Keep in a
dry, cool and well-ventilated place.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

**523-15 1L Racing Additive 1L Steel
drums**

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

		STEL	200 ppm 966 mg/m3	GB EH40
		STEL	150 ppm 723 mg/m3	2019/1831/ EU
	Further information: Indicative			
		TWA	50 ppm 241 mg/m3	2019/1831/ EU
	Further information: Indicative			
1-methoxy-2-propylacetate	108-65-6	TWA	50 ppm 274 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 548 mg/m3	GB EH40

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 550 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
isobutyl acetate	110-19-0	TWA	150 ppm 724 mg/m3	GB EH40
		STEL	187 ppm 903 mg/m3	GB EH40

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

		TWA	50 ppm 241 mg/m3	2019/1831/ EU
	Further information: Indicative			
		STEL	150 ppm 723 mg/m3	2019/1831/ EU
	Further information: Indicative			

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Required when there is a risk of eye contact.

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

certified according to EN ISO 374-1 is suitable: e.g.
nitrile gloves - material thickness: 0,35 mm Further
information on penetration time is available from the
manufacturer of the glove. Data are based on
information from the glove manufacturer, the raw
material manufacturer or according to specifics of the
product components. The suitability for a specific
workplace should be discussed with the producers of
the protective gloves. Request information on glove
permeation properties from the glove supplier. Gloves
should be discarded and replaced if there is any
indication of degradation or chemical breakthrough.
Preventive skin protection Suitable materials for short-
term contact (recommended: At least protective index
2, corresponding > 30 minutes of permeation time
according to EN ISO 374-1) Suitable materials also with
prolonged, direct contact (Recommended: Protective
index 6, corresponding > 480 minutes of permeation
time according to EN ISO 374-1): Suitable materials
against splashes (recommended: At least protective
index 1, corresponding > 10 minutes of permeation

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

time according to EN ISO 374-1)

Skin and body protection : Anti-static protective clothing

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits,

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and
safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Color	:	colorless
Odor	:	of glycol
pH	:	substance/mixture is non-polar/aprotic
Melting point/ range	:	not determined
	:	114.00 - 185.00 °C

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Flash point : 25 °C
Method: ISO 3679

Upper explosion limit / : not determined
Upper flammability limit

Lower explosion limit / : > 35.0 g/m³
Lower flammability limit

Vapor pressure : 12.0000 hPa (20 °C)

(50 °C)
not determined

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Relative vapor density : Heavier than air.

Density : 0.867 g/cm³ (20 °C)

Solubility(ies)
Water solubility : not determined

Partition coefficient: n-
octanol/water : not applicable for mixtures

Autoignition temperature : > 200 °C

Decomposition
temperature : No decomposition if stored and handled as
prescribed/indicated.

Viscosity
Viscosity, kinematic : 6.0 mm²/s (23 °C)

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

(40 °C)

not determined

Flow time : < 30 s

Cross section: 3 mm

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids) : Flammable liquid and vapour.

Self-heating substances : The substance or mixture is not classified as self heating.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Metal corrosion rate : Not corrosive to metals.

Particle size : The substance / product is marketed or used in a non
solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.
Heat, flames and sparks.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

n-Butyl acetate:

Result : Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified due to lack of data.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

n-Butyl acetate:

Partition coefficient: n- : Pow: 200 (25 °C)
octanol/water
log Pow: 2.3 (25 °C)

pH: 7

Method: OECD Test Guideline 117

GLP: yes

Hydrocarbons, C9, aromatics:

Partition coefficient: n- : log Pow: 3.17
octanol/water
GLP: no

1-methoxy-2-propylacetate:

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Partition coefficient: n-
octanol/water : log Pow: 1.2 (20 °C)
pH: 6.8
Method: OECD Test Guideline 117
GLP: yes

isobutyl acetate:

Partition coefficient: n-
octanol/water : log Pow: 2.3 (25 °C)
pH: 7
Method: OECD Test Guideline 117
GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater.

Observe national and local legal requirements.

Contaminated packaging : Containers which are not properly emptied must be

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

disposed pursuant to Directive 2008/98/EC

Packaging that is not properly emptied must be disposed
of as the unused product.

SECTION 14: Transport information

14.1 UN number

ADN	: UN 1263
ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263
IATA	: UN 1263

14.2 UN proper shipping name

ADN	: PAINT RELATED MATERIAL
-----	--------------------------

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

ADR	: PAINT RELATED MATERIAL
RID	: PAINT RELATED MATERIAL
IMDG	: PAINT RELATED MATERIAL
IATA	: PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

ADN

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3

ADR

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
Tunnel restriction code	:	(D/E)

RID

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Packing group : III

Classification Code : F1

Hazard Identification : 30
Number

Labels : 3

IMDG

Packing group : III

Labels : 3

EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo : 366
aircraft)

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable Liquids

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

IATA (Passenger)

Packing instruction (passenger aircraft)	: 355
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable liquid

14.5 Environmental hazards

ADN

Environmentally
hazardous : no

ADR

Environmentally
hazardous : no

RID

Environmentally : no

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

hazardous

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Conditions of restriction for the following entries should be considered: Number on list 3
--	---

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

gas oil blending streams),(d)
heavy fuel oils (e) alternative
fuels serving the same
purposes and with similar
properties as regards
flammability and
environmental hazards as the
products referred to in points
(a) to (d)

Volatile organic compounds : Volatile organic compounds (VOC) content: 870 g/l

Directive 2010/75/EU of 24 November 2010 on
industrial emissions (integrated pollution prevention and
control)

Volatile organic compounds (VOC) content: 99.08 %

Other regulations:

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

dropped

Limit value for maximum VOC content as specified in Annex IIB:

dropped

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapor.
H226	: Flammable liquid and vapor.
H304	: May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Flam. Liq. : Flammable liquids
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA : Limit Value - eight hours

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

2000/39/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data
sheets of all components.
Restricted to professional users.

Classification of the mixture:

Flam. Liq. 3 H226

STOT SE 3 H336

Classification procedure:

Based on product data or
assessment

Calculation method

SAFETY DATA SHEET

According to REACH Regulation (EC) No
1907/2006, as amended by UK REACH
Regulations SI 2019/758



We create chemistry

523-15 1L Racing Additive 1L Steel drums

Version	Revision Date:	SDS Number:	Date of last issue: 10.05.2024
2.0	20.01.2025	000000000050794 263	Date of first issue: 18.10.2023

Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN