According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : A-C-22 5L 5L Steel jerricans A-C-22 5L 5L Steel jerricans

Product code : 00000000050794104

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Spraying

Substance/Mixture

Clearcoat product

1.3 Details of the supplier of the safety data sheet

Company:

BASF Coatings GmbH Postfach 6123 48136 Münster Deutschland

Contact address:

BASF plc

4th and 5th Floors, 2 Stockport Exchange Railway Road, Stockport, SK1 3GG

United Kingdom

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

1.4 Emergency telephone

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single

exposure, Category 3, Central

nervous system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard,

Category 3

H412: Harmful to aquatic life with long lasting

effects.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :





Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting

effects.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin dryness or

cracking.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794 Date of first issue: 21.10.2023

104 Date of first issue: 21.10.2023

Precautionary Statements Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P261 Avoid breathing mist or vapors.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection/ hearing

protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse

skin with water.

P370 + P378 In case of fire: Use dry sand, dry chemical

or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

n-Butyl acetate

2-heptanone

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : organic solvent

acrylic resin

Components

Chemical name	CAS-No.	Classification	Concentratio
	EC-No.		n (% w/w)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Index-No. Registration number >= 20 - < 25 n-Butyl acetate 123-86-4 Flam. Liq. 3; H226 204-658-1 STOT SE 3; H336 (Central nervous 607-025-00-1 system) UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000 2-heptanone 110-43-0 Flam. Liq. 3; H226 >= 12.5 - < 15 203-767-1 Acute Tox. 4;

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

	606-024-00-3	H302	
	UK-20- 0537843089-5-	Acute Tox. 4; H332	
	0000	STOT SE 3; H336	
		(Central nervous system)	
Naphtha	64742-52-5	Flam. Liq. 3; H226	>= 3 - < 5
(petroleum),hydrotreated light, Kp > 140oC	265-155-0	STOT SE 3; H336	
'	649-465-00-7	(Central nervous	
	01-2119471843-32	system)	
		Asp. Tox. 1; H304	
		Aquatic	
		Chronic 3; H412	
xylene	1330-20-7	Flam. Liq. 3; H226	>= 3 - < 5
	215-535-7	Acute Tox. 4;	
	601-022-00-9	H332	
	UK-20-	Acute Tox. 4;	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

	2749242067-7- 0000 UK-20- 9702550300-0- 0000 UK-20- 0537843089-5- 0000 UK-20- 9642318150-0- 0000	H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Kidney, Liver, Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
2-butoxyethyl acetate	112-07-2	Acute Tox. 4;	>= 1 - < 2
	203-933-3	H302	
	607-038-00-2	Acute Tox. 4; H332	
	UK-20-		

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

	0537843089-5- 0000	Acute Tox. 4; H312	
	UK-20- 9642318150-0- 0000		
bis(1,2,2,6,6-pentamethyl-4- piperidyl)sebacate	41556-26-7 255-437-1	Skin Sens. 1A; H317	>= 0.5 - < 1
	UK-20- 0537843089-5- 0000	Repr. 2; H361f Aquatic Acute 1; H400	
	UK-20- 9642318150-0- 0000	Aquatic Chronic 1; H410	
Methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	82919-37-7 280-060-4	Skin Sens. 1A; H317	>= 0.1 - < 0.2
	UK-20- 0537843089-5- 0000	Repr. 2; H361f Aquatic Acute 1; H400	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

UK-20- Aquatic 9642318150-0- Chronic 1; H410 0000

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aid personnel should pay attention to their own

safety.

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

Immediately remove contaminated clothing.

In all cases of doubt, or when symptoms persist, seek

medical attention.

Move out of dangerous area.

Never give anything by mouth to an unconscious person.

If inhaled : If symptoms persist, call a physician.

If breathed in, move person into fresh air.

If breathing is irregular or stopped, administer artificial

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date:

2.0

04.03.2025

SDS Number:

00000000050794

104

Date of last issue: 10.05.2024

Date of first issue: 21.10.2023

respiration.

In case of skin contact : If symptoms persist, call a physician.

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Do NOT use solvents or thinners.

In case of eye contact : If symptoms persist, call a physician.

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

If swallowed : If symptoms persist, call a physician.

Do NOT induce vomiting.

Rinse mouth.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Information, i.e. additional information on symptoms

and effects may be included in the GHS labeling phrases

available in Section 2 and in the Toxicological

assessments available in Section 11.

Risks : May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing : Water spray jet

media

Dry powder

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Alcohol-resistant foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire : Fire will produce dense black smoke containing

fighting hazardous combustion products (see section 10).

5.3 Advice for firefighters

Special protective : Appropriate breathing apparatus may be required.

equipment for fire-fighters

Further information : In the event of fire, cool tanks with water spray.

Fire residues and contaminated fire extinguishing water

must be disposed of in accordance with local

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

regulations.

Collect contaminated fire extinguishing water separately.

This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.

Keep away from sources of ignition.

Advice on product handling can be found in sections 7

and 8 of this safety data sheet.

For non-emergency personnel:

For emergency responders:

Use personal protective equipment.

Ensure adequate ventilation, especially in confined

areas.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

6.2 Environmental precautions

Environmental precautions: Do not allow uncontrolled discharge of product into the

environment.

Avoid subsoil penetration.

If the product contaminates rivers and lakes or drains

inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see

section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide good ventilation of working area (local exhaust

ventilation if necessary).

Do not return residues to the storage containers.

Smoking, eating and drinking are forbidden in application area. For personal protection see section 8.

Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the

exposure limits.

The workplace should be equipped with an emergency

shower and eye-rinsing facility.

Avoid contact with the skin, eyes and clothing.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Handle in accordance with good industrial hygiene and

safety practice.

Do not breathe vapors or spray mist.

Advice on protection against fire and explosion

: Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors are heavier than air and may spread along floors. Vapors may form

explosive mixtures with air.

Hygiene measures : Remove contaminated clothing immediately and dispose

of safely. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal

feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on : Avoid direct sunlight. Close containers carefully once

opened and store them upright in order to prevent any

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

storage conditions leakage. No smoking. No admission for unauthorised

personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a

dry, cool and well-ventilated place.

Advice on common storage: Keep away from oxidizing agents, strongly alkaline and

strongly acid materials in order to avoid exothermic

reactions.

Packaging material : Suitable material: Carbon steel (Iron), tinned carbon

steel (Tinplate)

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further

information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m3	GB EH40
		STEL	200 ppm 966 mg/m3	GB EH40
		STEL	150 ppm 723 mg/m3	2019/1831/ EU
	Further information: Indicative			
		TWA	50 ppm 241 mg/m3	2019/1831/ EU
	Further information: Indicative			
2-heptanone	110-43-0	STEL	100 ppm 475 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned			

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

	substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm	GB EH40
			237 mg/m3	
	Further infor	mation: Can be ab	sorbed through the skin. T	he assigned
	substances a	re those for which	there are concerns that de	ermal
	absorption w	vill lead to systemic	c toxicity.	
		TWA	50 ppm	2000/39/EC
			238 mg/m3	
	Further information: Identifies the possibility of significant uptake			
	through the skin, Indicative			
		STEL	100 ppm	2000/39/EC
			475 mg/m3	
	Further information: Identifies the possibility of significant uptake			
	through the skin, Indicative			
xylene	1330-20-7	TWA	50 ppm	GB EH40

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

		220 mg/m3			
Furth	Further information: Can be absorbed through the skin. The assigned				
subst	ances are those for v	which there are concerns	that dermal		
absor	ption will lead to sys	temic toxicity.			
	STEL	100 ppm	GB EH40		
		441 mg/m3			
Furth	er information: Can	be absorbed through the	skin. The assigned		
subst	ances are those for v	which there are concerns	that dermal		
absor	absorption will lead to systemic toxicity.				
	TWA 50 ppm 2000/39/E				
		221 mg/m3			
Furth	er information: Iden	tifies the possibility of sig	nificant uptake		
throu	through the skin, Indicative				
	STEL	100 ppm	2000/39/EC		
		442 mg/m3			
Furth	Further information: Identifies the possibility of significant uptake				
throu	through the skin, Indicative				

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

2-butoxyethyl	112-07-2	TWA	20 ppm	GB EH40	
acetate			133 mg/m3		
	Further info	mation: Can be ab	sorbed through the skin. 1	he assigned	
	substances a	are those for which	there are concerns that d	ermal	
	absorption v	vill lead to systemi	c toxicity.		
		STEL	50 ppm	GB EH40	
			332 mg/m3		
	Further information: Can be absorbed through the skin. The assigned				
	substances a	substances are those for which there are concerns that dermal			
	absorption v	absorption will lead to systemic toxicity.			
		STEL	50 ppm	2000/39/EC	
			333 mg/m3		
	Further information: Identifies the possibility of significant uptake				
	through the skin, Indicative				
		TWA	20 ppm	2000/39/EC	
			133 mg/m3		
	Further information: Identifies the possibility of significant uptake				

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

through the skin, Indicative

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles (splash goggles) (e.g. EN

166)

Required when there is a risk of eye contact.

Hand protection

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Remarks

: Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Preventive skin protection Suitable materials for shortterm contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

time according to EN ISO 374-1)

Skin and body protection : chemical-resistant disposable coveralls

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant

synthetic fibres.

Respiratory protection : Suitable respiratory equipment:

half-mask with A1P2 class combination filter

When workers are facing concentrations above the exposure limit they must use appropriate certified

respirators.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Protective measures : Do not breathe vapour/spray.

Eye wash fountains and safety showers must be easily

accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits,

appropriate certified respirators must be worn.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Avoid contact with the skin, eyes and clothing.

Handle in accordance with good industrial hygiene and

safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Color : colorless

Odor : ester-like

pH : substance/mixture is non-polar/aprotic

Melting point/ range : not determined

Boiling point/boiling range : 116 °CMethod: calculated

Flash point : 26 °C

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date:

SDS Number: 000000000050794

104

Date of last issue: 10.05.2024

2.0 04.03.2025

Date of first issue: 21.10.2023

Method: ISO 3679

Evaporation rate : No data available

Lower explosion limit /
Lower flammability limit

: > 35 g/m3

Vapor pressure : 20.0000 hPa (20 °C)

Method: other (calculated)

(50 °C)

not determined

Relative vapor density : Heavier than air.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Density : 0.957 g/cm3 (20 °C)

Solubility(ies)

Water solubility : not determined

Partition coefficient: n-

octanol/water

: not applicable for mixtures

Autoignition temperature : > 200 °C

Decomposition : No decomposition if stored and handled as

temperature prescribed/indicated.

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 46.8 mm2/s (23 °C)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

04.03.2025

Version Revision Date:

2.0

SDS Number: 000000000050794

Date of last issue: 10.05.2024

104

Date of first issue: 21.10.2023

(40 °C)

not determined

Flow time : > 37 s at 23 °C

Cross section: 4 mm

Method: ISO 2431

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids) : Flammable liquid and vapour.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

Particle size : The substance / product is marketed or used in a non

solid or granular form.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form ignitable mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and

strongly acid materials in order to avoid exothermic

reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Exposure time: 4 h

Test atmosphere: vapor

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

2-heptanone:

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 16.7 mg/l

Exposure time: 4 h

Test atmosphere: vapor

2-butoxyethyl acetate:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Acute oral toxicity : LD50 (Rat): 1,880 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 1,500 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

n-Butyl acetate:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Based on available data, the classification criteria are not met.

Product:

No aspiration toxicity classification

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

n-Butyl acetate:

Partition coefficient: n- : Pow: 200 (25 °C)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

octanol/water log Pow: 2.3 (25 °C)

pH: 7

Method: OECD Test Guideline 117

GLP: yes

2-heptanone:

Partition coefficient: n-

octanol/water

: log Pow: 2.26 (30 °C)

pH: 7

Method: Regulation (EC) No. 440/2008, Annex, A.8

GLP: yes

xylene:

Partition coefficient: n-

: log Pow: 3.12 - 3.20 (25 °C)

octanol/water

GLP: no

Remarks: Information taken from reference works and

the literature.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

2-butoxyethyl acetate:

Partition coefficient: n- : log Pow: 1.51 (25 °C)

octanol/water

pH: 7

Method: OECD Test Guideline 107

GLP: no

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate:

Partition coefficient: n- : Remarks: No data available

octanol/water

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Partition coefficient: n- : Remarks: No data available

octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Assessment : This substance/mixture contains no components

considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative

(vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting

potential

: This substance/mixture does not contain components considered to have endocrine disrupting properties for

environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not discharge into drains/surface

waters/groundwater.

Observe national and local legal requirements.

Contaminated packaging : Containers which are not properly emptied must be

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

disposed pursuant to Directive 2008/98/EC

Packaging that is not properly emptied must be disposed

of as the unused product.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263

ADR : UN 1263

RID : UN 1263

IMDG : UN 1263

IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794 104 Date of first issue: 21.10.2023

ADR : PAINT

RID : PAINT

IMDG : PAINT

IATA : PAINT

14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 3

ADR : 3

RID : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADN

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Packing group : III

Classification Code : F1

Hazard Identification : 30

Number

Labels : 3

ADR

Packing group : III

Classification Code : F1

Hazard Identification : 30

Number

Labels : 3

Tunnel restriction code : (D/E)

RID

Packing group : III

Classification Code : F1

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Hazard Identification : 30

Number

Labels : 3

IMDG

Packing group : III

Labels : 3

EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction : 355

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

(passenger aircraft)

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable liquid

14.5 Environmental hazards

ADN

Environmentally : no

hazardous

ADR

Environmentally : no

hazardous

RID

Environmentally : no

hazardous

IMDG

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixtureRelevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the

following entries should be

considered:

Number on list 72, 3, 20

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Number on list 3

Number on list 20

UK REACH Candidate list of substances of very high : Not applicable

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations : Not applicable

(retained Regulation (EU) 2019/1021 as amended

for Great Britain)

Regulation (EC) on substances that deplete the : Not applicable

ozone layer

UK REACH List of substances subject to : Not applicable

authorisation (Annex XIV)

P5c

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Control of Major Accident Hazards P5c FLAMMABLE LIQUIDS

Regulations 2015 (COMAH)

Volatile organic : Volatile organic compounds (VOC) content: 525 g/l

compounds

Directive 2010/75/EU of 24 November 2010 on

industrial emissions (integrated pollution prevention and

control)

Volatile organic compounds (VOC) content: 55.95 %

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

Limit value for maximum VOC content as specified in Annex IIB: 420 g/l VOC content of the ready-for-use product according to ISO 11890-2: 419 g/l

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapor.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

H335 : May cause respiratory irritation.

H336 : May cause drowsiness or dizziness.

H361f : Suspected of damaging fertility.

H373 : May cause damage to organs through prolonged or

repeated exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard

Eye Irrit. : Eye irritation

Flam. Liq. : Flammable liquids

Repr. : Reproductive toxicity

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Skin Irrit. : Skin irritation

Skin Sens. : Skin sensitization

STOT RE : Specific target organ toxicity - repeated exposure

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a

first list of indicative occupational exposure limit values

2019/1831/EU : Europe. Commission Directive 2019/1831/EU

establishing a fifth list of indicative occupational

exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 BAT : UK. Biological monitoring guidance values

2000/39/EC / TWA : Limit Value - eight hours

2000/39/EC / STEL : Short term exposure limit

2019/1831/EU / TWA : Limit Value - eight hours

2019/1831/EU / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight: CLP - Classification Labelling Packaging Regulation: Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data

sheets of all components.

Restricted to professional users.

Classification of the mixture: Classification procedure: Flam. Liq. 3 H226 Based on product data or

assessment

Skin Sens. 1 H317 Calculation method

STOT SE 3 H336 Calculation method

Aquatic Chronic 3 H412 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



A-C-22 5L 5L Steel jerricans

Version Revision Date: SDS Number: Date of last issue: 10.05.2024

2.0 04.03.2025 00000000050794

104 Date of first issue: 21.10.2023

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB/EN